

Darnell & Associates, Inc.

- TRANSPORTATION PLANNING & TRAFFIC ENGINEERING

September 14, 2016

Neil Patel
Excel Hotel Group
10660 Scripps Ranch Boulevard, Suite 100,
San Diego, California 92131

D&A Ref. No: 160605

Subject: Parking Study for the proposed Springhill Residential Inn Project located on the southside of Wayne Mills Place in Santa Clarita, California.

Dear Mr. Patel,

In accordance with your authorization Darnell & Associates, Inc. (D&A) has analyzed the parking demands of the Hotel A, Hotel B and Denny's Restaurant to determine the recommended parking for the proposed project.

The proposed Valencia Springhill Suites + Residence Inn and Holiday Inn Express hotels project is proposed to be developed on the site of the existing Hotel B (Best Western Hotel) site. Figure 1 is a vicinity map showing the location of the project site and the adjacent existing Hotel A (Holiday Inn Express) and Denny's Restaurant. Figures 2 and 3 depict the project site, underground parking and primary access to Wayne Mills Place. The report has been revised based on discussions with the City of Santa Clarita Planning staff.

PROJECT AREA

The construction of the proposed project proposes the construction of the following:

- Springhill Suites/Residence Inn 182 Rooms
 - Holiday Inn Express 108 Rooms
- Total: 290 Rooms

The project site is presently occupied by the 120 room Hotel B. Immediately to the north of the project site is the 118 room Hotel A and Denny's Restaurant. The existing Hotel A operations will be moved to the project site and the Hotel B operations will be removed from the project site and occupy the existing Hotel A facility. Figure 4 is a Google Map showing the Hotel B Facility on the project site and the adjacent Hotel A Facilities.

PARKING ANALYSIS

As previously stated the proposed development of the Springhill Suites/Residence Inn Hotel and the Holiday Inn Express Building proposes construction of 274 parking spaces consisting of 203 at grade parking spaces and 71 in the garage under the Springhill Suites/Residence Inn Building.

Based on the City of Santa Clarita Parking requirements the project is required to provide one (1) parking spaces per room resulting in 290 parking spaces (1 space per room times 290 rooms = 290 parking spaces). Therefore the project provides 16 spaces less than the City requirements.

To determine the adequacy of the proposed 274 parking spaces D&A conducted parking demand surveys of the existing Hotel A and Hotel B and the Denny's Restaurant parking for 12 days from Friday June 24, 2016 through July 5, 2016.



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373
 DWG: 160605-AA DATE: SEPTEMBER 13, 2016 BY: DAB

FIGURE 1
VICINITY MAP




FIGURE 2
PROJECT SITE PLAN

Darnell & ASSOCIATES, INC.
 160605-A-A.dwg 07-29-16 JAM





FIGURE 3
Garage Parking Plan

Darnell & ASSOCIATES, INC.

160605-AA.dwg 07-29-16 JAM



Darnell & ASSOCIATES, INC.

2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 160605-AA DATE: SEPTEMBER 13, 2016 BY: DAB

FIGURE 4
 EXISTING DEVELOPMENT CONDITIONS

A copy of the field survey sheets are presented in Appendix A. Parking demands were collected at the following times:

- 12-1 PM
- 5-6 PM
- 6-7 PM
- 12-1 AM
- 7-8 AM
- 8-9 AM
- 11 AM – 12 PM

The parking areas were broken into three (3) survey areas. Figure 5 and 6 show the survey parking spaces for the Denny's Restaurant and Hotel A and Figure 7 shows the parking survey spaces for Hotel B. The parking areas for the Denny's Restaurant and Hotel A provide 144 parking spaces and the best western provides 167 parking spaces. In addition to the parking surveys D&A obtained room occupancy for each of the two (2) existing hotels for the survey dates.

Table 1 provides summary of the available rooms, occupied rooms and occupancy percentage for each hotel. The Hotel A had one (1) date with 100% occupancy on Saturday June 25, 2016 and the Hotel B had two (2) dates on Friday June 25, 2016 and Saturday June 26, 2016 with 100% occupancy. Table 2 provides a summary of the available 265 parking spaces.


The parking surveys conducted from Friday June 25, 2016 through July 5, 2016 were then broken down into weekday (Monday through Thursday) and weekend (Friday, Saturday and Sunday) parking demands. Table 3 presents the weekday parking demands and Table 4 presents the weekend parking demands. Also presented on Tables 3 and 4 are the calculation of the peak parking demand ratio for each day. Review of Table 3 shows the worst case parking demand was Wednesday June 29, 2016 for the weekday surveys with a parking demand ratio of 0.925 parking spaces per occupied room. For review of Table 4 shows the peak demand for the weekends occurred on Friday June 24, 2016 with a parking demand ratio of 0.865 parking spaces per room. The resulting peak hour demands are shown on Table 5 each day surveyed.

Utilizing the peak parking demand ratio of 0.925 spaces per room the required parking is 268 spaces. Table 6 provides the calculations for the project. Review of Table 6 shows the peak parking demand ratio with the requirement for 268 parking spaces compared to the proposed 274 parking spaces will result in an excess of 6 parking spaces being provided.

The final test on the available parking for the Denny's Restaurant and the existing Hotel A facility was tested using the Urban Land Institute (ULI) 2nd Edition Shared Parking Report and the following City of Santa Clarita Approved Parking requirements for restaurant and hotel uses:

- Denny's Restaurant - 27 Spaces
 - Hotel A - 118 Spaces
- Total: 145 Spaces

Table 7 was then prepared to show the parking demand by hours based on the ULI hourly rates. Review of Table 7 shows the hourly demands will not exceed the available 144 parking spaces. Further review of Table 7 shows there will be an excess of 12 to 47 spaces each hour.



Darnell & ASSOCIATES, INC.

160605 -AA.dwg 09-14-16 JAM

FIGURE 5

Denny's Restaurant/ Hotel A Parking Study Area



Darnell & ASSOCIATES, INC.

160605-AAA.dwg 09-14-16 JAM

FIGURE 6
Denny's Rearurant and Hotel A Parking Study Area



Darnell & ASSOCIATES, INC.

160605-AA.dwg 09-14-16 jam

FIGURE 7
Hotel B Parking Study Area

**Table 1 - Summary of Room Occupancy for the Hotel A and the Hotel B
Wayne Mills Place, Santa Clarita California**

Day of Week	Hotel A (Area A + Area B)			Hotel B (Area C)			Total Area A + Area B + Area C		
	Total Rooms	Occupied Rooms	Percent (%) of Occupied Rooms	Total Rooms	Occupied Rooms	Percent (%) of Occupied Rooms	Total Rooms	Total Occupied Rooms	Percent (%) of Occupied Rooms
Friday, June 24, 2016	118	94	80%	120	120	100%	238	214	90%
Saturday, June 25, 2016	118	118	100%	120	120	100%	238	238	100%
Sunday, June 26, 2016	118	96	81%	120	115	96%	238	211	89%
Monday, June 27, 2016	118	112	95%	120	113	94%	238	225	95%
Tuesday, June 28, 2016	118	112	95%	120	114	95%	238	226	95%
Wednesday, June 29, 2016	118	106	90%	120	108	90%	238	214	90%
Thursday, June 30, 2016	118	94	80%	120	106	88%	238	200	84%
Friday, July 01, 2016	118	73	62%	120	117	98%	238	190	80%
Saturday, July 02, 2016	118	100	85%	120	119	99%	238	219	92%
Sunday, July 03, 2016	118	79	67%	120	107	89%	238	186	78%
Monday, July 04, 2016	118	64	54%	120	56	47%	238	120	50%
Tuesday, July 05, 2016	118	81	69%	120	89	74%	238	170	71%

Table 2 Summary of Existing Parking Supply for the Denny's Restaurant, Hotel A and the Hotel B, Wayne Mills Place, Santa Clarita, California	
Facility	Available Parking Spaces
Denny's Restaurant/ Hotel A	144 Parking Spaces
Hotel B	121 Parking Spaces
Total:	265 Parking Spaces

Table 3 - Weekday Parking Demands Summary

Location	Dates											
	Monday, June 27, 2016			Tuesday, June 28, 2016			Wednesday, June 29, 2016			Thursday, June 30, 2016		
	Occupied Parking Spaces	Excess Parking	Occupied Rooms	Occupied Parking Spaces	Excess Parking	Occupied Rooms	Occupied Parking Spaces	Excess Parking	Occupied Rooms	Occupied Parking Spaces	Excess Parking	Occupied Rooms
Area A	Total Capacity											
	Time											
	49 12-1 PM	25	24	17	32	14	35	43	6	43		
	49 5-6 PM	18	31	16	33	8	41	22	27			
	49 6-7 PM	15	34	22	27	35	14	25	24			
	49 12-1 AM	12	37	11	38	47	2	38	11	N/A		
	49 7-8 AM	0	49	24	25	47	2	31	18			
	49 8-9 AM	16	33	19	30	34	15	26	23			
	49 11 AM-12 PM	24	25	11	38	9	40	15	34			
	Peak Demand	25	24	24	38	47	40	38	38			
Area B	Total Capacity											
	Time											
	95 12-1 PM	35	60	35	60	32	63	21	74			
	95 5-6 PM	60	35	53	42	45	50	45	50			
	95 6-7 PM	48	47	62	33	77	18	63	32			
	95 12-1 AM	64	31	59	36	88	7	91	4	73		
	95 7-8 AM	0	95	66	29	82	13	86	9			
	95 8-9 AM	70	25	55	40	70	25	64	31			
	95 11 AM-12 PM	59	36	24	71	21	74	28	67			
	Peak Demand	70	36	66	71	88	74	91	91			
Area A plus Area B:	Total Capacity											
	Time											
	144 12-1 PM	60	84	52	92	46	98	27	117			
	144 5-6 PM	78	66	69	75	53	91	67	77			
	144 6-7 PM	63	81	84	60	112	32	88	56			
	144 12-1 AM	76	68	70	74	135	9	129	15	73		
	144 7-8 AM	0	144	90	54	129	15	117	27			
	144 8-9 AM	86	58	74	70	104	40	90	54			
	144 11 AM-12 PM	83	61	35	109	30	114	43	101			
	Peak Demand	86	61	90	109	135	114	129	129			
Area C	Total Capacity											
	Time											
	121 12-1 PM	45	76	29	92	30	91	31	90			
	121 5-6 PM	47	74	76	45	40	81	67	54			
	121 6-7 PM	43	78	86	35	51	70	66	55			
	121 12-1 AM	117	4	99	22	112	9	108	13	117		
	121 7-8 AM	79	42	89	32	83	38	94	27			
	121 8-9 AM	63	58	59	62	72	49	79	42			
	121 11 AM-12 PM	36	85	33	88	31	90	24	97			
	Peak Demand	117	85	99	88	112	90	108	108			
Total Demand	Total Capacity											
	Time											
	216 12-1 PM	80	136	64	152	62	154	52	164			
	216 5-6 PM	107	109	129	87	85	131	112	104			
	216 6-7 PM	91	125	148	66	128	88	129	87			
	216 12-1 AM	181*	35	158*	58	200*	16	199*	17	190		
	216 7-8 AM	79	137	155	61	165	51	180	36			
	216 8-9 AM	133	83	114	102	142	74	143	73			
	216 11 AM-12 PM	95	121	57	159	52	164	52	164			
	Peak Demand	181	121	158	159	200	164	199	199	0.92 spaces/room		
Area B+ Area C	Peak Demand											199
	Parking/Room Ratio											0.92 spaces/room

**Table 5 - Summary of Peak Parking Demands
for the Hotel A and the Hotel B
Wayne Mills Place, Santa Clarita California**

Day of Week	Hotel A and Hotel B				
	Occupied Rooms	Peak Parking Demand	Parking Spaces	Excess Parking	Parking Spaces per room
Friday, June 24, 2016	214	187	216	29	0.865
Saturday, June 25, 2016	238	172	216	44	0.796
Sunday, June 26, 2016	211	193	216	23	0.894
Monday, June 27, 2016	225	187	216	29	0.865
Tuesday, June 28, 2016	226	165	216	51	0.764
Wednesday, June 29, 2016	214	200	216	16	0.926
Thursday, June 30, 2016	200	199	216	17	0.921
Friday, July 01, 2016	190	184	216	32	0.851
Saturday, July 02, 2016	219	171	216	45	0.792
Sunday, July 03, 2016	186	183	216	33	0.847
Monday, July 04, 2016	120	167	216	49	0.773

Table 6
Summary of Recommended Parking
for the Valencia Springhill/Residence Inn and the Valencia Holiday Inn Express Hotels,
Wayne Mills Place, Santa Clarita, California

Facility	Rooms	Parking Rate	Required Parking Spaces
Valencia Springhill/Residence Inn	182	0.925/per room	168 Parking Spaces
Valencia Holiday Inn Express	108	0.925/per room	100 Parking Spaces
Total Required Parking	290	0.925/per room	268 Parking Spaces
Proposed Parking:			274 Parking Spaces
Excess Parking:			6 Parking Spaces

Table 7 - Shared Parking for Denny's/ Hotel A

Time	Denny's Restaurant (Area A)		Hotel A (Area B)		Area A + B		
	Shared Parking Percentage (a)	Required Parking Spaces 27	Shared Parking Percentage (a)	Required Parking Spaces 118	Shared Parking Spaces	Available Parking Spaces	Excess Parking Spaces
6:00 AM	25%	7	95	112	119	144	+25
7:00 AM	50%	14	95	112	126	144	+18
8:00 AM	60%	16	90	106	122	144	+22
9:00 AM	75%	20	80	94	115	144	+29
10:00 AM	85%	23	70	83	106	144	+28
11:00 AM	90%	24	70	83	107	144	+26
12:00 PM	100%	27	65	77	104	144	+40
1:00 PM	90%	24	65	77	101	144	+42
2:00 PM	50%	14	70	83	96	144	+47
3:00 PM	45%	21	70	83	103	144	+49
4:00 PM	45%	12	75	89	101	144	+34
5:00 PM	75%	20	80	94	115	144	+19
6:00 PM	80%	22	80	94	116	144	+28
7:00 PM	80%	22	85	100	122	144	+28
8:00 PM	80%	22	90	106	128	144	+16
9:00 PM	60%	16	95	112	128	144	+16
10:00 PM	55%	15	95	112	127	144	+20
11:00 PM	50%	14	100	118	132	144	+12

(a) Based on Urban Land Institute Shared Parking 2nd Edition Report

SUMMARY

- The survey of existing parking demands at the Hotel A and Hotel B facilities found peak parking demand of 0.925 parking spaces per room.
- Application of the 0.925 spaces per room to the proposed 290 room Valencia Springhill Suites/Residence Inn and Holiday Inn Express hotels results in the need for 268 parking spaces.
- The proposed 274 parking spaces results in an excess of six (6) parking spaces for the project.

Please call if you have any questions.

Sincerely,



DARNELL & ASSOCIATES, INC.

Bill E. Darnell, P.E. RCE: 22338

BED/Jam
160605- Valencia Springhill Parking Study doc/09-16



9/14/2016
(Date)

Appendix A

Parking Lot	Zone	Parking Capacity	Thu, 06/23/16				Fri, 06/24/16					
			12-1 PM	5-6 PM	6-7 PM	12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM
Denny's	A1	10		2		6		3	4	4	0	1
	A2	10		4		4		5	5	8	0	4
	A3	18		2		8		5	3	2	2	5
	A4	11		2		4		3	3	6	5	2
	A5	5		2		4		5	3	2	3	2
	A6	2		2		2		2	0	0	1	1
	A7	11		2		10		8	5	6	2	2
	B1	19		9		19		11	10	11	9	8
	B2	11		6		11		7	6	3	6	10
	B3	10		4		10		8	3	4	3	5
Holiday Inn Express	B4	8		5		8		2	1	2	2	2
	B5	2		2		2		2	0	0	0	1
	B6	2		2		2		1	2	2	2	0
	B7	7		1		6		2	1	1	2	2
	B8	9		4		9		8	4	5	3	3
	B9	9		1		8		6	3	1	2	4
	C2	16		7		14		9	6	4	6	7
	C3	17		5		13		15	7	7	4	4
	C4	13		8		12		8	6	6	4	3
	C5	13		2		3		1	0	0	0	1
Best Western	C6	15		4		11		6	3	11	6	8
	C7	7		3		7		2	0	1	0	1
	C8	4		4		4		3	3	1	2	3
	C9	12		8		10		8	4	5	4	4
	C10	18		13		17		9	7	6	7	8

Parking Lot	Zone	Parking Capacity	Sat, 06/25/16					Sun, 06/26/16							
			12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM	12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM
Denny's	A1	10	2	3	8	8	4	0	3	10	10	4	4	2	1
	A2	10	3	1	10	7	4	6	5	2	7	8	8	4	4
	A3	18	2	5	13	13	9	0	3	6	14	18	6	7	6
	A4	11	3	4	8	7	6	3	5	6	9	11	10	6	6
	A5	5	5	4	5	5	4	1	2	4	5	5	4	2	2
	A6	2	2	2	2	1	0	1	1	2	2	2	2	0	0
	A7	11	6	7	8	9	4	5	5	9	9	11	9	6	8
	B1	19	18	19	18	14	6	9	13	19	17	18	15	10	10
	B2	11	11	10	11	5	4	6	7	11	8	11	8	3	9
	B3	10	10	10	8	4	3	5	5	9	7	10	9	4	7
Holiday Inn Express	B4	8	8	7	8	5	2	4	5	4	5	8	7	6	6
	B5	2	2	2	2	0	1	0	1	2	2	2	1	0	0
	B6	2	2	5	2	0	2	2	2	2	2	2	2	2	2
	B7	7	6	2	1	0	1	2	1	5	2	7	2	2	1
	B8	9	9	8	8	5	4	7	7	9	8	9	5	2	2
	B9	9	8	9	7	4	3	4	2	9	8	8	4	2	6
	C2	16			14	5	6	6	6	11	15	13	12	5	6
	C3	17			15	9	7	7	6	7	17	12	7	3	3
	C4	13			11	8	3	2	3	7	13	11	3	5	6
	C5	13			7	1	1	0	0	2	13	9	4	3	0
Best Western	C6	15			13	4	2	6	7	15	14	13	15	7	6
	C7	7			5	0	0	2	2	3	7	6	2	6	13
	C8	4			2	3	1	2	4	4	4	4	3	4	0
	C9	12			11	4	4	5	4	12	12	7	9	7	1
	C10	18			15	6	5	7	11	18	17	14	13	8	8

Parking Lot	Zone	Parking Capacity	Mon, 06/27/16					Tue, 06/28/16									
			12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM	12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM	
Denny's	A1	10	3		3	4	4	6	6	2	6	2	4	4	2	2	8
	A2	10	2		5	5	3	5	6	3	5	5	3	3	4	2	7
	A3	18	5		2	8	8	2	5	4	9	6	2	6	6	2	11
	A4	11	2		6	7	2	3	5	2	4	3	2	2	2	2	9
	A5	5	0		3	2	1	0	2	0	3	3	1	3	1	1	3
	A6	2	0		2	0	1	0	2	2	2	2	1	1	1	1	1
	A7	11	4		7	4	2	4	4	5	1	6	4	3	2	3	9
Holiday Inn Express	B1	19	18		14	12	8	11	19	17	10	8	4	3	2	3	9
	B2	11	10		8	10	6	9	10	10	10	4	4	8	4	4	14
	B3	10	10		7	6	6	5	6	7	8	6	3	4	4	4	10
	B4	8	8		8	5	2	6	6	6	6	4	2	5	5	6	6
	B5	2	2		1	2	2	2	2	2	2	2	1	1	0	2	2
	B6	2	2		2	2	2	2	2	2	2	2	2	2	2	2	2
	B7	7	2		3	2	1	2	2	2	2	6	3	3	0	3	6
	B8	9	6		7	7	2	6	6	4	5	6	2	4	4	8	7
	B9	9	2		8	7	2	6	6	2	5	7	1	1	0	4	7
	C2	16	12		7	5	2	7	7	6	9	13	5	3	4	7	10
Best Western	C3	17	17		12	12	3	10	11	10	12	9	9	7	2	4	4
	C4	13	13		8	8	5	4	10	9	12	10	4	1	2	5	5
	C5	13	13		10	6	1	7	8	10	5	3	0	0	2	3	3
	C6	15	15		9	7	7	4	12	13	15	12	8	5	4	5	7
	C7	7	7		2	0	1	0	7	7	7	3	1	0	2	2	2
	C8	4	4		4	4	3	1	3	4	4	4	3	1	0	3	1
	C9	12	12		8	5	4	6	7	12	12	9	6	2	3	4	4
	C10	18	18		16	10	4	4	15	12	17	13	9	5	5	8	11

Parking Lot	Zone	Parking Capacity	Wed, 06/29/16					Thu, 06/30/16									
			12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM	12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM	
Denny's	A1	10	10	10	8	3	1	5	6	9	9	7	5	3	2	5	6
	A2	10	10	10	7	3	2	6	7	9	9	6	5	3	1	4	6
	A3	18	16	17	10	2	2	6	6	13	13	12	10	5	3	6	7
	A4	11	10	10	9	1	1	5	6	7	7	6	6	4	4	3	4
	A5	5	5	5	4	1	2	4	5	4	4	5	1	2	2	3	4
	A6	2	2	2	2	1	2	1	1	2	2	2	2	1	0	2	2
Holiday Inn Express	A7	11	9	9	9	3	3	4	7	9	11	11	5	4	4	5	6
	B1	19	18	17	14	3	2	8	11	19	17	15	6	5	8	8	8
	B2	11	10	9	8	1	2	7	9	11	10	10	9	5	5	6	7
	B3	10	10	9	7	1	3	7	6	10	10	10	8	4	5	4	5
	B4	8	7	7	6	3	1	4	5	8	7	7	6	1	3	6	6
	B5	2	2	2	2	2	2	2	2	2	2	2	2	0	0	2	2
	B6	2	2	2	2	2	0	1	2	2	2	2	2	2	0	1	2
	B7	7	7	6	4	2	2	2	4	4	7	5	5	2	1	4	5
	B8	9	8	6	5	1	2	3	4	4	8	7	6	3	3	6	6
	B9	9	8	8	7	1	1	2	6	6	9	8	4	0	0	5	5
Best Western	C2	16	16	11	9	5	4	7	6	14	8	8	7	5	6	1	16
	C3	17	9	16	16	6	8	10	12	13	16	14	5	6	11	15	15
	C4	13	13	11	9	4	2	3	4	11	10	12	0	1	11	9	9
	C5	13	12	5	4	0	0	6	5	8	8	7	2	0	5	7	7
	C6	15	15	10	8	2	3	11	10	15	14	14	8	1	2	15	13
	C7	7	7	5	4	0	1	0	6	7	6	6	5	0	0	0	0
	C8	4	4	3	2	2	0	3	3	4	1	1	1	2	1	3	2
	C9	12	12	4	3	4	4	10	4	12	9	9	7	6	5	10	7
	C10	18	18	12	11	6	8	13	13	18	16	16	14	3	4	14	16

Parking Lot	Zone	Parking Capacity	Fri, 07/01/16					Sat, 07/02/16							
			12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM	12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM
Denny's	A1	10	7	5	4	2	1	3	5	5	5	4	1	2	6
	A2	10	6	5	4	1	4	4	4	4	5	4	3	3	5
	A3	18	7	7	5	4	3	6	5	6	4	3	1	4	5
	A4	11	4	4	4	2	3	3	4	5	3	1	2	5	6
	A5	5	4	5	3	2	1	2	3	4	2	1	0	1	2
	A6	2	2	2	2	0	0	1	1	2	2	1	0	2	2
	A7	11	6	9	6	2	4	4	4	6	4	1	2	4	6
	B1	19	9	16	11	3	3	3	5	6	12	9	3	3	6
	B2	11	9	9	7	5	3	4	6	7	7	1	2	3	7
	B3	10	7	10	8	5	3	4	6	7	7	1	2	3	7
Holiday Inn Express	B4	8	7	8	6	3	1	6	8	6	5	1	3	4	5
	B5	2	2	2	2	0	1	2	2	2	2	0	0	0	1
	B6	2	2	2	2	0	0	0	2	2	2	0	0	0	1
	B7	7	6	2	1	2	1	2	1	2	2	1	1	2	2
	B8	9	5	6	5	1	1	3	4	4	6	5	1	2	1
	B9	9	6	5	5	1	1	3	4	5	3	2	1	3	6
	C2	16	15	11	9	4	5	11	12	16	6	9	10	6	5
	C3	17	16	16	16	6	5	8	8	16	5	11	3	5	7
	C4	13	13	12	11	5	9	6	6	13	6	6	4	2	9
	C5	13	8	8	6	3	1	7	7	13	5	5	1	1	8
Best Western	C6	15	15	7	5	6	3	11	11	15	4	4	2	5	8
	C7	7	2	6	5	1	0	6	6	3	1	1	1	2	5
	C8	4	4	3	3	1	0	3	3	4	3	2	1	1	0
	C9	12	11	10	8	8	7	4	4	12	7	3	3	3	0
	C10	18	18	14	12	6	4	13	14	15	18	6	16	6	12

Parking Lot	Zone	Parking Capacity	Tue, 07/05/16						
			12-1 AM	7-8 AM	8-9 AM	11 AM-12 PM	12-1 PM	5-6 PM	6-7 PM
Denny's	A1	10	4	4	3	2	1	4	3
	A2	10	4	3	2	1	0	4	3
	A3	18	6	5	3	1	0	3	2
	A4	11	3	3	2	1	1	6	4
	A5	5	3	3	2	3	2	3	2
	A6	2	2	2	1	1	2	2	2
Holiday Inn Express	A7	11	5	5	4	5	1	4	3
	B1	19	7	8	6	2	1	6	7
	B2	11	6	8	7	3	1	4	4
	B3	10	7	7	6	2	2	4	6
	B4	8	5	6	6	2	2	3	3
	B5	2	2	2	1	0	0	2	0
	B6	2	2	2	1	1	2	2	2
	B7	7	1	2	2	1	2	1	2
	B8	9	5	6	5	3	3	4	5
	B9	9	6	5	4	2	2	4	7
Best Western	C2	16	8	10	9	1		6	6
	C3	17	0	8	8	7		13	8
	C4	13	13	7	5	1		3	8
	C5	13	2	1	0	0		3	6
	C6	15	2	5	3	2		11	7
	C7	7	0	4	1	1		6	5
	C8	4	0	4	3	0		2	3
	C9	12	8	4	2	0		4	4
	C10	18	10	14	13	5		14	9

WAYNE MILLS PLACE PROJECT

AIR QUALITY IMPACT ANALYSIS

PREPARED BY



NOVEMBER 2016

1.0 INTRODUCTION

1.1 Project Location 1.0-1
 1.2 Project Description 1.0-1

2.0 AIR QUALITY

2.1 Existing Setting..... 2.0-1
 2.2 Regulatory Framework 2.0-4
 2.3 Impact Assessment 2.0-9

TABLES

Table 2-1: Criteria Air Pollutants Summary of Common Sources and Effects..... 2.0-2
 Table 2-2: Ambient Air Quality Monitoring Data..... 2.0-3
 Table 2-3: Air Quality Standards 2.0-5
 Table 2-4: Federal and State Ambient Air Quality Attainment Status for Western Los Angeles
 County 2.0-6
 Table 2-5: SCAQMD Regional Significance Thresholds 2.0-10
 Table 2-6: Local Significance Threshold (LST) Analysis Screening Thresholds 2.0-11
 Table 2-7: Construction-Related Emissions 2.0-13
 Table 2-8: Localized Significance of Emissions – Pounds per Day 2.0-14
 Table 2-9: Long-Term Operational Emissions 2.0-15

FIGURES

Figure 1-1 Project Location 1.0-3
 Figure 1-2 Site Plan 1.0-5

APPENDICES

Appendix A Criteria Air Pollutant Modeling Outputs
 Appendix B Traffic Impact Study

This page is intentionally left blank.

1.0 INTRODUCTION

This report evaluates air quality impacts associated with the proposed Wayne Mills Place Project in accordance with methodologies recommended by the California Air Resources Board (CARB) and the South Coast Air Quality Management District (SCAQMD). Analyzed in this report are the project's consistency with applicable plans, policies, and regulations, as well as the introduction of new sources of air pollutants. Where quantification was required, emissions were modeled using the California Emissions Estimator Model (CalEEMod). Technical data is included as Appendix A, *Criteria Air Pollutant Modeling Outputs*.

1.1 PROJECT LOCATION

The project site is located at 27413 Wayne Mills Place in Santa Clarita, California, in Los Angeles County. The site is on the south side of Wayne Mills Place, east of Interstate 5 (I-5) and west of Tourney Road. Nearby communities include Castaic to the north, Acton to the east, and San Fernando to the south. Refer to Figure 1-1, *Project Location*.

Surrounding land uses include I-5 directly to the west, restaurants to the north, a business park to the east, and the Valencia Country Club golf course to the south and east. Six Flags Magic Mountain theme park is on the opposite side of I-5 from the project site.

1.2 PROJECT DESCRIPTION

The project would demolish an existing 120-room Best Western hotel and construct two new hotel buildings in its place, one Holiday Inn Express with 108 rooms and one Springhill Suites/Residence Inn with 182 rooms, on a 4.3-acre site. There would be a total of 192 automobile parking spots with access from an existing driveway located on Wayne Mills Place. Refer to Figure 1-2, *Site Plan*.

This page is intentionally left blank.

T:\GIS\Los Angeles County\Map\Santa Clarita\Wayne Mills\Project Location.mxd (11/12/2016)



Source: Los Angeles County (2016); ESRI.





Figure 1
Project Location



Source: Darnell & Associates, Inc.



Not To Scale

FIGURE 2
Site Plan

2.0 AIR QUALITY

This report describes the existing air quality–related setting in the project region, summarizes applicable air quality regulations, and analyzes potential short- and long-term impacts that could result from implementation of the proposed Wayne Mills Place Project.

2.1 EXISTING SETTING

South Coast Air Basin

CARB divides the state into 15 air basins that share similar meteorological and topographical features. The project site is in the western portion of the South Coast Air Basin (Basin). The Basin is a 6,600-square-mile area bounded by the Pacific Ocean to the west and the San Gabriel, San Bernardino, and San Jacinto mountains to the north and east. The Basin includes all of Orange County and the non-desert portions of Los Angeles, Riverside, and San Bernardino counties, in addition to the San Gorgonio Pass area in Riverside County. The Basin’s terrain and geographical location (i.e., a coastal plain with connecting broad valleys and low hills) determine its distinctive climate.

The general region lies in the semi-permanent high-pressure zone of the eastern Pacific. The climate is mild and tempered by cool sea breezes. The usually mild climatological pattern is interrupted infrequently by periods of extremely hot weather, winter storms, or Santa Ana winds. The extent and severity of the air pollution problem in the Basin is a function of the area’s natural physical characteristics (weather and topography), as well as man-made influences (development patterns and lifestyle). Factors such as wind, sunlight, temperature, humidity, rainfall, and topography all affect the accumulation and/or dispersion of pollutants throughout the Basin.

Air Pollutants of Concern

The air pollutants emitted into the ambient air by stationary and mobile sources are regulated by federal and state laws. These regulated air pollutants are known as “criteria air pollutants” and are categorized into primary and secondary pollutants. Primary air pollutants are those that are emitted directly from sources. Carbon monoxide (CO), reactive organic gases (ROG), nitrogen oxide (NO_x), sulfur dioxide (SO₂), coarse particulate matter (PM₁₀), fine particulate matter (PM_{2.5}), lead, and fugitive dust are primary air pollutants. Of these, CO, SO₂, PM₁₀, and PM_{2.5} are criteria pollutants. ROG and NO_x are criteria pollutant precursors and go on to form secondary criteria pollutants through chemical and photochemical reactions in the atmosphere (for example, ozone (O₃) is formed by a chemical reaction between ROG and NO_x in the presence of sunlight). O₃ and nitrogen dioxide (NO₂) are the principal secondary pollutants.

Sources and health effects commonly associated with criteria pollutants are summarized in Table 2-1, *Criteria Air Pollutants Summary of Common Sources and Effects*.

2.0 AIR QUALITY

TABLE 2-1: CRITERIA AIR POLLUTANTS SUMMARY OF COMMON SOURCES AND EFFECTS

Pollutant	Major Man-Made Sources	Human Health & Welfare Effects
Carbon Monoxide (CO)	An odorless, colorless gas formed when carbon in fuel is not burned completely; a component of motor vehicle exhaust.	Reduces the ability of blood to deliver oxygen to vital tissues, affecting the cardiovascular and nervous system. Impairs vision, causes dizziness, and can lead to unconsciousness or death.
Nitrogen Dioxide (NO ₂)	A reddish-brown gas formed during fuel combustion for motor vehicles and industrial sources. Sources include motor vehicles, electric utilities, and other sources that burn fuel.	Respiratory irritant; aggravates lung and heart problems. Precursor to ozone and acid rain. Contributes to global warming and nutrient overloading which deteriorates water quality. Causes brown discoloration of the atmosphere.
Ozone (O ₃)	Formed by a chemical reaction between volatile organic compounds (VOC) and nitrous oxides (NOx) in the presence of sunlight. VOCs are also commonly referred to as reactive organic gases (ROGs). Common sources of these precursor pollutants include motor vehicle exhaust, industrial emissions, gasoline storage and transport, solvents, paints, and landfills.	Irritates and causes inflammation of the mucous membranes and lung airways; causes wheezing, coughing, and pain when inhaling deeply; decreases lung capacity; aggravates lung and heart problems. Damages plants; reduces crop yield. Damages rubber, some textiles, and dyes.
Particulate Matter (PM ₁₀ and PM _{2.5})	Produced by power plants, steel mills, chemical plants, unpaved roads and parking lots, wood-burning stoves and fireplaces, automobiles, and others.	Increased respiratory symptoms, such as irritation of the airways, coughing, or difficulty breathing; aggravated asthma; development of chronic bronchitis; irregular heartbeat; nonfatal heart attacks; and premature death in people with heart or lung disease. Impairs visibility (haze).
Sulfur Dioxide (SO ₂)	A colorless, nonflammable gas formed when fuel containing sulfur is burned; when gasoline is extracted from oil; or when metal is extracted from ore. Examples are petroleum refineries, cement manufacturing, metal processing facilities, locomotives, and ships.	Respiratory irritant. Aggravates lung and heart problems. In the presence of moisture and oxygen, sulfur dioxide converts to sulfuric acid which can damage marble, iron and steel. Damages crops and natural vegetation. Impairs visibility. Precursor to acid rain.

Source: CAPCOA 2013

Ambient Air Quality

Criteria Air Pollutant Monitoring Data

Ambient air quality in Santa Clarita, and thus at the project site, can be inferred from ambient air quality measurements conducted at air quality monitoring stations. Existing levels of ambient air quality and historical trends in the region are documented by measurements made by the SCAQMD, the air pollution regulatory agency in the air basin that maintains air quality monitoring stations which process ambient air quality measurements.

Ozone, PM₁₀, and PM_{2.5} are the primary pollutants affecting the SCAQMD. The nearest air quality monitoring site to the project site that monitors ambient concentrations of ozone and airborne particulates is the Santa Clarita-Placerita Monitoring Station (22224 Placerita Canyon, Santa Clarita, CA 91321), approximately 4 miles southeast of the project site. Table 2-2, *Ambient Air*

Quality Monitoring Data, summarizes the published data since 2013 for each year that the monitoring data is provided.

TABLE 2-2: AMBIENT AIR QUALITY MONITORING DATA

Pollutant Standards	2013 ¹	2014 ¹	2015 ¹
Ozone			
Maximum 1-hour concentration (ppm)	0.134	0.134	0.126
Maximum 8-hour concentration (ppm) (state/federal)	0.104 / 0.104	0.111 / 0.110	0.109 / 0.108
Number of days above state 1-hour standard	30	32	23
Number of days above state/federal 8-hour standard	58 / 40	65 / 45	55 / 37
Coarse Particulate Matter			
Maximum 24-hour concentration ($\mu\text{g}/\text{m}^3$) (state/federal)	41.0 / 43.0	45.0 / 47.0	39.0 / 41.0
Number of days above state/federal standard	0 / 0	0 / 0	* / 0
Fine Particulate Matter			
Maximum 24-hour concentration ($\mu\text{g}/\text{m}^3$) (state/federal)	29.5 / *	28.9 / *	34.4 / *
Number of days above federal standard	*	*	*

Source: CARB 2015a

Notes: $\mu\text{g}/\text{m}^3$ = micrograms per cubic meter; ppm = parts per million; * = No data is currently available to determine the value.

1. Measurements taken at the Santa Clarita-Placerita Monitoring Station.

Toxic Air Contaminants

In addition to the criteria pollutants discussed above, toxic air contaminants (TACs) are another group of pollutants of concern. TACs are considered either carcinogenic or noncarcinogenic based on the nature of the health effects associated with exposure to the pollutant. For regulatory purposes, carcinogenic TACs are assumed to have no safe threshold below which health impacts would not occur, and cancer risk is expressed as excess cancer cases per one million exposed individuals. Noncarcinogenic TACs differ in that there is generally assumed to be a safe level of exposure below which no negative health impact is believed to occur. These levels are determined on a pollutant-by-pollutant basis.

There are many different types of TACs, with varying degrees of toxicity. Sources of TACs include industrial processes, such as petroleum refining and chrome-plating operations; commercial operations, such as gasoline stations and dry cleaners; and motor vehicle exhaust. Public exposure to TACs can result from emissions from normal operations, as well as from accidental releases of hazardous materials during upset conditions. The health effects associated with TACs are quite diverse and generally are assessed locally, rather than regionally. TACs can cause long-term health effects such as cancer, birth defects, neurological damage, asthma, bronchitis, or genetic damage, or short-term acute effects such as eye watering, respiratory irritation (a cough), runny nose, throat pain, and headaches.

2.0 AIR QUALITY

Since the last update to the TAC list in December 1999, CARB has designated 244 compounds as toxic air contaminants (CARB 1999). Additionally, CARB has implemented control measures for a number of compounds that pose high risks and show potential for effective control. The majority of the estimated health risks from TACs can be attributed to a relatively few compounds.

CARB identified diesel particulate matter (DPM) as a toxic air contaminant. Diesel particulate matter differs from other TACs in that it is not a single substance but rather a complex mixture of hundreds of substances. Diesel exhaust is a complex mixture of particles and gases produced when an engine burns diesel fuel. DPM is a concern because it causes lung cancer; many compounds found in diesel exhaust are carcinogenic. DPM includes the particle-phase constituents in diesel exhaust. The chemical composition and particle sizes of DPM vary between different engine types (heavy-duty, light-duty), engine operating conditions (idle, accelerate, decelerate), fuel formulations (high/low sulfur fuel), and the year of the engine (EPA 2002). Some short-term (acute) effects of diesel exhaust include eye, nose, throat, and lung irritation, and diesel exhaust can cause coughs, headaches, light-headedness, and nausea. DPM poses the greatest health risk among the TACs. Almost all diesel exhaust particle mass is 10 microns or less in diameter. Because of their extremely small size, these particles can be inhaled and eventually trapped in the bronchial and alveolar regions of the lung.

Some land uses are considered more sensitive to air pollution than others due to the types of population groups or activities involved. Sensitive population groups include children, the elderly, the acutely ill, and the chronically ill, especially those with cardiorespiratory diseases.

Residential areas are considered to be sensitive receptors to air pollution because residents (including children and the elderly) tend to be at home for extended periods of time, resulting in sustained exposure to any pollutants present. Children are considered more susceptible to health effects of air pollution due to their immature immune systems and developing organs (OEHHA 2007). As such, schools are also considered sensitive receptors, as children are present for extended durations and engage in regular outdoor activities. Other land uses considered sensitive receptors include playgrounds, childcare centers, long-term healthcare facilities, rehabilitation centers, convalescent centers, and retirement homes. The nearest sensitive receptors are the residences approximately 400 meters southwest of the project site, across I-5.

2.2 REGULATORY FRAMEWORK

Federal and State

Ambient Air Quality Standards

The proposed project has the ability to release gaseous emissions of criteria pollutants and dust into the ambient air; therefore, development activities under the proposed project fall under the ambient air quality standards promulgated at the local, state, and federal levels. The federal Clean Air Act of 1971 and the Clean Air Act Amendments (1977) established the national ambient air quality standards (NAAQS), which are promulgated by the US Environmental Protection

Agency (EPA). The State of California has also adopted its own California ambient air quality standards (CAAQS), which are promulgated by CARB. The project is in Los Angeles County, which is under the air quality regulatory jurisdiction of the South Coast Air Quality Management District, and is therefore subject to the rules and regulations adopted by the air district to achieve the NAAQS and CAAQS. Applicable federal, state, regional, and local laws, regulations, plans, and guidelines relevant to the California Environmental Quality Act (CEQA) review process are summarized below. As shown in Table 2-3, *Air Quality Standards*, these pollutants include O₃, CO, NO₂, SO₂, PM₁₀, PM_{2.5}, and lead. In addition, the State has set standards for sulfates, hydrogen sulfide, vinyl chloride, and visibility-reducing particles. These standards are designed to protect the health and welfare of the populace with a reasonable margin of safety.

TABLE 2-3: AIR QUALITY STANDARDS

Pollutant	Averaging Time	California Standards	National Standards
Ozone (O ₃)	8 Hour	0.070 ppm (137µg/m ³)	0.070 ppm (137µg/m ³)
	1 Hour	0.09 ppm (180 µg/m ³)	—
Carbon Monoxide (CO)	8 Hour	9.0 ppm (10 mg/m ³)	9 ppm (10 mg/m ³)
	1 Hour	20 ppm (23 mg/m ³)	35 ppm (40 mg/m ³)
Nitrogen Dioxide (NO ₂)	1 Hour	0.18 ppm (339 µg/m ³)	100 ppb
	Annual Arithmetic Mean	0.030 ppm (57 µg/m ³)	53 ppb (100 µg/m ³)
Sulfur Dioxide (SO ₂)	24 Hour	0.04 ppm (105 µg/m ³)	N/A
	3 Hour	—	N/A
	1 Hour	0.25 ppm (665 µg/m ³)	75 ppb
Particulate Matter (PM ₁₀)	Annual Arithmetic Mean	20 µg/m ³	N/A
	24 Hour	50 µg/m ³	150 µg/m ³
Particulate Matter – Fine (PM _{2.5})	Annual Arithmetic Mean	12 µg/m ³	15 µg/m ³
	24 Hour	N/A	35 µg/m ³
Sulfates	24 Hour	25 µg/m ³	N/A
Lead	Calendar Quarter	N/A	1.5 µg/m ³
	30 Day Average	1.5 µg/m ³)	N/A
Hydrogen Sulfide	1 Hour	0.03 ppm (42 µg/m ³)	N/A
Vinyl Chloride (chloroethene)	24 Hour	0.01 ppm (26 µg/m ³)	N/A
Visibility-Reducing Particles	8 Hour (10:00 to 18:00 PST)	—	N/A

Source: CARB 2015b

Notes: mg/m³=milligrams per cubic meter; ppm=parts per million; ppb=parts per billion; µg/m³=micrograms per cubic meter

Air Quality Attainment Plans

The SCAQMD and the Southern California Association of Governments (SCAG) are the agencies responsible for preparing the Air Quality Management Plan (AQMP) for the Basin pursuant to the federal Clean Air Act in order to reduce emissions of criteria pollutants for which the Basin is in nonattainment. The SCAQMD's adopted 2012 AQMP establishes a program of rules and

2.0 AIR QUALITY

regulations directed at reducing air pollutant emissions and achieving state (California) and national air quality standards. The 2012 AQMP is a regional and multi-agency effort including the SCAQMD, CARB, SCAG, and the EPA. The 2012 AQMP pollutant control strategies are based on the latest scientific and technical information and planning assumptions, including the 2012 Regional Transportation Plan/Sustainable Communities Strategy, updated emission inventory methodologies for various source categories, and SCAG's latest growth forecasts (SCAQMD 2013). (SCAG's latest growth forecasts were defined in consultation with local governments and with reference to local general plans.)

The AQMP provides local guidance for the State Implementation Plan (SIP), which establishes the framework for air quality basins to achieve attainment of the state and federal ambient air quality standards. Areas that meet ambient air quality standards are classified as attainment areas, while areas that do not meet these standards are classified as nonattainment areas. Areas for which there is insufficient data available are designated unclassified. The attainment status for the western region of Los Angeles County is included in Table 2-4, *Federal and State Ambient Air Quality Attainment Status for Western Los Angeles County*. The region is in nonattainment for state ozone, PM₁₀, and PM_{2.5} standards and nonattainment for federal ozone and PM_{2.5} standards.

TABLE 2-4: FEDERAL AND STATE AMBIENT AIR QUALITY ATTAINMENT STATUS FOR WESTERN LOS ANGELES COUNTY

Pollutant	Federal	State
8-Hour Ozone (O ₃)	Nonattainment	Nonattainment
Coarse Particulate Matter (PM ₁₀)	Attainment	Nonattainment
Fine Particulate Matter (PM _{2.5})	Nonattainment	Nonattainment
Carbon Monoxide (CO)	Unclassified/Attainment	Attainment
Nitrogen Dioxide (NO ₂)	Unclassified/Attainment	Attainment
Sulfur Dioxide (SO ₂)	Attainment	Attainment

Source: CARB 2015c

Toxic Air Contaminant Regulations

In 1983, the California legislature enacted a program to identify the health effects of TACs and to reduce exposure to these contaminants to protect the public health. The Health and Safety Code defines a TAC as "an air pollutant which may cause or contribute to an increase in mortality or in serious illness, or which may pose a present or potential hazard to human health." A substance that is listed as a hazardous air pollutant pursuant to subsection (b) of Section 112 of the federal Clean Air Act (42 United States Code Section 7412[b]) is a TAC. Under state law, the California Environmental Protection Agency, acting through CARB, is authorized to identify a substance as a TAC if it determines the substance is an air pollutant that may cause or contribute to an increase in mortality or to an increase in serious illness, or may pose a present or potential hazard to human health.

California regulates TACs primarily through Assembly Bill (AB) 1807 (Tanner Air Toxics Act) and AB 2588 (Air Toxics “Hot Spot” Information and Assessment Act of 1987). The Tanner Air Toxics Act sets forth a formal procedure for CARB to designate substances as toxic air contaminants. Once a TAC is identified, CARB adopts an “airborne toxics control measure” for sources that emit designated TACs. If there is a safe threshold for a substance (a point below which there is no toxic effect), the control measure must reduce exposure to below that threshold. If there is no safe threshold, the measure must incorporate toxics best available control technology to minimize emissions. To date, CARB has established formal control measures for eleven TACs, all of which are identified as having no safe threshold.

Air toxics from stationary sources are also regulated in California under the Air Toxics “Hot Spot” Information and Assessment Act of 1987. Under AB 2588, TAC emissions from individual facilities are quantified and prioritized by the air quality management district or air pollution control district. High-priority facilities are required to perform a health risk assessment and, if specific thresholds are exceeded, are required to communicate the results to the public in the form of notices and public meetings.

Since the last update to the TAC list in December 1999, CARB has designated 244 compounds as toxic air contaminants (CARB 1999). Additionally, CARB has implemented control measures for a number of compounds that pose high risks and show potential for effective control. The majority of the estimated health risks from TACs can be attributed to relatively few compounds, the most important being particulate matter from diesel-fueled engines.

California Diesel Risk Reduction Plan

In September 2000, CARB adopted the Diesel Risk Reduction Plan (DRRP), which recommends many control measures to reduce the risks associated with DPM and achieve a goal of an 85 percent reduction of DPM generated by 2020. The DRRP incorporates measures to reduce emissions from diesel-fueled vehicles and stationary diesel-fueled engines. CARB’s ongoing efforts to reduce diesel-exhaust emissions from these sources include the development of specific statewide regulations, which are designed to further reduce DPM emissions. The goal of each regulation is to make diesel engines as clean as possible by establishing state-of-the-art technology requirements or emission standards to reduce DPM emissions.

Since the initial adoption of the DRRP in September 2000, CARB has adopted numerous rules related to the reduction of diesel particulate matter from mobile sources, as well as the use of cleaner-burning fuels. Transportation sources addressed by these rules include public transit buses, school buses, on-road heavy-duty trucks, and off-road heavy-duty equipment.

On-Road Heavy-Duty Diesel Vehicles (In Use) Regulation

CARB’s On-Road Heavy-Duty Diesel Vehicles (In Use) Regulation requires diesel trucks and buses that operate in California to be upgraded to reduce emissions. Heavier trucks were required to be retrofitted with particulate matter filters beginning January 1, 2012, and older trucks were

2.0 AIR QUALITY

required to be replaced starting January 1, 2015. By January 1, 2023, nearly all trucks and buses will need to have 2010 model year engines or equivalent. The regulation applies to nearly all privately and federally owned diesel-fueled trucks and buses, as well as to privately and publicly owned school buses with a gross vehicle weight rating greater than 14,000 pounds.

Local

South Coast Air Quality Management District

The SCAQMD is the air pollution control agency for Orange County and the urban portions of Los Angeles, Riverside, and San Bernardino counties. The agency's primary responsibility is ensuring that the federal and state ambient air quality standards are attained and maintained in the South Coast Air Basin. The SCAQMD is also responsible for adopting and enforcing rules and regulations concerning air pollutant sources, issuing permits for stationary sources of air pollutants, inspecting stationary sources of air pollutants, responding to citizen complaints, monitoring ambient air quality and meteorological conditions, awarding grants to reduce motor vehicle emissions, and conducting public education campaigns, as well as many other activities. All projects are subject to SCAQMD rules and regulations in effect at the time of construction.

The following is a list of noteworthy SCAQMD rules that are required of the proposed project during construction activities:

- **Rule 402 (Nuisance).** This rule prohibits the discharge from any source whatsoever such quantities of air contaminants or other material which cause injury, detriment, nuisance, or annoyance to any considerable number of persons or to the public, or which endanger the comfort, repose, health, or safety of any such persons or the public, or which cause, or have a natural tendency to cause, injury or damage to business or property. The rule does not apply to odors emanating from agricultural operations necessary for the growing of crops or the raising of fowl or animals.
- **Rule 403 (Fugitive Dust).** This rule requires fugitive dust sources to implement Best Available Control Measures for all sources, and all forms of visible particulate matter are prohibited from crossing any property line. Rule 403 is intended to reduce PM₁₀ emissions from any transportation, handling, construction, or storage activity that has the potential to generate fugitive dust. Examples of some PM₁₀ suppression techniques are summarized below.
 - a. Portions of the construction site to remain inactive longer than a period of three months will be seeded and watered until grass cover is grown or otherwise stabilized in a manner acceptable to the City.
 - b. All on-site roads will be paved as soon as feasible or watered periodically or chemically stabilized.

- c. All material transported off-site will be either sufficiently watered or securely covered to prevent excessive amounts of dust.
 - d. The area disturbed by clearing, grading, earth moving, or excavation operations will be minimized at all times.
 - e. Where vehicles leave the construction site and enter adjacent public streets, the streets will be swept daily or washed down at the end of the work day to remove soil tracked onto the paved surface.
 - f. A wheel washing system will be installed and used to remove bulk material from tires and vehicle undercarriages before vehicles exit the site.
 - g. Water will be applied to active portions of the site, including unpaved roads, in sufficient quantity.
- **Rule 1113 (Architectural Coatings).** This rule requires manufacturers, distributors, and end-users of architectural and industrial maintenance coatings to reduce ROG emissions from the use of these coatings, primarily by placing limits on the ROG content of various coating categories.

2.3 IMPACT ASSESSMENT

The impact analysis below is based on guidance from the SCAQMD, the applicable air quality control agency for the Basin. According to the SCAQMD, an air quality impact is considered significant if a proposed project would violate any ambient air quality standard, contribute substantially to an existing or projected air quality violation, or expose sensitive receptors to substantial pollutant concentrations.

Methodology

The proposed project's criteria air pollutant emissions were calculated using the California Emissions Estimator Model (CalEEMod), version 2016.3.1 computer program (refer to Appendix A). CalEEMod is a statewide land use emissions computer model designed to provide a uniform platform for the use of government agencies, land use planners, and environmental professionals. This model was developed in coordination with the SCAQMD and is the most current emissions model approved for use in California by various other air districts. Emissions modeling is based on project-specific data (e.g., size and type of proposed use) and vehicle trip information from the project's traffic impact analysis (refer to Appendix B, *Traffic Impact Study*).

Thresholds of Significance

The following thresholds of significance are based, in part, on CEQA Guidelines Appendix G. For purposes of this analysis, the proposed project may have a significant adverse impact related to land use if it would do any of the following:

2.0 AIR QUALITY

- Violate any air quality standard or contribute substantially to an existing or projected air quality violation.
- Conflict with or obstruct implementation of any applicable air quality plan.
- Expose sensitive receptors to substantial pollutant concentrations.
- Create objectionable odors affecting a substantial number of people.
- Result in a cumulatively considerable net increase of any criteria pollutant for which the project region is nonattainment under an applicable federal or state ambient air quality standard (including releasing emissions which exceed quantitative thresholds for ozone precursors).

The significance criteria established by the applicable air quality management or air pollution control district (SCAQMD) may be relied upon to make the above determinations. According to the SCAQMD, an air quality impact is considered significant if a proposed project would violate any ambient air quality standard, contribute substantially to an existing or projected air quality violation, or expose sensitive receptors to substantial pollutant concentrations. The SCAQMD has established thresholds of significance for air quality for construction and operational activities of land use developments, which are applicable to the proposed project, as shown in Table 2-5, *SCAQMD Regional Significance Thresholds*.

TABLE 2-5: SCAQMD REGIONAL SIGNIFICANCE THRESHOLDS

Air Pollutant	Construction Activities	Operations
Reactive Organic Gases (ROG)	75 pounds/day	55 pounds/day
Carbon Monoxide (CO)	550 pounds/day	550 pounds/day
Nitrogen Oxides (NOx)	100 pounds/day	55 pounds/day
Sulfur Oxides (SOx)	150 pounds/day	150 pounds/day
Coarse Particulates (PM10)	150 pounds/day	150 pounds/day
Fine Particulates (PM2.5)	55 pounds/day	55 pounds/day

Source: SCAQMD 1993 (PM_{2.5} threshold adopted June 1, 2007)

Carbon Monoxide Hot-Spot Analysis

In addition to the daily thresholds listed above, the proposed project would be subject to the ambient air quality standards. These standards are addressed through an analysis of localized carbon monoxide impacts. The California 1-hour and 8-hour CO standards are:

- 1-hour = 20 parts per million
- 8-hour = 9 parts per million

The significance of localized impacts depends on whether ambient CO levels in the vicinity of a project are above state and federal CO standards. CO concentrations in Los Angeles County do not exceed the California or national ambient air quality standards criteria, and the Basin has been designated as attainment under the 1-hour and 8-hour standards.

Localized Significance Thresholds

In addition to the CO hot-spot analysis, the SCAQMD developed localized significance thresholds (LSTs) for emissions of NO₂, CO, PM₁₀, and PM_{2.5} generated at new development sites (off-site mobile source emissions are not included in the LST analysis). LST screening thresholds represent the maximum emissions at a project site that are not expected to cause or contribute to an exceedance of the most stringent national or state ambient air quality standard. LST screening thresholds are based on the ambient concentrations of that pollutant within the project source receptor area (SRA), as demarcated by the SCAQMD, and the distance to the nearest sensitive receptor. The project site is located in SCAQMD SRA 13. Table 2-6, *Local Significance Threshold (LST) Analysis Screening Thresholds – Pounds per Day*, shows the screening thresholds for a 1-acre, 2-acre, and 5-acre project site in SRA 13 with sensitive receptors located within 200 meters of a project site.

TABLE 2-6: LOCAL SIGNIFICANCE THRESHOLD (LST) ANALYSIS SCREENING THRESHOLDS – POUNDS PER DAY

Project Size	NO _x	CO	PM ₁₀	PM _{2.5}
1 Acre (construction/operations)	161 / 161	2,500 / 2,500	51 / 13	18 / 5
2 Acres (construction/operations)	190 / 190	3,108 / 3,108	59 / 15	20 / 5
5 Acres (construction/operations)	256 / 256	4,608 / 4,608	79 / 19	26 / 7

Source: SCAQMD 2009

Toxic Air Contaminant Thresholds

The SCAQMD regulates levels of air toxics through a permitting process that covers both construction and operation. The SCAQMD has adopted Rule 1401 for both new and modified sources that use materials classified as air toxics. The SCAQMD CEQA Guidelines for permit processing consider the following types of projects significant:

- Any project involving the emission of a carcinogenic or TAC identified in SCAQMD Rule 1401 that exceeds the maximum individual cancer risk of 1 in 1 million or 10 in 1 million if the project is constructed with best available control strategy for toxics using the procedures in SCAQMD Rule 1401.
- Any project that could accidentally release an acutely hazardous material or routinely release a TAC, posing an acute health hazard.
- Any project that could emit an air contaminant not currently regulated by SCAQMD rule but that is on the federal or state air toxics list.

2.0 AIR QUALITY

Based on these significance thresholds and criteria, the project's effects have been categorized as either "no impact," a "less than significant impact," or a "potentially significant impact." Mitigation measures are recommended for potentially significant impacts. If a potentially significant impact cannot be reduced to a less than significant level through the application of mitigation, it is categorized as a significant and unavoidable impact.

Impact Assessment

Violate Any Air Quality Standards or Contribute Substantially to an Existing or Projected Air Quality Violation During Project Construction

Construction associated with the project would generate short-term emissions of criteria air pollutants. The criteria pollutants of primary concern in the project area include ozone-precursor pollutants (i.e., ROG and NO_x) and PM₁₀. Construction-generated emissions are short term and of temporary duration, lasting only as long as construction activities occur, but have the potential to represent a significant air quality impact.

Construction results in the temporary generation of emissions ensuing from site grading and excavation, road paving, motor vehicle exhaust associated with construction equipment and worker trips, and the movement of construction equipment, especially on unpaved surfaces. Emissions of airborne particulate matter are largely dependent on the amount of ground disturbance associated with site preparation activities as well as weather conditions and the appropriate application of water. Construction-related emissions are expected from site preparation, grading, building construction, paving, architectural coatings, and construction workers commuting. Architectural coatings (i.e., painting) would occur sporadically throughout the building phase, as needed.

The estimate for construction duration is based on CalEEMod model defaults, as are the number and types of equipment that would be used. Please refer to specific detailed modeling inputs/outputs, including construction equipment assumptions, contained in Appendix A.

Construction-Related Regional Air Quality Impacts

The estimated maximum daily construction emissions are summarized in Table 2-7, *Construction-Related Emissions*. As previously stated, all construction projects in the South Coast Air Basin are subject to SCAQMD rules and regulations in effect at the time of construction, including Rule 403 described above. The construction emissions summarized in Table 2-7 account for the quantifiable PM-reducing requirements of SCAQMD Rule 403.

TABLE 2-7: CONSTRUCTION-RELATED EMISSIONS

Construction Activities	Maximum Emissions (pounds per day)					
	Reactive Organic Gases (ROG)	Nitrogen Oxide (NO _x)	Coarse Particulate Matter (PM ₁₀)	Fine Particulate Matter (PM _{2.5})	Carbon Monoxide (CO)	Sulfur Dioxide (SO ₂)
Year 1 (2017)	24.32	57.77	9.92	6.48	52.43	0.11
Year 2 (2018)	23.35	51.09	4.94	3.08	49.25	0.10
SCAQMD Thresholds	75	100	150	55	550	150
Exceed Threshold?	No	No	No	No	No	No

Notes: Emissions calculated using CalEEMod version 2016.3.1. Emission estimates account for the quantifiable PM-reducing requirements of SCAQMD Rule 403, including watering exposed surfaces three times daily; cleaning trackout on adjacent streets, covering stockpiles with tarps; watering all haul roads twice daily; and limiting speeds on unpaved roads to 15 miles per hour. Building construction, paving, and architectural coating assumed to occur simultaneously. Refer to Appendix A for daily emission model outputs.

As shown in Table 2-7, emissions resulting from project construction will not exceed any applicable thresholds. Construction-related regional air quality impacts are considered less than significant.

Construction-Related Localized Air Quality Impacts

Localized significance thresholds were developed in response to the SCAQMD Governing Board's Environmental Justice Enhancement Initiative (I-4). The SCAQMD provided the Final Localized Significance Threshold Methodology (dated June 2003 [revised 2009]) for guidance. The LST methodology assists lead agencies in analyzing localized air quality impacts.

For this project, the appropriate source receptor area (SRA) for the localized significance thresholds is the Santa Clarita Valley area (SRA 13) since this area includes the project site. LSTs apply to CO, NO₂, PM₁₀, and PM_{2.5}. The SCAQMD-produced look-up tables provide screening thresholds for projects that disturb 1 acre, 2 acres, and 5 acres, so 4.3 acres (size of the project site) was interpolated.

The SCAQMD's methodology clearly states that "off-site mobile emissions from the project should not be included in the emissions compared to LSTs." Therefore, for purposes of the construction LST analysis, only emissions included in the CalEEMod "on-site" emissions outputs were considered. The nearest existing sensitive receptors to the development boundaries are the residences located 400 meters from the proposed project site. Therefore, to be conservative, LST screening thresholds for receptors at 200 meters were used in this analysis.

Table 2-8, *Localized Significance of Emissions – Pounds per Day*, presents the results of localized emissions during construction activity. The LST screening thresholds have been adjusted to reflect a maximum disturbance of 4.3 acres for the proposed project.

2.0 AIR QUALITY

TABLE 2-8: LOCALIZED SIGNIFICANCE OF EMISSIONS – POUNDS PER DAY

Activity	Nitrogen Oxide (NO _x)	Coarse Particulate Matter (PM ₁₀)	Fine Particulate Matter (PM _{2.5})	Carbon Monoxide (CO)
Demolition (2017)	42.75	5.47	2.54	23.01
Site Preparation (2017)	52.28	9.79	6.45	23.46
Grading (2017)	33.89	4.28	2.92	17.10
Building Construction, Paving, and Architectural Coating (2017)	45.78	2.98	2.79	32.72
Building Construction, Paving, and Architectural Coating (2018)	39.92	2.49	2.33	31.86
Maximum Daily On-Site Emissions	52.28	9.79	6.45	32.72
SCAQMD Localized Screening Threshold (adjusted for 4.3 acres of disturbance)	240.6	74.3	24.6	4258
Significant?	No	No	No	No

Source: CalEEMod version 2016.3.1.

Notes: Emissions projections account for adherence to various components of SCAQMD Rule 403, including application of water on the project site, employment of wheel washing systems, replacement of ground cover in disturbed areas, sweeping adjacent streets daily, and reestablishing vegetation on inactive portions of the site. Building construction, paving, and architectural coating assumed to occur simultaneously.

As shown in Table 2-8, air pollutant emissions resulting from project construction would not exceed the applicable LST screening thresholds; therefore, this impact is less than significant.

Mitigation Measures: No mitigation measures are required.

Level of Significance: Less than significant impact.

Violate Any Air Quality Standards or Contribute Substantially to an Existing or Projected Air Quality Violation During Project Operation

Operational activities associated with the proposed project will result in emissions of ROG, NO_x, CO, sulfur oxides (SO_x), PM₁₀, and PM_{2.5}. Operational emissions would be expected from the following primary sources: vehicles, combustion of natural gas and electricity, landscape maintenance equipment, consumer products, and architectural coatings.

Operations-Related Regional Air Quality Impacts

The project's operations-related regional emissions burdens (as calculated with the CalEEMod program), along with a comparison of SCAQMD-recommended significance thresholds, are shown in Table 2-9, *Long-Term Operational Emissions*.

TABLE 2-9: LONG-TERM OPERATIONAL EMISSIONS

Source	Pollutant (pounds/day)					
	Reactive Organic Gases (ROG)	Nitrogen Oxide (NO _x)	Coarse Particulate Matter (PM ₁₀)	Fine Particulate Matter (PM _{2.5})	Carbon Monoxide (CO)	Sulfur Dioxide (SO ₂)
Summer Emissions						
Area Source	9.44	0.00	0.00	0.00	0.05	0.00
Energy Use	0.30	2.72	0.21	0.21	2.29	0.02
Mobile Source	5.40	22.44	7.41	2.24	64.41	0.17
Total	15.15	25.16	7.62	2.45	66.75	0.19
<i>Potentially Significant Impact Threshold (Daily Emissions)</i>	55	55	550	150	150	55
Exceed Daily Threshold?	No	No	No	No	No	No
Winter Emissions						
Area Source	9.44	0.00	0.00	0.00	0.05	0.00
Energy Use	0.30	2.72	0.21	0.21	2.29	0.02
Mobile Source	5.28	23.01	7.41	2.24	62.29	0.17
Total	15.03	25.73	7.62	2.45	64.62	0.18
<i>Potentially Significant Impact Threshold (Daily Emissions)</i>	55	55	550	150	150	55
Exceed Daily Threshold?	No	No	No	No	No	No

Notes: Emissions calculated using CalEEMod version 2016.3.1.

Refer to Appendix A for daily emission model outputs.

As shown in Table 2-9, emissions resulting from project operations would not exceed the SCAQMD regional emissions thresholds for operational activity. Therefore, this impact is less than significant.

Operations-Related Localized Air Quality Impacts

According to the SCAQMD methodology, LSTs apply to the operational phase of a proposed project if the project includes stationary sources or attracts mobile sources that may spend long periods queuing and idling at the site (e.g., warehouse or transfer facilities). Since the proposed project does not include these types of sources, an analysis of operational LSTs is not required.

Level of Significance: Less than significant impact.

Mitigation Measures: No mitigation measures are required.

Conflict with or Obstruct Implementation of the Applicable Air Quality Plan

As part of its enforcement responsibilities, the EPA requires each state with nonattainment areas to prepare and submit a State Implementation Plan (SIP) that demonstrates the means to attain the federal standards. The SIP must integrate federal, state, and local plan components and regulations to identify specific measures to reduce pollution in nonattainment areas, using a

2.0 AIR QUALITY

combination of performance standards and market-based programs. Similarly, under state law, the California Clean Air Act requires an air quality attainment plan to be prepared for areas designated as nonattainment with regard to the federal and state ambient air quality standards. Air quality attainment plans outline emissions limits and control measures to achieve and maintain these standards by the earliest practical date.

As previously mentioned, the project site is located in the South Coast Air Basin, which is under the jurisdiction of the SCAQMD. The SCAQMD is required, pursuant to the federal Clean Air Act, to reduce emissions of criteria pollutants for which the air basin is in nonattainment. In order to reduce such emissions, the SCAQMD drafted an Air Quality Management Plan (AQMP). There is currently a draft 2016 AQMP, but it has not yet been adopted (as of November 2016). Therefore, the project will be analyzed against the adopted 2012 AQMP. The 2012 AQMP establishes a program of rules and regulations directed at reducing air pollutant emissions and achieving state (California) and national air quality standards. The pollutant control strategies in the 2012 AQMP are based on the latest scientific and technical information and planning assumptions, including the 2016 Regional Transportation Plan/Sustainable Communities Strategy, updated emission inventory methodologies for various source categories, and SCAG's latest growth forecasts (SCAQMD 2013). (SCAG's latest growth forecasts were defined in consultation with local governments and with reference to local general plans.)

Criteria for determining consistency with the AQMP are defined by the following indicators:

- Consistency Criterion No. 1: The proposed project will not result in an increase in the frequency or severity of existing air quality violations, or cause or contribute to new violations, or delay the timely attainment of air quality standards or the interim emissions reductions specified in the AQMP.
- Consistency Criterion No. 2: The proposed project will not exceed the assumptions in the AQMP or increments based on the years of the project buildout phase.

The violations to which Consistency Criterion No. 1 refer are the California ambient air quality standards (CAAQS) and the national ambient air quality standards (NAAQS). As evaluated above, the project would not exceed the SCAQMD short-term construction thresholds or SCAQMD long-term operational thresholds. The project would not result in an increase in the frequency or severity of existing air quality violations, or cause or contribute to new violations, or delay the timely attainment of air quality standards. Thus, a less than significant impact is expected, and the project would be consistent with the first criterion.

Concerning Consistency Criterion No. 2, the AQMP contains air pollutant reduction strategies and demonstrates that the applicable ambient air quality standards can be achieved within the time frames required under federal law. Growth projections from local general plans adopted by cities in the district are provided to SCAG, which develops regional growth forecasts that are used to develop future air quality forecasts for the AQMP. Development consistent with the growth

projections in the City of Santa Clarita General Plan is considered to be consistent with the AQMP. The proposed project is consistent with the land use designation and development density specified in the General Plan and therefore would not exceed the population or job growth projections used by the SCAQMD to develop the Air Quality Management Plan. Thus, no impact would occur, as the project is consistent with both criteria.

Mitigation Measures: No mitigation measures are required.

Level of Significance: Less than significant impact.

Expose Sensitive Receptors to Substantial Pollutant Concentrations

Sensitive receptors are defined as facilities or land uses that include members of the population who are particularly sensitive to the effects of air pollutants, such as children, the elderly, and people with illnesses. Examples of these sensitive receptors are residences, schools, hospitals, and daycare centers. The California Air Resources Board (CARB) has identified the following groups of individuals as the most likely to be affected by air pollution: the elderly over 65, children under 14, athletes, and persons with cardiovascular and chronic respiratory diseases such as asthma, emphysema, and bronchitis. As previously stated, the nearest sensitive receptors are the residences approximately 400 meters southwest of the project site, across I-5.

Construction-Generated Air Toxics

Construction-generated diesel PM emissions contribute to negative health impacts when construction is extended over lengthy periods of time. The use of diesel-powered equipment during construction would be temporary and episodic and would occur over several locations isolated from one another. Furthermore, the proposed project would be subject to and would comply with California regulations limiting vehicle idling to no more than 5 minutes, which would further reduce nearby sensitive receptors' exposure to temporary and variable diesel particulate matter emissions. Project construction would not be a substantial source of other CARB-identified TACs.

Construction projects on a site of less than 5 acres are generally considered to represent less than significant health risk impacts due to (1) limitations on the off-road diesel equipment able to operate and thus a reduced amount of generated DPM, (2) the reduced amount of dust-generating ground disturbance possible compared to larger construction sites, and (3) the reduced duration of construction activities compared to the development of larger sites. For these reasons and because diesel fumes disperse rapidly over relatively short distances, DPM generated by most construction activities, in and of itself, would not be expected to create conditions where the probability of contracting cancer is greater than 10 in 1 million for nearby receptors. Since the project site is 4.3 acres, a less than significant impact is expected.

In addition, SCAQMD Rule 403 requires that basic construction mitigation measures are employed during all construction projects, including measures that would substantially reduce nuisance fugitive dust.

2.0 AIR QUALITY

Furthermore, as discussed in the LST analysis previously presented, results indicate that the proposed project would not exceed the SCAQMD localized significance thresholds, and a less than significant impact is expected during construction activity. LSTs were developed in response to environmental justice and health concerns raised by the public regarding exposure of individuals to criteria pollutants in local communities. Therefore, sensitive receptors would not be subject to a significant air quality impact during project construction. This impact is less than significant.

Carbon Monoxide Hot Spots

CO emissions are a function of vehicle idling time, meteorological conditions, and traffic flow. Under certain extreme meteorological conditions, CO concentrations near a congested roadway or intersection may reach unhealthful levels (i.e., adversely affecting residents, schoolchildren, hospital patients, the elderly, etc.).

The Basin is designated as an unclassified/attainment area for the federal CO standards and an attainment area for state standards. There has been a decline in CO emissions even though vehicle miles traveled on urban and rural roads in the United States have increased. On-road mobile source CO emissions declined 24 percent between 1989 and 1998, despite a 23 percent rise in motor vehicle miles traveled over the same 10 years. California trends have been consistent with national trends; CO emissions declined 20 percent in California from 1985 through 1997, while vehicle miles traveled increased 18 percent in the 1990s. Three major control programs have contributed to the reduced per-vehicle CO emissions: exhaust standards, cleaner-burning fuels, and motor vehicle inspection/maintenance programs.

A detailed CO analysis was conducted in the Federal Attainment Plan for Carbon Monoxide (CO Plan) for the SCAQMD's 2003 Air Quality Management Plan. The locations selected for microscale modeling in the CO Plan are worst-case intersections in the Basin and would likely experience the highest CO concentrations. Thus, the CO analysis in the CO Plan is used in a comparison to the proposed project, since it represents a worst-case scenario with heavy traffic volumes within the Basin.

Of the studied locations, the Wilshire Boulevard/Veteran Avenue intersection in Los Angeles experienced the highest CO concentration (4.6 parts per million [ppm]), which is well below the 35-ppm 1-hour CO federal standard. The Wilshire Boulevard/Veteran Avenue intersection is one of the most congested intersections in Southern California with an average daily traffic (ADT) volume of approximately 100,000 vehicles per day. Because CO hot spots were not experienced at the Wilshire Boulevard/Veteran Avenue intersection, it can be reasonably inferred that CO hot spots would not be experienced at any intersections near the project site due to the addition of approximately 1,237 daily trips that would occur as a result of project implementation. Therefore, impacts would be less than significant in this regard.

Mitigation Measures: No mitigation measures are required.

Level of Significance: Less than significant impact.

Create Objectionable Odors Affecting a Substantial Number of People

Typically, odors are regarded as an annoyance rather than a health hazard. However, manifestations of a person's reaction to foul odors can range from psychological (e.g., irritation, anger, or anxiety) to physiological (e.g., circulatory and respiratory effects, nausea, vomiting, and headache).

With respect to odors, the human nose is the sole sensing device. The ability to detect odors varies considerably among the population and overall is quite subjective. Some individuals have the ability to smell minute quantities of specific substances; others may not have the same sensitivity but may have sensitivities to odors of other substances. In addition, people may have different reactions to the same odor; in fact, an odor that is offensive to one person (e.g., from a fast-food restaurant) may be perfectly acceptable to another. It is also important to note that an unfamiliar odor is more easily detected and is more likely to cause complaints than a familiar one. This is because of the phenomenon known as odor fatigue, in which a person can become desensitized to almost any odor and recognition only occurs with an alteration in the intensity.

Quality and intensity are two properties present in any odor. The quality of an odor indicates the nature of the smell experience. For instance, if a person describes an odor as flowery or sweet, then the person is describing the quality of the odor. Intensity refers to the strength of the odor. For example, a person may use the word "strong" to describe the intensity of an odor. Odor intensity depends on the odorant concentration in the air. When an odorous sample is progressively diluted, the odorant concentration decreases. As this occurs, the odor intensity weakens and eventually becomes so low that the detection or recognition of the odor is quite difficult. At some point during dilution, the concentration of the odorant reaches a detection threshold. An odorant concentration below the detection threshold means that the concentration in the air is not detectable by the average human.

Construction activities associated with the project may generate detectable odors from heavy-duty equipment exhaust. Construction-related odors would be short-term in nature and cease upon project completion. Additionally, construction-related odors dissipate rapidly, as the nature of construction necessitates the need to move equipment around the construction site throughout a workday. Any construction-related impacts to existing adjacent land uses would be short term and are less than significant.

In terms of operational activities, the SCAQMD (1993) CEQA Air Quality Handbook identifies land uses associated with odor complaints. These include agricultural uses, wastewater treatment plants, food processing plants, chemical plants, composting, refineries, landfills, dairies, and fiberglass molding. The proposed project does not include any uses identified by the SCAQMD as being associated with odors. Any operational-related impacts to existing adjacent land uses would be less than significant.

2.0 AIR QUALITY

Mitigation Measures: No mitigation measures are required.

Level of Significance: Less than significant impact.

Result in a Cumulatively Considerable Net Increase of any Criteria Pollutant for Which the Project Region is Nonattainment Under an Applicable Federal or State Ambient Air Quality Standard (Including Releasing Emissions Which Exceed Quantitative Thresholds for Ozone Precursors)

Projects could contribute to an existing or projected air quality exceedance because the western region of Los Angeles County is currently in nonattainment for state ozone, PM₁₀, and PM_{2.5} standards and nonattainment for federal ozone and PM_{2.5} standards. With regard to determining the significance of the cumulative contribution from the project, the SCAQMD recommends that any given project's potential contribution to cumulative impacts be assessed using the same significance criteria as for project-specific impacts. Individual projects that do not generate operational or construction emissions exceeding the SCAQMD's daily thresholds for project-specific impacts would also not cause a cumulatively considerable increase in emissions for those pollutants for which the air basin is in nonattainment, and therefore would not be considered to have a significant, adverse air quality impact. Alternatively, individual project-related construction and operational emissions that exceed SCAQMD thresholds for project-specific impacts would be considered cumulatively considerable. As previously noted, the project will not exceed the applicable SCAQMD regional thresholds for construction and operational-source emissions. As such, the project will result in a less than cumulatively considerable impact.

Mitigation Measures: No mitigation measures are required.

Level of Significance: Less than cumulatively considerable impact.

References

- CAPCOA (California Air Pollution Control Officers Association). 2013. *Health Effects*. Accessed October 2016. www.capcoa.org/health-effects/.
- CARB (California Air Resources Board). 1999. *Final Staff Report: Update to the Toxic Air Contaminant List*.
- . 2015a. Aerometric Data Analysis and Management System (ADAM) Air Quality Data Statistics. Accessed October 2016. <http://www.arb.ca.gov/adam/index.html>.
- . 2015b. Ambient Air Quality Standards. Accessed October 2016. <http://www.arb.ca.gov/research/aaqs/aaqs2.pdf>.
- . 2015c. State and Federal Area Designation Maps. Accessed October 2016. <http://www.arb.ca.gov/desig/adm/adm.htm>.
- EPA (US Environmental Protection Agency). 2002. Health Assessment Document for Diesel Engine Exhaust. <http://cfpub.epa.gov/ncea/cfm/recordisplay.cfm?deid=29060>.
- OEHHA (Office of Environmental Health Hazard Assessment). 2007. Air Toxicology and Epidemiology: Air Pollution and Children's Health. http://oehha.ca.gov/public_info/facts/airkids.html.
- SCAQMD (South Coast Air Quality Management District). 1993. *CEQA Air Quality Handbook*.
- . 2009. Localized Significance Threshold Appendix C – Mass Rate LST Look-up Tables. www.aqmd.gov/ceqa/handbook/LST/LST.html.
- . 2013. *Final 2012 Air Quality Management Plan*.

APPENDICES

APPENDIX A
CRITERIA AIR POLLUTANT MODELING
OUTPUTS

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

Wayne Mills Place Project
Los Angeles-South Coast County, Summer

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Hotel	108.00	Room	1.30	156,816.00	0
Hotel	182.00	Room	2.30	264,264.00	0
Parking Lot	192.00	Space	0.70	76,800.00	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	33
Climate Zone	9			Operational Year	2018
Utility Company	Southern California Edison				
CO2 Intensity (lb/MWhr)	702.44	CH4 Intensity (lb/MWhr)	0.029	N2O Intensity (lb/MWhr)	0.006

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - Acreage adjusted per project applicant.

Construction Phase - Construction, paving, and painting assumed to occur simultaneously.

Demolition -

Vehicle Trips - Adjusted rates per traffic report.

Construction Off-road Equipment Mitigation - Per SCAQMD CEQA Handbook.

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

Table Name	Column Name	Default Value	New Value
tblConstDustMitigation	CleanPavedRoadPercentReduction	0	40
tblConstDustMitigation	WaterUnpavedRoadVehicleSpeed	40	15
tblConstructionPhase	NumDays	18.00	230.00
tblConstructionPhase	NumDays	18.00	230.00
tblConstructionPhase	PhaseEndDate	4/23/2018	3/2/2018
tblConstructionPhase	PhaseEndDate	3/28/2018	3/2/2018
tblConstructionPhase	PhaseStartDate	3/29/2018	4/15/2017
tblConstructionPhase	PhaseStartDate	3/3/2018	4/15/2017
tblLandUse	LotAcreage	3.60	1.30
tblLandUse	LotAcreage	6.07	2.30
tblLandUse	LotAcreage	1.73	0.70
tblVehicleTrips	ST_TR	8.19	4.27
tblVehicleTrips	SU_TR	5.95	4.27
tblVehicleTrips	WD_TR	8.17	4.27

2.0 Emissions Summary

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Area	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127
Energy	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264
Mobile	5.4037	22.4374	64.4136	0.1749	7.2023	0.2070	7.4092	2.0473	0.1947	2.2420		17,733.7558	17,733.7558	1.1077		17,761.4482
Total	15.1479	25.1614	66.7512	0.1912	7.2023	0.4142	7.6164	2.0473	0.4019	2.4492		21,002.0664	21,002.0664	1.1706	0.0599	21,049.1873

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Area	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127
Energy	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264
Mobile	5.4037	22.4374	64.4136	0.1749	7.2023	0.2070	7.4092	2.0473	0.1947	2.2420		17,733.7558	17,733.7558	1.1077		17,761.4482
Total	15.1479	25.1614	66.7512	0.1912	7.2023	0.4142	7.6164	2.0473	0.4019	2.4492		21,002.0664	21,002.0664	1.1706	0.0599	21,049.1873

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N2O	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Demolition	Demolition	3/1/2017	3/28/2017	5	20	
2	Site Preparation	Site Preparation	3/29/2017	4/4/2017	5	5	
3	Grading	Grading	4/5/2017	4/14/2017	5	8	
4	Building Construction	Building Construction	4/15/2017	3/2/2018	5	230	
5	Paving	Paving	4/15/2017	3/2/2018	5	230	
6	Architectural Coating	Architectural Coating	4/15/2017	3/2/2018	5	230	

Acres of Grading (Site Preparation Phase): 0

Acres of Grading (Grading Phase): 4

Acres of Paving: 0.7

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 631,620; Non-Residential Outdoor: 210,540; Striped Parking Area: 4,608 (Architectural Coating – sqft)

OffRoad Equipment

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Architectural Coating	Air Compressors	1	6.00	78	0.48
Paving	Cement and Mortar Mixers	2	6.00	9	0.56
Demolition	Concrete/Industrial Saws	1	8.00	81	0.73
Demolition	Excavators	3	8.00	158	0.38
Building Construction	Cranes	1	7.00	231	0.29
Building Construction	Forklifts	3	8.00	89	0.20
Grading	Excavators	1	8.00	158	0.38
Paving	Pavers	1	8.00	130	0.42
Paving	Rollers	2	6.00	80	0.38
Demolition	Rubber Tired Dozers	2	8.00	247	0.40
Grading	Rubber Tired Dozers	1	8.00	247	0.40
Building Construction	Tractors/Loaders/Backhoes	3	7.00	97	0.37
Building Construction	Generator Sets	1	8.00	84	0.74
Grading	Tractors/Loaders/Backhoes	3	8.00	97	0.37
Paving	Tractors/Loaders/Backhoes	1	8.00	97	0.37
Site Preparation	Tractors/Loaders/Backhoes	4	8.00	97	0.37
Grading	Graders	1	8.00	187	0.41
Paving	Paving Equipment	2	6.00	132	0.36
Site Preparation	Rubber Tired Dozers	3	8.00	247	0.40
Building Construction	Welders	1	8.00	46	0.45

Trips and VMT

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Architectural Coating	1	42.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	9	209.00	82.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Demolition	6	15.00	0.00	793.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	6	15.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	8	20.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Site Preparation	7	18.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

- Use Soil Stabilizer
- Replace Ground Cover
- Water Exposed Area
- Reduce Vehicle Speed on Unpaved Roads
- Clean Paved Roads

3.2 Demolition - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					8.5757	0.0000	8.5757	1.2984	0.0000	1.2984			0.0000			0.0000
Off-Road	4.1031	42.7475	23.0122	0.0388		2.1935	2.1935		2.0425	2.0425		3,924.2833	3,924.2833	1.0730		3,951.1070
Total	4.1031	42.7475	23.0122	0.0388	8.5757	2.1935	10.7692	1.2984	2.0425	3.3410		3,924.2833	3,924.2833	1.0730		3,951.1070

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.2 Demolition - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.4476	13.7825	2.8148	0.0325	0.6932	0.0728	0.7660	0.1900	0.0696	0.2597		3,500.4636	3,500.4636	0.2446		3,506.5776
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0938	0.0720	0.9234	1.9500e-003	0.1677	1.5600e-003	0.1692	0.0445	1.4400e-003	0.0459		193.3376	193.3376	8.0300e-003		193.5383
Total	0.5414	13.8544	3.7382	0.0344	0.8608	0.0744	0.9352	0.2345	0.0711	0.3056		3,693.8012	3,693.8012	0.2526		3,700.1159

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					3.2802	0.0000	3.2802	0.4967	0.0000	0.4967			0.0000			0.0000
Off-Road	4.1031	42.7475	23.0122	0.0388		2.1935	2.1935		2.0425	2.0425	0.0000	3,924.2833	3,924.2833	1.0730		3,951.1070
Total	4.1031	42.7475	23.0122	0.0388	3.2802	2.1935	5.4737	0.4967	2.0425	2.5392	0.0000	3,924.2833	3,924.2833	1.0730		3,951.1070

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.2 Demolition - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.4476	13.7825	2.8148	0.0325	0.4835	0.0728	0.5563	0.1385	0.0696	0.2082		3,500.4636	3,500.4636	0.2446		3,506.5776
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0938	0.0720	0.9234	1.9500e-003	0.1094	1.5600e-003	0.1109	0.0302	1.4400e-003	0.0316		193.3376	193.3376	8.0300e-003		193.5383
Total	0.5414	13.8544	3.7382	0.0344	0.5929	0.0744	0.6672	0.1687	0.0711	0.2398		3,693.8012	3,693.8012	0.2526		3,700.1159

3.3 Site Preparation - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					18.0663	0.0000	18.0663	9.9307	0.0000	9.9307			0.0000			0.0000
Off-Road	4.9608	52.2754	23.4554	0.0380		2.8786	2.8786		2.6483	2.6483		3,894.9500	3,894.9500	1.1934		3,924.7852
Total	4.9608	52.2754	23.4554	0.0380	18.0663	2.8786	20.9448	9.9307	2.6483	12.5790		3,894.9500	3,894.9500	1.1934		3,924.7852

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.3 Site Preparation - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1126	0.0863	1.1081	2.3300e-003	0.2012	1.8700e-003	0.2031	0.0534	1.7300e-003	0.0551		232.0052	232.0052	9.6300e-003		232.2460
Total	0.1126	0.0863	1.1081	2.3300e-003	0.2012	1.8700e-003	0.2031	0.0534	1.7300e-003	0.0551		232.0052	232.0052	9.6300e-003		232.2460

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					6.9103	0.0000	6.9103	3.7985	0.0000	3.7985			0.0000			0.0000
Off-Road	4.9608	52.2754	23.4554	0.0380		2.8786	2.8786		2.6483	2.6483	0.0000	3,894.9500	3,894.9500	1.1934		3,924.7852
Total	4.9608	52.2754	23.4554	0.0380	6.9103	2.8786	9.7889	3.7985	2.6483	6.4468	0.0000	3,894.9500	3,894.9500	1.1934		3,924.7852

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.3 Site Preparation - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1126	0.0863	1.1081	2.3300e-003	0.1312	1.8700e-003	0.1331	0.0362	1.7300e-003	0.0379		232.0052	232.0052	9.6300e-003		232.2460
Total	0.1126	0.0863	1.1081	2.3300e-003	0.1312	1.8700e-003	0.1331	0.0362	1.7300e-003	0.0379		232.0052	232.0052	9.6300e-003		232.2460

3.4 Grading - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					6.5523	0.0000	6.5523	3.3675	0.0000	3.3675			0.0000			0.0000
Off-Road	3.0705	33.8868	17.1042	0.0297		1.7774	1.7774		1.6352	1.6352		3,037.9107	3,037.9107	0.9308		3,061.1809
Total	3.0705	33.8868	17.1042	0.0297	6.5523	1.7774	8.3298	3.3675	1.6352	5.0027		3,037.9107	3,037.9107	0.9308		3,061.1809

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.4 Grading - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0938	0.0720	0.9234	1.9500e-003	0.1677	1.5600e-003	0.1692	0.0445	1.4400e-003	0.0459		193.3376	193.3376	8.0300e-003		193.5383
Total	0.0938	0.0720	0.9234	1.9500e-003	0.1677	1.5600e-003	0.1692	0.0445	1.4400e-003	0.0459		193.3376	193.3376	8.0300e-003		193.5383

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					2.5063	0.0000	2.5063	1.2881	0.0000	1.2881			0.0000			0.0000
Off-Road	3.0705	33.8868	17.1042	0.0297		1.7774	1.7774		1.6352	1.6352	0.0000	3,037.9107	3,037.9107	0.9308		3,061.1809
Total	3.0705	33.8868	17.1042	0.0297	2.5063	1.7774	4.2837	1.2881	1.6352	2.9233	0.0000	3,037.9107	3,037.9107	0.9308		3,061.1809

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.4 Grading - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.0938	0.0720	0.9234	1.9500e-003	0.1094	1.5600e-003	0.1109	0.0302	1.4400e-003	0.0316		193.3376	193.3376	8.0300e-003		193.5383
Total	0.0938	0.0720	0.9234	1.9500e-003	0.1094	1.5600e-003	0.1109	0.0302	1.4400e-003	0.0316		193.3376	193.3376	8.0300e-003		193.5383

3.5 Building Construction - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791		2,650.9797	2,650.9797	0.6531		2,667.3078
Total	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791		2,650.9797	2,650.9797	0.6531		2,667.3078

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.5 Building Construction - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.4281	10.6916	3.0420	0.0218	0.5249	0.0896	0.6145	0.1511	0.0857	0.2368		2,317.2620	2,317.2620	0.1602		2,321.2678
Worker	1.3070	1.0024	12.8662	0.0271	2.3361	0.0217	2.3579	0.6196	0.0201	0.6396		2,693.8377	2,693.8377	0.1118		2,696.6336
Total	1.7350	11.6940	15.9082	0.0489	2.8611	0.1113	2.9723	0.7707	0.1057	0.8764		5,011.0997	5,011.0997	0.2721		5,017.9013

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791	0.0000	2,650.9797	2,650.9797	0.6531		2,667.3078
Total	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791	0.0000	2,650.9797	2,650.9797	0.6531		2,667.3078

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.5 Building Construction - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.4281	10.6916	3.0420	0.0218	0.3753	0.0896	0.4649	0.1144	0.0857	0.2001		2,317.2620	2,317.2620	0.1602		2,321.2678
Worker	1.3070	1.0024	12.8662	0.0271	1.5237	0.0217	1.5455	0.4202	0.0201	0.4402		2,693.8377	2,693.8377	0.1118		2,696.6336
Total	1.7350	11.6940	15.9082	0.0489	1.8991	0.1113	2.0103	0.5346	0.1057	0.6403		5,011.0997	5,011.0997	0.2721		5,017.9013

3.5 Building Construction - 2018

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099		2,620.9351	2,620.9351	0.6421		2,636.9883
Total	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099		2,620.9351	2,620.9351	0.6421		2,636.9883

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.5 Building Construction - 2018

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.3772	10.0499	2.7478	0.0217	0.5249	0.0708	0.5958	0.1511	0.0678	0.2189		2,309.771 2	2,309.771 2	0.1521		2,313.573 5
Worker	1.1547	0.8714	11.2876	0.0263	2.3361	0.0208	2.3570	0.6196	0.0192	0.6388		2,620.211 8	2,620.211 8	0.0983		2,622.668 6
Total	1.5319	10.9213	14.0353	0.0480	2.8611	0.0917	2.9527	0.7707	0.0870	0.8576		4,929.983 0	4,929.983 0	0.2504		4,936.242 1

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099	0.0000	2,620.935 1	2,620.935 1	0.6421		2,636.988 3
Total	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099	0.0000	2,620.935 1	2,620.935 1	0.6421		2,636.988 3

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.5 Building Construction - 2018

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.3772	10.0499	2.7478	0.0217	0.3753	0.0708	0.4462	0.1144	0.0678	0.1822		2,309.771 2	2,309.771 2	0.1521		2,313.573 5
Worker	1.1547	0.8714	11.2876	0.0263	1.5237	0.0208	1.5446	0.4202	0.0192	0.4394		2,620.211 8	2,620.211 8	0.0983		2,622.668 6
Total	1.5319	10.9213	14.0353	0.0480	1.8991	0.0917	1.9907	0.5346	0.0870	0.6215		4,929.983 0	4,929.983 0	0.2504		4,936.242 1

3.6 Paving - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.6763	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376		1,901.776 6	1,901.776 6	0.5674		1,915.960 4
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.6843	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376		1,901.776 6	1,901.776 6	0.5674		1,915.960 4

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.6 Paving - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1251	0.0959	1.2312	2.5900e-003	0.2236	2.0800e-003	0.2256	0.0593	1.9200e-003	0.0612		257.7835	257.7835	0.0107		258.0511
Total	0.1251	0.0959	1.2312	2.5900e-003	0.2236	2.0800e-003	0.2256	0.0593	1.9200e-003	0.0612		257.7835	257.7835	0.0107		258.0511

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.6763	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376	0.0000	1,901.7766	1,901.7766	0.5674		1,915.9604
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.6843	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376	0.0000	1,901.7766	1,901.7766	0.5674		1,915.9604

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.6 Paving - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1251	0.0959	1.2312	2.5900e-003	0.1458	2.0800e-003	0.1479	0.0402	1.9200e-003	0.0421		257.7835	257.7835	0.0107		258.0511
Total	0.1251	0.0959	1.2312	2.5900e-003	0.1458	2.0800e-003	0.1479	0.0402	1.9200e-003	0.0421		257.7835	257.7835	0.0107		258.0511

3.6 Paving - 2018

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.4239	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718		1,872.5505	1,872.5505	0.5672		1,886.7312
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.4319	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718		1,872.5505	1,872.5505	0.5672		1,886.7312

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.6 Paving - 2018

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1105	0.0834	1.0802	2.5200e-003	0.2236	1.9900e-003	0.2256	0.0593	1.8400e-003	0.0611		250.7380	250.7380	9.4000e-003		250.9731
Total	0.1105	0.0834	1.0802	2.5200e-003	0.2236	1.9900e-003	0.2256	0.0593	1.8400e-003	0.0611		250.7380	250.7380	9.4000e-003		250.9731

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.4239	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718	0.0000	1,872.5505	1,872.5505	0.5672		1,886.7312
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.4319	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718	0.0000	1,872.5505	1,872.5505	0.5672		1,886.7312

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.6 Paving - 2018

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1105	0.0834	1.0802	2.5200e-003	0.1458	1.9900e-003	0.1478	0.0402	1.8400e-003	0.0420		250.7380	250.7380	9.4000e-003		250.9731
Total	0.1105	0.0834	1.0802	2.5200e-003	0.1458	1.9900e-003	0.1478	0.0402	1.8400e-003	0.0420		250.7380	250.7380	9.4000e-003		250.9731

3.7 Architectural Coating - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.3323	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733		281.4481	281.4481	0.0297		282.1909
Total	17.3965	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733		281.4481	281.4481	0.0297		282.1909

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.7 Architectural Coating - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2627	0.2015	2.5856	5.4500e-003	0.4695	4.3700e-003	0.4738	0.1245	4.0300e-003	0.1285		541.3454	541.3454	0.0225		541.9072
Total	0.2627	0.2015	2.5856	5.4500e-003	0.4695	4.3700e-003	0.4738	0.1245	4.0300e-003	0.1285		541.3454	541.3454	0.0225		541.9072

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.3323	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733	0.0000	281.4481	281.4481	0.0297		282.1909
Total	17.3965	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733	0.0000	281.4481	281.4481	0.0297		282.1909

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.7 Architectural Coating - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2627	0.2015	2.5856	5.4500e-003	0.3062	4.3700e-003	0.3106	0.0844	4.0300e-003	0.0885		541.3454	541.3454	0.0225		541.9072
Total	0.2627	0.2015	2.5856	5.4500e-003	0.3062	4.3700e-003	0.3106	0.0844	4.0300e-003	0.0885		541.3454	541.3454	0.0225		541.9072

3.7 Architectural Coating - 2018

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.2986	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506		281.4485	281.4485	0.0267		282.1171
Total	17.3629	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506		281.4485	281.4485	0.0267		282.1171

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.7 Architectural Coating - 2018

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2320	0.1751	2.2683	5.2900e-003	0.4695	4.1900e-003	0.4737	0.1245	3.8600e-003	0.1284		526.5497	526.5497	0.0198		527.0435
Total	0.2320	0.1751	2.2683	5.2900e-003	0.4695	4.1900e-003	0.4737	0.1245	3.8600e-003	0.1284		526.5497	526.5497	0.0198		527.0435

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.2986	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506	0.0000	281.4485	281.4485	0.0267		282.1171
Total	17.3629	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506	0.0000	281.4485	281.4485	0.0267		282.1171

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

3.7 Architectural Coating - 2018

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2320	0.1751	2.2683	5.2900e-003	0.3062	4.1900e-003	0.3104	0.0844	3.8600e-003	0.0883		526.5497	526.5497	0.0198		527.0435
Total	0.2320	0.1751	2.2683	5.2900e-003	0.3062	4.1900e-003	0.3104	0.0844	3.8600e-003	0.0883		526.5497	526.5497	0.0198		527.0435

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Mitigated	5.4037	22.4374	64.4136	0.1749	7.2023	0.2070	7.4092	2.0473	0.1947	2.2420		17,733.75 58	17,733.75 58	1.1077		17,761.44 82
Unmitigated	5.4037	22.4374	64.4136	0.1749	7.2023	0.2070	7.4092	2.0473	0.1947	2.2420		17,733.75 58	17,733.75 58	1.1077		17,761.44 82

4.2 Trip Summary Information

Land Use	Average Daily Trip Rate			Unmitigated	Mitigated
	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Hotel	461.16	461.16	461.16	1,100,407	1,100,407
Hotel	777.14	777.14	777.14	1,854,389	1,854,389
Parking Lot	0.00	0.00	0.00		
Total	1,238.30	1,238.30	1,238.30	2,954,796	2,954,796

4.3 Trip Type Information

Land Use	Miles			Trip %			Trip Purpose %		
	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Hotel	16.60	8.40	6.90	19.40	61.60	19.00	58	38	4
Hotel	16.60	8.40	6.90	19.40	61.60	19.00	58	38	4
Parking Lot	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

4.4 Fleet Mix

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
Hotel	0.547972	0.046127	0.199330	0.125604	0.017697	0.005953	0.018360	0.027618	0.002341	0.002583	0.004804	0.000667	0.000944
Hotel	0.547972	0.046127	0.199330	0.125604	0.017697	0.005953	0.018360	0.027618	0.002341	0.002583	0.004804	0.000667	0.000944
Parking Lot	0.547972	0.046127	0.199330	0.125604	0.017697	0.005953	0.018360	0.027618	0.002341	0.002583	0.004804	0.000667	0.000944

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
NaturalGas Mitigated	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.205 1	3,268.205 1	0.0626	0.0599	3,287.626 4
NaturalGas Unmitigated	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.205 1	3,268.205 1	0.0626	0.0599	3,287.626 4

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

5.2 Energy by Land Use - NaturalGas

Unmitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	lb/day										lb/day					
Hotel	10345.6	0.1116	1.0143	0.8520	6.0900e-003		0.0771	0.0771		0.0771	0.0771		1,217.1247	1,217.1247	0.0233	0.0223	1,224.3574
Hotel	17434.2	0.1880	1.7092	1.4358	0.0103		0.1299	0.1299		0.1299	0.1299		2,051.0805	2,051.0805	0.0393	0.0376	2,063.2690
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		0.2996	2.7235	2.2878	0.0164		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264

Mitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	lb/day										lb/day					
Hotel	17.4342	0.1880	1.7092	1.4358	0.0103		0.1299	0.1299		0.1299	0.1299		2,051.0805	2,051.0805	0.0393	0.0376	2,063.2690
Hotel	10.3456	0.1116	1.0143	0.8520	6.0900e-003		0.0771	0.0771		0.0771	0.0771		1,217.1247	1,217.1247	0.0233	0.0223	1,224.3574
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		0.2996	2.7235	2.2878	0.0164		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264

6.0 Area Detail

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

6.1 Mitigation Measures Area

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category	lb/day										lb/day						
Mitigated	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127
Unmitigated	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127

6.2 Area by SubCategory

Unmitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
SubCategory	lb/day										lb/day						
Architectural Coating	1.0753					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Consumer Products	8.3646					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Landscaping	4.7700e-003	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127
Total	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	lb/day										lb/day					
Architectural Coating	1.0753					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Consumer Products	8.3646					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Landscaping	4.7700e-003	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127
Total	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127

7.0 Water Detail

7.1 Mitigation Measures Water

8.0 Waste Detail

8.1 Mitigation Measures Waste

9.0 Operational Offroad

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	-----------	-------------	-------------	-----------

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

Wayne Mills Place Project - Los Angeles-South Coast County, Summer

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	------------	-------------	-------------	-----------

Boilers

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type
----------------	--------	----------------	-----------------	---------------	-----------

User Defined Equipment

Equipment Type	Number
----------------	--------

11.0 Vegetation

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

Wayne Mills Place Project
Los Angeles-South Coast County, Winter

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Hotel	108.00	Room	1.30	156,816.00	0
Hotel	182.00	Room	2.30	264,264.00	0
Parking Lot	192.00	Space	0.70	76,800.00	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	33
Climate Zone	9			Operational Year	2018
Utility Company	Southern California Edison				
CO2 Intensity (lb/MWhr)	702.44	CH4 Intensity (lb/MWhr)	0.029	N2O Intensity (lb/MWhr)	0.006

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - Acreage adjusted per project applicant.

Construction Phase - Construction, paving, and painting assumed to occur simultaneously.

Demolition -

Vehicle Trips - Adjusted rates per traffic report.

Construction Off-road Equipment Mitigation - Per SCAQMD CEQA Handbook.

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

Table Name	Column Name	Default Value	New Value
tblConstDustMitigation	CleanPavedRoadPercentReduction	0	40
tblConstDustMitigation	WaterUnpavedRoadVehicleSpeed	40	15
tblConstructionPhase	NumDays	18.00	230.00
tblConstructionPhase	NumDays	18.00	230.00
tblConstructionPhase	PhaseEndDate	4/23/2018	3/2/2018
tblConstructionPhase	PhaseEndDate	3/28/2018	3/2/2018
tblConstructionPhase	PhaseStartDate	3/29/2018	4/15/2017
tblConstructionPhase	PhaseStartDate	3/3/2018	4/15/2017
tblLandUse	LotAcreage	3.60	1.30
tblLandUse	LotAcreage	6.07	2.30
tblLandUse	LotAcreage	1.73	0.70
tblVehicleTrips	ST_TR	8.19	4.27
tblVehicleTrips	SU_TR	5.95	4.27
tblVehicleTrips	WD_TR	8.17	4.27

2.0 Emissions Summary

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Area	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127
Energy	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264
Mobile	5.2838	23.0104	62.2853	0.1661	7.2023	0.2088	7.4111	2.0473	0.1965	2.2438		16,850.9120	16,850.9120	1.1077		16,878.6047
Total	15.0280	25.7344	64.6230	0.1824	7.2023	0.4160	7.6182	2.0473	0.4037	2.4509		20,119.2227	20,119.2227	1.1706	0.0599	20,166.3438

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Area	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127
Energy	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264
Mobile	5.2838	23.0104	62.2853	0.1661	7.2023	0.2088	7.4111	2.0473	0.1965	2.2438		16,850.9120	16,850.9120	1.1077		16,878.6047
Total	15.0280	25.7344	64.6230	0.1824	7.2023	0.4160	7.6182	2.0473	0.4037	2.4509		20,119.2227	20,119.2227	1.1706	0.0599	20,166.3438

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N2O	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Demolition	Demolition	3/1/2017	3/28/2017	5	20	
2	Site Preparation	Site Preparation	3/29/2017	4/4/2017	5	5	
3	Grading	Grading	4/5/2017	4/14/2017	5	8	
4	Building Construction	Building Construction	4/15/2017	3/2/2018	5	230	
5	Paving	Paving	4/15/2017	3/2/2018	5	230	
6	Architectural Coating	Architectural Coating	4/15/2017	3/2/2018	5	230	

Acres of Grading (Site Preparation Phase): 0

Acres of Grading (Grading Phase): 4

Acres of Paving: 0.7

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 631,620; Non-Residential Outdoor: 210,540; Striped Parking Area: 4,608 (Architectural Coating – sqft)

OffRoad Equipment

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Architectural Coating	Air Compressors	1	6.00	78	0.48
Paving	Cement and Mortar Mixers	2	6.00	9	0.56
Demolition	Concrete/Industrial Saws	1	8.00	81	0.73
Demolition	Excavators	3	8.00	158	0.38
Building Construction	Cranes	1	7.00	231	0.29
Building Construction	Forklifts	3	8.00	89	0.20
Grading	Excavators	1	8.00	158	0.38
Paving	Pavers	1	8.00	130	0.42
Paving	Rollers	2	6.00	80	0.38
Demolition	Rubber Tired Dozers	2	8.00	247	0.40
Grading	Rubber Tired Dozers	1	8.00	247	0.40
Building Construction	Tractors/Loaders/Backhoes	3	7.00	97	0.37
Building Construction	Generator Sets	1	8.00	84	0.74
Grading	Tractors/Loaders/Backhoes	3	8.00	97	0.37
Paving	Tractors/Loaders/Backhoes	1	8.00	97	0.37
Site Preparation	Tractors/Loaders/Backhoes	4	8.00	97	0.37
Grading	Graders	1	8.00	187	0.41
Paving	Paving Equipment	2	6.00	132	0.36
Site Preparation	Rubber Tired Dozers	3	8.00	247	0.40
Building Construction	Welders	1	8.00	46	0.45

Trips and VMT

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Architectural Coating	1	42.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	9	209.00	82.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Demolition	6	15.00	0.00	793.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	6	15.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	8	20.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Site Preparation	7	18.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

- Use Soil Stabilizer
- Replace Ground Cover
- Water Exposed Area
- Reduce Vehicle Speed on Unpaved Roads
- Clean Paved Roads

3.2 Demolition - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					8.5757	0.0000	8.5757	1.2984	0.0000	1.2984			0.0000			0.0000
Off-Road	4.1031	42.7475	23.0122	0.0388		2.1935	2.1935		2.0425	2.0425		3,924.2833	3,924.2833	1.0730		3,951.1070
Total	4.1031	42.7475	23.0122	0.0388	8.5757	2.1935	10.7692	1.2984	2.0425	3.3410		3,924.2833	3,924.2833	1.0730		3,951.1070

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.2 Demolition - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.4583	13.9845	3.0133	0.0319	0.6932	0.0740	0.7671	0.1900	0.0708	0.2608		3,443.7355	3,443.7355	0.2543		3,450.0932
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1037	0.0797	0.8549	1.8300e-003	0.1677	1.5600e-003	0.1692	0.0445	1.4400e-003	0.0459		182.0869	182.0869	7.6100e-003		182.2772
Total	0.5621	14.0641	3.8681	0.0338	0.8608	0.0755	0.9364	0.2345	0.0722	0.3067		3,625.8225	3,625.8225	0.2619		3,632.3704

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					3.2802	0.0000	3.2802	0.4967	0.0000	0.4967			0.0000			0.0000
Off-Road	4.1031	42.7475	23.0122	0.0388		2.1935	2.1935		2.0425	2.0425	0.0000	3,924.2833	3,924.2833	1.0730		3,951.1070
Total	4.1031	42.7475	23.0122	0.0388	3.2802	2.1935	5.4737	0.4967	2.0425	2.5392	0.0000	3,924.2833	3,924.2833	1.0730		3,951.1070

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.2 Demolition - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.4583	13.9845	3.0133	0.0319	0.4835	0.0740	0.5575	0.1385	0.0708	0.2093		3,443.7355	3,443.7355	0.2543		3,450.0932
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1037	0.0797	0.8549	1.8300e-003	0.1094	1.5600e-003	0.1109	0.0302	1.4400e-003	0.0316		182.0869	182.0869	7.6100e-003		182.2772
Total	0.5621	14.0641	3.8681	0.0338	0.5929	0.0755	0.6684	0.1687	0.0722	0.2409		3,625.8225	3,625.8225	0.2619		3,632.3704

3.3 Site Preparation - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					18.0663	0.0000	18.0663	9.9307	0.0000	9.9307			0.0000			0.0000
Off-Road	4.9608	52.2754	23.4554	0.0380		2.8786	2.8786		2.6483	2.6483		3,894.9500	3,894.9500	1.1934		3,924.7852
Total	4.9608	52.2754	23.4554	0.0380	18.0663	2.8786	20.9448	9.9307	2.6483	12.5790		3,894.9500	3,894.9500	1.1934		3,924.7852

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.3 Site Preparation - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1245	0.0956	1.0259	2.2000e-003	0.2012	1.8700e-003	0.2031	0.0534	1.7300e-003	0.0551		218.5043	218.5043	9.1300e-003		218.7326
Total	0.1245	0.0956	1.0259	2.2000e-003	0.2012	1.8700e-003	0.2031	0.0534	1.7300e-003	0.0551		218.5043	218.5043	9.1300e-003		218.7326

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					6.9103	0.0000	6.9103	3.7985	0.0000	3.7985			0.0000			0.0000
Off-Road	4.9608	52.2754	23.4554	0.0380		2.8786	2.8786		2.6483	2.6483	0.0000	3,894.9500	3,894.9500	1.1934		3,924.7852
Total	4.9608	52.2754	23.4554	0.0380	6.9103	2.8786	9.7889	3.7985	2.6483	6.4468	0.0000	3,894.9500	3,894.9500	1.1934		3,924.7852

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.3 Site Preparation - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1245	0.0956	1.0259	2.2000e-003	0.1312	1.8700e-003	0.1331	0.0362	1.7300e-003	0.0379		218.5043	218.5043	9.1300e-003		218.7326
Total	0.1245	0.0956	1.0259	2.2000e-003	0.1312	1.8700e-003	0.1331	0.0362	1.7300e-003	0.0379		218.5043	218.5043	9.1300e-003		218.7326

3.4 Grading - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					6.5523	0.0000	6.5523	3.3675	0.0000	3.3675			0.0000			0.0000
Off-Road	3.0705	33.8868	17.1042	0.0297		1.7774	1.7774		1.6352	1.6352		3,037.9107	3,037.9107	0.9308		3,061.1809
Total	3.0705	33.8868	17.1042	0.0297	6.5523	1.7774	8.3298	3.3675	1.6352	5.0027		3,037.9107	3,037.9107	0.9308		3,061.1809

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.4 Grading - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1037	0.0797	0.8549	1.8300e-003	0.1677	1.5600e-003	0.1692	0.0445	1.4400e-003	0.0459		182.0869	182.0869	7.6100e-003		182.2772
Total	0.1037	0.0797	0.8549	1.8300e-003	0.1677	1.5600e-003	0.1692	0.0445	1.4400e-003	0.0459		182.0869	182.0869	7.6100e-003		182.2772

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					2.5063	0.0000	2.5063	1.2881	0.0000	1.2881			0.0000			0.0000
Off-Road	3.0705	33.8868	17.1042	0.0297		1.7774	1.7774		1.6352	1.6352	0.0000	3,037.9107	3,037.9107	0.9308		3,061.1809
Total	3.0705	33.8868	17.1042	0.0297	2.5063	1.7774	4.2837	1.2881	1.6352	2.9233	0.0000	3,037.9107	3,037.9107	0.9308		3,061.1809

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.4 Grading - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1037	0.0797	0.8549	1.8300e-003	0.1094	1.5600e-003	0.1109	0.0302	1.4400e-003	0.0316		182.0869	182.0869	7.6100e-003		182.2772
Total	0.1037	0.0797	0.8549	1.8300e-003	0.1094	1.5600e-003	0.1109	0.0302	1.4400e-003	0.0316		182.0869	182.0869	7.6100e-003		182.2772

3.5 Building Construction - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791		2,650.9797	2,650.9797	0.6531		2,667.3078
Total	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791		2,650.9797	2,650.9797	0.6531		2,667.3078

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.5 Building Construction - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.4455	10.7288	3.3338	0.0212	0.5249	0.0909	0.6159	0.1511	0.0870	0.2381		2,256.9551	2,256.9551	0.1708		2,261.2250
Worker	1.4452	1.1102	11.9114	0.0255	2.3361	0.0217	2.3579	0.6196	0.0201	0.6396		2,537.0778	2,537.0778	0.1060		2,539.7284
Total	1.8907	11.8390	15.2452	0.0467	2.8611	0.1127	2.9737	0.7707	0.1070	0.8777		4,794.0330	4,794.0330	0.2768		4,800.9534

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791	0.0000	2,650.9797	2,650.9797	0.6531		2,667.3078
Total	3.1149	26.5546	18.1825	0.0269		1.7879	1.7879		1.6791	1.6791	0.0000	2,650.9797	2,650.9797	0.6531		2,667.3078

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.5 Building Construction - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.4455	10.7288	3.3338	0.0212	0.3753	0.0909	0.4663	0.1144	0.0870	0.2014		2,256.9551	2,256.9551	0.1708		2,261.2250
Worker	1.4452	1.1102	11.9114	0.0255	1.5237	0.0217	1.5455	0.4202	0.0201	0.4402		2,537.0778	2,537.0778	0.1060		2,539.7284
Total	1.8907	11.8390	15.2452	0.0467	1.8991	0.1127	2.0117	0.5346	0.1070	0.6416		4,794.0330	4,794.0330	0.2768		4,800.9534

3.5 Building Construction - 2018

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099		2,620.9351	2,620.9351	0.6421		2,636.9883
Total	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099		2,620.9351	2,620.9351	0.6421		2,636.9883

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.5 Building Construction - 2018

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.3931	10.0725	3.0204	0.0211	0.5249	0.0720	0.5969	0.1511	0.0688	0.2200		2,248.0288	2,248.0288	0.1622		2,252.0838
Worker	1.2780	0.9650	10.3929	0.0248	2.3361	0.0208	2.3570	0.6196	0.0192	0.6388		2,467.4038	2,467.4038	0.0929		2,469.7252
Total	1.6711	11.0375	13.4133	0.0459	2.8611	0.0928	2.9539	0.7707	0.0880	0.8587		4,715.4326	4,715.4326	0.2551		4,721.8091

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099	0.0000	2,620.9351	2,620.9351	0.6421		2,636.9883
Total	2.6795	23.3900	17.5804	0.0269		1.4999	1.4999		1.4099	1.4099	0.0000	2,620.9351	2,620.9351	0.6421		2,636.9883

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.5 Building Construction - 2018

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.3931	10.0725	3.0204	0.0211	0.3753	0.0720	0.4473	0.1144	0.0688	0.1833		2,248.0288	2,248.0288	0.1622		2,252.0838
Worker	1.2780	0.9650	10.3929	0.0248	1.5237	0.0208	1.5446	0.4202	0.0192	0.4394		2,467.4038	2,467.4038	0.0929		2,469.7252
Total	1.6711	11.0375	13.4133	0.0459	1.8991	0.0928	1.9919	0.5346	0.0880	0.6226		4,715.4326	4,715.4326	0.2551		4,721.8091

3.6 Paving - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.6763	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376		1,901.7766	1,901.7766	0.5674		1,915.9604
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.6843	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376		1,901.7766	1,901.7766	0.5674		1,915.9604

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.6 Paving - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1383	0.1062	1.1398	2.4400e-003	0.2236	2.0800e-003	0.2256	0.0593	1.9200e-003	0.0612		242.7826	242.7826	0.0102		243.0362
Total	0.1383	0.1062	1.1398	2.4400e-003	0.2236	2.0800e-003	0.2256	0.0593	1.9200e-003	0.0612		242.7826	242.7826	0.0102		243.0362

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.6763	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376	0.0000	1,901.7766	1,901.7766	0.5674		1,915.9604
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.6843	17.0389	12.6556	0.0189		1.0172	1.0172		0.9376	0.9376	0.0000	1,901.7766	1,901.7766	0.5674		1,915.9604

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.6 Paving - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1383	0.1062	1.1398	2.4400e-003	0.1458	2.0800e-003	0.1479	0.0402	1.9200e-003	0.0421		242.7826	242.7826	0.0102		243.0362
Total	0.1383	0.1062	1.1398	2.4400e-003	0.1458	2.0800e-003	0.1479	0.0402	1.9200e-003	0.0421		242.7826	242.7826	0.0102		243.0362

3.6 Paving - 2018

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.4239	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718		1,872.5505	1,872.5505	0.5672		1,886.7312
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.4319	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718		1,872.5505	1,872.5505	0.5672		1,886.7312

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.6 Paving - 2018

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1223	0.0923	0.9945	2.3700e-003	0.2236	1.9900e-003	0.2256	0.0593	1.8400e-003	0.0611		236.1152	236.1152	8.8900e-003		236.3373
Total	0.1223	0.0923	0.9945	2.3700e-003	0.2236	1.9900e-003	0.2256	0.0593	1.8400e-003	0.0611		236.1152	236.1152	8.8900e-003		236.3373

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	1.4239	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718	0.0000	1,872.5505	1,872.5505	0.5672		1,886.7312
Paving	7.9700e-003					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.4319	14.5184	12.4333	0.0189		0.8370	0.8370		0.7718	0.7718	0.0000	1,872.5505	1,872.5505	0.5672		1,886.7312

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.6 Paving - 2018

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.1223	0.0923	0.9945	2.3700e-003	0.1458	1.9900e-003	0.1478	0.0402	1.8400e-003	0.0420		236.1152	236.1152	8.8900e-003		236.3373
Total	0.1223	0.0923	0.9945	2.3700e-003	0.1458	1.9900e-003	0.1478	0.0402	1.8400e-003	0.0420		236.1152	236.1152	8.8900e-003		236.3373

3.7 Architectural Coating - 2017

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.3323	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733		281.4481	281.4481	0.0297		282.1909
Total	17.3965	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733		281.4481	281.4481	0.0297		282.1909

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.7 Architectural Coating - 2017

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2904	0.2231	2.3937	5.1300e-003	0.4695	4.3700e-003	0.4738	0.1245	4.0300e-003	0.1285		509.8434	509.8434	0.0213		510.3760
Total	0.2904	0.2231	2.3937	5.1300e-003	0.4695	4.3700e-003	0.4738	0.1245	4.0300e-003	0.1285		509.8434	509.8434	0.0213		510.3760

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.3323	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733	0.0000	281.4481	281.4481	0.0297		282.1909
Total	17.3965	2.1850	1.8681	2.9700e-003		0.1733	0.1733		0.1733	0.1733	0.0000	281.4481	281.4481	0.0297		282.1909

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.7 Architectural Coating - 2017

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2904	0.2231	2.3937	5.1300e-003	0.3062	4.3700e-003	0.3106	0.0844	4.0300e-003	0.0885		509.8434	509.8434	0.0213		510.3760
Total	0.2904	0.2231	2.3937	5.1300e-003	0.3062	4.3700e-003	0.3106	0.0844	4.0300e-003	0.0885		509.8434	509.8434	0.0213		510.3760

3.7 Architectural Coating - 2018

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.2986	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506		281.4485	281.4485	0.0267		282.1171
Total	17.3629	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506		281.4485	281.4485	0.0267		282.1171

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.7 Architectural Coating - 2018

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2568	0.1939	2.0885	4.9800e-003	0.4695	4.1900e-003	0.4737	0.1245	3.8600e-003	0.1284		495.8419	495.8419	0.0187		496.3084
Total	0.2568	0.1939	2.0885	4.9800e-003	0.4695	4.1900e-003	0.4737	0.1245	3.8600e-003	0.1284		495.8419	495.8419	0.0187		496.3084

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	17.0642					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.2986	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506	0.0000	281.4485	281.4485	0.0267		282.1171
Total	17.3629	2.0058	1.8542	2.9700e-003		0.1506	0.1506		0.1506	0.1506	0.0000	281.4485	281.4485	0.0267		282.1171

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

3.7 Architectural Coating - 2018

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000		0.0000
Worker	0.2568	0.1939	2.0885	4.9800e-003	0.3062	4.1900e-003	0.3104	0.0844	3.8600e-003	0.0883		495.8419	495.8419	0.0187		496.3084
Total	0.2568	0.1939	2.0885	4.9800e-003	0.3062	4.1900e-003	0.3104	0.0844	3.8600e-003	0.0883		495.8419	495.8419	0.0187		496.3084

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Mitigated	5.2838	23.0104	62.2853	0.1661	7.2023	0.2088	7.4111	2.0473	0.1965	2.2438		16,850.91 20	16,850.91 20	1.1077		16,878.60 47
Unmitigated	5.2838	23.0104	62.2853	0.1661	7.2023	0.2088	7.4111	2.0473	0.1965	2.2438		16,850.91 20	16,850.91 20	1.1077		16,878.60 47

4.2 Trip Summary Information

Land Use	Average Daily Trip Rate			Unmitigated	Mitigated
	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Hotel	461.16	461.16	461.16	1,100,407	1,100,407
Hotel	777.14	777.14	777.14	1,854,389	1,854,389
Parking Lot	0.00	0.00	0.00		
Total	1,238.30	1,238.30	1,238.30	2,954,796	2,954,796

4.3 Trip Type Information

Land Use	Miles			Trip %			Trip Purpose %		
	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Hotel	16.60	8.40	6.90	19.40	61.60	19.00	58	38	4
Hotel	16.60	8.40	6.90	19.40	61.60	19.00	58	38	4
Parking Lot	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

4.4 Fleet Mix

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
Hotel	0.547972	0.046127	0.199330	0.125604	0.017697	0.005953	0.018360	0.027618	0.002341	0.002583	0.004804	0.000667	0.000944
Hotel	0.547972	0.046127	0.199330	0.125604	0.017697	0.005953	0.018360	0.027618	0.002341	0.002583	0.004804	0.000667	0.000944
Parking Lot	0.547972	0.046127	0.199330	0.125604	0.017697	0.005953	0.018360	0.027618	0.002341	0.002583	0.004804	0.000667	0.000944

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
NaturalGas Mitigated	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.205 1	3,268.205 1	0.0626	0.0599	3,287.626 4
NaturalGas Unmitigated	0.2996	2.7235	2.2877	0.0163		0.2070	0.2070		0.2070	0.2070		3,268.205 1	3,268.205 1	0.0626	0.0599	3,287.626 4

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

5.2 Energy by Land Use - NaturalGas

Unmitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	lb/day										lb/day					
Hotel	10345.6	0.1116	1.0143	0.8520	6.0900e-003		0.0771	0.0771		0.0771	0.0771		1,217.1247	1,217.1247	0.0233	0.0223	1,224.3574
Hotel	17434.2	0.1880	1.7092	1.4358	0.0103		0.1299	0.1299		0.1299	0.1299		2,051.0805	2,051.0805	0.0393	0.0376	2,063.2690
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		0.2996	2.7235	2.2878	0.0164		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264

Mitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	lb/day										lb/day					
Hotel	10.3456	0.1116	1.0143	0.8520	6.0900e-003		0.0771	0.0771		0.0771	0.0771		1,217.1247	1,217.1247	0.0233	0.0223	1,224.3574
Hotel	17.4342	0.1880	1.7092	1.4358	0.0103		0.1299	0.1299		0.1299	0.1299		2,051.0805	2,051.0805	0.0393	0.0376	2,063.2690
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		0.2996	2.7235	2.2878	0.0164		0.2070	0.2070		0.2070	0.2070		3,268.2051	3,268.2051	0.0626	0.0599	3,287.6264

6.0 Area Detail

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

6.1 Mitigation Measures Area

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category	lb/day										lb/day						
Mitigated	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127
Unmitigated	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127

6.2 Area by SubCategory

Unmitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
SubCategory	lb/day										lb/day						
Architectural Coating	1.0753					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Consumer Products	8.3646					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Landscaping	4.7700e-003	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127
Total	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004			0.1127

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	lb/day										lb/day					
Architectural Coating	1.0753					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Consumer Products	8.3646					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Landscaping	4.7700e-003	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127
Total	9.4446	4.7000e-004	0.0499	0.0000		1.8000e-004	1.8000e-004		1.8000e-004	1.8000e-004		0.1055	0.1055	2.9000e-004		0.1127

7.0 Water Detail

7.1 Mitigation Measures Water

8.0 Waste Detail

8.1 Mitigation Measures Waste

9.0 Operational Offroad

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	-----------	-------------	-------------	-----------

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

Wayne Mills Place Project - Los Angeles-South Coast County, Winter

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	------------	-------------	-------------	-----------

Boilers

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type
----------------	--------	----------------	-----------------	---------------	-----------

User Defined Equipment

Equipment Type	Number
----------------	--------

11.0 Vegetation

APPENDIX B
TRAFFIC IMPACT STUDY

TRAFFIC IMPACT STUDY

For

***Valencia Springhill Suites
Plus Residence Inn***

Santa Clarita, California

Submitted To:

***Excel Hotel Group
10660 Scripps Ranch Boulevard, Suite 100,
San Diego, California 92131***

Submitted By:

***Darnell & Associates, Inc.
4411 Mercury Street, Suite 207A
San Diego California, 92111***

September 14, 2016

Darnell & Associates, Inc.

- TRANSPORTATION PLANNING & TRAFFIC ENGINEERING

September 14, 2016

Neil Patel
Excel Hotel Group
10660 Scripps Ranch Boulevard, Suite 100,
San Diego, California 92123

D&A Ref. No.: 160605

Subject: Traffic Impact Study for the Proposed Valencia Springhill Suites Plus the Residence Inn located in Santa Clarita, California

Dear Mr. Neil Patel:

In accordance with your authorization, Darnell & Associates, Inc. (D&A) has prepared this Traffic Impact Study assessing the impacts associated with the proposed project located on the southside of Wayne Mills Place in the City of Santa Clarita.

The Traffic Impact Study analyzes the traffic impacts related to the project on the surrounding roadways and intersections under the following conditions: Existing and Existing Plus Project Conditions.

If you have any questions, please feel free to contact the office.

Sincerely,

DARNELL & ASSOCIATES, INC.



Bill E. Darnell, P.E.
Firm Principal
RCE 22338



Date Signed: 9/14/2016

BED/jam
160605 - Springhill Suites Residential Inn-Valencia Traffic Study/09/16

TRAFFIC IMPACT STUDY

FOR

***VALENCIA SPRINGHILL SUITES
PLUS RESIDENCE INN***

SANTA CLARITA, CALIFORNIA

Submitted To:

***Excel Hotel Group
10660 Scripps Ranch Boulevard, Suite 100,
San Diego, California 92131***

Submitted By:

***Darnell & Associates, Inc.
4411 Mercury Street, Suite 207A
San Diego California, 92111
(619) 233-9373***

September 14, 2016

160605 - Springhill Suites Residential Inn-Valencia Traffic Study/09/16

TABLE OF CONTENTS

SECTION I – INTRODUCTION.....1

PROJECT DESCRIPTION1

SCENARIOS STUDIED1

LEVEL OF SERVICE.....1

ANALYSIS METHODOLOGY4

REPORT ORGANIZATION.....4

SECTION II - EXISTING CONDITIONS.....5

EXISTING ROADWAY CHARACTERISTICS5

ROADWAY SEGMENT DAILY TRAFFIC5

KEY INTERSECTIONS.....5

INTERSECTION TRAFFIC COUNTS.....5

EXISTING LEVEL OF SERVICE CONDITIONS8

Roadway Segments8

Intersections.....8

SECTION III - PROJECT RELATED CONDITIONS.....9

TRIP GENERATION.....9

TRIP DISTRIBUTION/TRIP ASSIGNMENT10

SECTION IV – IMPACTS13

EXISTING PLUS PROJECT CONDITIONS13

Roadway Segments13

Intersections.....13

2017 OPENING DAY PLUS PROJECT CONDITIONS.....13

Roadway Segments13

Intersections.....13

SECTION V - SUMMARY OF FINDINGS AND CONCLUSIONS19

LIST OF FIGURES

Figure 1 - Vicinity Map	2
Figure 2 - Site Plan	3
Figure 3 - Existing Conditions	6
Figure 4 - Existing Traffic Volumes	7
Figure 5 - Trip Distribution	11
Figure 6 - Project Related Traffic Volumes	12
Figure 7 - Existing Plus Project Traffic Volumes	14
Figure 8 - 2017 Opening Day Traffic Volumes	16
Figure 9 - Existing Plus Project Plus 2017 Opening Day Traffic Volumes	14

LIST OF TABLES

Table 1 - Level of Service Criteria at Intersections	4
Table 2 - Existing Roadway Segment Level of Service Summary	8
Table 3 - Existing Intersection Level of Service Summary	8
Table 4 - Trip Generation Rates and Calculations Summary	9
Table 5 - Existing Plus Project Roadway Segment Level of Service Summary	15
Table 6 - Existing Plus Project Intersection Level of Service Summary	15
Table 7 - Existing Plus Project Plus 2017 Opening Day Roadway Segment Level of Service Summary	18
Table 8 - Existing Plus Project Plus 2017 Opening Day Intersection Level of Service Summary	18

APPENDICIES

APPENDIX A

- 24-Hour Segment Counts
- AM/PM Peak Hour Turn Counts

APPENDIX B

- Existing Conditions Analysis Worksheets

APPENDIX C

- Existing + Project Conditions Analysis Worksheets

APPENDIX D

- 2017 Opening Day Conditions Analysis Worksheets

SECTION I – INTRODUCTION

This traffic study evaluates the traffic conditions associated with the proposed Valencia Springhill plus Residence Inn project (herein referred to as “the project”) located at 27413 Wayne Mills Place in the City of Santa Clarita, CA. Figure 1 illustrates the location of the project site in the region.

PROJECT DESCRIPTION

The project site is generally located on the south side of Wayne Mills Place, east of I-5, and west of Tourney Road. The existing site currently is occupied by a 120-Room Best Western Hotel. The project will construct a 182-Room Springhill Suites/Residence Inn and a 108-room Holiday Inn Express on the existing Best Western Site. Access to the project will be through an existing driveway located on Wayne Mills Place. Figure 2 illustrates the project site plan.

SCENARIOS STUDIED

The following list contains the scenarios analyzed for the project:

Existing Conditions: This scenario refers to the conditions at the time traffic volume counts were obtained in July 2016 and account for the existing lane configurations at the study intersections and roadway segments.

Existing Plus Project Conditions: This scenario includes the project traffic, which is added to the existing traffic volumes.

2017 Opening Day Conditions: This scenario includes the project traffic, with 3% ambient growth added to the existing traffic volumes.

LEVEL OF SERVICE


Level of Service (LOS) is a professional industry standard by which the operating conditions of a given roadway segment or intersection are measured. Level of Service is defined on a scale of A to F; where LOS A represents the best operating conditions and LOS F represents the worst operating conditions. LOS A facilities are characterized as having free flowing traffic conditions with no restrictions on maneuvering or operating speeds; traffic volumes are low and travel speeds are high. LOS F facilities are characterized as having forced flow with many stoppages and low operating speeds.

For all signalized study area intersections, the Intersection Capacity Utilization (ICU) methodology is utilized to assess the operation and performance of the intersection. The ICU represents the ratio of the volume of traffic using the intersection with the capacity of the intersection.

For all unsignalized area intersections, the Highway Capacity Manual (HCM) methodology is utilized to estimate the LOS. The HCM method estimates the LOS based on intersection delay.

LOS along the roadway segments in the study area is determined utilizing the City’s volume to capacity at urban arterial highways.

Table 1 shows the criteria used for intersections. Table 2 summarizes the criteria used along arterial roadways. In the City of Santa Clarita, LOS D is considered the acceptable threshold for intersections and roadway segments.



PROJECT
SITE



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 160805-AA DATE: September 15, 2016 BY: JAB

FIGURE 1
VICINITY MAP

Table 1 - Level of Service Criteria at Intersections		
LOS	Intersections	
	Signalized Volume-to-Capacity Ratio (ICU) ¹	Unsignalized Delay (Seconds/Vehicle) ²
A	0.00 – 0.60	Less than or Equal to 10.0
B	0.61 – 0.70	10.1 to 15.0
C	0.71 to 0.80	15.1 to 25.0
D	0.81 – 0.90	25.1 to 35.0
E	0.91 – 1.00	35.1 to 50.0
F	> 1.00	> 50.0

¹ The volume of traffic using the intersection is compared with the capacity of the intersection. A 1,750 vehicle per hour per lane was assumed as the saturation flow value for through and turning lanes.

² The delay ranges shown are based on the 2000 Highway Capacity Manual (HCM)

LOS = Level of Service; mph = miles per hour

Table 2 - Level of Service Criteria Along Arterial Roadways					
LOS	8-Lane Divided	6-Lane Divided	4-Lane Divided	4-Lane Undivided	2-Lane Undivided
A	48,000	36,000	24,000	16,000	5,000
B	54,000	40,400	27,000	18,000	7,500
C	60,000	45,000	30,000	20,000	10,000
D	66,000	49,500	33,000	22,000	12,500
E	72,000	54,000	36,000	24,000	15,000
F	This condition represents system breakdown and does not have a specific relationship to service volumes.				

The values shown in the table are referenced from the City of Santa Clarita General Plan Circulation Element

ANALYSIS METHODOLOGY

The intersection analysis evaluated the operations of the study area intersections during a typical weekday for the AM and PM peak periods. The AM peak is defined as the time period between 7:00 and 9:00 AM. The PM peak is defined as the time period between 4:00 and 6:00 PM. Synchro 8 was used as the software program to evaluate the operations at unsignalized intersections.

REPORT ORGANIZATION

Following this section, Section II evaluates the existing roadway characteristics and traffic conditions surrounding the project area. Section III examines the project trip generation and distribution assumptions. Section IV analyzes the traffic for existing plus project conditions. Section V provides recommended mitigation measures. Section VII summarizes the report's findings and conclusions.

SECTION II - EXISTING CONDITIONS

This section of the traffic study is intended to assess the existing conditions of the roadways and intersections within the vicinity of the project to determine travel flow and/or delay difficulties, if any, that exist prior to adding the traffic generated by the proposed project. The existing conditions analysis establishes a base condition which is used to assess the other scenarios discussed in this report.

Darnell & Associates, Inc. (D&A) conducted a field review of the area surrounding the project in June 2016. The existing roadway geometrics are illustrated in Figure 3.

EXISTING ROADWAY CHARACTERISTICS

The key segments analyzed in the study area are identified below:

Magic Mountain Parkway: Magic Mountain Parkway is a six-lane divided roadway in the study area with painted medians and is classified as a major highway. The roadway generally runs in the east-west direction. Parking is restricted on both sides of the roadway and the posted speed limit is 50 miles per hour (mph). Based on the City's Circulation Element, an improvement to restripe the roadway from 6-lanes to 8-lanes.

Tourney Road: Tourney Road is a three-lane roadway with a center two-way left-turning lane in the study area and is classified as a secondary highway. The roadway generally runs in the north-south direction. Bicycle lanes and parking are provided on both sides of the roadway. There are no posted speed limit signs in the immediate vicinity of the project.

ROADWAY SEGMENT DAILY TRAFFIC

Daily traffic volume data were obtained along the study area roadway segments on Thursday, July 28, 2016. Figure 4 presents the existing conditions traffic volumes used in this analysis. Count summaries are included in Appendix A.


KEY INTERSECTIONS

Figure 3 provides intersection configurations and traffic control for the key intersections. The key intersections analyzed in the study area are identified below:

- The Old Road/Magic Mountain Parkway (signal);
- I-5 SB Ramps/Magic Mountain Parkway (signal);
- I-5 NB Ramps/Magic Mountain Parkway (signal);
- Tourney Road/Magic Mountain Parkway (signal);
- Tourney Road/Wayne Mills Place (two-way stopped control)

INTERSECTION TRAFFIC COUNTS

Peak-hour traffic volume data were obtained at the study area intersections on Thursday, July 28, 2016. Figure 4 presents the existing conditions traffic volumes used in this analysis. Count summaries are included in Appendix A.



Imagery Date: 2/8/17




Darnell & ASSOCIATES, INC.

2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 180605-AA DATE: SEPTEMBER 13, 2016 BY: DAB

FIGURE 3
 EXISTING DEVELOPMENT CONDITIONS



LEGEND

→ - DIRECTION OF TRAVEL

XX/YY - AM/PM PEAK HOUR TRAFFIC VOLUMES

⊠ - SIGNAL

○ - STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 180605-AA DATE: September 16, 2016 BY: JAB

FIGURE 4
EXISTING TRAFFIC VOLUMES

EXISTING LEVEL OF SERVICE CONDITIONS

Roadway Segments

Table 3 summarizes the LOS along the roadway segments in the study area. As shown in the table, all roadway segments operate at LOS A except for the Magic Mountain Parkway segment between Tourney Road and Wayne Mills Place, which operates at LOS “E”.

Roadway Segment	Classification	Existing Number of Lanes	LOS “E” Capacity	ADT	v/c	LOS
Magic Mountain Pkwy						
The Old Rd to I-5 SB Ramps	Major Arterial	6-Lane Divided	54,000	34,744	0.64	A
I-5 NB Ramps to Tourney Road				32,584	0.60	A
Tourney Road to Wayne Mills Place				51,703	0.96	E
Tourney Rd						
Magic Mountain Pkwy to Wayne Mills Place	Secondary Highway	4-Lane Undivided	24,000	10,230	0.43	A
South of Wayne Mills Place				5,999	0.25	A
Volume on this segment was estimated. Capacity is based on the upper limits of LOS E per the City of Santa Clarita General Plan Circulation Element; ADT= Average Daily Traffic; LOS= Level of Service.						

Intersections

Table 4 summarizes the LOS at the intersections in the study area. As shown in the table, all signalized intersections operate at LOS “A” during the peak periods. The unsignalized intersection of Tourney Road/Wayne Mills Place operates at LOS “D” or better during the peak periods.

#	Intersection	Traffic Control	Peak Hour	Existing Conditions	
				ICU/Delay (a)	LOS (b)
1	The Old Rd & Magic Mountain Pkwy	Signal	AM	0.196	A
			PM	0.470	A
2	I-5 SB Ramps & Magic Mountain Pkwy	Signal	AM	0.356	A
			PM	0.403	A
3	I-5 NB Ramps & Magic Mountain Pkwy	Signal	AM	0.493	A
			PM	0.510	A
4	Tourney Rd & Magic Mountain Pkwy	Signal	AM	0.465	A
			PM	0.530	A
5	Tourney Rd & Wayne Mills Pl	TWSC	AM	24.9	C
			PM	25.7	D
6	Project Dwy & Wayne Mills Pl	OWSC	AM	DNE	
			PM		
DNE: Does not exist					
(a) ICU’s are reported at signalized intersections. Delays are reported as the worst movement at unsignalized intersections.					
(b) LOS calculations are based on the methodology outlined in the 2000 Highway Capacity Manual (HCM) and performed using Synchro 8, TWSC = Two Way Stop Control, OWSC = One Way Stop Control.					

A copy of the analysis worksheets for conditions can be found in Appendix B.

SECTION III - PROJECT RELATED CONDITIONS

TRIP GENERATION

Trip generation rates published by the *Institute of Transportation Engineers (ITE) Trip Generation Manual, 9th Edition* were applied to the existing and proposed use in order to determine the traffic generation characteristics of the site. The existing site contains a 120-Room Best Western Hotel. The project consists of a 182-Room Springhill Suites/Residence Inn and a 108-Room Holiday Inn Express, which results in a net increase of 170 hotel rooms. Upon reviewing the various land uses contained in the *ITE Trip Generation Manual*, land use code of 312 (Business Hotel) was the most appropriate and applied to the project.

Table 4 summarizes the weekday trip generation. As shown in the table, the project is forecasted to generate a net increase of 1,237 daily trips with 99 AM peak-hour trips and 105 PM peak-hour trips.

Table 4 - Trip Generation Rates and Calculations Summary								
Trip Generation Rates								
Land Use	Daily	AM Peak Hour			PM Peak Hour			
		Rate	% In	% Out	Rate	% In	% Out	
Business Hotel	7.27 trips/rooms	0.58/Room	59%	41%	0.62/Room	60%	40%	
Trip Generation								
Land Use	Total No. of Units	Daily	AM Peak Hour			PM Peak Hour		
			Total	In	Out	Total	In	Out
Existing Uses								
Best Western	120 rooms	873	70	42	28	75	45	30
Proposed Uses								
Springhill Suites/Residence Inn	182 rooms	1,324	106	63	43	113	68	45
Holiday Inn Express	108 rooms	786	63	38	25	67	41	26
Subtotal (Proposed – Existing)		2,110	169	101	68	180	109	71
Net New Trips		1,237	99	59	40	105	64	41
Trip Generation Rates are based on rates published by the <i>Institute of Transportation Engineers (ITE) Trip Generation Manual, 9th Edition</i> .								


TRIP DISTRIBUTION/TRIP ASSIGNMENT

Based on existing travel patterns in the study area and on logical connections to regional facilities, the following list shows the assumed project trip distribution for the proposed project:

- 20 percent to/from the north via I-5;
- 40 percent to/from the south;
 - 30 percent via I-5;
 - 10 percent via Tourney Road;
- 20 percent to/from the east via Magic Mountain Parkway; and
- 20 percent to/from the west via Magic Mountain Parkway.

Figure 5 displays the assumed project trip distribution through the study intersections. Based on the project trip generation and distribution, the peak-hour trips were assigned to the intersections in the study area. Figure 6 illustrates the weekday project trip assignment.

The impacts associated with the addition of project traffic are discussed in the following section, Section IV.



PROJECT SITE


LEGEND
 → - DIRECTION OF TRAVEL
 XX% - TRIP DISTRIBUTION PERCENTAGE



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

FIGURE 5
PROJECT TRIP DISTRIBUTION

DWG: 180805-AA DATE: September 15, 2016 BY: JAB



LEGEND

→ - DIRECTION OF TRAVEL

XX/YY - AM/PM PEAK HOUR TRAFFIC VOLUMES

⊠ - SIGNAL

○ - STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

FIGURE 6
 PROJECT TRAFFIC

DWG: 160605-AA DATE: September 15, 2016 BY: JAB

SECTION IV – IMPACTS

This section describes the Level of Service analyses for the study area intersections and roadway segments with the addition of project traffic to Existing Conditions.

EXISTING PLUS PROJECT CONDITIONS

The daily and peak hour turn volumes for existing plus project conditions are illustrated in Figure 7.

Roadway Segments

The roadway segments were analyzed with the traffic generated from the proposed project added to existing traffic volumes. Table 5 displays the Level of Service Analysis results for the roadway segments under the Existing Plus Project scenario. As shown in the table, all roadway segments are expected to operate at LOS “A” with the addition of the project except for the segment between Tourney Road and Wayne Mills Place along Magic Mountain Parkway. This segment will continue to operate at LOS “E”. However, with the addition of the project traffic, the increase in v/c ratio does not exceed the significance threshold. As a result, no additional roadway improvements are required and/or recommended.

Intersections

The intersections were analyzed with the traffic generated from the proposed project added to existing traffic volumes. Table 6 displays the Level of Service Analysis results for the study intersections under the Existing Plus Project scenario. As shown in the table, all intersections, including the project driveway, are expected to operate at LOS “D” or better with the addition of the project traffic. The increase in delay does not exceed the significance thresholds. As a result, no additional intersection improvements are required and/or recommended.

A copy of the ICU/LOS worksheets for existing plus project conditions can be found in Appendix C.

2017 OPENING DAY PLUS PROJECT CONDITIONS


Opening Day 2017 traffic conditions are estimated by adding 3% ambient growth to existing traffic volumes plus project traffic. Figure 8 presents the 2017 Opening Day volumes and Figure 9 presents the Opening Day plus project conditions.

Roadway Segments

The roadway segments were analyzed with the traffic generated from the proposed project added to existing traffic volumes plus 3% ambient growth. Table 7 displays the Level of Service Analysis results for the roadway segments under the Existing Plus Project scenario. As shown in the table, all roadway segments are expected to operate at LOS “A” with the addition of the project except for the segment between Tourney Road and Wayne Mills Place along Magic Mountain Parkway. This segment will continue to operate at LOS “E”. However, with the addition of the project traffic, the increase in v/c ratio does not exceed the significance threshold. As a result, no additional roadway improvements are required and/or recommended.

Intersections

The intersections were analyzed with the traffic generated from the proposed project added to existing traffic volumes plus 3% ambient growth. Table 8 displays the Level of Service Analysis results for the study intersections under the Existing Plus Project scenario. As shown in the table, all intersections, including the project driveway, are expected to operate at LOS “D” or better with the addition of the project traffic. The increase in delay does not exceed the significance thresholds. As a result, no additional intersection improvements are required and/or recommended.



LEGEND

- - DIRECTION OF TRAVEL
- XX/YY - AM/PM PEAK HOUR TRAFFIC VOLUMES
- ⊞ - SIGNAL
- - STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 160005-AA DATE: September 15, 2016 BY: JAB

FIGURE 7
EXISTING PLUS PROJECT
TRAFFIC VOLUMES

Table 5 - Existing Plus Project Roadway Segment Level of Service Summary

Roadway Segment	Classification	Existing Number of Lanes	LOS "E" Capacity	Existing			Existing Plus Project			
				ADT	v/c	LOS	ADT	v/c	LOS	Δ in v/c
Magic Mountain Pkwy	Major Arterial	6-Lane Divided	54,000	34,744	0.64	A	34,991	0.65	A	0.00
The Old Rd to I-5 SB Ramps				32,584	0.60	A	33,450	0.62	A	0.02
I-5 NB Ramps to Tourney Road				51,703	0.96	E	51,950	0.96	E	0.00
Tourney Road	Secondary Highway	4-Lane Undivided	24,000	10,230	0.43	A	11,343	0.47	A	0.05
Magic Mountain Pkwy to Wayne Mills Place				5,999	0.25	A	6,123	0.26	A	0.01
South of Wayne Mills Place										
Wayne Mills Place										
West of Tourney Road	Local	2-Lane	5,000	1,434	0.29	A	2,671	0.53	A	0.24

Volume on this segment was estimated. Capacity is based on the upper limits of LOS E per the City of Santa Clarita General Plan Circulation Element. ADT= Average Daily Traffic, LOS= Level of Service.

Table 6 - Existing Plus Project Intersection Level of Service Summary

#	Intersection	Traffic Control	Peak Hour	Existing Conditions		Existing Plus Project		Δ in ICU/Delay
				ICU/Delay (a)	LOS (b)	ICU/Delay (a)	LOS (b)	
1	The Old Road & Magic Mountain Pkwy	Signal	AM PM	0.196 0.470	A A	0.198 0.475	A A	0.002 0.005
2	I-5 SB Ramps & Magic Mountain Pkwy	Signal	AM PM	0.356 0.403	A A	0.362 0.415	A A	0.006 0.012
3	I-5 NB Ramps & Magic Mountain Pkwy	Signal	AM PM	0.493 0.510	A A	0.496 0.523	A A	0.003 0.013
4	Tourney Road & Magic Mountain Pkwy	Signal	AM PM	0.465 0.530	A A	0.480 0.536	A A	0.015 0.006
5	Tourney Road & Wayne Mills Place	TWSC	AM PM	5.4 5.0	A A	6.8 6.4	A A	2.4 1.4
6	Project Driveway & Wayne Mills Place	OWSC	AM PM		DNE	8.8 8.9	A A	5.0 5.0


Notes:

DNE = Does not exist, TWSC = Two Way Stop Control, OWSC = One Way Stop Control.

a. ICU is reported at signalized intersections.

b. LOS calculations are based on the methodology outlined in the 2000 Highway Capacity Manual (HCM).

Delays at unsignalized intersections are reported based on intersection delay using Synchro 8 - Intersection Capacity Software



LEGEND


- - DIRECTION OF TRAVEL
- XX/YY - AM/PM PEAK HOUR TRAFFIC VOLUMES
- ◻ - SIGNAL
- - STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 180605-AA DATE: September 15, 2016 BY: JAB

FIGURE 8
 2017 OPENING DAY
 TRAFFIC VOLUMES



PROJECT SITE

LEGEND

→ - DIRECTION OF TRAVEL

XX/YY - AM/PM PEAK HOUR TRAFFIC VOLUMES

◻ - SIGNAL

○ - STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

FIGURE 9
 2017 PLUS OPENING DAY
 PLUS EXISTING PLUS PROJECT
 TRAFFIC VOLUMES

DWG: 160605-AA DATE: September 15, 2016 BY: JAB

Table 7 – Existing Plus Project Plus 2017 Opening Day Roadway Segment Level of Service Summary

Roadway Segment	Classification	Existing Number of Lanes	LOS "E" Capacity	Existing Plus Project			Existing Plus Project Plus Ambient Growth			
				ADT	v/c	LOS	ADT	v/c	LOS	Δ in v/c
Magic Mountain Pkwy										
The Old Rd to I-5 SB Ramps	Major Arterial	6-Lane Divided	54,000	34,991	0.65	A	36,041	0.67	B	0.02
I-5 NB Ramps to Tourney Road				33,450	0.62	B	34,454	0.64	B	0.02
Tourney Road to Wayne Mills Place				51,950	0.96	E	53,509	0.99	E	0.03
Tourney Road										
Magic Mountain Pkwy to Wayne Mills Place	Secondary Highway	4-Lane Undivided	24,000	11,343	0.47	A	11,683	0.49	A	0.02
South of Wayne Mills Place				6,123	0.26	A	6,307	0.26	A	0.00
Wayne Mills Place										
West of Tourney Road	Local	2-Lane	5,000	2,671	0.53	A	2,751	0.28	A	0.01

Volume on this segment was estimated. Capacity is based on the upper limits of LOS E per the City of Santa Clarita General Plan Circulation Element; ADT= Average Daily Traffic; LOS= Level of Service.

Table 8 - Existing Plus Project Plus 2017 Opening Day Intersection Level of Service Summary

#	Intersection	Traffic Control	Peak Hour	Existing Conditions		Existing Plus Project Conditions		Existing Plus Project Plus Ambient Growth		Δ in ICU/Delay
				ICU/Delay (a)	LOS (b)	ICU/Delay (a)	LOS (b)	ICU/Delay (a)	LOS (b)	
1	The Old Road & Magic Mountain Pkwy	Signal	AM	0.196	A	0.198	A	0.202	A	0.004
			PM	0.470	A	0.475	A	0.490	A	0.015
			AM	0.356	A	0.362	A	0.371	A	0.006
2	I-5 SB Ramps & Magic Mountain Pkwy	Signal	PM	0.403	A	0.415	A	0.426	A	0.012
			AM	0.493	A	0.496	A	0.510	A	0.003
			PM	0.510	A	0.523	A	0.543	A	0.013
3	I-5 NB Ramps & Magic Mountain Pkwy	Signal	AM	0.465	A	0.480	A	0.492	A	0.015
			PM	0.530	A	0.536	A	0.546	A	0.006
			AM	5.4	A	6.8	A	7.1	A	0.3
4	Tourney Road & Magic Mountain Pkwy	TWSC	PM	5.0	A	6.4	A	6.7	A	0.3
			AM		A	5.0	A	4.9	A	0.0
			PM		DNE	5.0	A	5.0	A	0.0

Notes:

DNE = Does not exist, TWSC = Two Way Stop Control, OWSC = One Way Stop Control.
 (a) ICU is reported at signalized intersections.

(b) LOS calculations are based on the methodology outlined in the 2000 Highway Capacity Manual (HCM).
 Delays at unsignalized intersections are reported based on intersection delay using Synchro 8 – Intersection Capacity Software

SECTION V - SUMMARY OF FINDINGS AND CONCLUSIONS

The following list provides a summary of the key findings for the project:

- The project is forecasted to generate a net increase of approximately 1,237 daily trips with 99 AM peak-hour trips and 105 PM peak-hour trips.
- All study area intersections, including the project driveway, are expected to operate at an acceptable LOS "D" or better during the AM and PM peak hours with the addition of project traffic.
- All study area roadway segments are expected to operate at an acceptable LOS "A" or better, except for the segment of Magic Mountain Parkway between Tourney Road and Wayne Mills Place, which is currently operating at LOS "E" and will continue to operate at LOS "E" with the addition of project traffic.
- The increase in project traffic at the study area intersections and roadway segments do not result in a significant impact and therefore no additional improvements are required and/or recommended.

APPENDIX A

- 24-Hour Segment Counts
- AM/PM Peak Hour Turn Counts

Prepared by NDS/ATD

VOLUME

Wayne Mills PI E/O Driveway #3

Day: Monday
Date: 7/4/2016

City: Santa Clarita
Project #: CA16_5446_001

DAILY TOTALS						NB	SB	EB	WB	Total	
						0	0	734	700	1,434	
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00			7	15	22	12:00			13	6	19
00:15			9	10	19	12:15			11	11	22
00:30			5	5	10	12:30			11	9	20
00:45			3	24	3	12:45			12	47	10
01:00			10	3	33	6	57		10	36	22
01:15			2	5	7				13	5	18
01:30			5	5	10	13:00			8	8	16
01:45			4	21	1	13:15			6	1	7
02:00			5	2	7	13:30			8	35	5
02:15			0	1	1	13:45			12	10	19
02:30			1	1	2	14:00			8	3	11
02:45			0	6	1	14:15			7	5	12
03:00			1	2	3	14:30			4	31	13
03:15			2	0	2	14:45			6	4	10
03:30			1	1	2	15:00			4	3	7
03:45			0	4	0	15:15			6	13	19
04:00			4	0	4	15:30			8	24	6
04:15			0	0	0	15:45			9	8	17
04:30			1	1	2	16:00			10	10	20
04:45			0	5	5	16:15			7	4	11
05:00			2	2	4	16:30			9	35	6
05:15			2	5	7	16:45			9	28	15
05:30			3	2	5	17:00			5	6	11
05:45			3	10	4	17:15			2	10	12
06:00			4	3	7	17:30			6	9	15
06:15			6	4	10	17:45			4	17	4
06:30			4	6	10	18:00			5	2	7
06:45			3	17	7	18:15			7	9	16
07:00			7	2	9	18:30			10	14	24
07:15			2	12	14	18:45			2	24	9
07:30			7	10	17	19:00			6	8	14
07:45			8	24	17	19:15			10	3	13
08:00			9	3	12	19:30			4	4	8
08:15			4	9	13	19:45			7	27	7
08:30			11	8	19	20:00			3	8	11
08:45			9	33	8	20:15			7	13	20
09:00			19	16	35	20:30			8	10	18
09:15			17	8	25	20:45			2	20	9
09:30			21	15	36	21:00			11	15	26
09:45			23	80	17	21:15			8	7	15
10:00			27	10	37	21:30			3	9	12
10:15			26	10	36	21:45			7	29	11
10:30			22	13	35	22:00			7	13	20
10:45			21	96	11	22:15			6	17	23
11:00			20	12	32	22:30			4	14	18
11:15			15	7	22	22:45			9	26	20
11:30			23	5	28	23:00			8	9	17
11:45			11	69	8	23:15			7	9	16
TOTALS			389	295	684	TOTALS			345	405	750
SPLIT %			56.9%	43.1%	47.7%	SPLIT %			46.0%	54.0%	52.3%

DAILY TOTALS						NB	SB	EB	WB	Total	
						0	0	734	700	1,434	
AM Peak Hour			09:45	09:00	09:30	PM Peak Hour			12:00	22:00	22:00
AM Pk Volume			98	56	149	PM Pk Volume			47	64	90
Pk Hr Factor			0.907	0.824	0.931	Pk Hr Factor			0.904	0.800	0.776
7 - 9 Volume			57	69	126	4 - 6 Volume			52	57	109
7 - 9 Peak Hour			08:00	07:15	07:45	4 - 6 Peak Hour			16:00	16:45	16:00
7 - 9 Pk Volume			33	42	69	4 - 6 Pk Volume			35	31	63
Pk Hr Factor			0.750	0.618	0.690	Pk Hr Factor			0.875	0.775	0.788

Existing AM/PM Peak Hour Traffic Counts

Prepared by NDS/ATD

VOLUME

Tourney Rd Bet. Magic Mountain Pkwy & Wayne Mills Pl

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_001

DAILY TOTALS						NB	SB	EB		WB	Total
						5,001	5,229	0		0	10,230
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00	13	7			20	12:00	137	76			213
00:15	9	5			14	12:15	132	90			222
00:30	3	5			8	12:30	104	96			200
00:45	6	31	5	22	11	12:45	116	489	115	377	231
01:00	4	4			8	13:00	78	135			213
01:15	5	5			10	13:15	85	109			194
01:30	4	3			7	13:30	84	99			183
01:45	1	14	1	13	2	13:45	91	338	116	459	207
02:00	6	3			9	14:00	78	76			154
02:15	2	11			13	14:15	78	88			166
02:30	2	5			7	14:30	78	102			180
02:45	2	12	2	21	4	14:45	91	325	100	366	191
03:00	5	1			6	15:00	91	85			176
03:15	3	0			3	15:15	81	87			168
03:30	8	4			12	15:30	101	69			170
03:45	3	19	4	9	7	15:45	83	356	71	312	154
04:00	0	3			3	16:00	105	85			190
04:15	3	6			9	16:15	101	78			179
04:30	8	6			14	16:30	137	60			197
04:45	7	18	11	26	18	16:45	136	479	73	296	209
05:00	11	13			24	17:00	182	66			248
05:15	25	23			48	17:15	95	69			164
05:30	23	15			38	17:30	127	55			182
05:45	24	83	17	68	41	17:45	94	498	46	236	140
06:00	29	24			53	18:00	95	51			146
06:15	21	40			61	18:15	57	60			117
06:30	43	34			77	18:30	63	48			111
06:45	31	124	77	175	108	18:45	61	276	38	197	99
07:00	33	55			88	19:00	40	34			74
07:15	39	97			136	19:15	41	33			74
07:30	38	118			156	19:30	45	34			79
07:45	40	150	155	425	195	19:45	37	163	30	131	67
08:00	38	153			191	20:00	41	31			72
08:15	55	177			232	20:15	36	35			71
08:30	41	138			179	20:30	39	29			68
08:45	48	182	145	613	193	20:45	21	137	24	119	45
09:00	70	116			186	21:00	50	33			83
09:15	82	88			170	21:15	20	16			36
09:30	85	99			184	21:30	25	30			55
09:45	75	312	102	405	177	21:45	27	122	30	109	57
10:00	86	120			206	22:00	22	18			40
10:15	82	99			181	22:15	16	23			39
10:30	102	72			174	22:30	14	11			25
10:45	72	342	99	390	171	22:45	9	61	10	62	19
11:00	101	84			185	23:00	15	13			28
11:15	86	91			177	23:15	13	6			19
11:30	125	91			216	23:30	11	9			20
11:45	110	422	89	355	199	23:45	9	48	15	43	24
TOTALS	1709	2522			4231	TOTALS	3292	2707			5999
SPLIT %	40.4%	59.6%			41.4%	SPLIT %	54.9%	45.1%			58.6%

DAILY TOTALS						NB	SB	EB		WB	Total
						5,001	5,229	0		0	10,230
AM Peak Hour	11:30	07:45			11:30	PM Peak Hour	16:15	13:00			12:00
AM Pk Volume	504	623			850	PM Pk Volume	556	459			866
PK Hr Factor	0.920	0.880			0.957	PK Hr Factor	0.764	0.850			0.937
7 - 9 Volume	332	1038			1370	4 - 6 Volume	977	532			1509
7 - 9 Peak Hour	08:00	07:45			07:45	4 - 6 Peak Hour	16:15	16:00			16:15
7 - 9 Pk Volume	182	623			797	4 - 6 Pk Volume	556	296			833
PK Hr Factor	0.827	0.880			0.859	PK Hr Factor	0.764	0.871			0.840

Prepared by NDS/ATD

VOLUME

Tourney Rd S/O Wayne Mills Pl

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_002

DAILY TOTALS					NB	SB	EB	WB	Total		
					2,940	3,059	0	0	5,999		
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00	12	6			18	12:00	42	53			95
00:15	4	8			12	12:15	47	53			100
00:30	10	5			15	12:30	42	56			98
00:45	6	32	3	22	9	12:45	33	164	49	211	82
01:00	3	6			9	13:00	49	48			97
01:15	3	3			6	13:15	40	65			105
01:30	4	6			10	13:30	50	58			108
01:45	5	15	4	19	9	13:45	48	187	37	208	85
02:00	7	8			15	14:00	44	42			86
02:15	8	4			12	14:15	30	43			73
02:30	5	2			7	14:30	50	45			95
02:45	5	25	3	17	8	14:45	46	170	40	170	86
03:00	5	2			7	15:00	43	53			96
03:15	1	6			7	15:15	45	51			96
03:30	5	8			13	15:30	41	34			75
03:45	5	16	3	19	8	15:45	45	174	47	185	92
04:00	8	7			15	16:00	41	39			80
04:15	9	13			22	16:15	45	41			86
04:30	13	4			17	16:30	50	40			90
04:45	16	46	8	32	24	16:45	49	185	54	174	103
05:00	14	10			24	17:00	54	43			97
05:15	21	13			34	17:15	50	61			111
05:30	26	9			35	17:30	65	55			120
05:45	19	80	25	57	44	17:45	51	220	72	231	123
06:00	27	21			48	18:00	67	41			108
06:15	29	26			55	18:15	51	44			95
06:30	29	26			55	18:30	50	45			95
06:45	25	110	39	112	64	18:45	50	218	37	167	87
07:00	31	25			56	19:00	45	53			98
07:15	30	45			75	19:15	43	45			88
07:30	42	44			86	19:30	33	52			85
07:45	32	135	25	139	57	19:45	36	157	54	204	90
08:00	35	36			71	20:00	41	48			89
08:15	28	24			52	20:15	37	49			86
08:30	32	31			63	20:30	48	46			94
08:45	35	130	23	114	58	20:45	36	162	57	200	93
09:00	30	36			66	21:00	40	38			78
09:15	38	33			71	21:15	42	36			78
09:30	35	37			72	21:30	30	29			59
09:45	45	148	34	140	79	21:45	26	138	27	130	53
10:00	22	48			70	22:00	21	27			48
10:15	34	34			68	22:15	22	21			43
10:30	40	40			80	22:30	16	12			28
10:45	42	138	40	162	82	22:45	15	74	23	83	38
11:00	43	39			82	23:00	17	26			43
11:15	35	38			73	23:15	17	11			28
11:30	34	58			92	23:30	14	22			36
11:45	48	160	57	192	105	23:45	8	56	12	71	20
TOTALS	1035	1025			2060	TOTALS	1905	2034			3939
SPLIT %	50.2%	49.8%			34.3%	SPLIT %	48.4%	51.6%			65.7%

DAILY TOTALS					NB	SB	EB	WB	Total
					2,940	3,059	0	0	5,999
AM Peak Hour	11:45	11:30			11:45	PM Peak Hour	17:30	17:00	17:15
AM Pk Volume	179	221			398	PM Pk Volume	234	231	462
Pk Hr Factor	0.932	0.953			0.948	Pk Hr Factor	0.873	0.802	0.939
7 - 9 Volume	265	258			518	4 - 6 Volume	405	405	810
7 - 9 Peak Hour	07:15	07:15			07:15	4 - 6 Peak Hour	17:00	17:00	17:00
7 - 9 Pk Volume	139	150			289	4 - 6 Pk Volume	220	231	451
Pk Hr Factor	0.827	0.833			0.840	Pk Hr Factor	0.846	0.802	0.917

Prepared by NDS/ATD

VOLUME

Magic Mountain Pkwy Bet. I-5 NB Ramps & Tourney Rd

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_003

DAILY TOTALS						NB	SB	EB	WB	Total		
						0	0	16,525	16,059	32,584		
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL	
00:00			50	34	84	12:00			263	227	490	
00:15			34	28	62	12:15			248	293	541	
00:30			25	36	61	12:30			261	282	543	
00:45		128	19	20	118	12:45			240	1012	249	1051
01:00			29	21	50	13:00			265	286	551	
01:15			28	14	42	13:15			249	273	522	
01:30			22	12	34	13:30			213	245	458	
01:45		96	17	12	59	13:45			200	927	238	1042
02:00			30	13	43	14:00			206	247	453	
02:15			22	7	29	14:15			224	213	437	
02:30			8	18	26	14:30			246	241	487	
02:45		68	8	14	52	14:45			229	905	247	948
03:00			10	6	16	15:00			240	258	498	
03:15			13	7	20	15:15			293	268	561	
03:30			23	19	42	15:30			306	243	549	
03:45		74	28	18	50	15:45			353	1192	253	1022
04:00			19	21	40	16:00			373	245	618	
04:15			25	28	53	16:15			358	272	630	
04:30			52	54	106	16:30			391	248	639	
04:45		164	68	60	163	16:45			392	1514	290	1055
05:00			57	94	151	17:00			402	276	678	
05:15			63	135	198	17:15			433	268	701	
05:30			67	147	214	17:30			366	223	589	
05:45		259	72	193	569	17:45			405	1606	249	1016
06:00			91	180	271	18:00			288	248	536	
06:15			87	169	256	18:15			277	215	492	
06:30			133	220	353	18:30			244	177	421	
06:45		488	177	237	806	18:45			218	1027	195	835
07:00			155	184	339	19:00			222	174	396	
07:15			177	250	427	19:15			203	163	366	
07:30			233	247	480	19:30			177	170	347	
07:45		850	285	279	960	19:45			189	791	174	681
08:00			270	257	527	20:00			181	136	317	
08:15			248	253	501	20:15			150	152	302	
08:30			227	233	460	20:30			138	165	303	
08:45		985	240	243	986	20:45			127	596	153	606
09:00			236	247	483	21:00			141	173	314	
09:15			206	245	451	21:15			135	164	299	
09:30			228	235	463	21:30			161	144	305	
09:45		927	257	217	944	21:45			138	575	124	605
10:00			208	239	447	22:00			97	110	207	
10:15			243	246	489	22:15			96	96	192	
10:30			208	229	437	22:30			78	82	160	
10:45		859	200	213	927	22:45			63	334	63	351
11:00			243	244	487	23:00			61	66	127	
11:15			211	252	463	23:15			54	52	106	
11:30			236	292	528	23:30			50	45	95	
11:45		924	234	238	1026	23:45			59	224	24	187
TOTALS			5822	6660	12482	TOTALS			10703	9399	20102	
SPLIT %			46.6%	53.4%	38.3%	SPLIT %			53.2%	46.8%	61.7%	

DAILY TOTALS						NB	SB	EB	WB	Total
						0	0	16,525	16,059	32,584

AM Peak Hour			07:30	11:30	07:30	PM Peak Hour			16:30	12:15	16:30
AM Pk Volume			1036	1050	2072	PM Pk Volume			1618	1110	2700
Pk Hr Factor			0.909	0.856	0.918	Pk Hr Factor			0.934	0.947	0.963
7 - 9 Volume	0	0	1835	1946	3781	4 - 6 Volume	0	0	3120	2071	5191
7 - 9 Peak Hour			07:30	07:30	07:30	4 - 6 Peak Hour			16:30	16:15	16:30
7 - 9 Pk Volume	0	0	1036	1036	2072	4 - 6 Pk Volume	0	0	1618	1086	2700
Pk Hr Factor	0.000	0.000	0.909	0.928	0.918	Pk Hr Factor	0.000	0.000	0.934	0.936	0.963

Prepared by NDS/ATD

VOLUME

Magic Mountain Pkwy Bet. The Old Rd & I-5 SB Ramps

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_004

DAILY TOTALS					NB	SB	EB	WB	Total		
					0	0	12,286	22,458	34,744		
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00			20	56	76	12:00			227	393	620
00:15			16	30	46	12:15			121	460	581
00:30			7	42	49	12:30			117	415	532
00:45			19	62	24	12:45			122	587	360
01:00			19	20	39	13:00			135	339	1628
01:15			6	20	26	13:15			111	323	474
01:30			14	26	40	13:30			213	303	434
01:45			14	53	20	13:45			121	580	208
02:00			8	24	32	14:00			189	275	1173
02:15			13	22	35	14:15			165	246	464
02:30			6	32	38	14:30			185	259	411
02:45			10	37	29	14:45			134	673	303
03:00			9	10	19	15:00			160	290	1083
03:15			10	22	32	15:15			218	335	450
03:30			5	36	41	15:30			261	287	553
03:45			12	36	60	15:45			256	895	329
04:00			1	37	38	16:00			241	312	1241
04:15			5	50	55	16:15			243	328	553
04:30			16	95	111	16:30			266	312	571
04:45			8	30	118	16:45			271	1021	359
05:00			12	103	115	17:00			268	344	1311
05:15			20	154	174	17:15			295	306	612
05:30			16	254	270	17:30			253	327	601
05:45			35	83	323	17:45			254	1070	347
06:00			38	178	216	18:00			228	417	1324
06:15			36	217	253	18:15			209	338	645
06:30			39	270	309	18:30			357	274	547
06:45			32	145	359	18:45			286	1080	289
07:00			52	297	349	19:00			270	246	1318
07:15			65	353	418	19:15			219	283	516
07:30			71	314	385	19:30			275	212	502
07:45			90	278	368	19:45			322	1086	209
08:00			61	338	399	20:00			301	178	950
08:15			81	292	373	20:15			244	192	479
08:30			71	266	337	20:30			346	191	436
08:45			75	288	292	20:45			393	1284	157
09:00			89	357	446	21:00			343	172	718
09:15			126	320	446	21:15			247	157	515
09:30			126	389	515	21:30			122	149	404
09:45			136	477	416	21:45			129	841	120
10:00			162	500	662	22:00			71	123	598
10:15			129	504	633	22:15			85	102	194
10:30			142	503	645	22:30			96	84	187
10:45			167	600	511	22:45			34	286	74
11:00			119	486	605	23:00			51	87	383
11:15			114	488	602	23:15			70	65	138
11:30			155	432	587	23:30			36	45	135
11:45			218	606	420	23:45			31	188	45
TOTALS			2695	10477	13172	TOTALS			9591	11981	21572
SPLIT %			20.5%	79.5%	37.9%	SPLIT %			44.5%	55.5%	62.1%

DAILY TOTALS					NB	SB	EB	WB	Total
					0	0	12,286	22,458	34,744

AM Peak Hour	11:30	10:00	10:00	PM Peak Hour	20:30	12:00	17:15
AM Pk Volume	721	2018	2618	PM Pk Volume	1329	1628	2427
Pk Hr Factor	0.794	0.987	0.965	Pk Hr Factor	0.845	0.885	0.941
7 - 9 Volume	566	2520	3086	4 - 6 Volume	2091	2635	4726
7 - 9 Peak Hour	07:30	07:15		4 - 6 Peak Hour	16:30	16:15	16:45
7 - 9 Pk Volume	303	1373	1660	4 - 6 Pk Volume	1100	1343	2423
Pk Hr Factor	0.842	0.933	0.906	Pk Hr Factor	0.932	0.995	0.962

Prepared by NOS/ATD

VOLUME

Magic Mountain Pkwy E/O Tourney Rd

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_005

DAILY TOTALS						NB	SB	EB	WB	Total	
						0	0	25,143	26,560	51,703	
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00			71	62	133	12:00			358	458	816
00:15			66	56	122	12:15			376	495	871
00:30			68	38	106	12:30			356	417	773
00:45			47	252	39	12:45			437	1527	1776
01:00			50	53	103	13:00			331	465	796
01:15			44	34	78	13:15			373	456	829
01:30			48	30	78	13:30			428	542	970
01:45			41	183	38	13:45			422	1554	1976
02:00			57	44	101	14:00			424	396	820
02:15			43	23	66	14:15			399	523	922
02:30			53	18	71	14:30			357	599	956
02:45			59	212	35	14:45			430	1610	2067
03:00			49	29	78	15:00			424	523	947
03:15			42	43	85	15:15			361	505	866
03:30			72	41	113	15:30			437	427	864
03:45			33	196	37	15:45			403	1625	2028
04:00			71	63	134	16:00			459	258	717
04:15			76	69	145	16:15			425	301	726
04:30			87	97	184	16:30			460	229	689
04:45			135	369	106	16:45			457	1801	2258
05:00			114	102	216	17:00			505	259	764
05:15			135	151	286	17:15			423	286	709
05:30			201	230	431	17:30			504	220	724
05:45			195	645	231	17:45			428	1860	2288
06:00			165	224	389	18:00			499	345	844
06:15			195	254	449	18:15			472	398	870
06:30			226	281	507	18:30			409	396	805
06:45			206	792	256	18:45			415	1795	2210
07:00			192	201	393	19:00			420	349	769
07:15			201	332	533	19:15			454	370	824
07:30			253	294	547	19:30			362	382	744
07:45			270	916	389	19:45			371	1607	1978
08:00			219	325	544	20:00			333	319	652
08:15			266	389	655	20:15			333	355	688
08:30			275	301	576	20:30			275	317	592
08:45			264	1024	341	20:45			283	1224	1507
09:00			288	333	621	21:00			290	419	709
09:15			262	364	626	21:15			290	406	696
09:30			287	427	714	21:30			234	284	518
09:45			351	1188	380	21:45			210	1024	1234
10:00			309	401	710	22:00			194	225	419
10:15			262	410	672	22:15			195	201	396
10:30			341	474	815	22:30			150	149	299
10:45			325	1237	344	22:45			154	693	847
11:00			353	411	764	23:00			127	141	268
11:15			343	463	806	23:15			118	114	232
11:30			313	447	760	23:30			115	109	224
11:45			360	1369	442	23:45			80	440	520
TOTALS			8383	10152	18535	TOTALS			16760	16408	33168
SPLIT %			45.2%	54.8%	35.8%	SPLIT %			50.5%	49.5%	64.2%

DAILY TOTALS						NB	SB	EB	WB	Total	
						0	0	25,143	26,560	51,703	
AM Peak Hour			11:45	11:30	11:45	PM Peak Hour			17:30	14:15	14:15
AM Pk Volume			1450	1842	3262	PM Pk Volume			1903	2194	3804
Pk Hr Factor			0.964	0.930	0.936	Pk Hr Factor			0.944	0.916	0.971
7 - 9 Volume			1940	2572	4512	4 - 6 Volume			3661	2149	5810
7 - 9 Peak Hour			07:45	07:45	07:45	4 - 6 Peak Hour			16:45	16:15	16:45
7 - 9 Pk Volume			1030	1404	2434	4 - 6 Pk Volume			1889	1120	2985
Pk Hr Factor			0.900	0.900	0.936	Pk Hr Factor			0.935	0.846	0.947

Existing 24 Hour Machine Counts

Intersection Turning Movement

Prepared by:
National Data & Surveying Services

Project ID: 16-5499-001

Day: Thursday

City: Santa Clarita

Date: 7/28/2016

NS/EW Streets:	AM													TOTAL
	I-5 WB Ramps			I-5 NB Ramps			Magic Mountain Pkwy			Magic Mountain Pkwy				
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND				
LANES:	NL 2	NT 0.5	NR 1.5	SL 0	ST 0	SR 0	EL 2	ET 3	ER 0	WL 0	WT 3.5	WR 1.5	TOTAL	
7:00 AM	235	0	93	0	0	0	1	63	0	0	145	39	576	
7:15 AM	280	0	108	0	0	0	11	87	0	0	196	53	723	
7:30 AM	237	0	129	0	0	0	11	117	0	0	197	51	742	
7:45 AM	292	0	143	0	0	0	9	128	0	0	207	72	851	
8:00 AM	253	0	158	0	0	0	9	116	0	0	201	41	778	
8:15 AM	221	0	125	0	0	0	4	115	0	0	216	52	736	
8:30 AM	186	0	123	0	0	0	5	107	0	0	192	35	648	
8:45 AM	212	0	117	0	0	0	6	119	0	0	210	39	793	
TOTAL VOLUMES :	1924	0	999	0	0	0	56	832	0	0	1564	382	5757	
APPROACH %'s :	65.82%	0.00%	34.18%	#DIV/0!	#DIV/0!	#DIV/0!	6.31%	93.69%	0.00%	0.00%	80.37%	19.63%		
PEAK HR START TIME :	7:30 AM													
PEAK HR VOL :	1003	0	558	0	0	0	33	476	0	0	221	216	3107	
PEAK HR FACTOR :	0.897			0.600			0.929			0.929			0.913	

CONTROL : Signalized

UTURNS			
NB	SB	EB	WB

NB 0	SB 0	EB 0	WB 0
---------	---------	---------	---------

ITM Peak Hour Summary




Prepared by:
National Data & Surveying Services


I-5 NB Ramps and Magic Mountain Pkwy, Santa Clarita

Date: 7/28/2016
Day: Thursday


Project#: 16-5499-001
City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



Intersection Turning Movement

Prepared by:
National Data & Surveying Services

Project ID: 16-5499-002

City: Santa Clarita

Day: Thursday

Date: 7/28/2016

NS/EW Streets:	AM												TOTAL
	I-5 SB Ramps			I-5 SB Ramp			Magic Mountain Pkwy			Magic Mountain Fwy			
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND			
LANES:	NL	NT	NR	SL	ST	SR	EL	ET	ER	WL	WT	WR	TOTAL
7:00 AM	0	0	0	31	1	11	0	37	17	119	262	0	
7:15 AM	0	0	0	39	0	10	0	32	30	135	346	0	592
7:30 AM	0	0	0	76	0	6	0	51	24	130	307	0	594
7:45 AM	0	0	0	85	1	10	0	57	26	117	355	0	651
8:00 AM	0	0	0	83	0	11	0	42	29	140	320	0	625
8:15 AM	0	0	0	67	0	10	0	53	22	151	285	0	591
8:30 AM	0	0	0	63	0	8	0	46	32	119	252	0	520
8:45 AM	0	0	0	70	1	15	0	54	20	140	286	0	586
TOTAL VOLUMES :	NL	NT	NR	SL	ST	SR	EL	ET	ER	WL	WT	WR	TOTAL
APPROACH %'s :	#DIV/0!	#DIV/0!	#DIV/0!	85.95%	0.50%	13.55%	0.00%	65.03%	34.97%	30.23%	69.77%	0.00%	4657

PEAK HR START TIME :	7:15 AM												TOTAL
PEAK HR VOL :	0	0	0	263	1	37	0	192	109	522	1328	0	2462
PEAK HR FACTOR :	0.000			0.836			0.877			0.962			0.945

CONTROL : Signalized

UTURNS			
NB	SB	EB	WB
			0
			0
			0
			0
			0
			1
			2
			0

NB	SB	EB	WB
0	0	0	3

Intersection Turning Movement

Prepared by:
National Data & Surveying Services

Project ID: 16-5499-002

Day: Thursday

City: Santa Carla

Date: 7/28/2016

NS/EW Streets:	PM												TOTAL
	I-5 SB Ramps			I-5 SB Ramps			Magic Mountain Pkwy			Magic Mountain Pkwy			
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND			
LANES:	NL 0	NT 0	NR 0	SL 1.5	ST 0.5	SR 2	EL 0	ET 3	ER 2	WL 2	WT 4	WR 0	
4:00 PM	0	0	0	70	0	42	0	177	73	77	279	0	718
4:15 PM	0	0	0	47	1	32	0	168	69	69	256	0	681
4:30 PM	0	0	0	76	0	25	0	173	99	87	279	0	739
4:45 PM	0	0	0	60	0	30	0	188	76	71	330	0	755
5:00 PM	0	0	0	67	0	32	0	195	89	106	300	0	788
5:15 PM	0	0	0	58	0	24	1	219	73	74	281	0	730
5:30 PM	0	0	0	43	0	25	0	180	75	84	254	0	701
5:45 PM	0	0	0	48	1	30	0	176	72	74	317	0	718
TOTAL VOLUMES	NL 0	NT 0	NR 0	SL 469	ST 2	SR 240	EL 1	ET 1476	ER 616	WL 642	WT 2384	WR 0	TOTAL 5830
APPROACH %'s :	#DIV/0	#DIV/0	#DIV/0	65.96%	0.28%	33.76%	0.05%	70.52%	28.43%	21.22%	78.78%	0.00%	
PEAK HR START TIME :	4:30 PM												
PEAK HR VOL :	0	0	0	761	0	111	1	775	328	338	1198	0	TOTAL 3012
PEAK HR FACTOR :	0.000			0.921			0.942			0.928			0.956

CONTROL : Signalized

UTURNS			
NB	SB	EB	WB
		0	0
		0	0
		0	0
		0	0
		1	0
		0	0
		0	1
NB 0	SB 0	EB 1	WB 1

ITM Peak Hour Summary

Prepared by:




National Data & Surveying Services


I-5 SB Ramps and Magic Mountain Pkwy, Santa Clarita

Date: 7/28/2016
Day: Thursday


Project #: 16-5469-002
City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



Intersection Turning Movement

Prepared by:
National Data & Surveying Services

Project ID: 16-5499-003

Day: Thursday

City: Santa Clarita

Date: 7/28/2016

NS/EW Streets:	AM													TOTAL
	The Old Rd			The Old Rd			Magic Mountain Hwy			Magic Mountain Hwy				
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND				
LANES:	NL 2	NT 3	NR 1	SL 2	ST 3	SR 1	EL 2	ET 4	ER 1	WL 2	WT 4	WR 1	TOTAL	
7:00 AM	5	54	13	36	20	0	6	6	1	24	20	255	440	
7:15 AM	12	62	16	33	28	0	4	16	0	36	20	293	520	
7:30 AM	5	71	18	38	28	0	9	16	1	32	22	263	503	
7:45 AM	5	81	25	43	29	1	7	13	1	35	18	316	574	
8:00 AM	2	69	19	33	48	0	7	24	0	25	18	291	536	
8:15 AM	3	66	20	37	54	0	4	9	4	26	10	269	513	
8:30 AM	4	73	14	42	40	0	4	21	1	25	22	218	464	
8:45 AM	11	88	23	49	30	1	5	15	2	30	18	240	517	
TOTAL VOLUMES :	NL 47	NT 584	NR 148	SL 302	ST 285	SR 2	EL 46	ET 120	ER 10	WL 233	WT 148	WR 2142	TOTAL 4067	
APPROACH %'s :	6.03%	74.97%	19.00%	51.27%	48.39%	0.34%	26.14%	68.18%	5.68%	9.24%	5.87%	84.90%		
PEAK HR START TIME :	7:15 AM												TOTAL	
PEAK HR VOL :	24	283	70	147	133	1	27	69	2	125	78	1181	1133	
PEAK HR FACTOR :	0.867			0.867			0.790			0.928			0.929	

UTURNS			
NB	SB	EB	WB
4		0	2
5		2	0
4		1	2
5		0	3
2		0	3
2		0	2
2		1	2
9		0	2
NB 32	SB 0	EB 4	WB 16

CONTROL : Signalized

Intersection Turning Movement

Prepared by
National Data & Surveying Services

Project ID: 16-5499-003

Day: Thursday

City: Santa Clarita

Date: 7/28/2016

NS/EW Streets:	PM												TOTAL
	The Old Rd			The Old Rd			Magic Mountain Fwy			Magic Mountain Fwy			
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND			
LANES:	NL 2	NT 3	NR 1	SL 2	ST 3	SR 1	EL 2	ET 4	ER 1	WL 2	WT 4	WR 1	
6:00 PM	20	103	57	110	185	6	9	92	20	70	35	202	909
6:15 PM	12	80	48	102	190	5	14	99	24	97	29	206	906
6:30 PM	15	88	61	131	251	8	17	92	18	65	28	212	981
6:45 PM	11	96	63	118	310	7	20	94	31	84	33	251	1116
7:00 PM	5	91	61	134	298	7	13	85	32	71	33	253	1063
7:15 PM	16	78	71	129	324	11	18	94	33	74	27	205	1130
7:30 PM	12	97	63	101	344	8	28	108	33	71	38	223	1128
7:45 PM	14	103	58	110	271	4	9	86	21	63	31	253	1023
TOTAL VOLUMES :	NL 105	NT 736	NR 484	SL 933	ST 2223	SR 56	EL 123	ET 750	ER 212	WL 595	WT 254	WR 1765	TOTAL 8256
APPROACH %s :	7.92%	55.55%	36.53%	29.05%	69.21%	1.74%	11.34%	69.12%	19.54%	22.59%	9.54%	67.77%	
PEAK HR START TIME :	4:45 PM												TOTAL
PEAK HR VOL :	41	362	260	480	1326	37	75	381	129	300	131	912	4437
PEAK HR FACTOR :	0.957												0.962

CONTROL : Signalized

UTURNS			
NB	SB	EB	WB
10	0	0	5
3	0	0	8
5	0	2	4
4	0	0	6
8	1	0	6
7	1	0	8
3	1	0	7
6	0	1	7
NB	SB	EB	WB
46	3	3	51

ITM Peak Hour Summary

Prepared by:
NDS

National Data & Surveying Services


The Old Rd and Magic Mountain Pkwy., Santa Clarita

Date: 7/29/2016


Day: Thursday

Project #: 16-5499-003


City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



Intersection Turning Movement

Prepared by:

National Data & Surveying Services

Project ID: 16-549-004

Day: Thursday

City: Santa Cruz

Date: 7/28/2016

NS/EW Streets:	AM												TOTAL
	Tourney Rd			Tourney Rd			Magic Mountain Pkwy			Magic Mountain Pkwy			
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND			
LANES:	NL 2	NT 0	NR 0	SL 0	ST 0	SR 0	EL 0	ET 3	ER 1	WL 1	WT 3	WR 0	TOTAL
7:00 AM	25	0	9	0	0	0	0	124	31	28	159	0	376
7:15 AM	27	0	10	0	0	0	0	127	38	63	226	0	491
7:30 AM	30	0	10	0	0	0	0	176	61	66	213	0	558
7:45 AM	32	0	6	0	0	0	0	217	66	91	252	0	664
8:00 AM	30	0	10	0	0	0	0	207	74	88	221	0	630
8:15 AM	33	0	15	0	0	0	0	178	62	117	225	0	630
8:30 AM	33	0	15	0	0	0	0	178	58	85	198	0	567
8:45 AM	32	0	15	0	0	0	0	163	63	82	220	0	575
TOTAL VOLUMES:	NL	NT	NR	SL	ST	SR	EL	ET	ER	WL	WT	WR	TOTAL
APPROACH %'s:	72.89%	0.00%	27.11%	#DIV/0!	#DIV/0!	#DIV/0!	0.00%	75.15%	24.85%	26.63%	73.37%	0.00%	4491
PEAK HR START TIME:	7:45 AM												TOTAL
PEAK HR VOL:	173	0	46	0	0	0	0	770	260	381	856	0	1491
PEAK HR FACTOR:	0.906												0.938

CONTROL : Signalized

UTURNS			
NB	SR	EB	WB
			2
			6
			3
			5
			6
			5
			1
			3
NB	SR	EB	WB
0	58	0	31

Intersection Turning Movement

Prepared by:
National Data & Surveying Services

Project ID: 16-5499004

Day: Thursday

City: Santa Clarita

Date: 7/28/2016

NS/EW Streets:	PM												TOTAL
	Tourney Rd			Tourney Rd			Magic Mountain Pkwy			Magic Mountain Pkwy			
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND			
LANES:	NL 2	NT 0	NR 1	SL 0	ST 0	SR 0	EL 0	ET 3	ER 1	WL 1	WT .3	WR 0	
4:00 PM	54	0	48	0	0	0	0	311	56	28	202	0	699
4:15 PM	33	0	53	0	0	0	0	310	43	37	212	0	717
4:30 PM	54	0	79	0	0	0	0	355	24	27	205	0	754
4:45 PM	68	0	74	0	0	0	0	347	32	42	214	0	777
5:00 PM	71	0	103	0	0	0	0	363	45	24	215	0	821
5:15 PM	46	0	59	0	0	0	0	365	42	27	214	0	773
5:30 PM	47	0	68	0	0	0	0	345	33	22	180	0	685
5:45 PM	45	0	54	0	0	0	0	374	28	16	203	0	720
TOTAL VOLUMES :	438	0	538	0	0	0	0	2799	313	223	1645	0	5956
APPROACH %'s :	44.88%	0.00%	55.12%	#DIV/0!	#DIV/0!	#DIV/0!	0.00%	69.94%	10.06%	11.94%	88.06%	0.00%	
PEAK HR START TIME :	ERE PM												TOTAL
PEAK HR VOL :	223	0	315	0	0	0	0	1450	153	120	848	0	3125
PEAK HR FACTOR :													0.952

CONTROL : Signalized

UTURNS			
NB	SB	EB	WB
			0
			2
			1
			1
			2
			1
			0
			0
NB	SB	EB	WB
0	0	0	7

ITM Peak Hour Summary

Prepared by:
NDS

National Data & Surveying Services


Tourney Rd and Magic Mountain Pkwy, Santa Clarita

Date: 7/28/2018


Day: Thursday

Project #: 18-5498-004


City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



Intersection Turning Movement

Prepared by:
National Data & Surveying Services

Project ID: 16-5499-005

Day: Thursday

City: Santa Clarita

Date: 7/28/2016

NS/EW Streets:	AM												TOTAL
	Tourney Rd			Tourney Rd			Wayne Hills Pl			Wayne Hills Pl			
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND			
LANES:	NL 1	NT 1	NR 1	SL 1	ST 1	SR 1	EL 0.5	ET 0.5	ER J	WL 0	WT 1	WR 0	
7:00 AM	0	7	6	23	25	11	12	1	0	5	2	19	112
7:15 AM	0	8	10	30	57	9	6	2	0	7	0	22	151
7:30 AM	2	8	11	35	78	7	12	2	1	13	1	16	186
7:45 AM	6	15	7	37	105	12	13	0	1	14	3	11	227
8:00 AM	2	14	8	34	113	7	11	2	3	13	0	21	228
8:15 AM	0	20	1	45	118	10	8	0	1	16	0	22	244
8:30 AM	1	14	7	31	100	10	6	0	2	12	1	18	202
8:45 AM	1	33	16	41	92	6	5	0	5	10	0	13	223
TOTAL VOLUMES :	12	119	69	276	689	72	73	7	17	90	7	142	1573
APPROACH % :	6.00%	59.50%	34.50%	26.62%	66.44%	6.94%	75.26%	7.22%	17.53%	37.66%	2.93%	59.41%	
PEAK HR START TIME :	7:45 AM												TOTAL
PEAK HR VOL :	9	63	26	147	436	39	38	2	10	55	4	72	501
PEAK HR FACTOR :	0.875												0.933

UTURNS			
NB	SB	EB	WB
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0
0	0	0	0

CONTROL : 2-Way Stop (EB/WB)

Intersection Turning Movement

Prepared by:
National Data & Surveying Services

Project ID: 16-5499-005

Day: Thursday

City: Santa Clarita

Date: 7/28/2016

NS/EW Streets:	PM												TOTAL
	Tourney Rd			Tourney Rd			Wayne Hill Pl			Wayne Hill Pl			
	NORTHBOUND			SOUTHBOUND			EASTBOUND			WESTBOUND			
LANES:	NL 1	NT 1	NR 1	SL 1	ST 1	SR 1	EL 0.5	ET 0.5	ER 1	WL 0	WT 1	WR 0	TOTAL
4:00 PM	1	69	14	28	43	14	6	0	4	11	1	27	218
4:15 PM	1	80	13	26	40	11	9	1	0	8	2	12	203
4:30 PM	0	109	9	21	28	12	12	0	2	11	1	15	220
4:45 PM	2	113	8	75	34	14	13	1	3	17	1	19	250
5:00 PM	0	136	8	18	37	11	9	1	3	12	0	32	267
5:15 PM	1	79	7	24	35	10	2	1	1	4	0	18	182
5:30 PM	0	95	7	19	27	9	9	0	0	12	1	19	199
5:45 PM	3	70	5	18	20	7	12	0	3	9	2	16	165
TOTAL VOLUMES :	NL 8	NT 752	NR 71	SL 179	ST 264	SR 88	EL 72	ET 4	ER 16	WL 84	WT 9	WR 158	TOTAL 1704
APPROACH %'s :	0.96%	90.49%	8.54%	33.71%	49.72%	16.57%	78.26%	4.35%	17.39%	33.60%	3.20%	63.20%	
PEAK HR START TIME :	4:15 PM												TOTAL
PEAK HR VOL :	3	438	38	90	139	45	43	3	8	48	1	78	940
PEAK HR FACTOR :	0.832												0.660

UTURNS			
NB	SB	EB	WB
0	0		
0	1		
0	0		
1	0		
0	0		
0	1		
0	1		
0	1		

NB	SB	EB	WB
1	4	0	0

CONTROL : 2-Way Stop (EB/WB)

ITM Peak Hour Summary


Prepared by:
NDS

National Data & Surveying Services


Tourney Rd and Wayne Mills Pl, Santa Clarita

Date: 7/28/2016
Day: Thursday


Project #: 16-5499-005
City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



APPENDIX B

- Existing Conditions Analysis Worksheets

EX

1. The Old Rd & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	24	0.007	44	0.013 *
NBT	3	5100	283	0.055 *	362	0.071
NBR	1	1700	78	0.046	260	0.153
SBL	2	3400	147	0.043 *	480	0.141
SBT	3	5100	133	0.026	1326	0.260 *
SBR	1	1700	1	0.001	33	0.019
EBL	2	3400	27	0.008	79	0.023
EBT	4	6800	69	0.010 *	381	0.056 *
EBR	1	1700	2	0.001	129	0.076
WBL	2	3400	128	0.038 *	300	0.088 *
WBT	4	6800	78	0.011	131	0.019
WBR	f	0	1163	0.000	912	0.000
RIGHT TURN ADJUSTMENT					WBR	0.003 *
CLEARANCE INTERVAL					0.050 *	0.050 *
TOTAL ICU				0.196		0.470

*d = defacto right turn lane, f = free right turn lane

2. I-5 SB Ramps & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	0	0	0	0.000	0	0.000
NBT	0	0	0	0.000	0	0.000
NBR	0	0	0	0.000	0	0.000
SBL	1.5	2550	283	0.111 *	261	0.102 *
SBT	0.5	850	1	0.001	0	0.000
SBR	2	3400	37	0.011	111	0.033
EBL	0	0	0	0.000	0	0.000
EBT	3	5100	182	0.036	775	0.152 *
EBR	2	3400	109	0.032	328	0.096
WBL	2	3400	527	0.155	338	0.099 *
WBT	4	6800	1328	0.195 *	1198	0.176
WBR	0	0	0	0.000	0	0.000
RIGHT TURN ADJUSTMENT						
CLEARANCE INTERVAL					0.050 *	0.050 *
TOTAL ICU				0.356		0.403

EX

3. I-5 NB Ramps & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	1003	0.295 *	847	0.249 *
NBT	0.5	850	0	0.000	2	0.002
NBR	1.5	2550	558	0.219	699	0.274
SBL	0	0	0	0.000	0	0.000
SBT	0	0	0	0.000	0	0.000
SBR	0	0	0	0.000	0	0.000
EBL	2	3400	33	0.010 *	121	0.036
EBT	3	5100	476	0.093	903	0.177 *
EBR	0	0	0	0.000	0	0.000
WBL	0	0	0	0.000	0	0.000
WBT	3.5	5950	821	0.138 *	702	0.118
WBR	1.5	2550	216	0.085	387	0.152
RIGHT TURN ADJUSTMENT					NBR	0.034 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.493		0.510

4. Tourney Rd & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	128	0.038 *	239	0.070 *
NBT	0	0	0	0.000	0	0.000
NBR	1	1700	315	0.185	315	0.185
SBL	0	0	0	0.000	0	0.000
SBT	0	0	0	0.000	0	0.000
SBR	0	0	0	0.000	0	0.000
EBL	0	0	0	0.000	0	0.000
EBT	3	5100	780	0.153 *	1450	0.284 *
EBR	1	1700	260	0.153	153	0.090
WBL	1	1700	381	0.224 *	120	0.071 *
WBT	3	5100	896	0.176	848	0.166
WBR	0	0	0	0.000	0	0.000
RIGHT TURN ADJUSTMENT					NBR	0.055 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.465		0.530

Santa Clarita Wayne Mills Hotel
5: Tourney Rd & Wayne Mills PI

Existing Conditions
 Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕	↗		↕		↖	↕	↗	↖	↕	↗
Volume (veh/h)	38	2	10	55	4	72	9	63	26	147	436	39
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	41	2	11	60	4	78	10	68	28	160	474	42
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage veh												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	962	910	474	888	924	68	516			97		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	962	910	474	888	924	68	516			97		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
fI (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	79	99	98	75	98	92	99			89		
cM capacity (veh/h)	195	243	590	235	238	995	1049			1497		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	54	142	10	68	28	160	474	42				
Volume Left	41	60	10	0	0	160	0	0				
Volume Right	11	78	0	0	28	0	0	42				
cSH	247	405	1049	1700	1700	1497	1700	1700				
Volume to Capacity	0.22	0.35	0.01	0.04	0.02	0.11	0.28	0.02				
Queue Length 95th (ft)	20	39	1	0	0	9	0	0				
Control Delay (s)	24.9	18.6	8.5	0.0	0.0	7.7	0.0	0.0				
Lane LOS	C	C	A			A						
Approach Delay (s)	24.9	18.6	0.8			1.8						
Approach LOS	C	C										
Intersection Summary												
Average Delay			5.4									
Intersection Capacity Utilization			44.0%	ICU Level of Service		A						
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
5: Tourney Rd & Wayne Mills PI

Existing Conditions
 Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (veh/h)	43	3	8	48	4	78	3	438	38	90	139	48
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	47	3	9	52	4	85	3	476	41	98	151	52
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	916	871	151	835	882	476	203			517		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	916	871	151	835	882	476	203			517		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	76	99	99	80	98	86	100			91		
cM capacity (veh/h)	198	262	895	261	258	589	1368			1048		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	59	141	3	476	41	98	151	52				
Volume Left	47	52	3	0	0	98	0	0				
Volume Right	9	85	0	0	41	0	0	52				
cSH	237	392	1368	1700	1700	1048	1700	1700				
Volume to Capacity	0.25	0.36	0.00	0.28	0.02	0.09	0.09	0.03				
Queue Length 95th (ft)	24	40	0	0	0	8	0	0				
Control Delay (s)	25.7	19.3	7.6	0.0	0.0	8.8	0.0	0.0				
Lane LOS	D	C	A			A						
Approach Delay (s)	25.7	19.3	0.0			2.9						
Approach LOS	D	C										
Intersection Summary												
Average Delay			5.0									
Intersection Capacity Utilization			52.4%	ICU Level of Service	A							
Analysis Period (min)			15									

APPENDIX C

➤ Existing + Project Conditions Analysis Worksheets

EXWP

1. The Old Rd & Magic Mountain Pkwy						
	LANES	CAPACITY	AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	24	0.007	44	0.013 *
NBT	3	5100	283	0.055 *	362	0.071
NBR	1	1700	78	0.046	260	0.153
SBL	2	3400	147	0.043 *	480	0.141
SBT	3	5100	133	0.026	1326	0.260 *
SBR	1	1700	1	0.001	33	0.019
EBL	2	3400	27	0.008	79	0.023
EBT	4	6800	81	0.012 *	394	0.058 *
EBR	1	1700	2	0.001	129	0.076
WBL	2	3400	128	0.038 *	300	0.088 *
WBT	4	6800	86	0.013	139	0.020
WBR	f	0	1163	0.000	912	0.000
RIGHT TURN ADJUSTMENT					EBR	0.006 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.198		0.475

*d = defacto right turn lane, f = free right turn lane

2. I-5 SB Ramps & Magic Mountain Pkwy						
	LANES	CAPACITY	AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	0	0	0	0.000	0	0.000
NBT	0	0	0	0.000	0	0.000
NBR	0	0	0	0.000	0	0.000
SBL	1.5	2550	295	0.116 *	274	0.107 *
SBT	0.5	850	1	0.001	0	0.000
SBR	2	3400	37	0.011	111	0.033
EBL	0	0	0	0.000	0	0.000
EBT	3	5100	194	0.038	788	0.155 *
EBR	2	3400	109	0.032	328	0.096
WBL	2	3400	534	0.157	350	0.103 *
WBT	4	6800	1336	0.196 *	1206	0.177
WBR	0	0	0	0.000	0	0.000
RIGHT TURN ADJUSTMENT						
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.362		0.415

EXWP

3. I-5 NB Ramps & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	1003	0.295 *	847	0.249 *
NBT	0.5	850	0	0.000	2	0.002
NBR	1.5	2550	576	0.226	718	0.282
SBL	0	0	0	0.000	0	0.000
SBT	0	0	0	0.000	0	0.000
SBR	0	0	0	0.000	0	0.000
EBL	2	3400	33	0.010 *	121	0.036
EBT	3	5100	500	0.098	929	0.182 *
EBR	0	0	0	0.000	0	0.000
WBL	0	0	0	0.000	0	0.000
WBT	3.5	5950	841	0.141 *	723	0.122
WBR	1.5	2550	224	0.088	395	0.155
RIGHT TURN ADJUSTMENT					NBR	0.042 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.496		0.523

4. Tourney Rd & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	156	0.046 *	268	0.079 *
NBT	0	0	0	0.000	0	0.000
NBR	1	1700	46	0.027	315	0.185
SBL	0	0	0	0.000	0	0.000
SBT	0	0	0	0.000	0	0.000
SBR	0	0	0	0.000	0	0.000
EBL	0	0	0	0.000	0	0.000
EBT	3	5100	780	0.153 *	1450	0.284 *
EBR	1	1700	301	0.177	198	0.116
WBL	1	1700	393	0.231 *	133	0.078 *
WBT	3	5100	896	0.176	848	0.166
WBR	0	0	0	0.000	0	0.000
RIGHT TURN ADJUSTMENT					NBR	0.045 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.480		0.536

Santa Clarita Wayne Mills Hotel
5: Tourney Rd & Wayne Mills PI

Existing Plus Project
 Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (veh/h)	66	10	14	55	4	72	15	63	26	147	436	92
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	72	11	15	60	4	78	16	68	28	160	474	100
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type							None			None		
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	975	923	474	908	995	68	574			97		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	975	923	474	908	995	68	574			97		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	62	95	97	73	98	92	98			89		
cM capacity (veh/h)	190	237	590	219	215	995	999			1497		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	98	142	16	68	28	160	474	100				
Volume Left	72	60	16	0	0	160	0	0				
Volume Right	15	78	0	0	28	0	0	100				
cSH	232	383	999	1700	1700	1497	1700	1700				
Volume to Capacity	0.42	0.37	0.02	0.04	0.02	0.11	0.28	0.06				
Queue Length 95th (ft)	49	42	1	0	0	9	0	0				
Control Delay (s)	32.2	19.9	8.7	0.0	0.0	7.7	0.0	0.0				
Lane LOS	D	C	A			A						
Approach Delay (s)	32.2	19.9	1.2			1.7						
Approach LOS	D	C										
Intersection Summary												
Average Delay			6.8									
Intersection Capacity Utilization			44.0%		ICU Level of Service					A		
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
5: Tourney Rd & Wayne Mills PI

Existing Plus Project
 Timing Plan: PM PEAK

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑	↗		↖		↖	↑	↗	↖	↑	↗
Volume (veh/h)	72	11	12	48	4	78	9	438	38	90	139	106
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	78	12	13	52	4	85	10	476	41	98	151	115
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	929	884	151	855	958	476	266			517		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	929	884	151	855	958	476	266			517		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
IF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	59	95	99	79	98	86	99			91		
cM capacity (veh/h)	193	256	895	244	232	589	1298			1048		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	103	141	10	476	41	98	151	115				
Volume Left	78	52	10	0	0	98	0	0				
Volume Right	13	85	0	0	41	0	0	115				
cSH	231	376	1298	1700	1700	1048	1700	1700				
Volume to Capacity	0.45	0.38	0.01	0.28	0.02	0.09	0.09	0.07				
Queue Length 95th (ft)	54	43	1	0	0	8	0	0				
Control Delay (s)	33.1	20.3	7.8	0.0	0.0	8.8	0.0	0.0				
Lane LOS	D	C	A			A						
Approach Delay (s)	33.1	20.3	0.1			2.4						
Approach LOS	D	C										
Intersection Summary												
Average Delay			6.4									
Intersection Capacity Utilization			52.4%	ICU Level of Service	A							
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
6: Proj Dwy & Wayne Mills PI

Existing Plus Project
Timing Plan: AM PEAK

	→	↘	↙	←	↖	↗
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		↓	↑	↓	
Volume (veh/h)	50	0	101	52	0	68
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	54	0	110	57	0	74
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLTL			None		
Median storage (veh)	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			54		330	54
vC1, stage 1 conf vol					54	
vC2, stage 2 conf vol					276	
vCu, unblocked vol			54		330	54
IC, single (s)			4.1		6.4	6.2
IC, 2 stage (s)					5.4	
IF (s)			2.2		3.5	3.3
p0 queue free %			93		100	93
cM capacity (veh/h)			1551		693	1013
Direction/Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	54	110	57	74		
Volume Left	0	110	0	0		
Volume Right	0	0	0	74		
cSH	1700	1551	1700	1013		
Volume to Capacity	0.03	0.07	0.03	0.07		
Queue Length 95th (ft)	0	6	0	6		
Control Delay (s)	0.0	7.5	0.0	8.8		
Lane LOS		A		A		
Approach Delay (s)	0.0	4.9		8.8		
Approach LOS				A		
Intersection Summary						
Average Delay			5.0			
Intersection Capacity Utilization			23.1%		ICU Level of Service	A
Analysis Period (min)			15			

Santa Clarita Wayne Mills Hotel
10: Proj Dwy & Wayne Mills PI

Existing Plus Project
Timing Plan: PM PEAK

	→	↘	↙	←	↖	↗
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		↓	↑	↓	
Volume (veh/h)	54	0	109	55	0	71
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	59	0	118	60	0	77
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLT			None		
Median storage (veh)	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			59		355	59
vC1, stage 1 conf vol					59	
vC2, stage 2 conf vol					297	
vCu, unblocked vol			59		355	59
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					5.4	
tF (s)			2.2		3.5	3.3
p0 queue free %			92		100	92
cM capacity (veh/h)			1545		674	1007
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	59	118	60	77		
Volume Left	0	118	0	0		
Volume Right	0	0	0	77		
cSH	1700	1545	1700	1007		
Volume to Capacity	0.03	0.08	0.04	0.08		
Queue Length 95th (ft)	0	6	0	6		
Control Delay (s)	0.0	7.5	0.0	8.9		
Lane LOS		A		A		
Approach Delay (s)	0.0	5.0		8.9		
Approach LOS				A		
Intersection Summary						
Average Delay			5.0			
Intersection Capacity Utilization			23.8%		ICU Level of Service	A
Analysis Period (min)			15			

APPENDIX D

➤ 2017 Opening Day Conditions Analysis Worksheets

Santa Clarita Wayne Mills Hotel
6: Proj Dwy & Wayne Mills PI

Existing Plus Ambient Plus Project
 Timing Plan: AM PEAK

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		↙	↑	↘	
Volume (veh/h)	52	0	101	54	0	68
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	57	0	110	59	0	74
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLT			None		
Median storage (veh)	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			57		335	57
vC1, stage 1 conf vol					57	
vC2, stage 2 conf vol					278	
vCu, unblocked vol			57		335	57
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					5.4	
tF (s)			2.2		3.5	3.3
p0 queue free %			93		100	93
cM capacity (veh/h)			1548		691	1010

Direction, Lane #	EB 1	WB 1	WB 2	NB 1
Volume Total	57	110	59	74
Volume Left	0	110	0	0
Volume Right	0	0	0	74
cSH	1700	1548	1700	1010
Volume to Capacity	0.03	0.07	0.03	0.07
Queue Length 95th (ft)	0	6	0	6
Control Delay (s)	0.0	7.5	0.0	8.8
Lane LOS		A		A
Approach Delay (s)	0.0	4.9		8.8
Approach LOS				A

Intersection Summary			
Average Delay		4.9	
Intersection Capacity Utilization		23.1%	ICU Level of Service
Analysis Period (min)		15	A

Santa Clarita Wayne Mills Hotel
6: Proj Dwy & Wayne Mills PI

Existing Plus Ambient Plus Project
 Timing Plan: PM PEAK

	→	↘	↙	←	↖	↗
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		↘	↑	↙	
Volume (veh/h)	56	0	109	57	0	71
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	61	0	118	62	0	77
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLTL		None			
Median storage (veh)	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			61		360	61
vC1, stage 1 conf vol					61	
vC2, stage 2 conf vol					299	
vCu, unblocked vol			61		360	61
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					5.4	
tF (s)			2.2		3.5	3.3
p0 queue free %			92		100	92
cM capacity (veh/h)			1542		672	1004
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	61	118	62	77		
Volume Left	0	118	0	0		
Volume Right	0	0	0	77		
cSH	1700	1542	1700	1004		
Volume to Capacity	0.04	0.08	0.04	0.08		
Queue Length 95th (ft)	0	6	0	6		
Control Delay (s)	0.0	7.5	0.0	8.9		
Lane LOS	A		A			
Approach Delay (s)	0.0	4.9	8.9			
Approach LOS	A					
Intersection Summary						
Average Delay			5.0			
Intersection Capacity Utilization			23.8%	ICU Level of Service	A	
Analysis Period (min)			15			

Santa Clarita Wayne Mills Hotel
5: Tourney Rd & Wayne Mills PI

Existing Plus Ambient Plus Project
 Timing Plan: AM PEAK

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕	↗		↕		↖	↕	↗	↖	↕	↗
Volume (veh/h)	67	10	14	57	4	74	15	65	27	151	449	93
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	73	11	15	62	4	80	16	71	29	164	488	101
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)	6											
Median type							None			None		
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	1002	949	488	933	1021	71	589			100		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	1002	949	488	933	1021	71	589			100		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	60	95	97	70	98	92	98			89		
cM capacity (veh/h)	181	228	580	209	207	992	986			1493		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	99	147	16	71	29	164	488	101				
Volume Left	73	62	16	0	0	164	0	0				
Volume Right	15	80	0	0	29	0	0	101				
cSH	221	369	986	1700	1700	1493	1700	1700				
Volume to Capacity	0.45	0.40	0.02	0.04	0.02	0.11	0.29	0.06				
Queue Length 95th (ft)	53	46	1	0	0	9	0	0				
Control Delay (s)	34.7	21.1	8.7	0.0	0.0	7.7	0.0	0.0				
Lane LOS	D	C	A			A						
Approach Delay (s)	34.7	21.1	1.2			1.7						
Approach LOS	D	C										
Intersection Summary												
Average Delay			7.1									
Intersection Capacity Utilization			44.9%		ICU Level of Service				A			
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
5: Tourney Rd & Wayne Mills PI

Existing Plus Ambient Plus Project
Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR	
Lane Configurations													
Volume (veh/h)	73	11	12	49	4	80	9	451	39	93	143	107	
Sign Control		Stop			Stop			Free			Free		
Grade		0%			0%			0%			0%		
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	
Hourly flow rate (vph)	79	12	13	53	4	87	10	490	42	101	155	116	
Pedestrians													
Lane Width (ft)													
Walking Speed (ft/s)													
Percent Blockage													
Right turn flare (veh)			6										
Median type								None			None		
Median storage (veh)													
Upstream signal (ft)													
pX, platoon unblocked													
vC, conflicting volume	957	910	155	880	984	490	272			533			
vC1, stage 1 conf vol													
vC2, stage 2 conf vol													
vCu, unblocked vol	957	910	155	880	984	490	272			533			
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1			
tC, 2 stage (s)													
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2			
p0 queue free %	57	95	99	77	98	85	99			90			
cM capacity (veh/h)	183	246	890	234	223	578	1292			1035			
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3					
Volume Total	104	145	10	490	42	101	155	116					
Volume Left	79	53	10	0	0	101	0	0					
Volume Right	13	87	0	0	42	0	0	116					
cSH	218	363	1292	1700	1700	1035	1700	1700					
Volume to Capacity	0.48	0.40	0.01	0.29	0.02	0.10	0.09	0.07					
Queue Length 95th (ft)	59	46	1	0	0	8	0	0					
Control Delay (s)	36.1	21.3	7.8	0.0	0.0	8.9	0.0	0.0					
Lane LOS	E	C	A			A							
Approach Delay (s)	36.1	21.3	0.1			2.4							
Approach LOS	E	C											
Intersection Summary													
Average Delay			6.7										
Intersection Capacity Utilization			53.4%		ICU Level of Service		A						
Analysis Period (min)			15										

EXAMBWP

1. The Old Rd & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	25	0.007	45	0.013 *
NBT	3	5100	291	0.057 *	373	0.073
NBR	1	1700	80	0.047	268	0.158
SBL	2	3400	151	0.044 *	494	0.145
SBT	3	5100	137	0.027	1366	0.268 *
SBR	1	1700	1	0.001	34	0.020
EBL	2	3400	28	0.008	81	0.024
EBT	4	6800	83	0.012 *	405	0.060 *
EBR	1	1700	2	0.001	133	0.078
WBL	2	3400	132	0.039 *	309	0.091 *
WBT	4	6800	88	0.013	143	0.021
WBR	f	0	1198	0.000	939	0.000
RIGHT TURN ADJUSTMENT					EBR	0.008 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.202		0.490

*d = defacto right turn lane, f = free right turn lane

2. I-5 SB Ramps & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	0	0	0	0.000	0	0.000
NBT	0	0	0	0.000	0	0.000
NBR	0	0	0	0.000	0	0.000
SBL	1.5	2550	303	0.119 *	282	0.111 *
SBT	0.5	850	1	0.001	0	0.000
SBR	2	3400	38	0.011	114	0.034
EBL	0	0	0	0.000	0	0.000
EBT	3	5100	199	0.039	811	0.159 *
EBR	2	3400	112	0.033	338	0.099
WBL	2	3400	550	0.162	360	0.106 *
WBT	4	6800	1376	0.202 *	1242	0.183
WBR	0	0	0	0.000	0	0.000
RIGHT TURN ADJUSTMENT						
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU				0.371		0.426

EXAMBWP

3. I-5 NB Ramps & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	1033	0.304 *	872	0.256 *
NBT	0.5	850	0	0.000	2	0.002
NBR	1.5	2550	593	0.233	739	0.290
SBL	0	0	0	0.000	0	0.000
SBT	0	0	0	0.000	0	0.000
SBR	0	0	0	0.000	0	0.000
EBL	2	3400	34	0.010 *	125	0.037
EBT	3	5100	514	0.101	956	0.187 *
EBR	0	0	0	0.000	0	0.000
WBL	0	0	0	0.000	0	0.000
WBT	3.5	5950	866	0.146 *	744	0.125
WBR	1.5	2550	230	0.090	407	0.160
RIGHT TURN ADJUSTMENT					NBR	0.050 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU			0.510		0.543	

4. Tourney Rd & Magic Mountain Pkwy						
	LANES CAPACITY		AM PEAK HOUR		PM PEAK HOUR	
			VOL	V/C	VOL	V/C
NBL	2	3400	160	0.047 *	275	0.081 *
NBT	0	0	0	0.000	0	0.000
NBR	1	1700	47	0.028	324	0.191
SBL	0	0	0	0.000	0	0.000
SBT	0	0	0	0.000	0	0.000
SBR	0	0	0	0.000	0	0.000
EBL	0	0	0	0.000	0	0.000
EBT	3	5100	803	0.157 *	1494	0.293 *
EBR	1	1700	309	0.182	203	0.119
WBL	1	1700	404	0.238 *	137	0.081 *
WBT	3	5100	923	0.181	873	0.171
WBR	0	0	0	0.000	0	0.000
RIGHT TURN ADJUSTMENT					NBR	0.041 *
CLEARANCE INTERVAL				0.050 *		0.050 *
TOTAL ICU			0.492		0.546	

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

August 17, 2016


ACOUSTICAL ANALYSIS

VALENCIA SPRINGHILL & RESIDENCE INN

WAYNE MILLS PLACE

CITY OF SANTA CLARITA

Prepared by:



Christopher Jean, INCE

Prepared for:

MR. NEIL PATEL
EXCEL HOTEL GROUP
10660 Scripps Ranch Blvd., Suite 100
San Diego, California 92131

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

SUMMARY

This analysis has been completed to determine the exterior and interior noise exposure and the necessary mitigation measures for the proposed Valencia Springhill & Residence Inn off of Wayne Mills Place in the City of Santa Clarita. A list of requirements and recommendations is given in the following summary. Details are discussed in the body of the report.

A. EXTERIOR NOISE CONTROL

Sound walls at least six feet (6') high must be erected between the Residence Inn entry portico and the adjacent pool area. Sound walls at least ten feet (10') high must be erected around the west end of the Holiday Inn pool area.

B. NOISE CONTROL BARRIER CONSTRUCTION MATERIALS

The required noise control barriers may be constructed using any of the following materials:

- (1) Masonry block
- (2) Stucco on wood frame
- (3) 3/4" plywood
- (4) 1/4" tempered glass or 1/2" Lexan
- (5) Earthen berm
- (6) Any combination of the above materials or any material with a surface weight of at least 3.5 pounds per square foot.

Each completed noise control barrier must present a solid face from top-to-bottom and end-to-end. Cutouts are not permitted except for drain holes.

C. INTERIOR NOISE CONTROL

The buildings shall be constructed, as a minimum, in accordance with the outline of Table 7 found in the body of the report. This will be adequate for all units with the following upgrades:

- (1) Add STC 40 glazing to all rooms along the west face of both buildings.
- (2) Add STC 36 glazing to all rooms along the north and south building faces of both buildings.
- (3) Add STC 28 glazing to all remaining rooms of both buildings including all rooms facing the central courtyard of the Residence Inn building.
- (4) Add resilient channels and two layers 5/8" drywall to the exterior wall assemblies of all rooms along the west, north and south building faces of both buildings.
- (5) Add resilient channels and two layers 5/8" drywall to the ceilings of all top floor rooms along the west, north and south building faces of both buildings.

D. VENTILATION

This analysis assumed that all windows and doors are kept closed. If the allowable interior noise levels are met by requiring that windows and doors be kept closed, then the design of the structure must also specify a ventilation or air conditioning system to provide a habitable interior environment. The ventilation system must not compromise the dwelling or guest room noise reduction.

E. UNIT-TO-UNIT NOISE CONTROL

Common floor/ceiling assemblies between units are subject to Title 24 Sound Transmission Class (STC) and Impact Insulation Class (IIC) requirements. The plan set provided for this analysis did not include common floor/ceiling assembly details. It is highly recommended that one of the following widely used common floor/ceiling assemblies, all of which rate at least STC 50, be incorporated into the building plans:

- (1) 8" concrete slab (Riverbank Acoustical Labs, TL 76-77, 1977, 16f; for Pre-stressed Concrete Institute, STC 58 – IIC 71 with carpet, IIC 34 for bare floor)
- (2) 1 1/2" lightweight concrete, plywood sub-floor, 3 1/2" thick fiberglass insulation, resilient channels, drywall ceiling (Geiger and Hamme CCA-14MT, CCA-15MT, 1972, 16f, for Cellular Concrete Association, STC 60 – IIC 73 with carpet, IIC 47 with vinyl tile)
- (3) 1 3/8" Gyp-Crete, plywood sub-floor, 2" by 10" wood joists, 3 1/2" thick fiberglass insulation, resilient channels, 1/2" drywall ceiling (Riverbank Acoustical Labs TL 81-16,

for Gyp-Crete Corporation, 1981, STC 60 – Riverbank Acoustical Labs IN 81-14, for Gyp-Crete Corporation, 1981, IIC 51 with sheet vinyl)

As can be seen by the above list, some of the recommended assemblies cannot meet the IIC 50 minimum requirement without carpet. Uncarpeted areas above other living units will require some form of proprietary isolation product included in the assembly to achieve the required rating. Such products include Enkasonic, Acousti-Mat, Regupol and others. Such products are designed to be installed atop the bare sub-floor and topped with either lightweight concrete/Gyp-Crete pour or additional layers of plywood. Each product has its own specific installation requirements. These products can produce both design and field IIC compliance with sheet vinyl or wood flooring. While various lab tests have shown these same products to produce design IIC compliance when used with ceramic tile, field testing experience has proven that actual ceramic tile installations are marginal. The use of ceramic tile or marble is not recommended, regardless of the installation method.

The plan set provided for this analysis did not include common wall assembly details. It is highly recommended that one of the following widely used common wall assemblies, all of which rate at least STC 50, be incorporated into the building plans:

- (1) Two layers of 1/2" direct nailed drywall, 2" by 6" plate, 2" by 4" staggered studs, 3 1/2" thick fiberglass insulation, two layers 1/2" direct nailed drywall (Owens/Corning Fiberglas, OCF W-55-69, 1969, 16f, for Owens/Corning Fiberglas, STC 54)
- (2) Two layers of 5/8" direct nailed drywall, 2" by 6" plate, 2" by 4" staggered studs, 3 1/2" thick fiberglass insulation, two layers 5/8" direct nailed drywall (National Gypsum Company NGC 2376, 1970, 16f, STC 53)
- (3) 5/8" direct nailed drywall, 2" by 4" plate with 2" by 4" studs, 3 1/2" thick fiberglass insulation, 1" clear air space at plate, 2" by 4" plate with 2" by 4" studs, 5/8" direct nailed drywall (Owens/Corning Fiberglas OCF 448, 1967, 16f, STC 56)
- (4) Same as #3 but with two layers of 3 1/2" thick fiberglass insulation (Riverbank Acoustical Labs TL 75-83, 1975, 16f, for U. S. Department of Agriculture, STC 57)
- (5) Two layers 5/8" direct nailed drywall, 2" by 4" plate with 2" by 4" studs, 3 1/2" thick fiberglass insulation, 1" clear air space at plate, 2" by 4" plate with 2" by 4" studs, two layers 5/8" direct nailed drywall (National Gypsum Company, NGC 3056, 1970, 16f, for Gypsum Association, STC 58)
- (6) Same as #5 but with two layers of 3 1/2" thick fiberglass insulation (Riverbank Acoustical Labs TL 75-82, 1975, 16f, for U. S. Department of Agriculture, STC 63)

All wall assemblies between any common space and a living unit must be an STC 50 minimum rated assembly. All plumbing, mechanical and electrical installations shall be installed per the instructions and details contained in Appendix 7. Add all appropriate details to the project plans.

F. PROJECT DISCLOSURE

The acoustical code requirements represent minimal acceptable standards. Compliance with the Building Department acoustical criteria does not require, guarantee or even imply that local sound sources will be mitigated to inaudibility. Compliance with an exterior noise limit of 65 dBA CNEL means that exterior noise will remain clearly audible within the mitigated exterior space. Compliance with an interior noise limit of 45 dBA CNEL means that exterior noise sources will remain audible on the interior of a building.

Due to quality control and other field related problems, the code minimum laboratory ratings of STC/IIC 50 for common assemblies does not guarantee that all common assemblies will pass a field test. In fact, there is a 50 percent chance that half of all common assemblies rated at the STC/IIC minimum could fail field tests. An STC 50 rated assembly will produce around 45 dBA of voice reduction in the field. This means that normal conversation in adjoining units will be audible a certain percentage of the time.

Do not misrepresent the degree of exterior to interior or unit-to-unit acoustical isolation as anything more than meeting code during any phase of this project. Never, ever, use any form of the term "Soundproof" to describe any portion of this project.

G. PROJECT NOISE MITIGATION

Project generated noise levels should not exceed the existing ambient conditions as long as no truck deliveries occur prior to 7:00 a.m. or after 10:00 p.m., all rooftop mechanical equipment has a specified noise rating of no more than 8.5 bels, rooftop parapet or freestanding acoustic screen walls at least as tall as the tallest piece of rooftop mechanical equipment are erected, and all guest room HVAC units have a specified noise rating of no more than 6.5 bels.

H. CONSTRUCTION NOISE

Construction noise is normally exempt from compliance with the City noise limits. However, even unrestricted construction activities are not likely to exceed the ambient noise conditions produce by the adjacent freeway.

CHRISTOPHER JEAN & ASSOCIATES, INC.

ACOUSTICAL CONSULTING SERVICES

1.0 INTRODUCTION

This report presents the results of a noise impact and design study of the proposed Valencia Springhill & Residence Inn project located off of Wayne Mills Place in the City of Santa Clarita. This report includes a discussion of the expected exterior community noise environment and the recommendations for control of noise in the exterior and interior living spaces.

A vicinity map showing the general location of the project site is presented in Exhibit 1 – Site Location Map. An aerial photograph of the existing project site and its surroundings is shown on Exhibit 2. The project site plan is shown on Exhibit 3. The project consists of two hotel buildings.

2.0 APPLICABLE NOISE CRITERIA

The City of Santa Clarita requires all hotel projects to conform to the requirements of Table 1.

TABLE 1

APPLICABLE NOISE CRITERIA (1)

Exterior	65 dBA CNEL
Interior	45 dBA CNEL
Unit-to-Unit	STC 50/IIC 50

- (1) Please see Noise Rating Methods (Appendix 1) for an explanation of the commonly applicable acoustical terminology.

The City of Santa Clarita also has a noise ordinance designed to control noise across common property lines. The allowed noise limits for both residential (other hotels in this case) and commercial properties are listed in Table 2 on the following page.

TABLE 2
MUNICIPAL CODE NOISE LIMITS

<u>DURATION</u>	<u>SYMBOL</u>	<u>RESIDENTIAL</u>		<u>COMMERCIAL</u>	
		<u>DAY</u>	<u>NIGHT</u>	<u>DAY</u>	<u>NIGHT</u>
More than 15 minutes in hour	L25	65	55	80	70
More than 5, less than 15 minutes	L8	70	60	85	75
More than 1, less than 5 minutes	L2	75	65	90	80
Less than 1 minute	Lmax	85	75	100	90

As can be seen from the Table 2 criteria, the noise limits will be most stringent when applied to continuous noise sources such as rooftop mechanical equipment and guest room air conditioning units. Intermittent noise caused by daytime truck deliveries and typical parking lot activities should be able to comply with the various noise limits without much effort, especially due to the high ambient noise levels in the project area (Interstate 5).

In addition, the City noise ordinance exempts construction noise produced within 300 feet of a residential property as long as it occurs only between the hours of 7:00 a.m. to 7:00 p.m. Monday through Friday, and 8:00 a.m. to 6:00 p.m. on Saturday.

3.0 EXISTING NOISE LEVELS

3.1 ROADWAYS

A measurement was performed on the site. The measurement was conducted using a Larson-Davis Model 700 Integrating Sound Level Meter. The average noise level reported from the measurement taken at a point approximately 150 feet from the centerline of Interstate 5 was 79 dBA Leq.

Ten minute traffic counts were taken during the measurement period. The results of the counts are listed in Table 3 on the following page.

TABLE 3OBSERVED INTERSTATE 5 TRAFFIC COUNTS

	<u>AUTOS</u>	<u>MEDIUM TRUCKS</u>	<u>HEAVY TRUCKS</u>	<u>TOTAL</u>
<u>TEN MINUTES</u>	1,365	44	133	1,542
<u>HOURLY EQUIVALENT</u>	8,190	264	798	9,252
<u>PERCENTAGE</u>	88.5	2.9	8.6	100.0

The primary function of the measurements is to calibrate the Noise Model (FHWA RD-77-108) used to compute the CNEL data. The model relies on the acoustical metric of the average noise level (Leq). By taking the traffic count during the measurement, calculating the Leq value for that traffic sample, and comparing it the measured Leq value, it is possible to calibrate the CNEL model for any factors that are present and not adequately identified in the prediction equations.

The Leq value computer calculation printout is contained in Appendix 2. The calculated and measured Leq values are compared in Table 4.

TABLE 4COMPARISON OF CALCULATED AND MEASURED AVERAGE NOISE LEVELS

Calculated	82
Measured	79
DIFFERENCE	- 3

The results of Table 4 show that area conditions produce slightly noise than would normally be predicted by the standard computer calculation model. The resulting correction factor will be applied to the design noise level (CNEL) calculations.

3.2 RAILROAD

There are no railroad operations in the vicinity of the project site. Railroad noise does not impact the site.

3.3 AIRCRAFT

There are no concentrated aircraft operations in the vicinity of the project site. Aircraft noise does not impact the site.

4.0 DESIGN NOISE LEVELS

4.1 ROADWAY

The expected future roadway noise impact was projected using the Federal Highway Administration's Highway Noise Prediction Model (FHWA RD-77-108) together with several roadway and site parameters that determine the projected impact of vehicular traffic noise. These include the roadway cross-section (e.g. number of lanes), the roadway active width, the average daily traffic (ADT), the vehicle travel speed, the percentage of auto and truck traffic, the roadway grade, the angle of view, the site conditions ("hard" or "soft" site), and the percentage of average daily traffic that flows each hour throughout a 24 hour period.

The forecast traffic volume was obtained from Caltrans data. CALTRANS data was also used for the percentage of truck traffic and to project the distribution by time of day. The input data is listed in Table 5.

TABLE 5

TRAFFIC INPUT DATA – I-5 FREEWAY

	<u>% DAY</u>	<u>% EVENING</u>	<u>% NIGHT</u>	<u>% VOLUME</u>
Autos	73.00	8.60	18.40	87.4
Medium Trucks	73.00	8.60	18.40	2.8
Heavy Trucks	69.10	6.70	24.20	9.8
Volume =	188,000 ADT on			
Speed =	65 MPH			

The calculations are contained in Appendix 3. The calculations, with the Table 4 correction factor applied, yield a design noise level of 83 dBA CNEL at 150 feet from the centerline of the I-5 Freeway.

4.2 RAILROAD

Railroad noise is not expected to increase. Thus, railroad noise will not impact the project site.

4.3 AIRCRAFT

Aircraft noise is not expected to increase. Thus, aircraft noise will not impact the project site.

5.0 MITIGATION MEASURES

5.1 EXTERIOR

The project proposes two exterior use areas. The Residence Inn hotel proposes a central courtyard including a pool area. The proposed building will partially shield this courtyard from freeway noise although the entrance opening in the west side of the building will allow freeway noise to encroach upon this space. The Holiday Inn also proposes an exterior pool area between the two hotel buildings. While the two buildings will partially shield this pool area from freeway noise, the west side of this pool area is open to the freeway. As exterior noise levels are expected to be as high as 83 dBA CNEL outside the west building faces, mitigation of exterior noise would require a sound barrier along the west sides of both pool areas. For purposes of analysis, the barrier height calculations assume that the barrier is located at the top of any slope between the roadway and building pads, and is only intended to reduce exterior noise to 65 dBA CNEL at the first floor level. The assumptions for the barrier height calculations are listed in Table 6 on the following page.

TABLE 6

BARRIER ANALYSIS GENERAL ASSUMPTIONS
FOR RECEIVER AND SOURCE GEOMETRY

<u>RECEIVER ASSUMPTIONS</u>	
<u>HORIZONTAL GEOMETRY</u>	<u>VERTICAL GEOMETRY</u>
Distance behind top-of-roadways barrier: 5' to 10'	Height above pad for ground level receivers: 5'
Distance behind individual patio and balcony barriers: 1' to 3'	Height above pad for second level receivers: 14'
<u>SOURCE ASSUMPTIONS</u>	
<u>HORIZONTAL GEOMETRY *</u>	<u>VERTICAL GEOMETRY</u>
For roadways with grades no greater than 2%, all vehicles were located at the single lane equivalent acoustic center of the full roadway. For roadways with over 2% grade, vehicle count was divided in half and located at the single lane equivalent acoustic center for each side of the roadway.	Automobiles: 0' above center of road grade Medium Trucks: 2.3' above center of road grade Heavy Trucks: 8' above center of road grade

* = Single Lane Equivalent (SLE) location.

The barrier calculations are contained in Appendix 4. These calculations show that barriers at least six feet (6') high must be erected between the Residence Inn entry portico and the adjacent pool area. The barrier calculations also show that a sound barrier at least ten feet (10') high must be erected around the west end of the Holiday Inn pool area.

The required noise control barriers may be constructed using any of the following materials:

- (1) Masonry block
- (2) Stucco on wood frame
- (3) 3/4" plywood
- (4) 1/4" tempered glass or 1/2" Lexan
- (5) Earthen berm

- (6) Any combination of the above materials or any material with a surface weight of at least 3.5 pounds per square foot.

Each completed noise control barrier must present a solid face from top-to-bottom. Cutouts and/or openings are not permitted except for drain holes.

5.2 INTERIOR

The City's exposure criteria for new hotel construction require that the interior noise environment, attributable to outside noise sources, be limited to 45 dBA CNEL. Analysis and recommendations for control of outdoor-to-indoor noise intrusion are presented in this section.

The exterior-to-interior noise reduction expected for the planned construction was based on a detailed analysis of sample rooms and units planned for the development. Calculations of the expected typical noise reduction performance were performed for sample rooms. The analysis was based on the typical spectra expected for the primary sources of community noise impact, the typical octave-band transmission loss for each element in the planned building shell, the relative square footage of each element of the planned building shell, the expected typical interior surface treatment, and the acoustical absorption coefficient for each interior surface treatment. Corrections for the "A" Weighted room absorption factors are also included.

Each component of the building shell (e.g. exterior wall, windows, doors, etc.) provides a different amount of transmission loss for each "A" Weighted octave-band of community noise. With the knowledge of the building shell components and their individual octave band transmission loss values for the noise sources, calculations of the composite building shell transmission loss can be made for each room.

The characteristics of the basic building shell are listed in Table 7 on the following page.

TABLE 7BASIC BUILDING SHELL CHARACTERISTICS

<u>PANEL</u>	<u>CONSTRUCTION</u>
Exterior Wall	Siding or stucco, 2" X 4" studs, R-13 fiberglass insulation, 5/8" drywall
Windows	Double pane
Sliding Glass Door	Double pane
Roof	Built-up over 1/2" plywood, R-30 fiberglass insulation, 5/8" drywall
Floor	Carpeted except baths

Table 7 construction minimums will provide around 20 dBA of interior noise reduction.

For convenience of assessment, the specific noise levels at the building faces are given in Table 8.

TABLE 8NOISE LEVELS AT THE BUILDING FACES

	<u>F A C E</u>			
	<u>NORTH</u>	<u>EAST</u>	<u>SOUTH</u>	<u>WEST</u>
Residence Inn	79	70	80	82
Holiday Inn	80	70	80	83

The results of Table 8 show that interior noise reduction levels as high as 38 dBA will be required for rooms facing Interstate 5. Since Table 7 construction will yield only around 20 dBA, specific room calculations were carried out to determine whether additional mitigation is needed.

The calculations are contained in Appendix 5, and the results are given in Table 9 on the following page.

TABLE 9ROOM NOISE REDUCTION VALUES

<u>BLDG</u>	<u>ROOM</u>	<u>NOISE REDUCTION VS. GLAZING STC</u>									
		<u>24</u>	<u>26</u>	<u>28</u>	<u>30</u>	<u>32</u>	<u>34</u>	<u>36</u>	<u>38</u>	<u>40</u>	
Res Inn	Studio/1 Bedroom	23	24	26	27	28	29	29	30	30	
	Double Queen	26	27	28	28	29	29	29	29	29	
	King	26	28	29	30	31	31	32	32	32	
Hol Inn	King	25	27	28	28	29	29	29	29	30	
	Double Queen	24	25	27	28	29	30	30	31	31	

The results of Table 9 show that Table 7 construction cannot provide the required 38 dBA of interior noise reduction even with significant glazing upgrades. It will be necessary to upgrade the exterior walls and roof/ceiling assemblies. Such upgrades will consist of adding resilient channels to the interior side of the wall studs plus two layers of 5/8" drywall. Similarly, the roof/ceiling assembly (top floor only) can be upgraded by adding resilient channels to the ceiling joists plus two layers of 5/8" drywall.

Additional interior noise reduction calculations were performed to determine the effect of the exterior wall and roof/ceiling upgrades. The calculations are contained in Appendix 6 and the results are given in Table 10.

TABLE 10ROOM NOISE REDUCTION VALUES
WITH EXTERIOR WALL AND ROOF/CEILING UPGRADES

<u>BLDG</u>	<u>ROOM</u>	<u>NOISE REDUCTION VS. GLAZING STC</u>									
		<u>24</u>	<u>26</u>	<u>28</u>	<u>30</u>	<u>32</u>	<u>34</u>	<u>36</u>	<u>38</u>	<u>40</u>	
Res Inn	Studio/1 Bedroom	23	25	27	29	31	33	34	36	37	
	Double Queen	28	30	32	33	35	36	37	38	38	
	King	28	29	31	33	35	36	38	39	40	
Hol Inn	King	27	29	31	33	34	35	37	38	38	
	Double Queen	25	27	28	30	32	34	35	37	38	

- (1) Add STC 40 glazing to all rooms along the west face of both buildings.
- (2) Add STC 36 glazing to all rooms along the north and south building faces of both buildings.

- (3) Add STC 28 glazing to all remaining rooms of both buildings including all rooms facing the central courtyard of the Residence Inn building.
- (4) Add resilient channels and two layers 5/8" drywall to the exterior wall assemblies of all rooms along the west, north and south building faces of both buildings.
- (5) Add resilient channels and two layers 5/8" drywall to the ceilings of all top floor rooms along the west, north and south building faces of both buildings.

5.3 VENTILATION

If interior allowable noise levels are met by requiring that windows be unopenable or remain closed, then the design of the structure must also specify a ventilation or air conditioning system to provide a habitable interior environment. The ventilation system must not compromise the dwelling unit or guest room noise reduction.

5.4 UNIT-TO-UNIT NOISE CONTROL

Common floor/ceiling assemblies between units are subject to Title 24 Sound Transmission Class(STC) and Impact Insulation Class (IIC) requirements. The plan set provided for this analysis did not include common floor/ceiling assembly details. It is highly recommended that one of the following widely used common floor/ceiling assemblies, all of which rate at least STC 50, be incorporated into the building plans:

- (1) 8" concrete slab (Riverbank Acoustical Labs, TL 76-77, 1977, 16f, Pre-stressed Concrete Institute, STC 58 -- IIC 71 with carpet, IIC 34 for bare floor)
- (2) 1 1/2" lightweight concrete, sub-floor, R-11 insulation, resilient channel, drywall ceiling (Geiger and Hamme CCA-14MT, CCA-15MT, 1972, 16f, Cellular Concrete Associates, STC 60 --IIC 73 with carpet, IIC 47 with vinyl tile)
- (3) 1 3/8" Gyp-Crete, sub-floor, 2" by 10" joists, R-11 insulation, resilient channel, 1/2" drywall ceiling (Riverbank Acoustical Labs TL 81-16, Gyp-Crete Corp., 1981, STC 60 -- Riverbank Acoustical Labs IN 81-14, Gyp-Crete Corp., 1981, IIC 51 with sheet vinyl)

As can be seen by the above list, some of the recommended assemblies cannot meet the IIC 50 minimum requirement without carpet. Uncarpeted areas above other living units will require some form of proprietary isolation product under the floor to achieve the required rating. Such products include Enkasonic, Acousti-Mat, Monsanto SC50, and others. Such products are designed to be installed atop the bare sub-floor and

topped with either a LWC/Gyp-Crete pour or additional layers of plywood. Each product has its own specific installation requirements. These products can produce both design and field IIC compliance with sheet vinyl or wood flooring. While various lab tests have shown these same products to produce design IIC compliance when used with ceramic tile, field testing experience has proven that actual ceramic tile installations are marginal. The use of ceramic tile or marble flooring is not recommended, regardless of the installation method.

The plan set provided for this analysis did not include common wall assembly details. It is highly recommended that one of the following widely used common wall assemblies, all of which rate at least STC 50, be incorporated into the building plans:

- (1) Two layers 1/2" direct nailed drywall, 2" by 6" plate, 2" by 4" staggered studs, fiberglass insulation, two layers 1/2" direct nailed drywall (Owens/Corning Fiberglas, OCF W-55-69, 1969, 16f, Owens/Corning Fiberglas, STC 54)
- (2) Two layers 5/8" direct nailed drywall, 2" by 6" plate, 2" by 4" staggered studs, R-11 insulation, two layers 5/8" direct nailed drywall (National Gypsum Co. NGC 2376, 1970, 16f, STC 53)
- (3) 5/8" direct nailed drywall, 2" by 4" plate with 2" by 4" studs, R-11 insulation, 1" airspace at plate, 2" by 4" plate with 2" by 4" studs, 5/8" direct nailed drywall (Owens/Corning Fiberglas OCF 448, 1967, 16f, STC 56)
- (4) Same as #3 with two layers of R-11 insulation (Riverbank Acoustical Labs TL75-83, 1975, 16f, U.S. Department of Agriculture, STC 57)
- (5) Two layers 5/8" drywall direct nailed, 2" by 4" plate with 2" x 4" studs, 1" air space, 2" by 4" plate with 2" by 4" studs, R-11 insulation, two layers 5/8" drywall (National Gypsum Co. NGC 3056, 1970, 16f, Gypsum Association, STC 58)
- (6) Same as #5 with two layers of R-11 insulation (Riverbank Acoustical Labs TL 75-82, 1975, 16f, U.S. Department of Agriculture, STC 63)

All wall assemblies between any common space and a living unit must be an STC 50 minimum rated assembly. All Plumbing and electrical installations shall be installed per the instructions contained in Appendix 7. Put all details onto Plans.

5.5 PROJECT DISCLOSURE

The acoustical code requirements are minimal acceptable standards. Compliance with Building Department acoustical criteria does not require, guarantee or even imply that local sound sources will be mitigated to inaudibility. Compliance with an exterior noise limit of 65 dBA CNEL means that exterior noise will remain clearly audible within

the mitigated exterior space. Compliance with an interior noise limit of 45 dBA CNEL means that exterior noise sources will remain audible on the interior of a structure.

Due to quality control and other field related problems, the code minimum laboratory rating of STC/IIC 50 for common assemblies does not guarantee that all common assemblies will pass a field test. In fact, there is a 50% chance that half of all laboratory rated STC/IIC 50 common assemblies could fail field tests. An STC 50 rated assembly will produce around 45 dBA of voice reduction in the field. This means that normal conversation in adjoining units will be audible a certain percentage of the time.

Do not misrepresent the degree of exterior to interior or unit to unit acoustical isolation as anything more than meeting code during any phase of this project. Never, ever, use any form of the term "Soundproof" to describe any portion of this project.

6.0 PROJECT GENERATED NOISE

Once completed, the operations of the two hotel buildings will generate noise from various sources. Such sources include, motor vehicles moving on and off the project site, truck deliveries, rooftop mechanical units and individual guest room HVAC units, and even people's voices. These various noise sources will combine at the project boundaries and must comply with the City noise limits. This section will examine the various noise sources and compare the combined source noise levels at the project boundaries to the City noise limits.

6.1 PARKING LOT ACTIVITY

Patron and employee vehicles will enter and exit the project site as well as maneuver around the project parking areas once on site. Field measurement experience has shown that a cycle of people entering a parked vehicle, slamming the doors, starting the engine, maneuvering out of the parking space and driving away, immediately followed by another vehicle pulling up, maneuvering into the parking space, shutting off the engine, people exiting the vehicle and slamming the doors produces an average noise level of 68 dBA Leq at a distance of 10 feet. Maximum noise levels are typically 10 dBA higher or 78 dBA max at 10 feet. The analysis has shown that future traffic noise levels from Interstate 5 will be as high as 70 dBA CNEL on the east side of the project site. This means that typical parking lot activities will produce less noise than the adjacent freeway.

6.2 TRUCK DELIVERIES

Deliveries of various products such as linens, toiletries, food and such will be made periodically. Most such deliveries will be made by smaller trucks such as those

used by UPS or FedEx. However, larger deliveries could also be made by tractor-trailer rigs. Typical noise sources and levels are given in Table 11.

TABLE 11

TRUCK DELIVERY NOISE LEVELS

<u>SOURCE</u>	<u>DBA @ 10'</u>	<u>DURATION</u>
Truck engine idle	68	15 minutes
Moving Truck (under 10 mph)	76	1 minute
Air brakes	94	8 seconds
Unloading noise	72	15 minutes

The Exhibit 3 site plan shows truck unloading areas on the east side of the Residence in building as well as on the south side of the Holiday Inn Express Building. The unloading area on the east side of the Residence Inn building is about 100 feet from the common property line of the existing hotel (residential) use to the north and about 45 feet from the common property line of the commercial use to the east. These distances would reduce the Table 11 source noise levels by 20 dBA to the north and 13 dBA to the east. This results in 15 minute noise levels of 53 dBA to the north and 60 dBA to the east. Both are well under the allowed L25 noise limits of Table 2. Moving trucks must pass the hotel use to the north creating noise levels similar to the allowed daytime noise limit. Only air brakes have the potential to violate the allowed noise limits. However, air brake noise from trucks delivering to the project hotels will be indistinguishable from air brake noise from trucks delivering to the existing hotel.

6.3 ROOFTOP MECHANICAL/GUEST ROOM HVAC UNITS

Both project buildings will employ rooftop mechanical units as well as individual HVAC units for each guest room. Since noise from such equipment is typically continuous, the combined noise levels from such units must comply with the base noise limits of Table 2 at the adjacent properties. Rooftop mechanical plans were not available for this analysis. For purposes of analysis, each building will be assumed to have 10 rooftop mechanical units, all rated at 9.0 bels (70 dBA at 10 feet). If all ten of these units were located in a cluster approximately 30 feet from the common property line to the north, a combined continuous level of 70 dBA would occur. Rooftop parapet walls at least as tall as the tallest piece of equipment would reduce this level at least 5 dBA. Specifying a maximum manufacturer noise rating of 8.5 bels (65 dBA at 10 feet) would reduce the rooftop mechanical noise by another 5 dBA. Assuming that rooftop parapet walls are used and no rooftop equipment produces more than 65 dBA at 10 feet, the worst-case rooftop noise level at the existing hotel property to the north will be 60 dBA. Even this mitigated level exceeds the nighttime residential use noise limit of Table 2.

Noise from guest room HVAC units will be defined by the nearest 12 units to a single receiver point. If each guest room HVAC unit produces 7.5 bels (55 dBA at 10 feet), then the nearest 12 units to any point on the common property line of the existing hotel use to the north will produce a combined level of 82 dBA. Specifying units with a sound rating of only 6.5 bels would produce a combined level of 72 dBA. Even this mitigated level exceeds the nighttime residential noise limit of Table 2.

The analysis has shown that even mitigated noise from the building mechanical systems will likely exceed the City noise limits. However, freeway noise levels as high as 80 dBA CNEL will occur along the north side of the Residence Inn building. Thus, a building mechanical noise level of 72 dBA will be below the ambient noise levels produced by the freeway. To ensure that this situation remains the case, the project should specify a rooftop mechanical unit maximum allowable noise rating of 8.5 bels and the use of rooftop parapet or freestanding acoustical screen walls at least as tall as the tallest piece of rooftop equipment. Likewise, a maximum allowable noise rating of 6.5 bels should be specified for all guest room HVAC units.

7.0 CONSTRUCTION NOISE

Construction noise is expressly exempted from compliance with the City noise limits as long as all construction activity is restricted to between the hours of 7:00 a.m. and 7:00 p.m. Monday through Friday, and between 8:00 a.m. and 6:00 p.m. on Saturday. Construction noise should not occur on Sundays and/or holidays. It should be noted that, due to the extremely loud ambient noise levels produced by the adjacent freeway, construction noise is not likely to exceed the ambient noise conditions on a frequent basis.

EXHIBIT 1 SITE LOCATION




EXHIBIT 2
AERIAL PHOTO



CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

APPENDIX 1

NOISE RATING METHODOLOGY

CHRISTOPHER JEAN & ASSOCIATES, INC.

ACOUSTICAL CONSULTING SERVICES

NOISE RATING METHODOLOGY

The A-weighted decibel (dBA) or "A" scale on a sound level meter is typically used for environmental noise measurements because the weighting characteristics of the "A" scale approximate the subjective response of the human ear to a broad frequency band noise source by discriminating against the very low and very high frequencies of the audible sound spectrum.

Since community noise is seldom constant, varying from moment to moment and throughout the day, the "A" weighted noise level needs to be further described to provide meaningful data. The Environmental Protection Agency, the Federal Department of Transportation, several foreign countries and many private consultants are now using three time-exceeded percentile figures to describe noise, which are:

- (1) L_{90} is the noise level that is exceeded 90 percent of any sample measurement period (such as 24 hours) and is often used to describe the background or ambient noise level.
- (2) L_{50} is the noise level that is exceeded 50 percent of any sample measurement period. It is generally considered to represent the median noise level.
- (3) L_{10} is the noise level that is exceeded 10 percent of any sample measurement period. It is a good descriptor of fluctuating noise sources such as vehicular traffic. It indicates the near-maximum noise levels that occur for groups of single noise events. Being related to the subjective annoyance to community noise, the L_{10} is a good design tool in the planning of acoustical barriers.

More recent noise assessment methods are based on the equivalent energy concept where $Leq(x)$ represents the average energy content of a fluctuating noise source over a sample measurement period. The subscript (x) represents the period over which the energy is computed and/or measured. Current practice references the time quantity to either one (1) hour, eight (8) hours, or twenty-four (24) hours. When referenced to one (1) hour, Leq is also called the HNL (Hourly Noise Level).

Since Leq is the summation of the functional products of noise level and duration, many different combinations of noise levels, duration times and time histories can produce similar Leq values. Thus a value of $Leq(24)$ equals 50 means only that the average noise level is 50 dB. During that 24-hour period, there can be times when the noise level is higher than 50 dB and times when it is lower than 50 dB.

If the period of the measurement is only a single event, the energy content is not averaged. The energy expression for a single event is simply the sum of the functional product of the noise level and duration time of the event. This term is called the Le or SENEL (Single Event Noise Exposure Level). The summation of Le values averaged over one hour is $Leq(1)$, over eight hours is $Leq(8)$, over 24 hours is $Leq(24)$, etc.

Leq is further refined into Ldn (Level Day-Night) and $CNEL$ (Community Noise Equivalent Level), where noise that occurs during certain hours of the day are weighted (or penalized) in an attempt to compensate for the general perception that such noise is more annoying during these time periods (typically evening and nighttime hours).

- (1) Ldn is the sound level in dBA that corresponds to the average energy content of the noise being measured over a 24-hour period but includes a ten (10) dBA weighting penalty for noise that occurs during the nighttime hours between 10:00 PM and 7:00 AM. The Ldn is a noise rating method recommended by the Environmental Protection Agency because it takes into account those subjectively more annoying noise events that occur during normal sleeping hours.
- (2) $CNEL$ is the sound level in dBA that corresponds to the average energy content of the noise being measured over a 24-hour period but includes a five (5) dBA penalty for noise that occurs during the evening hours between 7:00 PM and 10:00 PM, and a ten (10) dBA penalty for noise that occurs during the nighttime hours between 10:00 PM and 7:00 AM. For typical highway vehicular traffic situations, computer analysis has shown that the Ldn and $CNEL$ values correlate within 0.5 dBA.

The percentile figures L_{10} , L_{50} and L_{90} can be directly scaled from a graphical recording of the measured noise sample over a particular time period. These figures can also be measured directly using modern automatic noise measuring equipment. Measurement of the parameters Le , Leq , Ldn and $CNEL$ requires even more sophisticated and correspondingly expensive noise measuring equipment. As a result, engineers have devised ways of estimating Leq (and hence, Ldn) using standard instrumentation and methods.

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

APPENDIX 2

EXISTING TRAFFIC NOISE CALCULATIONS

HOURLY NOISE LEVEL

PROJECT : SPRINGHILL & RESIDENCE INN
 STREET NAME : CONT
 SITE TYPE : HARD

INPUT DATA

	AUTO	METK	HVTK
SPEED:	65	65	65
% VOLUME:	88.5	2.9	8.600001
VOLUME	= 9252		
HVY TRK GRADIENT	= 0 DBA		

NOISE LEVEL

AUTO	81.3
MED. TRK.	76.0
HVY. TRK.	83.9
TOTAL	86.2

NOISE LEVEL AT 150 FT

AUTO	MEDIUM TRK	HEAVY TRK	TOTAL
76.5	71.2	79.1	81.5

LEQ AT SPECIFIED DISTANCES

DISTANCE	LEQ
50	86.2
75	84.5
100	83.2
125	82.3
150	81.5
175	80.8
200	80.2
250	79.3
300	78.5
350	77.8
400	77.2
450	76.7
500	76.2
550	75.8
600	75.5
650	75.1
700	74.8
750	74.5
800	74.2
1000	73.2

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

APPENDIX 3

FUTURE TRAFFIC NOISE CALCULATIONS

FHWA RD-77-108 HIGHWAY NOISE PREDICTION MODEL

 PROJECT NAME : SPRINGHILL & RESIDENCE INN
 SITE LOCATION : SANTA CLARITA
 DESCRIPTION : INTERSTATE 5
 SITE TYPE : HARD

INPUT DATA	AUTO	MEDIUM TRUCK	HEAVY TRUCK
SPEED	65	65	65
% DAY	73	73	69.1
% EVENING	8.60	8.60	6.70
% NIGHT	18.4	18.4	24.2
% VOLUME	87.4	2.8	9.8
VOLUME	188000		

 ---AVERAGE HOURLY NOISE LEVELS AT 50 FEET---

	DAY	EVENING	NIGHT	24 HOUR	CNEL
AUTO	82.17	78.91	77.44	80.53	85.05
MEDIUM TRK.	76.79	73.52	72.05	75.14	79.66
HEAVY TRK.	85.16	81.05	81.86	83.76	88.96
TOTAL	87.33	83.57	83.52	85.84	90.79

 NOISE LEVEL AT SPECIFIED DISTANCES

DISTANCE	CNEL
50	90.79
75	89.03
100	87.78
125	86.81
150	86.02
175	85.35
200	84.77
225	84.26
250	83.80
275	83.38
300	83.01
325	82.66
350	82.34
375	82.04
400	81.76
450	81.25
500	80.79
550	80.37
600	80.00
650	79.65
700	79.33
750	79.03
800	78.75

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

APPENDIX 4

SOUND BARRIER HEIGHT CALCULATIONS

BARRIER NOISE REDUCTION ANALYSIS, WALL HEIGHT VARIABLE

 REFERENCE VEHICLE LEVELS AT 50 FEET

AUTO.....= 82.05
 M.TRUCK.....= 76.66001
 H.TRUCK.....= 85.96

PROJECT.....RESIDENCE INN
 DESCRIPTION..POOL AREA NOISE BARRIER
 SOURCE ELEVATION..... 0
 RECEIVER ELEVATION..... 8
 BARRIER ELEVATION..... 8
 RECEIVER HEIGHT..... 5
 DISTANCE TO SOURCE..... 175
 DISTANCE TO RECEIVER... 20
 AUTO NOISE LEVEL..... 76.13936
 M.TRK NOISE LEVEL..... 70.74936
 H.TRK NOISE LEVEL..... 80.04936
 SOURCE NOISE LEVEL..... 71.09

ANGULAR CORRECTION(DB) - 10.79181

WALL HEIGHT	ANL	MTNL	HTNL	TNL	TIL
0.00 FN	65.35 0.0000	59.96 0.0000	69.26 0.0000	71.09	0.00
1.00 FN	65.35 0.0000	59.96 0.0000	69.26 0.0000	71.09	0.00
2.00 FN	65.35 0.0000	59.96 0.0000	69.26 0.0000	71.09	0.00
3.00 FN	65.35 0.0000	59.96 0.0000	69.26 0.0000	71.09	0.00
4.00 FN	60.31 0.0028	54.95 0.0004	69.26 0.0000	69.92	1.17
5.00 FN	59.80 0.0483	54.56 0.0351	64.17 0.0072	65.86	5.23
6.00 FN	59.05 0.1494	53.77 0.1254	63.55 0.0634	65.20	5.89
7.00 FN	58.24 0.3059	53.03 0.2712	62.84 0.1750	64.46	6.63
8.00 FN	57.22 0.5174	52.03 0.4719	61.97 0.3416	63.54	7.55

BARRIER NOISE REDUCTION ANALYSIS, WALL HEIGHT VARIABLE

 REFERENCE VEHICLE LEVELS AT 50 FEET

AUTO.....= 82.05
 M.TRUCK.....= 76.66001
 H.TRUCK.....= 85.96

PROJECT.....HOLIDAY INN
 DESCRIPTION..POOL AREA SOUND BARRIER
 SOURCE ELEVATION..... 0
 RECEIVER ELEVATION..... 2
 BARRIER ELEVATION..... 2
 RECEIVER HEIGHT..... 5
 DISTANCE TO SOURCE..... 175
 DISTANCE TO RECEIVER... 20
 AUTO NOISE LEVEL..... 76.13936
 M.TRK NOISE LEVEL..... 70.74936
 H.TRK NOISE LEVEL..... 80.04936
 SOURCE NOISE LEVEL..... 74.10

ANGULAR CORRECTION(DB) - 7.781512

WALL HEIGHT	ANL	MTNL	HTNL	TNL	TIL
0.00 FN	68.36 0.0000	62.97 0.0000	72.27 0.0000	74.10	0.00
1.00 FN	68.36 0.0000	62.97 0.0000	72.27 0.0000	74.10	0.00
2.00 FN	68.36 0.0000	62.97 0.0000	72.27 0.0000	74.10	0.00
3.00 FN	68.36 0.0000	62.97 0.0000	72.27 0.0000	74.10	0.00
4.00 FN	68.36 0.0000	62.97 0.0000	72.27 0.0000	74.10	0.00
5.00 FN	63.20 0.0138	57.88 0.0072	72.27 0.0000	72.91	1.18
6.00 FN	62.47 0.0808	57.26 0.0634	67.01 0.0222	68.65	5.45
7.00 FN	61.79 0.2033	56.55 0.1750	66.19 0.0996	67.87	6.23
8.00 FN	60.87 0.3807	55.68 0.3416	65.55 0.2319	67.14	6.95
9.00 FN	59.82 0.6121	54.64 0.5622	64.60 0.4183	66.16	7.94
10.00 FN	58.77 0.8963	53.58 0.8357	63.55 0.6576	65.11	8.99

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

APPENDIX 5

INTERIOR NOISE REDUCTION CALCULATIONS

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 24

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	22	.05	35	0.22084
WINDOW 2	25	.05	0	0.00000
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.26629
-10LOG(ET*S)				5.7
10LOGA				22.9
NOISE REDUCTION				22.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 26

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	24	.05	35	0.13934
WINDOW 2	27	.05	0	0.00000
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.18479
-10LOG(ET*S)				7.3
10LOGA				22.9
NOISE REDUCTION				24.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 28

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	26	.05	35	0.08792
WINDOW 2	29	.05	0	0.00000
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.13337
-10LOG(ET*S)				8.7
10LOGA				22.9
NOISE REDUCTION				25.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 30

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	28	.05	35	0.05547
WINDOW 2	31	.05	0	0.00000
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.10093
-10LOG(ET*S)				10.0
10LOGA				22.9
NOISE REDUCTION				26.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 32

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	30	.05	35	0.03500
WINDOW 2	33	.05	0	0.00000
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.08046
-10LOG(ET*S)				10.9
10LOGA				22.9
NOISE REDUCTION				27.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 34

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	32	.05	35	0.02208
WINDOW 2	35	.05	0	0.00000
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.06754
-10LOG(ET*S)				11.7
10LOGA				22.9
NOISE REDUCTION				28.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 36

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	34	.05	35	0.01393
WINDOW 2	37	.05	0	0.00000
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.05939
-10LOG(ET*S)				12.3
10LOGA				22.9
NOISE REDUCTION				29.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 38

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	36	.05	35	0.00879
WINDOW 2	39	.05	0	0.00000
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.05425
-10LOG(ET*S)				12.7
10LOGA				22.9
NOISE REDUCTION				29.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + STC = 40

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		45	0.00226
EXT.WALL 3	50		0	0.00000
INT.WALL			450	
WINDOW 1	38	.05	35	0.00555
WINDOW 2	41	.05	0	0.00000
WINDOW 3	48	.05	0	0.00000
SGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	261	0.02610
FLOOR		.6	261	
ET*S				0.05100
-10LOG(ET*S)				12.9
10LOGA				22.9
NOISE REDUCTION				29.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 24

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	22	.05	0	0.00000
WINDOW 2	25	.05	25	0.07906
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.13922
-10LOG(ET*S)				8.6
10LOGA				23.3
NOISE REDUCTION				25.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 26

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	24	.05	0	0.00000
WINDOW 2	27	.05	25	0.04988
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.11004
-10LOG(ET*S)				9.6
10LOGA				23.3
NOISE REDUCTION				26.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 28

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	26	.05	0	0.00000
WINDOW 2	29	.05	25	0.03147
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.09163
-10LOG(ET*S)				10.4
10LOGA				23.3
NOISE REDUCTION				27.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 30

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	28	.05	0	0.00000
WINDOW 2	31	.05	25	0.01986
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.08002
-10LOG(ET*S)				11.0
10LOGA				23.3
NOISE REDUCTION				28.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 32

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	30	.05	0	0.00000
WINDOW 2	33	.05	25	0.01253
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.07269
-10LOG(ET*S)				11.4
10LOGA				23.3
NOISE REDUCTION				28.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 34

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	32	.05	0	0.00000
WINDOW 2	35	.05	25	0.00791
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.06806
-10LOG(ET*S)				11.7
10LOGA				23.3
NOISE REDUCTION				29.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 36

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	34	.05	0	0.00000
WINDOW 2	37	.05	25	0.00499
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.06515
-10LOG(ET*S)				11.9
10LOGA				23.3
NOISE REDUCTION				29.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 38

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	36	.05	0	0.00000
WINDOW 2	39	.05	25	0.00315
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.06331
-10LOG(ET*S)				12.0
10LOGA				23.3
NOISE REDUCTION				29.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + STC = 40

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		268	0.02680
EXT.WALL 2	43		73	0.00366
EXT.WALL 3	50		0	0.00000
INT.WALL			351	
WINDOW 1	38	.05	0	0.00000
WINDOW 2	41	.05	25	0.00199
WINDOW 3	48	.05	0	0.00000
SGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	297	0.02970
FLOOR		.6	297	
ET*S				0.06214
-10LOG(ET*S)				12.1
10LOGA				23.3
NOISE REDUCTION				29.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 24

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	22	.05	0	0.00000
WINDOW 2	25	.05	25	0.07906
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.10586
-10LOG(ET*S)				9.8
10LOGA				22.6
NOISE REDUCTION				26.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 26

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	24	.05	0	0.00000
WINDOW 2	27	.05	25	0.04988
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.07669
-10LOG(ET*S)				11.2
10LOGA				22.6
NOISE REDUCTION				27.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 28

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	26	.05	0	0.00000
WINDOW 2	29	.05	25	0.03147
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.05828
-10LOG(ET*S)				12.3
10LOGA				22.6
NOISE REDUCTION				29.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 30

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	28	.05	0	0.00000
WINDOW 2	31	.05	25	0.01986
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.04666
-10LOG(ET*S)				13.3
10LOGA				22.6
NOISE REDUCTION				29.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 32

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	30	.05	0	0.00000
WINDOW 2	33	.05	25	0.01253
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.03933
-10LOG(ET*S)				14.1
10LOGA				22.6
NOISE REDUCTION				30.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 34

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT,WALL			549	
WINDOW 1	32	.05	0	0.00000
WINDOW 2	35	.05	25	0.00791
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.03471
-10LOG(ET*S)				14.6
10LOGA				22.6
NOISE REDUCTION				31.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 36

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	34	.05	0	0.00000
WINDOW 2	37	.05	25	0.00499
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.03179
-10LOG(ET*S)				15.0
10LOGA				22.6
NOISE REDUCTION				31.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 38

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	36	.05	0	0.00000
WINDOW 2	39	.05	25	0.00315
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.02995
-10LOG(ET*S)				15.2
10LOGA				22.6
NOISE REDUCTION				31.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + STC = 40

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		0	0.00000
EXT.WALL 2	43		38	0.00190
EXT.WALL 3	50		0	0.00000
INT.WALL			549	
WINDOW 1	38	.05	0	0.00000
WINDOW 2	41	.05	25	0.00199
WINDOW 3	48	.05	0	0.00000
SGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.02879
-10LOG(ET*S)				15.4
10LOGA				22.6
NOISE REDUCTION				32.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + STC = 24

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	40		171	0.01710
EXT. WALL 2	43		99	0.00496
EXT. WALL 3	50		0	0.00000
INT. WALL			282	
WINDOW 1	22	.05	0	0.00000
WINDOW 2	25	.05	25	0.07906
WINDOW 3	22	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.12502
-10LOG(ET*S)				9.0
10LOGA				22.4
NOISE REDUCTION				25.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + STC = 26

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	40		171	0.01710
EXT. WALL 2	43		99	0.00496
EXT. WALL 3	50		0	0.00000
INT. WALL			282	
WINDOW 1	24	.05	0	0.00000
WINDOW 2	27	.05	25	0.04988
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.09584
-10LOG(ET*S)				10.2
10LOGA				22.4
NOISE REDUCTION				26.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HLOIDAY KING + STC = 28

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		99	0.00496
EXT.WALL 3	50		0	0.00000
INT.WALL			282	
WINDOW 1	26	.05	0	0.00000
WINDOW 2	29	.05	25	0.03147
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.07743
-10LOG(ET*S)				11.1
10LOGA				22.4
NOISE REDUCTION				27.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HLOIDAY KING + STC = 30

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		99	0.00496
EXT.WALL 3	50		0	0.00000
INT.WALL			282	
WINDOW 1	28	.05	0	0.00000
WINDOW 2	31	.05	25	0.01986
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.06582
-10LOG(ET*S)				11.8
10LOGA				22.4
NOISE REDUCTION				28.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HLOIDAY KING + STC = 32

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		99	0.00496
EXT.WALL 3	50		0	0.00000
INT.WALL			282	
WINDOW 1	30	.05	0	0.00000
WINDOW 2	33	.05	25	0.01253
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.05849
-10LOG(ET*S)				12.3
10LOGA				22.4
NOISE REDUCTION				28.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HLOIDAY KING + STC = 34

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		99	0.00496
EXT.WALL 3	50		0	0.00000
INT.WALL			282	
WINDOW 1	32	.05	0	0.00000
WINDOW 2	35	.05	25	0.00791
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.05387
-10LOG(ET*S)				12.7
10LOGA				22.4
NOISE REDUCTION				29.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HLOIDAY KING + STC = 36

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		99	0.00496
EXT.WALL 3	50		0	0.00000
INT.WALL			282	
WINDOW 1	34	.05	0	0.00000
WINDOW 2	37	.05	25	0.00499
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.05095
-10LOG(ET*S)				12.9
10LOGA				22.4
NOISE REDUCTION				29.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HLOIDAY KING + STC = 38

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		171	0.01710
EXT.WALL 2	43		99	0.00496
EXT.WALL 3	50		0	0.00000
INT.WALL			282	
WINDOW 1	36	.05	0	0.00000
WINDOW 2	39	.05	25	0.00315
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	
ET*S				0.04911
-10LOG(ET*S)				13.1
10LOGA				22.4
NOISE REDUCTION				29.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + STC = 40

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	40		171	0.01710
EXT. WALL 2	43		99	0.00496
EXT. WALL 3	50		0	0.00000
INT. WALL			282	
WINDOW 1	38	.05	0	0.00000
WINDOW 2	41	.05	25	0.00199
WINDOW 3	43	.05	0	0.00000
SGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	239	0.02390
FLOOR		.6	239	

ET*S				0.04795
-10LOG (ET*S)				13.2
10LOGA				22.4
NOISE REDUCTION				29.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 24

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	22	.05	25	0.15774
WINDOW 2	25	.05	0	0.00000
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.19254
-10LOG(ET*S)				7.2
10LOGA				22.6
NOISE REDUCTION				23.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 26

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	24	.05	25	0.09953
WINDOW 2	27	.05	0	0.00000
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.13433
-10LOG(ET*S)				8.7
10LOGA				22.6
NOISE REDUCTION				25.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 28

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	26	.05	25	0.06280
WINDOW 2	29	.05	0	0.00000
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.09760
-10LOG(ET*S)				10.1
10LOGA				22.6
NOISE REDUCTION				26.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 30

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	28	.05	25	0.03962
WINDOW 2	31	.05	0	0.00000
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.07442
-10LOG(ET*S)				11.3
10LOGA				22.6
NOISE REDUCTION				27.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 32

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	30	.05	25	0.02500
WINDOW 2	33	.05	0	0.00000
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.05980
-10LOG(ET*S)				12.2
10LOGA				22.6
NOISE REDUCTION				28.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 34

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	32	.05	25	0.01577
WINDOW 2	35	.05	0	0.00000
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.05057
-10LOG(ET*S)				13.0
10LOGA				22.6
NOISE REDUCTION				29.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 36

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	34	.05	25	0.00995
WINDOW 2	37	.05	0	0.00000
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.04475
-10LOG(ET*S)				13.5
10LOGA				22.6
NOISE REDUCTION				30.1

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + STC = 38

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	40		99	0.00990
EXT.WALL 2	43		0	0.00000
EXT.WALL 3	50		0	0.00000
INT.WALL			456	
WINDOW 1	36	.05	25	0.00628
WINDOW 2	39	.05	0	0.00000
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	
ET*S				0.04108
-10LOG(ET*S)				13.9
10LOGA				22.6
NOISE REDUCTION				30.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DEL. QUEEN + STC = 40

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	40		99	0.00990
EXT. WALL 2	43		0	0.00000
EXT. WALL 3	50		0	0.00000
INT. WALL			456	
WINDOW 1	38	.05	25	0.00396
WINDOW 2	41	.05	0	0.00000
WINDOW 3	48	.05	0	0.00000
SGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	40	.04	249	0.02490
FLOOR		.6	249	

ET*S				0.03876
-10LOG (ET*S)				14.1
10LOGA				22.6
NOISE REDUCTION				30.8

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

APPENDIX 6

INTERIOR NOISE REDUCTION CALCULATIONS
WITH EXTERIOR WALL AND ROOF/CEILING UPGRADES

P. O. BOX 2325 • FULLERTON, CALIFORNIA • 92837
PHONE: 714-805-0115

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 24

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		171	0.00171
EXT. WALL 2	53		45	0.00023
EXT. WALL 3	60		0	0.00000
INT. WALL			450	
WINDOW 1	22	.05	35	0.22084
WINDOW 2	25	.05	0	0.00000
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.22538
-10LOG(ET*S)				6.5
10LOGA				22.9
NOISE REDUCTION				23.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 26

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		171	0.00171
EXT. WALL 2	53		45	0.00023
EXT. WALL 3	60		0	0.00000
INT. WALL			450	
WINDOW 1	24	.05	35	0.13934
WINDOW 2	27	.05	0	0.00000
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.14388
-10LOG(ET*S)				8.4
10LOGA				22.9
NOISE REDUCTION				25.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 28

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		45	0.00023
EXT.WALL 3	60		0	0.00000
INT.WALL			450	
WINDOW 1	26	.05	35	0.08792
WINDOW 2	29	.05	0	0.00000
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.09246
-10LOG(ET*S)				10.3
10LOGA				22.9
NOISE REDUCTION				27.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 30

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		45	0.00023
EXT.WALL 3	60		0	0.00000
INT.WALL			450	
WINDOW 1	28	.05	35	0.05547
WINDOW 2	31	.05	0	0.00000
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.06002
-10LOG(ET*S)				12.2
10LOGA				22.9
NOISE REDUCTION				29.1

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 32

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		45	0.00023
EXT.WALL 3	60		0	0.00000
INT.WALL			450	
WINDOW 1	30	.05	35	0.03500
WINDOW 2	33	.05	0	0.00000
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.03955
-10LOG(ET*S)				14.0
10LOGA				22.9
NOISE REDUCTION				30.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 34

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		45	0.00023
EXT.WALL 3	60		0	0.00000
INT.WALL			450	
WINDOW 1	32	.05	35	0.02208
WINDOW 2	35	.05	0	0.00000
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.02663
-10LOG(ET*S)				15.7
10LOGA				22.9
NOISE REDUCTION				32.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 36

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		45	0.00023
EXT.WALL 3	60		0	0.00000
INT.WALL			450	
WINDOW 1	34	.05	35	0.01393
WINDOW 2	37	.05	0	0.00000
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.01848
-10LOG(ET*S)				17.3
10LOGA				22.9
NOISE REDUCTION				34.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 38

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		45	0.00023
EXT.WALL 3	60		0	0.00000
INT.WALL			450	
WINDOW 1	36	.05	35	0.00879
WINDOW 2	39	.05	0	0.00000
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.01334
-10LOG(ET*S)				18.7
10LOGA				22.9
NOISE REDUCTION				35.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN STUDIO/1 BR + UPGRADES + STC = 40

FLOOR AREA 261

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		171	0.00171
EXT WALL 2	53		45	0.00023
EXT WALL 3	60		0	0.00000
INT WALL			450	
WINDOW 1	38	.05	35	0.00555
WINDOW 2	41	.05	0	0.00000
WINDOW 3	48	.05	0	0.00000
SGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	261	0.00261
FLOOR		.6	261	
ET*S				0.01009
-10LOG(ET*S)				20.0
10LOGA				22.9
NOISE REDUCTION				36.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 24

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	22	.05	0	0.00000
WINDOW 2	25	.05	25	0.07906
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.08507
-10LOG(ET*S)				10.7
10LOGA				23.3
NOISE REDUCTION				28.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 26

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	24	.05	0	0.00000
WINDOW 2	27	.05	25	0.04988
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.05590
-10LOG(ET*S)				12.5
10LOGA				23.3
NOISE REDUCTION				29.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 28

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	26	.05	0	0.00000
WINDOW 2	29	.05	25	0.03147
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.03749
-10LOG(ET*S)				14.3
10LOGA				23.3
NOISE REDUCTION				31.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 30

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	28	.05	0	0.00000
WINDOW 2	31	.05	25	0.01986
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.02587
-10LOG(ET*S)				15.9
10LOGA				23.3
NOISE REDUCTION				33.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 32

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	30	.05	0	0.00000
WINDOW 2	33	.05	25	0.01253
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.01855
-10LOG(ET*S)				17.3
10LOGA				23.3
NOISE REDUCTION				34.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 34

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	32	.05	0	0.00000
WINDOW 2	35	.05	25	0.00791
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.01392
-10LOG(ET*S)				18.6
10LOGA				23.3
NOISE REDUCTION				35.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 36

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	34	.05	0	0.00000
WINDOW 2	37	.05	25	0.00499
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.01100
-10LOG(ET*S)				19.6
10LOGA				23.3
NOISE REDUCTION				36.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 38

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	36	.05	0	0.00000
WINDOW 2	39	.05	25	0.00315
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	
ET*S				0.00916
-10LOG(ET*S)				20.4
10LOGA				23.3
NOISE REDUCTION				37.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN DBL QUEEN + UPGRADES + STC = 40

FLOOR AREA 297

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		268	0.00268
EXT.WALL 2	53		73	0.00037
EXT.WALL 3	60		0	0.00000
INT.WALL			351	
WINDOW 1	38	.05	0	0.00000
WINDOW 2	41	.05	25	0.00199
WINDOW 3	48	.05	0	0.00000
SGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	297	0.00297
FLOOR		.6	297	

ET*S				0.00800
-10LOG(ET*S)				21.0
10LOGA				23.3
NOISE REDUCTION				38.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 24

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		0	0.00000
EXT. WALL 2	53		38	0.00019
EXT. WALL 3	60		0	0.00000
INT. WALL			549	
WINDOW 1	22	.05	0	0.00000
WINDOW 2	25	.05	25	0.07906
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.08174
-10LOG(ET*S)				10.9
10LOGA				22.6
NOISE REDUCTION				27.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 26

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		0	0.00000
EXT. WALL 2	53		38	0.00019
EXT. WALL 3	60		0	0.00000
INT. WALL			549	
WINDOW 1	24	.05	0	0.00000
WINDOW 2	27	.05	25	0.04988
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.05256
-10LOG(ET*S)				12.8
10LOGA				22.6
NOISE REDUCTION				29.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 28

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		0	0.00000
EXT. WALL 2	53		38	0.00019
EXT. WALL 3	60		0	0.00000
INT. WALL			549	
WINDOW 1	26	.05	0	0.00000
WINDOW 2	29	.05	25	0.03147
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.03415
-10LOG(ET*S)				14.7
10LOGA				22.6
NOISE REDUCTION				31.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 30

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		0	0.00000
EXT. WALL 2	53		38	0.00019
EXT. WALL 3	60		0	0.00000
INT. WALL			549	
WINDOW 1	28	.05	0	0.00000
WINDOW 2	31	.05	25	0.01986
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.02254
-10LOG(ET*S)				16.5
10LOGA				22.6
NOISE REDUCTION				33.1

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 32

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		0	0.00000
EXT. WALL 2	53		38	0.00019
EXT. WALL 3	60		0	0.00000
INT. WALL			549	
WINDOW 1	30	.05	0	0.00000
WINDOW 2	33	.05	25	0.01253
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.01521
-10LOG(ET*S)				18.2
10LOGA				22.6
NOISE REDUCTION				34.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 34

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		0	0.00000
EXT. WALL 2	53		38	0.00019
EXT. WALL 3	60		0	0.00000
INT. WALL			549	
WINDOW 1	32	.05	0	0.00000
WINDOW 2	35	.05	25	0.00791
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.01059
-10LOG(ET*S)				19.8
10LOGA				22.6
NOISE REDUCTION				36.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 36

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		0	0.00000
EXT WALL 2	53		38	0.00019
EXT WALL 3	60		0	0.00000
INT WALL			549	
WINDOW 1	34	.05	0	0.00000
WINDOW 2	37	.05	25	0.00499
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.00767
-10LOG(ET*S)				21.2
10LOGA				22.6
NOISE REDUCTION				37.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INN KING + UPGRADES + STC = 38

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		0	0.00000
EXT WALL 2	53		38	0.00019
EXT WALL 3	60		0	0.00000
INT WALL			549	
WINDOW 1	36	.05	0	0.00000
WINDOW 2	39	.05	25	0.00315
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.00583
-10LOG(ET*S)				22.3
10LOGA				22.6
NOISE REDUCTION				39.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME RES INNA KING + UPGRADES + STC = 40

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		0	0.00000
EXT WALL 2	53		38	0.00019
EXT WALL 3	60		0	0.00000
INT WALL			549	
WINDOW 1	38	.05	0	0.00000
WINDOW 2	41	.05	25	0.00199
WINDOW 3	48	.05	0	0.00000
SCD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	

ET*S				0.00467
-10LOG(ET*S)				23.3
10LOGA				22.6
NOISE REDUCTION				39.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 24

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		171	0.00171
EXT WALL 2	53		99	0.00050
EXT WALL 3	60		0	0.00000
INT WALL			282	
WINDOW 1	22	.05	0	0.00000
WINDOW 2	25	.05	25	0.07906
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	

ET*S	0.08365
-10LOG(ET*S)	10.8
10LOGA	22.4
NOISE REDUCTION	27.1

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 26

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		171	0.00171
EXT WALL 2	53		99	0.00050
EXT WALL 3	60		0	0.00000
INT WALL			282	
WINDOW 1	24	.05	0	0.00000
WINDOW 2	27	.05	25	0.04988
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	

ET*S	0.05448
-10LOG(ET*S)	12.6
10LOGA	22.4
NOISE REDUCTION	29.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 28

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		171	0.00171
EXT. WALL 2	53		99	0.00050
EXT. WALL 3	60		0	0.00000
INT. WALL			282	
WINDOW 1	26	.05	0	0.00000
WINDOW 2	29	.05	25	0.03147
WINDOW 3	36	.05	0	0.00000
SGD	46	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	
ET*S				0.03607
-10LOG (ET*S)				14.4
10LOGA				22.4
NOISE REDUCTION				30.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 30

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		171	0.00171
EXT. WALL 2	53		99	0.00050
EXT. WALL 3	60		0	0.00000
INT. WALL			282	
WINDOW 1	28	.05	0	0.00000
WINDOW 2	31	.05	25	0.01986
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	
ET*S				0.02445
-10LOG (ET*S)				16.1
10LOGA				22.4
NOISE REDUCTION				32.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 32

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		171	0.00171
EXT. WALL 2	53		99	0.00050
EXT. WALL 3	60		0	0.00000
INT. WALL			282	
WINDOW 1	30	.05	0	0.00000
WINDOW 2	33	.05	25	0.01253
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	
ET*S				0.01713
-10LOG(ET*S)				17.7
10LOGA				22.4
NOISE REDUCTION				34.0

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 34

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		171	0.00171
EXT. WALL 2	53		99	0.00050
EXT. WALL 3	60		0	0.00000
INT. WALL			282	
WINDOW 1	32	.05	0	0.00000
WINDOW 2	35	.05	25	0.00791
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	
ET*S				0.01250
-10LOG(ET*S)				19.0
10LOGA				22.4
NOISE REDUCTION				35.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 36

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		99	0.00050
EXT.WALL 3	60		0	0.00000
INT.WALL			282	
WINDOW 1	34	.05	0	0.00000
WINDOW 2	37	.05	25	0.00499
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	
ET*S				0.00958
-10LOG(ET*S)				20.2
10LOGA				22.4
NOISE REDUCTION				36.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY KING + UPGRADES + STC = 38

FLOOR AREA 239

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		171	0.00171
EXT.WALL 2	53		99	0.00050
EXT.WALL 3	60		0	0.00000
INT.WALL			282	
WINDOW 1	36	.05	0	0.00000
WINDOW 2	39	.05	25	0.00315
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	
ET*S				0.00774
-10LOG(ET*S)				21.1
10LOGA				22.4
NOISE REDUCTION				37.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME: HOLIDAY KING + UPGRADES + STC = 40

FLOOR AREA: 239

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		171	0.00171
EXT WALL 2	53		99	0.00050
EXT WALL 3	60		0	0.00000
INT WALL			282	
WINDOW 1	38	.05	0	0.00000
WINDOW 2	41	.05	25	0.00199
WINDOW 3	48	.05	0	0.00000
GGD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	239	0.00239
FLOOR		.6	239	

ET*S				0.00658
-10LOG(ET*S)				21.8
10LOGA				22.4
NOISE REDUCTION				38.2

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 24

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		99	0.00099
EXT. WALL 2	53		0	0.00000
EXT. WALL 3	60		0	0.00000
INT. WALL			456	
WINDOW 1	22	.05	25	0.15774
WINDOW 2	25	.05	0	0.00000
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.16122
-10LOG(ET*S)				7.9
10LOGA				22.6
NOISE REDUCTION				24.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 26

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		99	0.00099
EXT. WALL 2	53		0	0.00000
EXT. WALL 3	60		0	0.00000
INT. WALL			456	
WINDOW 1	24	.05	25	0.09953
WINDOW 2	27	.05	0	0.00000
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.10301
-10LOG(ET*S)				9.9
10LOGA				22.6
NOISE REDUCTION				26.5

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 28

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		99	0.00099
EXT.WALL 2	53		0	0.00000
EXT.WALL 3	60		0	0.00000
INT.WALL			456	
WINDOW 1	26	.05	25	0.06280
WINDOW 2	29	.05	0	0.00000
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.06628
-10LOG(ET*S)				11.8
10LOGA				22.6
NOISE REDUCTION				28.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 30

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		99	0.00099
EXT.WALL 2	53		0	0.00000
EXT.WALL 3	60		0	0.00000
INT.WALL			456	
WINDOW 1	28	.05	25	0.03962
WINDOW 2	31	.05	0	0.00000
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.04310
-10LOG(ET*S)				13.7
10LOGA				22.6
NOISE REDUCTION				30.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 32

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		99	0.00099
EXT.WALL 2	53		0	0.00000
EXT.WALL 3	60		0	0.00000
INT.WALL			456	
WINDOW 1	30	.05	25	0.02500
WINDOW 2	33	.05	0	0.00000
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.02848
-10LOG(ET*S)				15.5
10LOGA				22.6
NOISE REDUCTION				32.1

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 34

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		99	0.00099
EXT.WALL 2	53		0	0.00000
EXT.WALL 3	60		0	0.00000
INT.WALL			456	
WINDOW 1	32	.05	25	0.01577
WINDOW 2	35	.05	0	0.00000
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.01925
-10LOG(ET*S)				17.2
10LOGA				22.6
NOISE REDUCTION				33.8

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 36

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		99	0.00099
EXT.WALL 2	53		0	0.00000
EXT.WALL 3	60		0	0.00000
INT.WALL			456	
WINDOW 1	34	.05	25	0.00995
WINDOW 2	37	.05	0	0.00000
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.01343
-10LOG(ET*S)				18.7
10LOGA				22.6
NOISE REDUCTION				35.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 38

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		99	0.00099
EXT.WALL 2	53		0	0.00000
EXT.WALL 3	60		0	0.00000
INT.WALL			456	
WINDOW 1	36	.05	25	0.00628
WINDOW 2	39	.05	0	0.00000
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.00976
-10LOG(ET*S)				20.1
10LOGA				22.6
NOISE REDUCTION				36.7

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY DBL QUEEN + UPGRADES + STC = 40

FLOOR AREA 249

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		99	0.00099
EXT. WALL 2	53		0	0.00000
EXT. WALL 3	60		0	0.00000
INT. WALL			456	
WINDOW 1	38	.05	25	0.00396
WINDOW 2	41	.05	0	0.00000
WINDOW 3	48	.05	0	0.00000
GLD	38	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	249	0.00249
FLOOR		.6	249	
ET*S				0.00744
-10LOG(ET*S)				21.3
10LOGA				22.6
NOISE REDUCTION				37.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 24

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		132	0.00132
EXT. WALL 2	53		137	0.00069
EXT. WALL 3	60		0	0.00000
INT. WALL			357	
WINDOW 1	22	.05	25	0.15774
WINDOW 2	25	.05	25	0.07906
WINDOW 3	32	.05	0	0.00000
SGD	22	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.24263
-10LOG(ET*S)				6.2
10LOGA				24.3
NOISE REDUCTION				24.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 26

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		132	0.00132
EXT. WALL 2	53		137	0.00069
EXT. WALL 3	60		0	0.00000
INT. WALL			357	
WINDOW 1	24	.05	25	0.09953
WINDOW 2	27	.05	25	0.04988
WINDOW 3	34	.05	0	0.00000
SGD	24	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.15524
-10LOG(ET*S)				8.1
10LOGA				24.3
NOISE REDUCTION				26.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 28

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		132	0.00132
EXT. WALL 2	53		137	0.00069
EXT. WALL 3	60		0	0.00000
INT. WALL			357	
WINDOW 1	26	.05	25	0.06280
WINDOW 2	29	.05	25	0.03147
WINDOW 3	36	.05	0	0.00000
SGD	26	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.10011
-10LOG(ET*S)				10.0
10LOGA				24.3
NOISE REDUCTION				28.3

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 30

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		132	0.00132
EXT. WALL 2	53		137	0.00069
EXT. WALL 3	60		0	0.00000
INT. WALL			357	
WINDOW 1	28	.05	25	0.03962
WINDOW 2	31	.05	25	0.01986
WINDOW 3	38	.05	0	0.00000
SGD	28	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.06532
-10LOG(ET*S)				11.8
10LOGA				24.3
NOISE REDUCTION				30.1

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 32

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		132	0.00132
EXT. WALL 2	53		137	0.00069
EXT. WALL 3	60		0	0.00000
INT. WALL			357	
WINDOW 1	30	.05	25	0.02500
WINDOW 2	33	.05	25	0.01253
WINDOW 3	40	.05	0	0.00000
SGD	30	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.04337
-10LOG(ET*S)				13.6
10LOGA				24.3
NOISE REDUCTION				31.9

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 34

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT. WALL 1	50		132	0.00132
EXT. WALL 2	53		137	0.00069
EXT. WALL 3	60		0	0.00000
INT. WALL			357	
WINDOW 1	32	.05	25	0.01577
WINDOW 2	35	.05	25	0.00791
WINDOW 3	42	.05	0	0.00000
SGD	32	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.02952
-10LOG(ET*S)				15.3
10LOGA				24.3
NOISE REDUCTION				33.6

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 36

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		132	0.00132
EXT.WALL 2	53		137	0.00069
EXT.WALL 3	60		0	0.00000
INT.WALL			357	
WINDOW 1	34	.05	25	0.00995
WINDOW 2	37	.05	25	0.00499
WINDOW 3	44	.05	0	0.00000
SGD	34	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.02078
-10LOG(ET*S)				16.8
10LOGA				24.3
NOISE REDUCTION				35.1

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME HOLIDAY NW KING (101-401) + UPGRADES + STC = 38

FLOOR AREA 383

SURFACES	TL	@	AREA	T*S
EXT.WALL 1	50		132	0.00132
EXT.WALL 2	53		137	0.00069
EXT.WALL 3	60		0	0.00000
INT.WALL			357	
WINDOW 1	36	.05	25	0.00628
WINDOW 2	39	.05	25	0.00315
WINDOW 3	46	.05	0	0.00000
SGD	36	.05	0	0.00000
DOORS	0	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	
ET*S				0.01526
-10LOG(ET*S)				18.2
10LOGA				24.3
NOISE REDUCTION				36.4

WORK SHEET FOR CALCULATING ROOM NOISE REDUCTION VALUE

ROOM NAME: HOLIDAY NW KING (101-401) + UPGRADES + STC = 40

FLOOR AREA: 383

SURFACES	TL	@	AREA	T*S
EXT WALL 1	50		132	0.00132
EXT WALL 2	53		137	0.00069
EXT WALL 3	60		0	0.00000
INT WALL			357	
WINDOW 1	38	.05	25	0.00396
WINDOW 2	41	.05	25	0.00199
WINDOW 3	48	.05	0	0.00000
GGD	38	.05	0	0.00000
DOORS	60	.04	0	0.00000
ROOF	50	.04	383	0.00383
FLOOR		.6	383	

ET*S				0.01178
-10LOG (ET*S)				19.3
10LOGA				24.3
NOISE REDUCTION				37.6

CHRISTOPHER JEAN & ASSOCIATES, INC.
ACOUSTICAL CONSULTING SERVICES

APPENDIX 7

PLUMBING AND ELECTRICAL INSTALLATIONS

CHRISTOPHER JEAN & ASSOCIATES
ACOUSTICAL CONSULTING SERVICES

PLUMBING NOISE REDUCTION REQUIREMENTS FOR
COMPLIANCE WITH THE CALIFORNIA CODE OF REGULATIONS
TITLE 24, PART 2, APPENDIX CHAPTER 35

REQUIRED PLUMBING DESIGN FEATURE IN COMMON WALL AND
FLOOR/CEILING ASSEMBLIES

The plumbing system, by its nature, can degrade the acoustical integrity of a common wall or floor/ceiling assembly. This is primarily due to the fact that the plumbing system, a sound carrier and a sound source, is generally attached to the studs, plates, joists and drywall of a building's walls and floors. In order to alleviate the problem of plumbing system noise, one hundred percent of the plumbing system must be isolated from the building structure (not just at the common assemblies). Special installation requirements are necessary in order to:

- (1) reduce the level of noise from the plumbing system, and
- (2) isolate the total plumbing system from the building structure.

These special isolation procedures may be accomplished by using an approved commercial isolation system. Hard plastic "isolators" are **NOT** acceptable. Examples of approved commercial isolation systems in order of preference are:

- (1) "Acousto-Plumb"™ system by Specialty Products, Inc. (www.ispproducts.com),
- (2) Holdrite Silencer System by Holdrite, Inc. (www.holdrite.com), and

- (3) the felt lined series of isolators, clamps and hangers from Tolco, Inc.

Only when appropriate commercial isolation products are not available for unusual applications or extra large pipe sizes, will it be acceptable to use high density, 1/4" thick, 2" wide, adhesive backed felt wrap and/or 1/2" thick pre-formed, self-adhesive foam rubber pipe insulation such as Armaflex or Rubatex. If the felt wrap or pre-formed pipe insulation is used, great care must be taken not to compress the insulation material when strapping or anchoring the attachment points. Use of expanding foam products as plumbing isolation is **strictly prohibited**.

SUPPLY LINES

- All hot and cold water pipes, fittings and valves shall NEVER come in direct contact with either the building structure framing or drywall. Supply lines are to be isolated using Acousto-Plumb, Holdrite Silencer System, Tolco I.S.P. felt lined isolator products, 1/4" high density felt wrap or 1/2" pre-formed pipe insulation. Acousto-Plumb products and installation details can be found at www.lspproducts.com. Holdrite Silencer System products and installation details can be found at www.holdrite.com. Tolco I.S.P. products can be found at www.cooperindustries.com. Installation details for use of felt wrap or pre-formed pipe insulation are available upon request and approval. If felt wrap or pre-formed pipe insulation are used (and only with prior written approval by the acoustical consultant when appropriate commercial isolation products cannot be located), these installation details must be followed to the letter. No deviations from these details will be allowed.
- All sink and shower faucets, spouts and risers shall be isolated with resilient gaskets that are positioned between the faucet, spout or riser and its mounting surface.
- Water supply stub-outs shall be temporarily isolated from the drywall using the Acousto-Sleeve™ during drywall installation, and then permanently isolated using the Acousto-Scutcheon™ or resilient caulking and a standard plumbing escutcheon.
- Water pressure shall not exceed 65 psi.
- Shower head flow restrictors shall be used to limit water flow to less than three (3) gallons per minute.

- The pipe stubs commonly installed to combat water hammer are not effective. A commercially produced water hammer device consisting of a bellows, similar to that made by Plumbing Products, Inc., is recommended.
- Sections of the plumbing supply system employing PEX (cross linked polyethylene tubing) do not require acoustical isolation except where it transitions to or from conventional copper lines.

WASTE LINES

- The cavity under plastic or fiberglass tubs and showers shall be packed with fiberglass or spray-on insulation materials and/or lightweight concrete pours. The bottoms of such tubs shall be blocked or supported by lightweight concrete to reduce drumming.
- All waste lines above the slab and at the penetrations of any floor/ceiling assemblies and any walls (including non-common walls) shall be cast iron. The use of ABS waste lines is not recommended. If ABS is used, the entire framing cavity surrounding the ABS pipe shall be completely packed with fiberglass, mineral wool or spray-on adhesive cellulose insulation materials. All elbows below toilet and tub waste outlets shall be isolated from all positioning blocks using carpet padding or high-density 1/4" felt material. The entire framing cavity surrounding these elbows shall be completely packed with fiberglass, mineral wool or spray-on adhesive cellulose insulation materials.
- Waste lines of a diameter greater than two and a half inches (2.5") shall never be installed in a wall framed with less than 2" by 6" studs. Walls framed with 2" by 4" studs simply don't allow sufficient clearance to properly insulate and isolate waste lines and/or avoid pipe contact with the drywall.

Failure to COMPLETELY isolate the plumbing system from the building structure will result in a significant transfer of plumbing noise into the building. Therefore, it is important that all of the above measures and techniques are employed. Collectively, these measures and techniques act as parts of a complete system, each designed to perform a particular function of the total effort. Any circumvention of the function of any one component, whether intentional or not, will ultimately lessen the effectiveness of the entire system. **QUALITY CONTROL IS CRITICAL TO PROPER PLUMBING SYSTEM ISOLATION.**

CHRISTOPHER JEAN & ASSOCIATES, INC.

ACOUSTICAL CONSULTING SERVICES

ELECTRICAL SYSTEM INSTALLATION NOTES

The following items shall be incorporated into the building plans:

COMMON WALLS

- Electrical outlets, switches, phone jacks, television antennae boxes and computer outlet boxes installed in opposite sides of a common wall shall be offset a minimum of 24" to comply with the fire code. This offset is not needed for acoustical reasons if insulation is used in the framing cavities and Lowry's #10 putty pads or 3M fire pads are applied around the backs and sides of all outlets, switches, phone jacks, etc.
- All electrical outlets, switches, phone jacks, television antennae boxes and computer outlet boxes installed in common walls shall be backed by and Lowry's #10 putty pads, 3M fire pads or equivalent. Pads shall be stapled to the studs to insure that they remain in place indefinitely (the adhesive backing of the pads deteriorates over time).
- Wiring shall avoid crossing over the air gap of common walls. Where unavoidable, wiring crossovers between common wall studs shall include a loop where the depth is equal to its width.
- Electrical panel boxes, fixture boxes or outlet boxes greater than 25 square inches shall be set in raised boxes that do not touch the opposite side of the common wall.

COMMON FLOOR/CEILINGS

- Recessed lighting shall be set in recessed and airtight boxes made of plywood or drywall.
- All other precautions applicable to common wall installations shall also apply to common floor/ceiling installations.

TRAFFIC IMPACT STUDY

For

***Valencia Springhill Suites
Plus Residence Inn***

Santa Clarita, California

Submitted To:

***Excel Hotel Group
10660 Scripps Ranch Boulevard, Suite 100,
San Diego, California 92131***

Submitted By:

***Darnell & Associates, Inc.
4411 Mercury Street, Suite 207A
San Diego California, 92111***

Revised: December 5, 2016
Revised: November 15, 2016
Revised: November 1, 2016
Original: September 14, 2016

Darnell & Associates, Inc.

TRANSPORTATION PLANNING & TRAFFIC ENGINEERING

December 5, 2016

Neil Patel
Excel Hotel Group
10660 Scripps Ranch Boulevard, Suite 100,
San Diego, California 92123

D&A Ref. No.: 160605

Subject: Traffic Impact Study for the Proposed Valencia Springhill Suites Plus the Residence Inn located in Santa Clarita, California

Dear Mr. Neil Patel:

In accordance with your authorization, Darnell & Associates, Inc. (D&A) has prepared this Traffic Impact Study assessing the impacts associated with the proposed project located on the southside of Wayne Mills Place in the City of Santa Clarita.

The Traffic Impact Study analyzes the traffic impacts related to the project on the surrounding roadways and intersections under the following conditions: Existing and Existing Plus Project Conditions. The report has been revised to respond to City Traffic Engineers comments dated October 18, 2016.

If you have any questions, please feel free to contact the office.

Sincerely,

DARNELL & ASSOCIATES, INC.



Bill E. Darnell, P.E.
Firm Principal
RCE 22338

Date Signed:

12/5/2016

Date Signed:

12/5/2016

BED/jam

160605 - Springhill Suites Residential Inn-Valencia Traffic Study_ Dec 5 2016

TRAFFIC IMPACT STUDY

FOR

***VALENCIA SPRINGHILL SUITES
PLUS RESIDENCE INN***

SANTA CLARITA, CALIFORNIA

Submitted To:

***Excel Hotel Group
10660 Scripps Ranch Boulevard, Suite 100,
San Diego, California 92131***

Submitted By:

***Darnell & Associates, Inc.
4411 Mercury Street, Suite 207A
San Diego California, 92111
(619) 233-9373***

December 5, 2016

TABLE OF CONTENTS

SECTION I – INTRODUCTION 1

 PROJECT DESCRIPTION 1

 SCENARIOS STUDIED 1

 LEVEL OF SERVICE 1

 ANALYSIS METHODOLOGY 4

 REPORT ORGANIZATION 4

SECTION II - EXISTING CONDITIONS 5

 EXISTING ROADWAY CHARACTERISTICS 5

 ROADWAY SEGMENT DAILY TRAFFIC 5

 KEY INTERSECTIONS 6

 INTERSECTION TRAFFIC COUNTS 6

 EXISTING LEVEL OF SERVICE CONDITIONS 9

Roadway Segments 9

Intersections 9

SECTION III - PROJECT RELATED CONDITIONS 10

 TRIP GENERATION 10

 TRIP DISTRIBUTION/TRIP ASSIGNMENT 11

SECTION IV – IMPACTS 14

 EXISTING PLUS PROJECT CONDITIONS 14

Roadway Segments 14

Intersections 14

 2017 OPENING DAY PLUS PROJECT CONDITIONS 14

Roadway Segments 14

Intersections 14

SECTION V - SUMMARY OF FINDINGS AND CONCLUSIONS 20

LIST OF FIGURES

Figure 1 - Vicinity Map 2
Figure 2 - Site Plan 3
Figure 3 - Existing Conditions 7
Figure 4 - Existing Traffic Volumes 8
Figure 5 - Trip Distribution..... 12
Figure 6 - Project Related Traffic Volumes..... 13
Figure 7 - Existing Plus Project Traffic Volumes 15
Figure 8 – 2018 Opening Day Traffic Volumes 17
Figure 9 - Existing Plus Project Plus 2018 Opening Day Traffic Volumes..... 18

LIST OF TABLES

Table 1 - Level of Service Criteria at Intersections 4
Table 2 - Existing Roadway Segment Level of Service Summary 9
Table 3 - Existing Intersection Level of Service Summary 9
Table 4 - Trip Generation Rates and Calculations Summary 10
Table 5 - Existing Plus Project Roadway Segment Level of Service Summary 16
Table 6 - Existing Plus Project Intersection Level of Service Summary 16
Table 7 –Existing Plus Project Plus 2018 Opening Day Roadway Segment Level of Service Summary.. 19
Table 8 - Existing Plus Project Plus 2018 Opening Day Intersection Level of Service Summary 19

APPENDICES

APPENDIX A

- 24-Hour Segment Counts
- AM/PM Peak Hour Turn Counts

APPENDIX B

- Existing Conditions Analysis Worksheets

APPENDIX C

- Existing + Project Conditions Analysis Worksheets

APPENDIX D

- 2018 Opening Day Conditions Analysis Worksheets

APPENDIX E

- 2018 Opening Day Plus Project Conditions Analysis Worksheets

SECTION I – INTRODUCTION

This traffic study evaluates the traffic conditions associated with the proposed Valencia Springhill plus Residence Inn project (herein referred to as “the project”) located at 27413 Wayne Mills Place in the City of Santa Clarita, CA. Figure 1 illustrates the location of the project site in the region.

PROJECT DESCRIPTION

The project site is generally located on the south side of Wayne Mills Place, east of I-5, and west of Tourney Road. The existing site currently is occupied by a 120-Room Best Western Hotel. The project will construct a 182-Room Springhill Suites/Residence Inn and a 108-room Holiday Inn Express on the existing Best Western Site. Access to the project will be through an existing driveway located on Wayne Mills Place. Figure 2 illustrates the project site plan.

SCENARIOS STUDIED

The following list contains the scenarios analyzed for the project:

Existing Conditions: This scenario refers to the conditions at the time peak hour turning movement volume counts were obtained in October 2016 and account for the existing lane configurations at the study intersections and roadway segments.

Existing Plus Project Conditions: This scenario includes the project traffic, which is added to the existing traffic volumes.

2018 Opening Day Conditions: This scenario includes the project traffic, with 3% per year (6 % total) ambient growth added to the existing traffic volumes.

LEVEL OF SERVICE

Level of Service (LOS) is a professional industry standard by which the operating conditions of a given roadway segment or intersection are measured. Level of Service is defined on a scale of A to F; where LOS “A” represents the best operating conditions and LOS “F” represents the worst operating conditions. LOS “A” facilities are characterized as having free flowing traffic conditions with no restrictions on maneuvering or operating speeds; traffic volumes are low and travel speeds are high. LOS “F” facilities are characterized as having forced flow with many stoppages and low operating speeds.

For all signalized study area intersections, the Highway Capacity Manual (HCM) methodology is utilized to estimate the LOS. The HCM method estimates the LOS based on intersection delay.


For all unsignalized area intersections, the Highway Capacity Manual (HCM) methodology is utilized to estimate the LOS. The HCM method estimates the LOS based on intersection delay.

LOS along the roadway segments in the study area is determined utilizing the City’s volume to capacity at urban arterial highways.

Table 1 shows the criteria used for intersections. Table 2 summarizes the criteria used along arterial roadways. In the City of Santa Clarita, LOS “D” is considered the acceptable threshold for intersections and roadway segments.



SCALE: NONE



PROJECT
SITE



Darnell & ASSOCIATES, INC.
2870 MERCURY STREET, SUITE 207A
SAN DIEGO, CA 92111
(619) 233-9373

DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB

FIGURE 1
VICINITY MAP

Table 1 - Level of Service Criteria at Intersections		
LOS	Intersections	
	Average Control Delay (Seconds/Vehicle)	Unsignalized Delay (Seconds/Vehicle)
A	≤ 10	Less than or Equal to 10.0
B	> 10 – 20	10.0 to 15.0
C	>20 to 35	15.0 to 25.0
D	>35 – 55	25.0 to 35.0
E	>55 – 80	35.0 to 50.0
F	> 80	> 50.0

The delay ranges shown are based on the 2010 Highway Capacity Manual (HCM)
LOS = Level of Service;

Table 2 - Level of Service Criteria Along Arterial Roadways					
LOS	8-Lane Divided	6-Lane Divided	4-Lane Divided	4-Lane Undivided	2-Lane Undivided
A	48,000	36,000	24,000	16,000	5,000
B	54,000	40,400	27,000	18,000	7,500
C	60,000	45,000	30,000	20,000	10,000
D	66,000	49,500	33,000	22,000	12,500
E	72,000	54,000	36,000	24,000	15,000
F	This condition represents system breakdown and does not have a specific relationship to service volumes.				

The values shown in the table are referenced from the City of Santa Clarita General Plan Circulation Element

ANALYSIS METHODOLOGY

The intersection analysis evaluated the operations of the study area intersections during a typical weekday for the AM and PM peak periods. The AM peak is defined as the time period between 7:00 and 9:00 AM. The PM peak is defined as the time period between 4:00 and 6:00 PM. The signalized intersections were analyzed using the Intersection Capacity Utilization (ICU) procedures with lane capacity of 1,750 vehicles per lane. Synchro 8 was used as the software program to evaluate the operations at unsignalized intersections.

REPORT ORGANIZATION

Following this section, Section II evaluates the existing roadway characteristics and traffic conditions surrounding the project area. Section III examines the project trip generation and distribution assumptions. Section IV analyzes the traffic for existing plus project conditions. Section V provides recommended mitigation measures. Section VII summarizes the report's findings and conclusions.

SECTION II - EXISTING CONDITIONS

This section of the traffic study is intended to assess the existing conditions of the roadways and intersections within the vicinity of the project to determine travel flow and/or delay difficulties, if any, that exist prior to adding the traffic generated by the proposed project. The existing conditions analysis establishes a base condition which is used to assess the other scenarios discussed in this report.

Darnell & Associates, Inc. (D&A) conducted a field review of the area surrounding the project in June 2016. The existing roadway geometrics are illustrated in Figure 3.

EXISTING ROADWAY CHARACTERISTICS

The key segments analyzed in the study area are identified below:

Magic Mountain Parkway: Magic Mountain Parkway is a six-lane divided roadway in the study area with painted medians and is classified as a major highway. The roadway generally runs in the east-west direction. Parking is restricted on both sides of the roadway and the posted speed limit is 50 miles per hour (mph) based on the City's Circulation Element, an improvement to restripe the roadway from 6-lanes to 8-lanes.

Tourney Road: Tourney Road is a three-lane roadway with a center two-way left-turning lane in the study area and is classified as a secondary highway. The roadway generally runs in the north-south direction. Bicycle lanes and parking are provided on both sides of the roadway. There are no posted speed limit signs in the immediate vicinity of the project.

Wayne Mills Place: Wayne Mills Place is a two-lane roadway with a center two-way left-turning lane. At Tourney Road it provides one-lane westbound, a painted median, a shared eastbound left and through lane and a exclusive right turn lane.

ROADWAY SEGMENT DAILY TRAFFIC

Daily traffic volume data were obtained along the study area roadway segments on Thursday, July 28, 2016 and October 25, 2016. The July 28, 2016 counts were then adjusted using the October 25, 2016 peak hour counts. Analysis of the July 28, 2016 traffic counts concluded that traffic on Magic Mountain Parkway are impacted in the summer months by traffic generated by Magic Mountain. Review of the July 28, 2016 and October 25, 2016 traffic counts allowed the conclusion that the July daily traffic volumes can be adjusted to represent the non-summer traffic conditions. Figure 4 presents the adjusted counts with 10.5 percent reduction on Magic Mountain Parkway west of Interstate 5 and a 3.7 percent reduction west of Tourney Road. A copy of the October 25, 2016 counts are presented in Appendix A. The roadway segments analyzed are:

- Magic Mountain Parkway west of Old Road;
- Magic Mountain Parkway west of Tourney Road
- Magic Mountain Parkway east of Tourney Road;
- Tourney Road between Magic Mountain Parkway and Wayne Mills Place;
- Tourney Road south of Wayne Mills Place; and
- Wayne Mills Place west of Tourney Road.

The Study Area limits were established based on City of Santa Clarita Guidelines to address roadways and intersections that the project would add 50 or more peak hour direction trips.


KEY INTERSECTIONS

Figure 3 provides intersection configurations and traffic control for the key intersections. The key intersections analyzed in the study area are identified below:

- I-5 SB Ramps/Magic Mountain Parkway (signal);
- I-5 NB Ramps/Magic Mountain Parkway (signal);
- Tourney Road/Magic Mountain Parkway (signal);
- Tourney Road/Wayne Mills Place (two-way stopped control)


INTERSECTION TRAFFIC COUNTS

Peak-hour traffic volume data were obtained at the study area intersections on October 25, 2016. Figure 4 presents the existing conditions traffic volumes used in this analysis. A copy of the count worksheet is included in Appendix A.



LEGEND

- - DIRECTION OF TRAVEL
- ◻ - SIGNAL
- - STOP SIGN
- TWLT - TWO WAY LEFT TURN




Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373
 DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB

FIGURE 3
 EXISTING ROADWAY GEOMETRY



SCALE: NONE



LEGEND

- - DIRECTION OF TRAVEL
- XX/YY - AM/PM PEAK HOUR TRAFFIC VOLUMES
- ◻ - SIGNAL
- - STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB

FIGURE 4
EXISTING TRAFFIC VOLUMES

EXISTING LEVEL OF SERVICE CONDITIONS

Roadway Segments

Table 3 summarizes the LOS along the roadway segments in the study area. As shown in the table, all roadway segments operate at LOS A except for the Magic Mountain Parkway segment between I-5 northbound on/off ramp and Tourney Road, which operates at LOS "B".

Roadway Segment	Classification	Existing Number of Lanes	LOS "E" Capacity	ADT	v/c	LOS
Magic Mountain Pkwy						
The Old Rd to I-5 SB Ramps	Major Arterial	6-Lane Divided	54,000	31,096	0.576	A
I-5 NB Ramps to Tourney Road				31,378	0.584	B
Tourney Road to Wayne Mills Place				31,542	0.580	A
Tourney Rd						
Magic Mountain Pkwy to Wayne Mills Place	Secondary Highway	4-Lane Undivided	24,000	9,892	0.412	A
South of Wayne Mills Place				5,801	0.242	A
Volume on this segment was estimated. Capacity is based on the upper limits of LOS E per the City of Santa Clarita General Plan Circulation Element; ADT= Average Daily Traffic; LOS= Level of Service.						

Intersections

Table 4 summarizes the LOS at the intersections in the study area. As shown in the table, all signalized intersections operate at LOS "B" or better during the AM and PM peak periods. The unsignalized intersection of Tourney Road/Wayne Mills Place operates at LOS "B" or better during the AM and PM peak periods.

#	Intersection	Traffic Control	Peak Hour	Existing Conditions	
				Delay (a)	LOS (b)
1	I-5 SB Ramps & Magic Mountain Pkwy	Signal	AM	13.1	B
			PM	14.8	B
2	I-5 NB Ramps & Magic Mountain Pkwy	Signal	AM	18.9	B
			PM	19.3	B
3	Tourney Rd & Magic Mountain Pkwy	Signal	AM	19.0	B
			PM	19.6	B
4	Tourney Rd & Wayne Mills Pl	TWSC	AM	4.4	A
			PM	4.7	B
5	Project Dwy & Wayne Mills Pl	OWSC	AM	DNE	
			PM		
DNE: Does not exist					
(a) HCM's are reported at the signalized intersections. Delays are reported as the worst movement at unsignalized intersections.					
(b) LOS calculations are based on the methodology outlined in the 2000 Highway Capacity Manual (HCM) and performed using Synchro 8, TWSC = Two Way Stop Control, OWSC = One Way Stop Control.					

A copy of the analysis worksheets for conditions can be found in Appendix B.

SECTION III - PROJECT RELATED CONDITIONS

TRIP GENERATION

Trip generation rates published by the *Institute of Transportation Engineers (ITE) Trip Generation Manual, 9th Edition* were applied to the existing and proposed use in order to determine the traffic generation characteristics of the site. The existing site contains a 120 Room Best Western Hotel. The project consists of a 182 Room Springhill Suites/Residence Inn and a 108 Room Holiday Inn Express, which results in a net increase of 170 hotel rooms. Upon reviewing the various land uses contained in the *ITE Trip Generation Manual*, land use code of 312 (Business Hotel) was the most appropriate and applied to the project.

Table 4 summarizes the weekday trip generation. As shown in the table, the project is forecasted to generate a net increase of 1,237 daily trips with 99 AM peak-hour trips and 105 PM peak-hour trips.

Table 4 - Trip Generation Rates and Calculations Summary								
Trip Generation Rates								
Land Use	Daily	AM Peak Hour			PM Peak Hour			
		Rate	% In	% Out	Rate	% In	% Out	
Business Hotel	7.27 trips/rooms	0.58/Room	59%	41%	0.62/Room	60%	40%	
Trip Generation								
Land Use	Total No. of Units	Daily	AM Peak Hour			PM Peak Hour		
			Total	In	Out	Total	In	Out
Existing Uses								
Best Western	120 rooms	873	70	42	28	75	45	30
Proposed Uses								
Springhill Suites/Residence Inn	182 rooms	1,324	106	63	43	113	68	45
Holiday Inn Express	108 rooms	786	63	38	25	67	41	26
Subtotal (Proposed – Existing)		2,110	169	101	68	180	109	71
Net New Trips		1,237	99	59	40	105	64	41
Trip Generation Rates are based on rates published by the <i>Institute of Transportation Engineers (ITE) Trip Generation Manual, 9th Edition</i> .								


TRIP DISTRIBUTION/TRIP ASSIGNMENT

Based on existing travel patterns in the study area and on logical connections to regional facilities, the following list shows the assumed project trip distribution for the proposed project:

- 20 percent to/from the north via I-5;
- 40 percent to/from the south;
 - 30 percent via I-5;
 - 10 percent via Tourney Road;
- 20 percent to/from the east via Magic Mountain Parkway; and
- 20 percent to/from the west via Magic Mountain Parkway.

Figure 5 displays the assumed project trip distribution through the study intersections. Based on the project trip generation and distribution, the peak-hour trips were assigned to the intersections in the study area. Figure 6 illustrates the weekday project trip assignment.

The impacts associated with the addition of project traffic are discussed in the following section, Section IV.




PROJECT SITE



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB


FIGURE 5
PROJECT TRIP DISTRIBUTION



PROJECT SITE

LEGEND

- > — DIRECTION OF TRAVEL
- XX/YY — AM/PM PEAK HOUR TRAFFIC VOLUMES
- ⊠ — SIGNAL
- — STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373
 DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB

FIGURE 6
 PROJECT TRAFFIC

SECTION IV – IMPACTS

This section describes the Level of Service analyses for the study area intersections and roadway segments with the addition of project traffic to Existing Conditions.

EXISTING PLUS PROJECT CONDITIONS

The daily and peak hour turn volumes for existing plus project conditions are illustrated in Figure 7.

Roadway Segments

The roadway segments were then analyzed with the traffic generated from the proposed project added to existing traffic volumes. Table 5 displays the Level of Service Analysis results for the roadway segments under the Existing Plus Project scenario. As shown in the table, all roadway segments are expected to operate at LOS “C” or better with the addition of the project.

Intersections

The intersections were then analyzed with the traffic generated from the proposed project added to existing traffic volumes. Table 6 displays the Level of Service Analysis results for the study intersections under the Existing Plus Project scenario. As shown in the table, all signalized intersections, are expected to operate at LOS “C” or better with the addition of the project traffic. The unsignalized intersections and the Project Driveway on Wayne Mills Place will operate at LOS “A” and the Tourney Road/Wayne Milles Place intersection will operate at LOS “B or better”. The increase in delay does not exceed the significance thresholds.

2018 OPENING DAY PLUS PROJECT CONDITIONS

Opening Day 2018 traffic conditions are estimated by adding 3% per year (6% total) ambient growth to existing traffic volumes plus project traffic. Figure 8 presents the 2018 Opening Day volumes and Figure 9 presents the 2018 Opening Day plus project conditions.

Roadway Segments


The roadway segments were analyzed with the traffic generated from the proposed project added to existing traffic volumes plus 3% ambient growth. Table 7 displays the Level of Service Analysis results for the roadway segments under the Existing Plus Project scenario. As shown in the table, all roadway segments are expected to operate at LOS “B” or better with the addition of the project.

Intersections

The intersections were analyzed with the traffic generated from the proposed project added to existing traffic volumes plus the addition of 3% ambient growth. Table 8 displays the Level of Service Analysis results for the study intersections under the Existing Plus Project scenario. As shown in Table 8, all intersections, including the project driveway, are expected to operate at LOS “C” or better with the addition of the project traffic. Therefore no mitigation is required.

MITIGATION

The project does not create any direct impacts that require mitigation.



PROJECT SITE



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB

FIGURE 7
EXISTING PLUS PROJECT
TRAFFIC VOLUMES

Table 5 - Existing Plus Project Roadway Segment Level of Service Summary

Roadway Segment	Classification	Existing Number of Lanes	LOS "E" Capacity	Existing		Proj. ADT	Existing Plus Project		Δ in v/c
				ADT	v/c		LOS	LOS	
Magic Mountain Pkwy	Major Arterial	6-Lane Divided	54,000	31,096	0.576	247	31,347	0.580	0.004
The Old Rd to I-5 SB Ramps				31,378	0.584	866	32,244	0.597	0.016
I-5 NB Ramps to Tourney Road				31,542	0.580	247	31,789	0.592	0.002
Tourney Road to Wayne Mills Place									
Tourney Road	Secondary Highway	4-Lane Undivided	24,000	9,892	0.412	1,113	11,005	0.459	0.047
Magic Mountain Pkwy to Wayne Mills Place				5,801	0.242	123	5,924	0.247	0.005
South of Wayne Mills Place									
Wayne Mills Place	Local	2-Lane	5,000	1,434	0.286	1,236	2,671	0.534	0.248
West of Tourney Road									

Volume on this segment was estimated. Capacity is based on the upper limits of LOS E per the City of Santa Clarita General Plan Circulation Element; ADT= Average Daily Traffic; LOS= Level of Service., Proj. ADT = Project Average Daily Traffic.

Table 6 - Existing Plus Project Intersection Level of Service Summary

#	Intersection	Traffic Control	Peak Hour	Existing Conditions		Existing Plus Project		Sign.(c)
				Delay (a)	LOS (b)	Delay (a)	LOS (b)	
1	I-5 SB Ramps & Magic Mountain Pkwy	Signal	AM	13.1	B	13.3	B	No
			PM	14.8	B	15.2	B	No
2	I-5 NB Ramps & Magic Mountain Pkwy	Signal	AM	18.9	B	19.2	B	No
			PM	19.3	B	19.5	B	No
3	Tourney Road & Magic Mountain Pkwy	Signal	AM	19.0	B	20.1	C	No
			PM	19.6	B	20.9	C	No
4	Tourney Road & Wayne Mills Place	TWSC	AM	4.4	A	5.6	A	No
			PM	4.7	B	5.9	B	No
5	Project Driveway & Wayne Mills Place	OWSC	DNE		6.0	B	6.0	No
					5.8	B	5.8	No

Notes:

DNE = Does not exist, TWSC = Two Way Stop Control, OWSC = One Way Stop Control.

a. HCM is reported at signalized intersections. Sign. = Significance.


b. LOS calculations are based on the methodology outlined in the 2010 Highway Capacity Manual (HCM).

c. Delays at unsignalized intersections are reported based on intersection delay using Synchro 8 - Intersection Capacity Software

Project Impacts are considered significant if the Intersection LOS degrades from LOS "D" of better to LOS "E" of LOS "F"




SCALE: NONE



LEGEND


- ▶— DIRECTION OF TRAVEL
- XX/YY — AM/PM PEAK HOUR TRAFFIC VOLUMES
- ◻ — SIGNAL
- — STOP SIGN

PROJECT SITE



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373
 DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB

FIGURE 8
 2018 OPENING DAY
 TRAFFIC VOLUMES



PROJECT SITE

LEGEND

- - DIRECTION OF TRAVEL
- XX/YY - AM/PM PEAK HOUR TRAFFIC VOLUMES
- ⊞ - SIGNAL
- - STOP SIGN



Darnell & ASSOCIATES, INC.
 2870 MERCURY STREET, SUITE 207A
 SAN DIEGO, CA 92111
 (619) 233-9373

DWG: 160605-DD DATE: DECEMBER 5, 2016 BY: JAB

FIGURE 9
 2018 OPENING DAY PLUS
 PROJECT TRAFFIC VOLUMES

Roadway Segment	Classification	Existing Number of Lanes	LOS ‘E’ Capacity	Existing Plus Ambient		Existing Plus Project Plus Ambient Growth		Sign. (a)			
				ADT	v/c	LOS	ADT		v/c	LOS	Δ v/c
Magic Mountain Pkwy											
The Old Rd to I-5 SB Ramps	Major Arterial	6-Lane Divided	54,000	32,961	0.610	B	33,208	0.615	B	0.005	No
I-5 NB Ramps to Tourney Road				33,260	0.616	B	34,126	0.632	B	0.018	No
Tourney Road to Wayne Mills Place				31,542	0.584	B	32,488	0.602	B	0.018	No
Tourney Road											
Magic Mountain Pkwy to Wayne Mills Place	Secondary Highway	4-Lane Undivided	24,000	10,485	0.437	A	11,598	0.483	A	0.046	No
South of Wayne Mills Place				6,149	0.256	A	6,272	0.261	A	0.005	No
Wayne Mills Place											
West of Tourney Road	Local	2-Lane	5,000	1,565	0.313	A	2,802	0.560	A	0.247	NO

Volume on this segment was estimated. Capacity is based on the upper limits of LOS E per the City of Santa Clarita General Plan Circulation Element; ADT= Average Daily Traffic; LOS= Level of Service. Sign. = Significance. (a) Project Impacts are considered significant if the Intersection LOS degrades from LOS “D” of better to LOS “E” of LOS “F” and increases the v/c 0.2 or greater.

#	Intersection	Traffic Control	Peak Hour	Existing Plus 2018 Ambient Growth Conditions		Existing Plus Project Plus 2018 Ambient Growth Conditions		Δ in Delay	Significant (c)
				Delay (a)	LOS (b)	Delay (a)	LOS (b)		
1	I-5 SB Ramps & Magic Mountain Pkwy	Signal	AM	13.7	B	14.1	B	0.4	No
			PM	15.5	B	15.9	B	0.4	No
2	I-5 NB Ramps & Magic Mountain Pkwy	Signal	AM	19.5	B	19.7	B	0.2	No
			PM	19.6	B	19.8	B	0.2	No
3	Tourney Road & Magic Mountain Pkwy	Signal	AM	19.9	B	20.7	C	0.8	No
			PM	21.1	C	22.4	C	1.3	No
4	Tourney Road & Wayne Mills Place	TWSC	AM	4.7	A	6.1	A	1.4	No
			PM	5.2	B	6.6	B	1.4	No
5	Project Driveway & Wayne Mills Place	OWSC	AM	DNE		5.9	A	5.9	No
			PM	DNE		5.7	A	5.7	No

Notes:
DNE = Does not exist, TWSC = Two Way Stop Control, OWSC = One Way Stop Control.
(a) HCM is reported at signalized intersections.
(b) LOS calculations are based on the methodology outlined in the 2000 Highway Capacity Manual (HCM). Delays at unsignalized intersections are reported based on intersection delay using Synchro 8 – Intersection Capacity Software
(c) . Project Impacts are considered significant if the Intersection LOS degrades from LOS “D” of better to LOS “E” of LOS “F”

SECTION V - SUMMARY OF FINDINGS AND CONCLUSIONS

The following list provides a summary of the key findings for the project:

- The project is forecasted to generate a net increase of approximately 1,237 daily trips with 99 AM peak-hour trips and 105 PM peak-hour trips.
- All study area roadway segments are expected to operate at an acceptable LOS "C" or better for Existing, 2018 Opening Day and 2018 Opening Day Plus Project Conditions.
- The addition of project traffic to the 2018 Opening Day Conditions does not result in a significant impact on the roadway segments analyzed. Therefore no mitigation is required.
- All study area intersections, including the project driveway, are expected to operate at an acceptable LOS "C" or better during the AM and PM peak hours with the addition of project traffic to 2018 Opening Day Conditions.
- The addition of project traffic to the 2018 Opening Day Conditions does not result in a significant impact on the intersections analyzed. Therefore no mitigation is required.

APPENDIX A

- 24-Hour Segment Counts
- AM/PM Peak Hour Turn Counts
- City of Santa Clarita Traffic Guidelines

➤ 24-Hour Segment Counts

Prepared by NDS/ATD

VOLUME

Wayne Mills PI E/O Driveway #3

Day: Monday
Date: 7/4/2016

City: Santa Clarita
Project #: CA16_5446_001

DAILY TOTALS					NB	SB	EB	WB	Total		
					0	0	734	700	1,434		
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00			7	15	22	12:00			13	6	19
00:15			9	10	19	12:15			11	11	22
00:30			5	5	10	12:30			11	9	20
00:45			3	24	3	12:45			12	47	36
01:00			10	3	13	13:00			13	5	18
01:15			2	5	7	13:15			8	8	16
01:30			5	5	10	13:30			6	1	7
01:45			4	21	1	13:45			8	35	5
02:00			5	2	7	14:00			12	10	22
02:15			0	1	1	14:15			8	3	11
02:30			1	1	2	14:30			7	5	12
02:45			0	6	1	14:45			4	31	13
03:00			1	2	3	15:00			6	4	10
03:15			2	0	2	15:15			4	3	7
03:30			1	1	2	15:30			6	13	19
03:45			0	4	0	15:45			8	24	6
04:00			4	0	4	16:00			9	8	17
04:15			0	0	0	16:15			10	10	20
04:30			1	1	2	16:30			7	4	11
04:45			0	5	5	16:45			9	35	6
05:00			2	2	4	17:00			5	6	11
05:15			2	5	7	17:15			2	10	12
05:30			3	2	5	17:30			6	9	15
05:45			3	10	4	17:45			4	17	4
06:00			4	3	7	18:00			5	2	7
06:15			6	4	10	18:15			7	9	16
06:30			4	6	10	18:30			10	14	24
06:45			3	17	7	18:45			2	24	9
07:00			7	2	9	19:00			6	8	14
07:15			2	12	14	19:15			10	3	13
07:30			7	10	17	19:30			4	4	8
07:45			8	24	17	19:45			7	27	7
08:00			9	3	12	20:00			3	8	11
08:15			4	9	13	20:15			7	13	20
08:30			11	8	19	20:30			8	10	18
08:45			9	33	8	20:45			2	20	9
09:00			19	16	35	21:00			11	15	26
09:15			17	8	25	21:15			8	7	15
09:30			21	15	36	21:30			3	9	12
09:45			23	80	17	21:45			7	29	11
10:00			27	10	37	22:00			7	13	20
10:15			26	10	36	22:15			6	17	23
10:30			22	13	35	22:30			4	14	18
10:45			21	96	11	22:45			9	26	20
11:00			20	12	32	23:00			8	9	17
11:15			15	7	22	23:15			7	9	16
11:30			23	5	28	23:30			10	8	18
11:45			11	69	8	23:45			5	30	8
TOTALS			389	295	684	TOTALS			345	405	750
SPLIT %			56.9%	43.1%	47.7%	SPLIT %			46.0%	54.0%	52.3%

DAILY TOTALS					NB	SB	EB	WB	Total
					0	0	734	700	1,434
AM Peak Hour	09:45	09:00	09:30	PM Peak Hour	12:00	22:00	22:00		
AM Pk Volume	98	56	149	PM Pk Volume	47	64	90		
Pk Hr Factor	0.907	0.824	0.931	Pk Hr Factor	0.904	0.800	0.776		
7 - 9 Volume	57	69	126	4 - 6 Volume	52	57	109		
7 - 9 Peak Hour	08:00	07:15	07:45	4 - 6 Peak Hour	16:00	16:45	16:00		
7 - 9 Pk Volume	33	42	69	4 - 6 Pk Volume	35	31	63		
Pk Hr Factor	0.750	0.618	0.690	Pk Hr Factor	0.875	0.775	0.788		

Prepared by NDS/ATD

VOLUME

Tourney Rd Bet. Magic Mountain Pkwy & Wayne Mills Pl

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_001

DAILY TOTALS					NB	SB	EB	WB	Total
					5,001	5,229	0	0	10,230

AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00	13	7			20	12:00	137	76			213
00:15	9	5			14	12:15	132	90			222
00:30	3	5			8	12:30	104	96			200
00:45	6	31	5	22	11	12:45	116	489	115	377	231
01:00	4	4			8	13:00	78	135			213
01:15	5	5			10	13:15	85	109			194
01:30	4	3			7	13:30	84	99			183
01:45	1	14	1	13	2	13:45	91	338	116	459	207
02:00	6	3			9	14:00	78	76			154
02:15	2	11			13	14:15	78	88			166
02:30	2	5			7	14:30	78	102			180
02:45	2	12	2	21	4	14:45	91	325	100	366	191
03:00	5	1			6	15:00	91	85			176
03:15	3	0			3	15:15	81	87			168
03:30	8	4			12	15:30	101	69			170
03:45	3	19	4	9	7	15:45	83	356	71	312	154
04:00	0	3			3	16:00	105	85			190
04:15	3	6			9	16:15	101	78			179
04:30	8	6			14	16:30	137	60			197
04:45	7	18	11	26	18	16:45	136	479	73	296	209
05:00	11	13			24	17:00	182	66			248
05:15	25	23			48	17:15	95	69			164
05:30	23	15			38	17:30	127	55			182
05:45	24	83	17	68	41	17:45	94	498	46	236	140
06:00	29	24			53	18:00	95	51			146
06:15	21	40			61	18:15	57	60			117
06:30	43	34			77	18:30	63	48			111
06:45	31	124	77	175	108	18:45	61	276	38	197	99
07:00	33	55			88	19:00	40	34			74
07:15	39	97			136	19:15	41	33			74
07:30	38	118			156	19:30	45	34			79
07:45	40	150	155	425	195	19:45	37	163	30	131	67
08:00	38	153			191	20:00	41	31			72
08:15	55	177			232	20:15	36	35			71
08:30	41	138			179	20:30	39	29			68
08:45	48	182	145	613	193	20:45	21	137	24	119	45
09:00	70	116			186	21:00	50	33			83
09:15	82	88			170	21:15	20	16			36
09:30	85	99			184	21:30	25	30			55
09:45	75	312	102	405	177	21:45	27	122	30	109	57
10:00	86	120			206	22:00	22	18			40
10:15	82	99			181	22:15	16	23			39
10:30	102	72			174	22:30	14	11			25
10:45	72	342	99	390	171	22:45	9	61	10	62	19
11:00	101	84			185	23:00	15	13			28
11:15	86	91			177	23:15	13	6			19
11:30	125	91			216	23:30	11	9			20
11:45	110	422	89	355	199	23:45	9	48	15	43	24
TOTALS	1709	2522			4231	TOTALS	3292	2707			5999
SPLIT %	40.4%	59.6%			41.4%	SPLIT %	54.9%	45.1%			58.6%

DAILY TOTALS					NB	SB	EB	WB	Total
					5,001	5,229	0	0	10,230

AM Peak Hour	11:30	07:45			11:30	PM Peak Hour	16:15	13:00			12:00
AM Pk Volume	504	623			850	PM Pk Volume	556	459			866
Pk Hr Factor	0.920	0.880			0.957	Pk Hr Factor	0.764	0.850			0.866
7 - 9 Volume	332	1038			1370	4 - 6 Volume	977	532			0.937
7 - 9 Peak Hour	08:00	07:45			07:45	4 - 6 Peak Hour	16:15	16:00			1509
7 - 9 Pk Volume	182	623			797	4 - 6 Pk Volume	556	296			16:15
Pk Hr Factor	0.827	0.880	0.000	0.000	0.859	Pk Hr Factor	0.764	0.871	0.000	0.000	833
											0.840

Prepared by NDS/ATD

VOLUME

Tourney Rd S/O Wayne Mills PI

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_002

DAILY TOTALS											NB	SB	EB	WB	Total
											2,940	3,059	0	0	5,999
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL				
00:00	12	6			18	12:00	42	53			95				
00:15	4	8			12	12:15	47	53			100				
00:30	10	5			15	12:30	42	56			98				
00:45	6	32	3	22	9	12:45	33	164	49	211	82	375			
01:00	3	6			9	13:00	49	48			97				
01:15	3	3			6	13:15	40	65			105				
01:30	4	6			10	13:30	50	58			108				
01:45	5	15	4	19	9	13:45	48	187	37	208	85	395			
02:00	7	8			15	14:00	44	42			86				
02:15	8	4			12	14:15	30	43			73				
02:30	5	2			7	14:30	50	45			95				
02:45	5	25	3	17	8	14:45	46	170	40	170	86	340			
03:00	5	2			7	15:00	43	53			96				
03:15	1	6			7	15:15	45	51			96				
03:30	5	8			13	15:30	41	34			75				
03:45	5	16	3	19	8	15:45	45	174	47	185	92	359			
04:00	8	7			15	16:00	41	39			80				
04:15	9	13			22	16:15	45	41			86				
04:30	13	4			17	16:30	50	40			90				
04:45	16	46	8	32	24	16:45	49	185	54	174	103	359			
05:00	14	10			24	17:00	54	43			97				
05:15	21	13			34	17:15	50	61			111				
05:30	26	9			35	17:30	65	55			120				
05:45	19	80	25	57	44	17:45	51	220	72	231	123	451			
06:00	27	21			48	18:00	67	41			108				
06:15	29	26			55	18:15	51	44			95				
06:30	29	26			55	18:30	50	45			95				
06:45	25	110	39	112	64	18:45	50	218	37	167	87	385			
07:00	31	25			56	19:00	45	53			98				
07:15	30	45			75	19:15	43	45			88				
07:30	42	44			86	19:30	33	52			85				
07:45	32	135	25	139	57	19:45	36	157	54	204	90	361			
08:00	35	36			71	20:00	41	48			89				
08:15	28	24			52	20:15	37	49			86				
08:30	32	31			63	20:30	48	46			94				
08:45	35	130	23	114	58	20:45	36	162	57	200	93	362			
09:00	30	36			66	21:00	40	38			78				
09:15	38	33			71	21:15	42	36			78				
09:30	35	37			72	21:30	30	29			59				
09:45	45	148	34	140	79	21:45	26	138	27	130	53	268			
10:00	22	48			70	22:00	21	27			48				
10:15	34	34			68	22:15	22	21			43				
10:30	40	40			80	22:30	16	12			28				
10:45	42	138	40	162	82	22:45	15	74	23	83	38	157			
11:00	43	39			82	23:00	17	26			43				
11:15	35	38			73	23:15	17	11			28				
11:30	34	58			92	23:30	14	22			36				
11:45	48	160	57	192	105	23:45	8	56	12	71	20	127			
TOTALS	1035	1025			2060	TOTALS	1905	2034				3939			
SPLIT %	50.2%	49.8%			34.3%	SPLIT %	48.4%	51.6%				65.7%			

DAILY TOTALS											NB	SB	EB	WB	Total
											2,940	3,059	0	0	5,999
AM Peak Hour	11:45	11:30			11:45	PM Peak Hour	17:30	17:00			17:15				
AM Pk Volume	179	221			398	PM Pk Volume	234	231			462				
Pk Hr Factor	0.932	0.953			0.948	Pk Hr Factor	0.873	0.802			0.939				
7 - 9 Volume	265	253	0	0	518	4 - 6 Volume	405	405	0	0	810				
7 - 9 Peak Hour	07:15	07:15			518	4 - 6 Peak Hour	17:00	17:00			17:00				
7 - 9 Pk Volume	139	150	0	0	289	4 - 6 Pk Volume	220	231	0	0	451				
Pk Hr Factor	0.827	0.833	0.000	0.000	0.840	Pk Hr Factor	0.846	0.802	0.000	0.000	0.917				

Prepared by NDS/ATD

VOLUME

Magic Mountain Pkwy Bet. I-5 NB Ramps & Tourney Rd

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_003

DAILY TOTALS											NB		SB		EB		WB		Total	
											0		0		16,525		16,059		32,584	
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL									
00:00			50	34	84	12:00			263	227	490									
00:15			34	28	62	12:15			248	293	541									
00:30			25	36	61	12:30			261	282	543									
00:45			19	128	20	118	12:45		240	1012	249	1051	489	2063						
01:00			29	21	50	13:00			265	286	551									
01:15			28	14	42	13:15			249	273	522									
01:30			22	12	34	13:30			213	245	458									
01:45			17	96	12	59	13:45		200	927	238	1042	438	1969						
02:00			30	13	43	14:00			206	247	453									
02:15			22	7	29	14:15			224	213	437									
02:30			8	18	26	14:30			246	241	487									
02:45			8	68	14	52	14:45		229	905	247	948	476	1853						
03:00			10	6	16	15:00			240	258	498									
03:15			13	7	20	15:15			293	268	561									
03:30			23	19	42	15:30			306	243	549									
03:45			28	74	18	50	15:45		353	1192	253	1022	606	2214						
04:00			19	21	40	16:00			373	245	618									
04:15			25	28	53	16:15			358	272	630									
04:30			52	54	106	16:30			391	248	639									
04:45			68	164	60	163	16:45		392	1514	290	1055	682	2569						
05:00			57	94	151	17:00			402	276	678									
05:15			63	135	198	17:15			433	268	701									
05:30			67	147	214	17:30			366	223	589									
05:45			72	259	193	569	17:45		405	1606	249	1016	654	2622						
06:00			91	180	271	18:00			288	248	536									
06:15			87	169	256	18:15			277	215	492									
06:30			133	220	353	18:30			244	177	421									
06:45			177	488	237	806	18:45		218	1027	195	835	413	1862						
07:00			155	184	339	19:00			222	174	396									
07:15			177	250	427	19:15			203	163	366									
07:30			233	247	480	19:30			177	170	347									
07:45			285	850	279	960	19:45		189	791	174	681	363	1472						
08:00			270	257	527	20:00			181	136	317									
08:15			248	253	501	20:15			150	152	302									
08:30			227	233	460	20:30			138	165	303									
08:45			240	985	243	986	20:45		127	596	153	606	280	1202						
09:00			236	247	483	21:00			141	173	314									
09:15			206	245	451	21:15			135	164	299									
09:30			228	235	463	21:30			161	144	305									
09:45			257	927	217	944	21:45		138	575	124	605	262	1180						
10:00			208	239	447	22:00			97	110	207									
10:15			243	246	489	22:15			96	96	192									
10:30			208	229	437	22:30			78	82	160									
10:45			200	859	213	927	22:45		63	334	63	351	126	685						
11:00			243	244	487	23:00			61	66	127									
11:15			211	252	463	23:15			54	52	106									
11:30			236	292	528	23:30			50	45	95									
11:45			234	924	238	1026	23:45		59	224	24	187	83	411						
TOTALS			5822	6660	12482	TOTALS			10703	9399	20102									
SPLIT %			46.6%	53.4%	38.3%	SPLIT %			53.2%	46.8%	61.7%									

DAILY TOTALS											NB		SB		EB		WB		Total	
											0		0		16,525		16,059		32,584	
AM Peak Hour			07:30	11:30	07:30	PM Peak Hour			16:30	12:15	16:30									
AM Pk Volume			1036	1050	2072	PM Pk Volume			1618	1110	2700									
Pk Hr Factor			0.909	0.896	0.918	Pk Hr Factor			0.934	0.947	0.963									
7 - 9 Volume			1835	1946	3781	4 - 6 Volume			3120	2071	5191									
7 - 9 Peak Hour			07:30	07:30	07:30	4 - 6 Peak Hour			16:30	16:15	16:30									
7 - 9 Pk Volume			1036	1036	2072	4 - 6 Pk Volume			1618	1086	2700									
Pk Hr Factor			0.909	0.928	0.918	Pk Hr Factor			0.934	0.936	0.963									

Prepared by NDS/ATD

VOLUME

Magic Mountain Pkwy Bet. The Old Rd & I-5 SB Ramps

Day: Thursday
Date: 7/28/2016

City: Santa Clarita
Project #: CA16_5500_004

DAILY TOTALS											NB		SB		EB		WB		Total
											0		0		12,286		22,458		34,744
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL								
00:00			20	56	76	12:00			227	393	620								
00:15			16	30	46	12:15			121	460	581								
00:30			7	42	49	12:30			117	415	532								
00:45			19	62	81	12:45			122	587	709								
01:00			19	20	39	13:00			135	339	474								
01:15			6	20	26	13:15			111	323	434								
01:30			14	26	40	13:30			213	303	516								
01:45			14	53	67	13:45			121	580	701								
02:00			8	24	32	14:00			189	275	464								
02:15			13	22	35	14:15			165	246	411								
02:30			6	32	38	14:30			185	259	444								
02:45			10	37	47	14:45			134	673	807								
03:00			9	10	19	15:00			160	290	450								
03:15			10	22	32	15:15			218	335	553								
03:30			5	36	41	15:30			261	287	548								
03:45			12	36	48	15:45			256	895	1151								
04:00			1	37	38	16:00			241	312	553								
04:15			5	50	55	16:15			243	328	571								
04:30			16	95	111	16:30			266	312	578								
04:45			8	30	38	16:45			271	1021	1292								
05:00			12	103	115	17:00			268	344	612								
05:15			20	154	174	17:15			295	306	601								
05:30			16	254	270	17:30			253	327	580								
05:45			35	83	118	17:45			254	1070	1324								
06:00			38	178	216	18:00			228	417	645								
06:15			36	217	253	18:15			209	338	547								
06:30			39	270	309	18:30			357	274	631								
06:45			32	145	177	18:45			286	1080	1366								
07:00			52	297	349	19:00			270	246	516								
07:15			65	353	418	19:15			219	283	502								
07:30			71	314	385	19:30			275	212	487								
07:45			90	278	368	19:45			322	1086	1408								
08:00			61	338	399	20:00			301	178	479								
08:15			81	292	373	20:15			244	192	436								
08:30			71	266	337	20:30			346	191	537								
08:45			75	288	363	20:45			393	1284	1677								
09:00			89	357	446	21:00			343	172	515								
09:15			126	320	446	21:15			247	157	404								
09:30			126	389	515	21:30			122	149	271								
09:45			136	477	613	21:45			129	841	970								
10:00			162	500	662	22:00			71	123	194								
10:15			129	504	633	22:15			85	102	187								
10:30			142	503	645	22:30			96	84	180								
10:45			167	600	767	22:45			34	286	320								
11:00			119	486	605	23:00			51	87	138								
11:15			114	488	602	23:15			70	65	135								
11:30			155	432	587	23:30			36	45	81								
11:45			218	606	824	23:45			31	188	219								
TOTALS			2695	10477	13172	TOTALS			9591	11981	21572								
SPLIT %			20.5%	79.5%	37.9%	SPLIT %			44.5%	55.5%	62.1%								

DAILY TOTALS											NB		SB		EB		WB		Total
											0		0		12,286		22,458		34,744
AM Peak Hour			11:30	10:00	10:00	PM Peak Hour			20:30	12:00	17:15								
AM Pk Volume			721	2018	2618	PM Pk Volume			1329	1628	2427								
Pk Hr Factor			0.794	0.987	0.965	Pk Hr Factor			0.845	0.885	0.941								
7 - 9 Volume	0	0	566	2520	3086	4 - 6 Volume	0	0	2091	2635	4726								
7 - 9 Peak Hour			07:30	07:15	07:15	4 - 6 Peak Hour			16:30	16:15	16:45								
7 - 9 Pk Volume	0	0	303	1373	1660	4 - 6 Pk Volume	0	0	1100	1343	2423								
Pk Hr Factor	0.000	0.000	0.842	0.933	0.906	Pk Hr Factor	0.000	0.000	0.932	0.935	0.962								

VOLUME

Magic Mountain Pkwy Bet. Tourney Rd & Wayne Mills PI

Day: Tuesday
Date: 11/1/2016

City: Santa Clarita
Project #: CA16_5710_001

DAILY TOTALS						NB	SB	EB	WB	Total		
						0	0	16,532	15,010	31,542		
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL	
00:00			36	23	59	12:00			254	195	449	
00:15			36	23	59	12:15			264	209	473	
00:30			28	10	38	12:30			268	242	510	
00:45			26	126	8	64	12:45		254	1040	231	877
01:00			17	13	30	13:00			260	238	498	
01:15			19	8	27	13:15			226	200	426	
01:30			19	5	24	13:30			241	228	469	
01:45			16	71	4	30	13:45		225	952	189	855
02:00			17	5	22	14:00			242	213	455	
02:15			12	1	13	14:15			226	235	461	
02:30			15	12	27	14:30			240	228	468	
02:45			14	58	5	23	14:45		266	974	205	881
03:00			9	9	18	15:00			272	228	500	
03:15			9	12	21	15:15			323	250	573	
03:30			10	21	31	15:30			367	267	634	
03:45			14	42	17	59	15:45		361	1323	222	967
04:00			19	22	41	16:00			354	219	573	
04:15			15	35	50	16:15			387	207	594	
04:30			31	55	86	16:30			389	205	594	
04:45			51	116	78	190	16:45		439	1569	244	875
05:00			51	85	136	17:00			480	252	732	
05:15			56	159	215	17:15			438	246	684	
05:30			58	208	266	17:30			453	255	708	
05:45			86	251	224	676	17:45		417	1788	237	990
06:00			67	211	278	18:00			361	274	635	
06:15			99	261	360	18:15			367	228	595	
06:30			107	319	426	18:30			318	189	507	
06:45			143	416	298	1089	18:45		308	1354	194	885
07:00			127	290	417	19:00			269	174	443	
07:15			139	330	469	19:15			249	177	426	
07:30			184	338	522	19:30			215	152	367	
07:45			244	694	335	1293	19:45		197	930	139	642
08:00			218	329	547	20:00			167	144	311	
08:15			232	290	522	20:15			143	127	270	
08:30			192	276	468	20:30			157	117	274	
08:45			216	858	251	1146	20:45		132	599	98	486
09:00			212	225	437	21:00			131	133	264	
09:15			161	202	363	21:15			121	101	222	
09:30			163	178	341	21:30			95	82	177	
09:45			188	724	222	827	21:45		104	451	70	386
10:00			170	166	336	22:00			103	61	164	
10:15			163	176	339	22:15			92	42	134	
10:30			205	169	374	22:30			68	60	128	
10:45			200	738	185	696	22:45		69	332	36	199
11:00			221	177	398	23:00			58	40	98	
11:15			215	189	404	23:15			52	40	92	
11:30			234	177	411	23:30			44	34	78	
11:45			257	927	205	748	23:45		45	199	12	126
TOTALS			5021	6841	11862	TOTALS			11511	8169	19680	
SPLIT %			42.3%	57.7%	37.6%	SPLIT %			58.5%	41.5%	62.4%	

DAILY TOTALS						NB	SB	EB	WB	Total	
						0	0	16,532	15,010	31,542	
AM Peak Hour			11:45	07:15	07:30	PM Peak Hour			16:45	17:15	16:45
AM Pk Volume			1043	1332	2170	PM Pk Volume			1810	1012	2807
Pk Hr Factor			0.973	0.985	0.937	Pk Hr Factor			0.943	0.923	0.959
7 - 9 Volume	0	0	1552	2439	3991	4 - 6 Volume	0	0	3357	1865	5222
7 - 9 Peak Hour			07:45	07:15	07:30	4 - 6 Peak Hour			16:45	16:45	16:45
7 - 9 Pk Volume	0	0	886	1332	2170	4 - 6 Pk Volume	0	0	1810	997	2807
Pk Hr Factor	0.000	0.000	0.908	0.985	0.937	Pk Hr Factor	0.000	0.000	0.943	0.977	0.959

➤ AM/PM Peak Hour Turn Counts

ITM Peak Hour Summary

Prepared by:




National Data & Surveying Services


I-5 SB Ramps and Magic Mountain Pkwy, Santa Clarita

Date: 10/25/2016
Day: Tuesday


Project #: 16-5709-002
City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



ITM Peak Hour Summary

Prepared by:




National Data & Surveying Services


I-5 NB Ramps and Magic Mountain Pkwy, Santa Clarita

Date: 10/25/2016
Day: Tuesday


Project #: 16-5709-001
City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



ITM Peak Hour Summary

Prepared by:



National Data & Surveying Services


The Old Rd and Magic Mountain Pkwy, Santa Clarita

Date: 10/25/2016


Day: Tuesday

Project #: 16-5709-003


City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



ITM Peak Hour Summary

Prepared by:




National Data & Surveying Services

Tourney Rd and Magic Mountain Pkwy, Santa Clarita


Date: 10/25/2016
Day: Tuesday

Project #: 16-5709-004
City: Santa Clarita




Count Periods	Start	End
AM	7:00 AM	9:00 AM
NOON	NONE	NONE
PM	4:00 PM	6:00 PM

Total Ins & Outs



Total Volume Per Leg



ITM Peak Hour Summary

Prepared by:



National Data & Surveying Services


Tourney Rd and Wayne Mills Pl, Santa Clarita

Date: 10/25/2016


Day: Tuesday

Project #: 16-5709-005


City: Santa Clarita



Total Ins & Outs



Total Volume Per Leg



APPENDIX B

- Existing Conditions Analysis Worksheets

Santa Clarita Wayne Mills Hotel
 1: Magic Mountain Pkwy & I-5 SB Ramps

Existing Conditions
 Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑	↑↑	↑↑↑					↑	↑	↑↑
Volume (vph)	0	244	75	568	1467	0	0	0	0	317	1	30
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Frt		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Flt Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Flt Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	265	82	617	1595	0	0	0	0	345	1	33
RTOR Reduction (vph)	0	0	56	0	0	0	0	0	0	0	0	26
Lane Group Flow (vph)	0	265	26	617	1595	0	0	0	0	172	174	7
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Effective Green, g (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Actuated g/C Ratio		0.32	0.32	0.30	0.68					0.21	0.21	0.21
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)		1638	898	1029	4343					354	355	588
v/s Ratio Prot		0.05		c0.18	c0.25					0.10	c0.10	
v/s Ratio Perm			0.01									0.00
v/c Ratio		0.16	0.03	0.60	0.37					0.49	0.49	0.01
Uniform Delay, d1		21.8	20.9	26.9	6.2					31.2	31.2	28.1
Progression Factor		1.00	1.00	0.74	0.46					1.00	1.00	1.00
Incremental Delay, d2		0.2	0.1	0.7	0.2					4.7	4.8	0.0
Delay (s)		22.0	20.9	20.7	3.0					35.9	36.0	28.1
Level of Service		C	C	C	A					D	D	C
Approach Delay (s)		21.8			8.0		0.0				35.3	
Approach LOS		C			A		A				D	

Intersection Summary		
HCM 2000 Control Delay	13.1	HCM 2000 Level of Service
HCM 2000 Volume to Capacity ratio	0.49	B
Actuated Cycle Length (s)	90.0	Sum of lost time (s)
Intersection Capacity Utilization	62.7%	15.0
Analysis Period (min)	15	ICU Level of Service
c Critical Lane Group		B

Santa Clarita Wayne Mills Hotel
 I: Magic Mountain Pkwy & I-5 SB Ramps

Existing Conditions
 Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑	↑↑	↑↑↑					↓	↓	↑↑
Volume (vph)	0	435	167	419	1190	0	0	0	0	317	1	57
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Flt		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Flt Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Flt Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	473	182	455	1293	0	0	0	0	345	1	62
RTOR Reduction (vph)	0	0	119	0	0	0	0	0	0	0	0	48
Lane Group Flow (vph)	0	473	63	455	1293	0	0	0	0	172	174	14
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Effective Green, g (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Actuated g/C Ratio		0.34	0.34	0.26	0.66					0.23	0.23	0.23
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)		1751	959	877	4200					392	393	650
v/s Ratio Prot		0.09		c0.13	c0.20					0.10	c0.10	
v/s Ratio Perm			0.02									0.01
v/c Ratio		0.27	0.07	0.52	0.31					0.44	0.44	0.02
Uniform Delay, d1		21.3	19.8	28.8	6.7					29.5	29.5	26.6
Progression Factor		1.00	1.00	0.78	0.47					1.00	1.00	1.00
Incremental Delay, d2		0.4	0.1	0.4	0.2					3.5	3.6	0.1
Delay (s)		21.7	19.9	22.8	3.3					33.0	33.1	26.7
Level of Service		C	B	C	A					C	C	C
Approach Delay (s)		21.2			8.3		0.0				32.1	
Approach LOS		C			A		A				C	
Intersection Summary												
HCM 2000 Control Delay		14.8										
HCM 2000 Volume to Capacity ratio		0.42										
Actuated Cycle Length (s)		90.0								15.0		
Intersection Capacity Utilization		57.6%										
Analysis Period (min)		15										
c Critical Lane Group												

Santa Clarita Wayne Mills Hotel
2: I-5 NB Ramps & Magic Mountain Pkwy

Existing Conditions
Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↔↔	↑↑↑			↑↑↑	↔	↔↔	↑	↔			
Volume (vph)	29	531	0	0	893	229	1143	0	566	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Frt	1.00	1.00			0.99	0.85	1.00	0.85	0.85			
Flt Protected	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (prot)	3433	5085			6004	1282	3433	1504	1504			
Flt Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			6004	1282	3433	1504	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	32	577	0	0	971	249	1242	0	615	0	0	0
RTOR Reduction (vph)	0	0	0	0	5	153	0	65	65	0	0	0
Lane Group Flow (vph)	32	577	0	0	1001	61	1242	243	242	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Effective Green, g (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Actuated g/C Ratio	0.03	0.37			0.28	0.28	0.52	0.52	0.52			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	91	1864			1707	364	1792	785	785			
v/s Ratio Prot	0.01	c0.11			c0.17		c0.36	0.16				
v/s Ratio Perm						0.05			0.16			
v/c Ratio	0.35	0.31			0.59	0.17	0.69	0.31	0.31			
Uniform Delay, d1	43.0	20.4			27.7	24.2	16.1	12.2	12.2			
Progression Factor	0.47	0.26			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d2	2.2	0.4			1.5	1.0	2.2	1.0	1.0			
Delay (s)	22.6	5.7			29.1	25.2	18.3	13.3	13.3			
Level of Service	C	A			C	C	B	B	B			
Approach Delay (s)		6.6			28.4			16.7			0.0	
Approach LOS		A			C			B			A	
Intersection Summary												
HCM 2000 Control Delay		18.9										
HCM 2000 Volume to Capacity ratio		0.65										
Actuated Cycle Length (s)		90.0										
Intersection Capacity Utilization		62.7%							15.0			
Analysis Period (min)		15										
c Critical Lane Group												

Santa Clarita Wayne Mills Hotel
2: I-5 NB Ramps & Magic Mountain Pkwy

Existing Conditions
Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↔↔	↔↔↔			↔↔↔	↔	↔↔	↔	↔			
Volume (vph)	51	696	0	0	712	396	890	1	858	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Fr _t	1.00	1.00			0.97	0.85	1.00	0.85	0.85			
Fl _t Protected	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (prot)	3433	5085			5841	1282	3433	1505	1504			
Fl _t Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			5841	1282	3433	1505	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	55	757	0	0	774	430	967	1	933	0	0	0
RTOR Reduction (vph)	0	0	0	0	54	154	0	41	43	0	0	0
Lane Group Flow (vph)	55	757	0	0	931	65	967	427	424	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Effective Green, g (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Actuated g/C Ratio	0.04	0.39			0.30	0.30	0.50	0.50	0.50			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	122	1977			1739	381	1716	752	752			
v/s Ratio Prot	0.02	c0.15			c0.16		0.28	c0.28				
v/s Ratio Perm						0.05			0.28			
v/c Ratio	0.45	0.38			0.54	0.17	0.56	0.57	0.56			
Uniform Delay, d1	42.5	19.7			26.4	23.4	15.7	15.7	15.7			
Progression Factor	0.64	0.47			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d2	2.5	0.5			1.2	1.0	1.3	3.1	3.0			
Delay (s)	29.8	9.8			27.6	24.4	17.0	18.8	18.7			
Level of Service	C	A			C	C	B	B	B			
Approach Delay (s)		11.1			27.0			17.9			0.0	
Approach LOS		B			C			B			A	

Intersection Summary		
HCM 2000 Control Delay	19.3	HCM 2000 Level of Service
HCM 2000 Volume to Capacity ratio	0.56	B
Actuated Cycle Length (s)	90.0	Sum of lost time (s)
Intersection Capacity Utilization	57.6%	15.0
Analysis Period (min)	15	ICU Level of Service
c Critical Lane Group		B

Santa Clarita Wayne Mills Hotel
3: Tourney Rd & Magic Mountain Pkwy

Existing Conditions
Timing Plan: AM PEAK




Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑↑	↑	↑	↑↑↑↑	↑↑	↑
Volume (vph)	866	233	346	1011	118	62
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Frt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	941	253	376	1099	128	67
RTOR Reduction (vph)	0	172	0	0	0	58
Lane Group Flow (vph)	941	81	376	1099	128	9
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	31.2	31.2	38.0	74.2	13.4	13.4
Effective Green, g (s)	31.2	31.2	38.0	74.2	13.4	13.4
Actuated g/C Ratio	0.32	0.32	0.39	0.76	0.14	0.14
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	1497	466	634	3560	434	200
v/s Ratio Prot	c0.20		c0.23	0.23	c0.04	
v/s Ratio Perm		0.06				0.01
v/c Ratio	0.63	0.17	0.59	0.31	0.29	0.05
Uniform Delay, d1	28.3	23.9	23.7	3.7	37.9	36.6
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.8	0.2	1.5	0.0	0.4	0.1
Delay (s)	29.1	24.1	25.2	3.7	38.2	36.6
Level of Service	C	C	C	A	D	D
Approach Delay (s)	28.0			9.2	37.7	
Approach LOS	C			A	D	

Intersection Summary

HCM 2000 Control Delay	19.0	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.56		
Actuated Cycle Length (s)	97.6	Sum of lost time (s)	15.0
Intersection Capacity Utilization	55.1%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
3: Tourney Rd & Magic Mountain Pkwy

Existing Conditions
Timing Plan: PM PEAK



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑	↑	↑	↑↑↑	↑↑	↑
Volume (vph)	1447	118	138	862	246	332
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Flt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	1573	128	150	937	267	361
RTOR Reduction (vph)	0	46	0	0	0	286
Lane Group Flow (vph)	1573	82	150	937	267	75
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	54.9	54.9	17.3	77.2	18.4	18.4
Effective Green, g (s)	54.9	54.9	17.3	77.2	18.4	18.4
Actuated g/C Ratio	0.52	0.52	0.16	0.73	0.17	0.17
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	2435	757	267	3424	550	254
v/s Ratio Prot	c0.34		c0.09	0.20	c0.08	
v/s Ratio Perm		0.06				0.05
v/c Ratio	0.65	0.11	0.56	0.27	0.49	0.30
Uniform Delay, d1	18.3	12.9	40.7	4.8	39.3	38.0
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.6	0.1	2.7	0.0	0.7	0.7
Delay (s)	18.9	13.0	43.4	4.8	40.0	38.6
Level of Service	B	B	D	A	D	D
Approach Delay (s)	18.5			10.1	39.2	
Approach LOS	B			B	D	

Intersection Summary

HCM 2000 Control Delay	19.6	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.60		
Actuated Cycle Length (s)	105.6	Sum of lost time (s)	15.0
Intersection Capacity Utilization	61.0%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
4: Tourney Rd & Wayne Mills PI

Existing Conditions
Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕	↕		↕		↕	↕	↕	↕	↕	↕
Volume (veh/h)	24	2	2	46	0	58	5	79	41	162	420	23
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	26	2	2	50	0	63	5	86	45	176	457	25
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	968	950	457	908	930	86	482			130		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	968	950	457	908	930	86	482			130		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	87	99	100	78	100	94	99			88		
cM capacity (veh/h)	197	227	604	229	234	973	1081			1455		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	30	113	5	86	45	176	457	25				
Volume Left	26	50	5	0	0	176	0	0				
Volume Right	2	63	0	0	45	0	0	25				
cSH	215	400	1081	1700	1700	1455	1700	1700				
Volume to Capacity	0.14	0.28	0.01	0.05	0.03	0.12	0.27	0.01				
Queue Length 95th (ft)	12	29	0	0	0	10	0	0				
Control Delay (s)	24.9	17.5	8.3	0.0	0.0	7.8	0.0	0.0				
Lane LOS	C	C	A			A						
Approach Delay (s)	24.9	17.5	0.3			2.1						
Approach LOS	C	C										
Intersection Summary												
Average Delay			4.4									
Intersection Capacity Utilization			41.5%		ICU Level of Service					A		
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
4: Tourney Rd & Wayne Mills PI

Existing Conditions
Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔	↔		↔		↔	↑	↔	↔	↑	↔
Volume (veh/h)	18	4	7	43	3	100	3	467	31	97	133	34
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	20	4	8	47	3	109	3	508	34	105	145	37
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	980	903	145	876	907	508	182			541		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	980	903	145	876	907	508	182			541		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	88	98	99	81	99	81	100			90		
cM capacity (veh/h)	168	248	903	243	247	565	1394			1027		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	32	159	3	508	34	105	145	37				
Volume Left	20	47	3	0	0	105	0	0				
Volume Right	8	109	0	0	34	0	0	37				
cSH	241	399	1394	1700	1700	1027	1700	1700				
Volume to Capacity	0.13	0.40	0.00	0.30	0.02	0.10	0.09	0.02				
Queue Length 95th (ft)	11	47	0	0	0	9	0	0				
Control Delay (s)	23.1	19.9	7.6	0.0	0.0	8.9	0.0	0.0				
Lane LOS	C	C	A			A						
Approach Delay (s)	23.1	19.9	0.0			3.3						
Approach LOS	C	C										
Intersection Summary												
Average Delay			4.7									
Intersection Capacity Utilization			55.3%		ICU Level of Service					B		
Analysis Period (min)			15									

APPENDIX C

- Existing + Project Conditions Analysis Worksheets

Santa Clarita Wayne Mills Hotel
1: Magic Mountain Pkwy & I-5 SB Ramps

Existing Plus Project
Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑	↑↑	↑↑↑					↑	↑	↑↑
Volume (vph)	0	256	75	580	1475	0	0	0	0	329	1	30
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Frt		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Flt Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Flt Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	278	82	630	1603	0	0	0	0	358	1	33
RTOR Reduction (vph)	0	0	56	0	0	0	0	0	0	0	0	26
Lane Group Flow (vph)	0	278	26	630	1603	0	0	0	0	179	180	7
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Effective Green, g (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Actuated g/C Ratio		0.32	0.32	0.30	0.68					0.21	0.21	0.21
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)		1638	898	1029	4343					354	355	588
v/s Ratio Prot		0.05		c0.18	c0.25					0.11	c0.11	
v/s Ratio Perm			0.01									0.00
v/c Ratio		0.17	0.03	0.61	0.37					0.51	0.51	0.01
Uniform Delay, d1		21.9	20.9	27.0	6.2					31.4	31.4	28.1
Progression Factor		1.00	1.00	0.74	0.45					1.00	1.00	1.00
Incremental Delay, d2		0.2	0.1	0.8	0.2					5.1	5.1	0.0
Delay (s)		22.1	20.9	20.7	3.0					36.4	36.5	28.1
Level of Service		C	C	C	A					D	D	C
Approach Delay (s)		21.8			8.0		0.0					
Approach LOS		C			A		A				D	

Intersection Summary

HCM 2000 Control Delay	13.3	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.50		
Actuated Cycle Length (s)	90.0	Sum of lost time (s)	15.0
Intersection Capacity Utilization	63.0%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
 1: Magic Mountain Pkwy & I-5 SB Ramps

Existing Plus Project
 Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑	↑↓	↑↑↑					↑	↑	↑↑
Volume (vph)	0	448	167	431	1198	0	0	0	0	330	1	57
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Frt		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Flt Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Flt Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	487	182	468	1302	0	0	0	0	359	1	62
RTOR Reduction (vph)	0	0	119	0	0	0	0	0	0	0	0	48
Lane Group Flow (vph)	0	487	63	468	1302	0	0	0	0	179	181	14
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Effective Green, g (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Actuated g/C Ratio		0.34	0.34	0.26	0.66					0.23	0.23	0.23
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)		1751	959	877	4200					392	393	650
v/s Ratio Prot		0.10		c0.14	c0.20					0.11	c0.11	
v/s Ratio Perm			0.02									0.01
v/c Ratio		0.28	0.07	0.53	0.31					0.46	0.46	0.02
Uniform Delay, d1		21.4	19.8	28.9	6.7					29.6	29.6	26.6
Progression Factor		1.00	1.00	0.79	0.50					1.00	1.00	1.00
Incremental Delay, d2		0.4	0.1	0.5	0.2					3.8	3.8	0.1
Delay (s)		21.8	19.9	23.2	3.5					33.4	33.5	26.7
Level of Service		C	B	C	A					C	C	C
Approach Delay (s)		21.3			8.7		0.0				32.4	
Approach LOS		C			A		A				C	
Intersection Summary												
HCM 2000 Control Delay			15.2			HCM 2000 Level of Service					B	
HCM 2000 Volume to Capacity ratio			0.43									
Actuated Cycle Length (s)			90.0			Sum of lost time (s)			15.0			
Intersection Capacity Utilization			58.5%			ICU Level of Service			B			
Analysis Period (min)			15									
c Critical Lane Group												

Santa Clarita Wayne Mills Hotel
2: I-5 NB Ramps & Magic Mountain Pkwy

Existing Plus Project
Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↔↔	↔↔↔			↔↔↔	↔	↔↔	↔	↔			
Volume (vph)	29	555	0	0	913	237	1143	0	584	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Fr _t	1.00	1.00			0.99	0.85	1.00	0.85	0.85			
Fl _t Protected	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (prot)	3433	5085			6001	1282	3433	1504	1504			
Fl _t Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			6001	1282	3433	1504	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	32	603	0	0	992	258	1242	0	635	0	0	0
RTOR Reduction (vph)	0	0	0	0	6	157	0	59	59	0	0	0
Lane Group Flow (vph)	32	603	0	0	1025	62	1242	259	258	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Effective Green, g (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Actuated g/C Ratio	0.03	0.37			0.28	0.28	0.52	0.52	0.52			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	91	1864			1706	364	1792	785	785			
v/s Ratio Prot	0.01	c0.12			c0.17		c0.36	0.17				
v/s Ratio Perm						0.05			0.17			
v/c Ratio	0.35	0.32			0.60	0.17	0.69	0.33	0.33			
Uniform Delay, d ₁	43.0	20.5			27.8	24.2	16.1	12.4	12.4			
Progression Factor	0.53	0.32			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d ₂	2.2	0.4			1.6	1.0	2.2	1.1	1.1			
Delay (s)	25.1	7.1			29.4	25.2	18.3	13.5	13.5			
Level of Service	C	A			C	C	B	B	B			
Approach Delay (s)		8.0			28.6			16.7			0.0	
Approach LOS		A			C			B			A	

Intersection Summary			
HCM 2000 Control Delay	19.2	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.66		
Actuated Cycle Length (s)	90.0	Sum of lost time (s)	15.0
Intersection Capacity Utilization	63.0%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
2: I-5 NB Ramps & Magic Mountain Pkwy

Existing Plus Project
Timing Plan: PM PEAK


Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↔↔	↔↔↔			↔↔↔	↔	↔↔	↔	↔			
Volume (vph)	51	722	0	0	733	404	890	1	877	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Flt	1.00	1.00			0.97	0.85	1.00	0.85	0.85			
Flt Protected	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (prot)	3433	5085			5843	1282	3433	1505	1504			
Flt Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			5843	1282	3433	1505	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	55	785	0	0	797	439	967	1	953	0	0	0
RTOR Reduction (vph)	0	0	0	0	53	157	0	37	43	0	0	0
Lane Group Flow (vph)	55	785	0	0	959	67	967	441	434	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Effective Green, g (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Actuated g/C Ratio	0.04	0.39			0.30	0.30	0.50	0.50	0.50			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	122	1977			1739	381	1716	752	752			
v/s Ratio Prot	0.02	c0.15			c0.16		0.28	c0.29				
v/s Ratio Perm						0.05		0.29				
v/c Ratio	0.45	0.40			0.55	0.18	0.56	0.59	0.58			
Uniform Delay, d1	42.5	19.9			26.5	23.4	15.7	15.9	15.8			
Progression Factor	0.65	0.48			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d2	2.5	0.6			1.3	1.0	1.3	3.3	3.2			
Delay (s)	30.3	10.1			27.8	24.4	17.0	19.3	19.0			
Level of Service	C	B			C	C	B	B	B			
Approach Delay (s)		11.4			27.2			18.1			0.0	
Approach LOS		B			C			B			A	

Intersection Summary

HCM 2000 Control Delay	19.5	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.58		
Actuated Cycle Length (s)	90.0	Sum of lost time (s)	15.0
Intersection Capacity Utilization	58.5%	ICU Level of Service	B
Analysis Period (min)	15		
c. Critical Lane Group			

Santa Clarita Wayne Mills Hotel
 3: Tourney Rd & Magic Mountain Pkwy

Existing Plus Project
 Timing Plan: AM PEAK




Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑	↑	↑	↑↑↑	↑↑	↑
Volume (vph)	866	274	358	1011	146	62
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Frt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	-0.92	0.92	0.92
Adj. Flow (vph)	941	298	389	1099	159	67
RTOR Reduction (vph)	0	204	0	0	0	58
Lane Group Flow (vph)	941	94	389	1099	159	9
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	31.9	31.9	39.7	76.6	14.2	14.2
Effective Green, g (s)	31.9	31.9	39.7	76.6	14.2	14.2
Actuated g/C Ratio	0.32	0.32	0.39	0.76	0.14	0.14
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	1482	461	641	3559	445	205
v/s Ratio Prot	c0.20		c0.24	0.23	c0.05	
v/s Ratio Perm		0.06				0.01
v/c Ratio	0.63	0.20	0.61	0.31	0.36	0.05
Uniform Delay, d1	29.5	25.2	24.3	3.8	39.2	37.4
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.9	0.2	1.6	0.0	0.5	0.1
Delay (s)	30.4	25.4	26.0	3.8	39.7	37.5
Level of Service	C	C	C	A	D	D
Approach Delay (s)	29.2			9.6	39.0	
Approach LOS	C			A	D	

Intersection Summary

HCM 2000 Control Delay	20.1	HCM 2000 Level of Service	C
HCM 2000 Volume to Capacity ratio	0.58		
Actuated Cycle Length (s)	100.8	Sum of lost time (s)	15.0
Intersection Capacity Utilization	56.7%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
 3: Tourney Rd & Magic Mountain Pkwy

Existing Plus Project
 Timing Plan: PM PEAK



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑	↑	↑	↑↑↑	↑↑	↑
Volume (vph)	1447	163	151	862	275	332
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Frt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	1573	177	164	937	299	361
RTOR Reduction (vph)	0	63	0	0	0	284
Lane Group Flow (vph)	1573	114	164	937	299	77
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	57.3	57.3	18.6	80.9	19.7	19.7
Effective Green, g (s)	57.3	57.3	18.6	80.9	19.7	19.7
Actuated g/C Ratio	0.52	0.52	0.17	0.73	0.18	0.18
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	2426	755	274	3426	563	259
v/s Ratio Prot	c0.34		c0.10	0.20	c0.09	
v/s Ratio Perm		0.08				0.05
v/c Ratio	0.65	0.15	0.60	0.27	0.53	0.30
Uniform Delay, d1	19.3	13.9	42.5	5.0	41.3	39.4
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.6	0.1	3.5	0.0	1.0	0.6
Delay (s)	19.9	14.0	46.0	5.0	42.2	40.1
Level of Service	B	B	D	A	D	D
Approach Delay (s)	19.3			11.1	41.0	
Approach LOS	B			B	D	

Intersection Summary			
HCM 2000 Control Delay	20.9	HCM 2000 Level of Service	C
HCM 2000 Volume to Capacity ratio	0.61		
Actuated Cycle Length (s)	110.6	Sum of lost time (s)	15.0
Intersection Capacity Utilization	61.0%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
4:Tourney Rd & Wayne Mills PI

Existing Plus Project
Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SEL	SBT	SBR
Lane Configurations		↖	↗		↕		↖	↕	↗	↖	↕	↗
Volume (veh/h)	52	10	6	46	0	58	11	79	41	162	420	76
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	57	11	7	50	0	63	12	86	45	176	457	83
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type							None				None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	982	963	457	927	1001	86	539			130		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	982	963	457	927	1001	86	539			130		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	71	95	99	77	100	94	99			88		
cM capacity (veh/h)	192	222	604	213	211	973	1029			1455		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	74	113	12	86	45	176	457	83				
Volume Left	57	50	12	0	0	176	0	0				
Volume Right	7	63	0	0	45	0	0	83				
cSH	216	378	1029	1700	1700	1455	1700	1700				
Volume to Capacity	0.34	0.30	0.01	0.05	0.03	0.12	0.27	0.05				
Queue Length 95th (ft)	36	31	1	0	0	10	0	0				
Control Delay (s)	30.6	18.6	8.5	0.0	0.0	7.8	0.0	0.0				
Lane LOS	D	C	A			A						
Approach Delay (s)	30.6	18.6	0.7			1.9						
Approach LOS	D	C										
Intersection Summary												
Average Delay			5.6									
Intersection Capacity Utilization			41.5%		ICU Level of Service					A		
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
4: Tourney Rd & Wayne Mills PI

Existing Plus Project
Timing Plan: PM PEAK


Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↖	↗		↕		↖	↗	↗	↖	↕	↖
Volume (veh/h)	47	12	11	43	3	100	9	467	31	97	133	92
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	51	13	12	47	3	109	10	508	34	105	145	100
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	993	916	145	895	983	508	245			541		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	993	916	145	895	983	508	245			541		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	69	95	99	79	99	81	99			90		
cM capacity (veh/h)	164	242	903	227	222	565	1322			1027		

Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3
Volume Total	76	159	10	508	34	105	145	100
Volume Left	51	47	10	0	0	105	0	0
Volume Right	12	109	0	0	34	0	0	100
cSH	214	384	1322	1700	1700	1027	1700	1700
Volume to Capacity	0.36	0.41	0.01	0.30	0.02	0.10	0.09	0.06
Queue Length 95th (ft)	38	49	1	0	0	9	0	0
Control Delay (s)	31.5	20.8	7.7	0.0	0.0	8.9	0.0	0.0
Lane LOS	D	C	A			A		
Approach Delay (s)	31.5	20.8	0.1			2.7		
Approach LOS	D	C						

Intersection Summary		
Average Delay		5.9
Intersection Capacity Utilization	55.3%	ICU Level of Service
Analysis Period (min)		15
		B

Santa Clarita Wayne Mills Hotel
5: Proj Dwy & Wayne Mills PI

Existing Plus Project
Timing Plan: AM PEAK



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		←	↑	←	↑
Volume (veh/h)	28	0	101	28	0	68
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	30	0	110	30	0	74
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLTL			None		
Median storage (veh)	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			30		280	30
vC1, stage 1 conf vol					30	
vC2, stage 2 conf vol					250	
vCu, unblocked vol			30		280	30
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					5.4	
tF (s)			2.2		3.5	3.3
p0 queue free %			93		100	93
cM capacity (veh/h)			1582		716	1044

Direction, Lane #	EB 1	WB 1	WB 2	NB 1
Volume Total	30	110	30	74
Volume Left	0	110	0	0
Volume Right	0	0	0	74
cSH	1700	1582	1700	1044
Volume to Capacity	0.02	0.07	0.02	0.07
Queue Length 95th (ft)	0	6	0	6
Control Delay (s)	0.0	7.4	0.0	8.7
Lane LOS		A		A
Approach Delay (s)	0.0	5.8		8.7
Approach LOS				A

Intersection Summary			
Average Delay		6.0	
Intersection Capacity Utilization		23.1%	ICU Level of Service
Analysis Period (min)		15	A

Santa Clarita Wayne Mills Hotel
5: Proj Dwy & Wayne Mills PI

Existing Plus Project
Timing Plan: PM PEAK

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		↓	↑	↓	
Volume (veh/h)	29	0	109	40	0	71
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	32	0	118	43	0	77
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLTL			None		
Median storage (veh)	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			32		312	32
vC1, stage 1 conf vol					32	
vC2, stage 2 conf vol					280	
vCu, unblocked vol			32		312	32
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					5.4	
tF (s)			2.2		3.5	3.3
p0 queue free %			93		100	93
cM capacity (veh/h)			1581		690	1042

Direction, Lane #	EB 1	WB 1	WB 2	NB 1
Volume Total	32	118	43	77
Volume Left	0	118	0	0
Volume Right	0	0	0	77
cSH	1700	1581	1700	1042
Volume to Capacity	0.02	0.07	0.03	0.07
Queue Length 95th (ft)	0	6	0	6
Control Delay (s)	0.0	7.5	0.0	8.7
Lane LOS		A		A
Approach Delay (s)	0.0	5.5		8.7
Approach LOS				A


Intersection Summary			
Average Delay		5.8	
Intersection Capacity Utilization		23.8%	ICU Level of Service
Analysis Period (min)		15	A

APPENDIX D

- 2018 Opening Day Conditions Analysis Worksheets

Santa Clarita Wayne Mills Hotel
1: Magic Mountain Pkwy & I-5 SB Ramps

Existing Plus Ambient
Timing Plan: AM PEAK



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑	↑↑	↑↑↑					↑	↑	↑↑
Volume (vph)	0	259	80	602	1555	0	0	0	0	336	1	32
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Fr _t		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Fl _t Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Fl _t Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	282	87	654	1690	0	0	0	0	365	1	35
RTOR Reduction (vph)	0	0	59	0	0	0	0	0	0	0	0	28
Lane Group Flow (vph)	0	282	28	654	1690	0	0	0	0	182	184	7
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Effective Green, g (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Actuated g/C Ratio		0.32	0.32	0.30	0.68					0.21	0.21	0.21
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)		1638	898	1029	4343					354	355	588
v/s Ratio Prot		0.06		c0.19	c0.26					0.11	c0.11	
v/s Ratio Perm			0.01									0.00
v/c Ratio		0.17	0.03	0.64	0.39					0.51	0.52	0.01
Uniform Delay, d1		21.9	20.9	27.2	6.3					31.4	31.4	28.1
Progression Factor		1.00	1.00	0.76	0.51					1.00	1.00	1.00
Incremental Delay, d2		0.2	0.1	1.0	0.2					5.3	5.3	0.0
Delay (s)		22.1	20.9	21.8	3.4					36.7	36.8	28.1
Level of Service		C	C	C	A					D	D	C
Approach Delay (s)		21.8			8.6		0.0					
Approach LOS		C			A		A				D	

Intersection Summary

HCM 2000 Control Delay	13.7	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.52		
Actuated Cycle Length (s)	90.0	Sum of lost time (s)	15.0
Intersection Capacity Utilization	65.5%	ICU Level of Service	C
Analysis Period (min)	15		
c - Critical Lane Group			

Santa Clarita Wayne Mills Hotel
1: Magic Mountain Pkwy & I-5 SB Ramps

Existing Plus Ambient
Timing Plan: PM PEAK



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑↑	↑↑↑	↑↑↑					↑	↑	↑↑↑
Volume (vph)	0	461	177	444	1261	0	0	0	0	336	1	60
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Fr _t		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Fl _t Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Fl _t Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	501	192	483	1371	0	0	0	0	365	1	65
RTOR Reduction (vph)	0	0	126	0	0	0	0	0	0	0	0	50
Lane Group Flow (vph)	0	501	66	483	1371	0	0	0	0	182	184	15
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Effective Green, g (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Actuated g/C Ratio		0.34	0.34	0.26	0.66					0.23	0.23	0.23
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)	1751	959		877	4200					392	393	650
v/s Ratio Prot		0.10		c0.14	c0.21					0.11	c0.11	
v/s Ratio Perm			0.02									0.01
v/c Ratio	0.29	0.07		0.55	0.33					0.46	0.47	0.02
Uniform Delay, d ₁	21.5	19.8		29.0	6.8					29.7	29.7	26.6
Progression Factor	1.00	1.00		0.82	0.57					1.00	1.00	1.00
Incremental Delay, d ₂	0.4	0.1		0.6	0.2					3.9	4.0	0.1
Delay (s)	21.9	19.9		24.5	4.1					33.6	33.7	26.7
Level of Service	C	B		C	A					C	C	C
Approach Delay (s)	21.3				9.4		0.0					
Approach LOS	C				A		A					C

Intersection Summary		
HCM 2000 Control Delay	15.5	HCM 2000 Level of Service
HCM 2000 Volume to Capacity ratio	0.45	B
Actuated Cycle Length (s)	90.0	Sum of lost time (s)
Intersection Capacity Utilization	60.1%	15.0
Analysis Period (min)	15	ICU Level of Service
		B

c Critical Lane Group

Santa Clarita Wayne Mills Hotel
 2: I-5 NB Ramps & Magic Mountain Pkwy

Existing Plus Ambient
 Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (vph)	31	563	0	0	947	243	1212	0	600	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Frt	1.00	1.00			0.99	0.85	1.00	0.85	0.85			
Flt Protected	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (prot)	3433	5085			6004	1282	3433	1504	1504			
Flt Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			6004	1282	3433	1504	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	34	612	0	0	1029	264	1317	0	652	0	0	0
RTOR Reduction (vph)	0	0	0	0	5	162	0	57	57	0	0	0
Lane Group Flow (vph)	34	612	0	0	1061	65	1317	269	269	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Effective Green, g (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Actuated g/C Ratio	0.03	0.37			0.28	0.28	0.52	0.52	0.52			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	91	1864			1707	364	1792	785	785			
v/s Ratio Prot	0.01	c0.12			c0.18		c0.38	0.18				
v/s Ratio Perm						0.05			0.18			
v/c Ratio	0.37	0.33			0.62	0.18	0.73	0.34	0.34			
Uniform Delay, d1	43.1	20.5			28.0	24.3	16.7	12.5	12.5			
Progression Factor	0.49	0.27			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d2	2.4	0.4			1.7	1.1	2.7	1.2	1.2			
Delay (s)	23.4	6.0			29.7	25.3	19.4	13.7	13.7			
Level of Service	C	A			C	C	B	B	B			
Approach Delay (s)		6.9			28.9			17.5			0.0	
Approach LOS		A			C			B			A	
Intersection Summary												
HCM 2000 Control Delay		19.5			HCM 2000 Level of Service			B				
HCM 2000 Volume to Capacity ratio		0.69										
Actuated Cycle Length (s)		90.0			Sum of lost time (s)			15.0				
Intersection Capacity Utilization		65.5%			ICU Level of Service			C				
Analysis Period (min)		15										
c Critical Lane Group												


Santa Clarita Wayne Mills Hotel
2: I-5 NB Ramps & Magic Mountain Pkwy

Existing Plus Ambient
Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖↗	↑↑↑			↑↑↑	↖	↖↗	↑	↖			
Volume (vph)	54	738	0	0	755	420	943	1	909	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Frt	1.00	1.00			0.97	0.85	1.00	0.85	0.85			
Flt Protected	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (prot)	3433	5085			5841	1282	3433	1505	1504			
Flt Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			5841	1282	3433	1505	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	59	802	0	0	821	457	1025	1	988	0	0	0
RTOR Reduction (vph)	0	0	0	0	54	164	0	35	43	0	0	0
Lane Group Flow (vph)	59	802	0	0	991	69	1025	460	452	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Effective Green, g (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Actuated g/C Ratio	0.04	0.39			0.30	0.30	0.50	0.50	0.50			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	122	1977			1739	381	1716	752	752			
v/s Ratio Prot	0.02	c0.16			c0.17		0.30	c0.31				
v/s Ratio Perm						0.05			0.30			
v/c Ratio	0.48	0.41			0.57	0.18	0.60	0.61	0.60			
Uniform Delay, d1	42.6	20.0			26.7	23.5	16.0	16.2	16.1			
Progression Factor	0.60	0.42			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d2	2.8	0.6			1.4	1.0	1.5	3.7	3.5			
Delay (s)	28.4	8.9			28.1	24.5	17.6	19.9	19.6			
Level of Service	C	A			C	C	B	B	B			
Approach Delay (s)		10.2			27.4			18.6			0.0	
Approach LOS		B			C			B			A	
Intersection Summary												
HCM 2000 Control Delay		19.6										
HCM 2000 Volume to Capacity ratio		0.60										
Actuated Cycle Length (s)		90.0										
Intersection Capacity Utilization		60.1%							15.0			
Analysis Period (min)		15										
c Critical Lane Group												

Santa Clarita Wayne Mills Hotel
 3: Tourney Rd & Magic Mountain Pkwy

Existing Plus Ambient
 Timing Plan: AM PEAK




Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑↑	↑	↑	↑↑↑↑	↑↑	↑
Volume (vph)	918	247	367	1072	125	66
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Frt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	998	268	399	1165	136	72
RTOR Reduction (vph)	0	180	0	0	0	62
Lane Group Flow (vph)	998	88	399	1165	136	10
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	33.8	33.8	40.3	79.1	13.7	13.7
Effective Green, g (s)	33.8	33.8	40.3	79.1	13.7	13.7
Actuated g/C Ratio	0.33	0.33	0.39	0.77	0.13	0.13
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	1540	479	638	3604	421	194
v/s Ratio Prot	c0.21		c0.24	0.25	c0.04	
v/s Ratio Perm		0.06				0.01
v/c Ratio	0.65	0.18	0.63	0.32	0.32	0.05
Uniform Delay, d1	29.4	24.6	25.2	3.6	40.4	38.9
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.9	0.2	1.9	0.1	0.4	0.1
Delay (s)	30.4	24.8	27.1	3.7	40.8	39.0
Level of Service	C	C	C	A	D	D
Approach Delay (s)	29.2			9.7	40.2	
Approach LOS	C			A	D	

Intersection Summary			
HCM 2000 Control Delay	19.9	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.59		
Actuated Cycle Length (s)	102.8	Sum of lost time (s)	15.0
Intersection Capacity Utilization	57.7%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
3: Tourney Rd & Magic Mountain Pkwy

Existing Plus Ambient
Timing Plan: PM PEAK



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑	↑	↑	↑↑↑	↑↑	↑
Volume (vph)	1534	125	146	914	261	352
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Frt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	1667	136	159	993	284	383
RTOR Reduction (vph)	0	45	0	0	0	284
Lane Group Flow (vph)	1667	91	159	993	284	99
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	60.1	60.1	18.5	83.6	19.6	19.6
Effective Green, g (s)	60.1	60.1	18.5	83.6	19.6	19.6
Actuated g/C Ratio	0.53	0.53	0.16	0.74	0.17	0.17
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	2486	774	266	3459	547	252
v/s Ratio Prot	c0.36		c0.10	0.21	c0.09	
v/s Ratio Perm		0.06				0.07
v/c Ratio	0.67	0.12	0.60	0.29	0.52	0.39
Uniform Delay, d1	19.3	13.3	43.9	4.9	42.5	41.5
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.7	0.1	3.6	0.0	0.8	1.0
Delay (s)	20.1	13.4	47.5	5.0	43.4	42.5
Level of Service	C	B	D	A	D	D
Approach Delay (s)	19.6			10.8	42.9	
Approach LOS	B			B	D	

Intersection Summary			
HCM 2000 Control Delay	21.1	HCM 2000 Level of Service	C
HCM 2000 Volume to Capacity ratio	0.63		
Actuated Cycle Length (s)	113.2	Sum of lost time (s)	15.0
Intersection Capacity Utilization	64.2%	ICU Level of Service	C
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
4:Tourney Rd & Wayne Mills PI

Existing Plus Ambient
 Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (veh/h)	25	2	2	49	0	61	5	84	43	172	445	24
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	27	2	2	53	0	66	5	91	47	187	484	26
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	1026	1007	484	962	986	91	510			138		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	1026	1007	484	962	986	91	510			138		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	85	99	100	75	100	93	99			87		
cM capacity (veh/h)	178	209	583	209	215	966	1055			1446		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	32	120	5	91	47	187	484	26				
Volume Left	27	53	5	0	0	187	0	0				
Volume Right	2	66	0	0	47	0	0	26				
cSH	194	370	1055	1700	1700	1446	1700	1700				
Volume to Capacity	0.16	0.32	0.01	0.05	0.03	0.13	0.28	0.02				
Queue Length 95th (ft)	14	34	0	0	0	11	0	0				
Control Delay (s)	27.6	19.3	8.4	0.0	0.0	7.9	0.0	0.0				
Lane LOS	D	C	A			A						
Approach Delay (s)	27.6	19.3	0.3			2.1						
Approach LOS	D	C										
Intersection Summary												
Average Delay			4.7									
Intersection Capacity Utilization			43.2%		ICU Level of Service					A		
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
4:Tourney Rd & Wayne Mills PI

Existing Plus Ambient
Timing Plan: PM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↖	↗		↕		↖	↗	↗	↖	↕	↗
Volume (veh/h)	19	4	7	46	3	106	3	495	33	103	141	36
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	21	4	8	50	3	115	3	538	36	112	153	39
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage veh												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	1039	958	153	928	961	538	192			574		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	1039	958	153	928	961	538	192			574		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	86	98	99	77	99	79	100			89		
cM capacity (veh/h)	149	228	893	222	227	543	1381			999		

Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3
Volume Total	33	168	3	538	36	112	153	39
Volume Left	21	50	3	0	0	112	0	0
Volume Right	8	115	0	0	36	0	0	39
cSH	212	373	1381	1700	1700	999	1700	1700
Volume to Capacity	0.15	0.45	0.00	0.32	0.02	0.11	0.09	0.02
Queue Length 95th (ft)	13	57	0	0	0	9	0	0
Control Delay (s)	26.0	22.4	7.6	0.0	0.0	9.1	0.0	0.0
Lane LOS	D	C	A			A		
Approach Delay (s)	26.0	22.4	0.0			3.3		
Approach LOS	D	C						

Intersection Summary

Average Delay	5.2
Intersection Capacity Utilization	57.7%
Analysis Period (min)	15
ICU Level of Service	B

APPENDIX E

- 2018 Opening Day Plus Project Conditions Analysis Worksheets

Santa Clarita Wayne Mills Hotel
1: Magic Mountain Pkwy & I-5 SB Ramps

Existing Plus Ambient Plus Project
Timing Plan: AM PEAK



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑	↑↑	↑↑↑					↑	↑	↑↑
Volume (vph)	0	271	80	614	1563	0	0	0	0	348	1	32
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Frt		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Flt Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Flt Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	295	87	667	1699	0	0	0	0	378	1	35
RTOR Reduction (vph)	0	0	59	0	0	0	0	0	0	0	0	28
Lane Group Flow (vph)	0	295	28	667	1699	0	0	0	0	189	190	7
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Effective Green, g (s)		29.0	29.0	27.0	61.0					19.0	19.0	19.0
Actuated g/C Ratio		0.32	0.32	0.30	0.68					0.21	0.21	0.21
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)		1638	898	1029	4343					354	355	588
v/s Ratio Prot		0.06		c0.19	c0.27					0.11	c0.11	
v/s Ratio Perm			0.01									0.00
v/c Ratio		0.18	0.03	0.65	0.39					0.53	0.54	0.01
Uniform Delay, d1		21.9	20.9	27.4	6.4					31.6	31.6	28.1
Progression Factor		1.00	1.00	0.78	0.54					1.00	1.00	1.00
Incremental Delay, d2		0.2	0.1	1.0	0.2					5.7	5.7	0.0
Delay (s)		22.2	20.9	22.3	3.6					37.2	37.3	28.1
Level of Service		C	C	C	A					D	D	C
Approach Delay (s)		21.9			8.9		0.0					
Approach LOS		C			A		A				D	

Intersection Summary			
HCM 2000 Control Delay	14.1	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.53		
Actuated Cycle Length (s)	90.0	Sum of lost time (s)	15.0
Intersection Capacity Utilization	65.8%	ICU Level of Service	C
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
1: Magic Mountain Pkwy & I-5 SB Ramps

Existing Plus Ambient Plus Project
Timing Plan: PM PEAK



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑↑	↑↑	↑↑	↑↑↑					↑	↑	↑↑
Volume (vph)	0	474	177	456	1269	0	0	0	0	349	1	60
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Lane Util. Factor		0.91	0.88	0.97	0.86					0.95	0.95	0.88
Frt		1.00	0.85	1.00	1.00					1.00	1.00	0.85
Flt Protected		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (prot)		5085	2787	3433	6408					1681	1686	2787
Flt Permitted		1.00	1.00	0.95	1.00					0.95	0.95	1.00
Satd. Flow (perm)		5085	2787	3433	6408					1681	1686	2787
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	515	192	496	1379	0	0	0	0	379	1	65
RTOR Reduction (vph)	0	0	126	0	0	0	0	0	0	0	0	50
Lane Group Flow (vph)	0	515	66	496	1379	0	0	0	0	189	191	15
Turn Type		NA	Perm	Prot	NA					Split	NA	Perm
Protected Phases		2		1	6					4	4	
Permitted Phases			2									4
Actuated Green, G (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Effective Green, g (s)		31.0	31.0	23.0	59.0					21.0	21.0	21.0
Actuated g/C Ratio		0.34	0.34	0.26	0.66					0.23	0.23	0.23
Clearance Time (s)		5.0	5.0	5.0	5.0					5.0	5.0	5.0
Vehicle Extension (s)		3.0	3.0	3.0	3.0					3.0	3.0	3.0
Lane Grp Cap (vph)		1751	959	877	4200					392	393	650
v/s Ratio Prot		0.10		c0.14	c0.22					0.11	c0.11	
v/s Ratio Perm			0.02									0.01
v/c Ratio		0.29	0.07	0.57	0.33					0.48	0.49	0.02
Uniform Delay, d1		21.5	19.8	29.2	6.8					29.8	29.8	26.6
Progression Factor		1.00	1.00	0.84	0.61					1.00	1.00	1.00
Incremental Delay, d2		0.4	0.1	0.7	0.2					4.2	4.3	0.1
Delay (s)		21.9	19.9	25.1	4.3					34.0	34.1	26.7
Level of Service		C	B	C	A					C	C	C
Approach Delay (s)		21.4			9.8		0.0					
Approach LOS		C			A		A				C	

Intersection Summary

HCM 2000 Control Delay	15.9	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.46		
Actuated Cycle Length (s)	90.0	Sum of lost time (s)	15.0
Intersection Capacity Utilization	61.4%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
2-I-5 NB Ramps & Magic Mountain Pkwy

Existing Plus Ambient Plus Project
Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↔↔	↑↑↑			↑↑↑	↔	↔↔	↑	↔			
Volume (vph)	31	587	0	0	967	251	1212	0	618	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Flt Protected	1.00	1.00			0.99	0.85	1.00	0.85	0.85			
Satd. Flow (prot)	3433	5085			6001	1282	3433	1504	1504			
Flt Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			6001	1282	3433	1504	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	34	638	0	0	1051	273	1317	0	672	0	0	0
RTOR Reduction (vph)	0	0	0	0	6	166	0	52	52	0	0	0
Lane Group Flow (vph)	34	638	0	0	1086	66	1317	284	284	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Effective Green, g (s)	2.4	33.0			25.6	25.6	47.0	47.0	47.0			
Actuated g/C Ratio	0.03	0.37			0.28	0.28	0.52	0.52	0.52			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	91	1864			1706	364	1792	785	785			
v/s Ratio Prot	0.01	c0.13			c0.18		c0.38	0.19				
v/s Ratio Perm						0.05			0.19			
v/c Ratio	0.37	0.34			0.64	0.18	0.73	0.36	0.36			
Uniform Delay, d1	43.1	20.6			28.1	24.3	16.7	12.7	12.7			
Progression Factor	0.49	0.28			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d2	2.4	0.5			1.8	1.1	2.7	1.3	1.3			
Delay (s)	23.7	6.2			30.0	25.4	19.4	14.0	14.0			
Level of Service	C	A			C	C	B	B	B			
Approach Delay (s)		7.1			29.2			17.6				0.0
Approach LOS		A			C			B				A
Intersection Summary												
HCM 2000 Control Delay		19.7			HCM 2000 Level of Service			B				
HCM 2000 Volume to Capacity ratio		0.70										
Actuated Cycle Length (s)		90.0			Sum of lost time (s)			15.0				
Intersection Capacity Utilization		65.8%			ICU Level of Service			C				
Analysis Period (min)		15										

Santa Clarita Wayne Mills Hotel
2: I-5 NB Ramps & Magic Mountain Pkwy

Existing Plus Ambient Plus Project
Timing Plan: PM PEAK


Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↔↔	↑↑↑			↑↑↑	↔	↔↔	↑	↔			
Volume (vph)	54	764	0	0	776	428	943	1	928	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Lane Util. Factor	0.97	0.91			0.81	0.81	0.97	0.95	0.95			
Frt	1.00	1.00			0.97	0.85	1.00	0.85	0.85			
Flt Protected	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (prot)	3433	5085			5843	1282	3433	1505	1504			
Flt Permitted	0.95	1.00			1.00	1.00	0.95	1.00	1.00			
Satd. Flow (perm)	3433	5085			5843	1282	3433	1505	1504			
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	59	830	0	0	843	465	1025	1	1009	0	0	0
RTOR Reduction (vph)	0	0	0	0	53	166	0	32	43	0	0	0
Lane Group Flow (vph)	59	830	0	0	1018	71	1025	475	462	0	0	0
Turn Type	Prot	NA			NA	Perm	Split	NA	Perm			
Protected Phases	5	2			6		8	8				
Permitted Phases						6			8			
Actuated Green, G (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Effective Green, g (s)	3.2	35.0			26.8	26.8	45.0	45.0	45.0			
Actuated g/C Ratio	0.04	0.39			0.30	0.30	0.50	0.50	0.50			
Clearance Time (s)	5.0	5.0			5.0	5.0	5.0	5.0	5.0			
Vehicle Extension (s)	3.0	3.0			3.0	3.0	3.0	3.0	3.0			
Lane Grp Cap (vph)	122	1977			1739	381	1716	752	752			
v/s Ratio Prot	0.02	c0.16			c0.17		0.30	c0.32				
v/s Ratio Perm						0.06			0.31			
v/c Ratio	0.48	0.42			0.59	0.19	0.60	0.63	0.61			
Uniform Delay, d1	42.6	20.1			26.9	23.5	16.0	16.4	16.2			
Progression Factor	0.61	0.42			1.00	1.00	1.00	1.00	1.00			
Incremental Delay, d2	2.8	0.6			1.4	1.1	1.5	4.0	3.7			
Delay (s)	28.9	9.2			28.3	24.6	17.6	20.4	20.0			
Level of Service	C	A			C	C	B	C	B			
Approach Delay (s)		10.5			27.6			18.9				
Approach LOS		B			C			B			0.0	A

Intersection Summary

HCM 2000 Control Delay	19.8	HCM 2000 Level of Service	B
HCM 2000 Volume to Capacity ratio	0.62		
Actuated Cycle Length (s)	90.0	Sum of lost time (s)	15.0
Intersection Capacity Utilization	61.4%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
3:Tourney Rd & Magic Mountain Pkwy

Existing Plus Ambient Plus Project
Timing Plan: AM PEAK




Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑	↑	↑	↑↑↑	↑↑	↑
Volume (vph)	918	288	379	1072	153	66
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Frt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	998	313	412	1165	166	72
RTOR Reduction (vph)	0	209	0	0	0	62
Lane Group Flow (vph)	998	104	412	1165	166	10
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	35.0	35.0	40.3	80.3	14.6	14.6
Effective Green, g (s)	35.0	35.0	40.3	80.3	14.6	14.6
Actuated g/C Ratio	0.33	0.33	0.38	0.77	0.14	0.14
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	1562	486	626	3585	440	202
v/s Ratio Prot	c0.21		c0.25	0.25	c0.05	
v/s Ratio Perm		0.07				0.01
v/c Ratio	0.64	0.21	0.66	0.32	0.38	0.05
Uniform Delay, d1	29.6	25.1	26.6	3.8	41.0	39.1
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.9	0.2	2.5	0.1	0.5	0.1
Delay (s)	30.5	25.3	29.1	3.9	41.6	39.2
Level of Service	C	C	C	A	D	D
Approach Delay (s)	29.2			10.5	40.9	
Approach LOS	C			B	D	

Intersection Summary			
HCM 2000 Control Delay	20.7	HCM 2000 Level of Service	C
HCM 2000 Volume to Capacity ratio	0.60		
Actuated Cycle Length (s)	104.9	Sum of lost time (s)	15.0
Intersection Capacity Utilization	59.3%	ICU Level of Service	B
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
3: Tourney Rd & Magic Mountain Pkwy

Existing Plus Ambient Plus Project
Timing Plan: PM PEAK



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑↑↑	↑	↑	↑↑↑	↑↑	↑
Volume (vph)	1534	170	159	914	290	352
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Lane Util. Factor	0.91	1.00	1.00	0.91	0.97	1.00
Frt	1.00	0.85	1.00	1.00	1.00	0.85
Flt Protected	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (prot)	4684	1458	1630	4684	3162	1458
Flt Permitted	1.00	1.00	0.95	1.00	0.95	1.00
Satd. Flow (perm)	4684	1458	1630	4684	3162	1458
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	1667	185	173	993	315	383
RTOR Reduction (vph)	0	61	0	0	0	284
Lane Group Flow (vph)	1667	124	173	993	315	99
Turn Type	NA	Perm	Prot	NA	Prot	Perm
Protected Phases	2		1	6	8	
Permitted Phases		2				8
Actuated Green, G (s)	63.0	63.0	20.0	88.0	20.9	20.9
Effective Green, g (s)	63.0	63.0	20.0	88.0	20.9	20.9
Actuated g/C Ratio	0.53	0.53	0.17	0.74	0.18	0.18
Clearance Time (s)	5.0	5.0	5.0	5.0	5.0	5.0
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)	2481	772	274	3466	555	256
v/s Ratio Prot	c0.36		c0.11	0.21	c0.10	
v/s Ratio Perm		0.09				0.07
v/c Ratio	0.67	0.16	0.63	0.29	0.57	0.39
Uniform Delay, d1	20.4	14.4	46.0	5.1	44.9	43.3
Progression Factor	1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2	0.7	0.1	4.7	0.0	1.3	1.0
Delay (s)	21.1	14.5	50.7	5.1	46.2	44.3
Level of Service	C	B	D	A	D	D
Approach Delay (s)	20.5			11.9	45.2	
Approach LOS	C			B	D	

Intersection Summary			
HCM 2000 Control Delay	22.4	HCM 2000 Level of Service	C
HCM 2000 Volume to Capacity ratio	0.64		
Actuated Cycle Length (s)	118.9	Sum of lost time (s)	15.0
Intersection Capacity Utilization	64.2%	ICU Level of Service	C
Analysis Period (min)	15		
c Critical Lane Group			

Santa Clarita Wayne Mills Hotel
4: Tourney Rd & Wayne Mills PI

Existing Plus Ambient Plus Project
Timing Plan: AM PEAK

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↖	↗		↕		↘	↕	↗	↘	↕	↗
Volume (veh/h)	53	10	6	49	0	61	11	84	43	172	445	77
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	58	11	7	53	0	66	12	91	47	187	484	84
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type							None				None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	1039	1020	484	982	1057	91	567			138		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	1039	1020	484	982	1057	91	567			138		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	67	95	99	72	100	93	99			87		
cM capacity (veh/h)	174	204	583	194	194	966	1005			1446		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3				
Volume Total	75	120	12	91	47	187	484	84				
Volume Left	58	53	12	0	0	187	0	0				
Volume Right	7	66	0	0	47	0	0	84				
cSH	195	348	1005	1700	1700	1446	1700	1700				
Volume to Capacity	0.38	0.34	0.01	0.05	0.03	0.13	0.28	0.05				
Queue Length 95th (ft)	42	37	1	0	0	11	0	0				
Control Delay (s)	35.0	20.7	8.6	0.0	0.0	7.9	0.0	0.0				
Lane LOS	D	C	A			A						
Approach Delay (s)	35.0	20.7	0.7			1.9						
Approach LOS	D	C										
Intersection Summary												
Average Delay			6.1									
Intersection Capacity Utilization			43.2%		ICU Level of Service					A		
Analysis Period (min)			15									

Santa Clarita Wayne Mills Hotel
4: Tournay Rd & Wayne Mills PI

Existing Plus Ambient Plus Project
Timing Plan: PM PEAK


Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↖	↗		↕		↖	↗	↗	↖	↗	↖
Volume (veh/h)	48	12	11	46	3	106	9	495	33	103	141	94
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	52	13	12	50	3	115	10	538	36	112	153	102
Pedestrians												
Lane Width (ft)												
Walking Speed (ft/s)												
Percent Blockage												
Right turn flare (veh)			6									
Median type								None			None	
Median storage (veh)												
Upstream signal (ft)												
pX, platoon unblocked												
vC, conflicting volume	1052	971	153	947	1037	538	255			574		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	1052	971	153	947	1037	538	255			574		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	64	94	99	76	98	79	99			89		
cM capacity (veh/h)	145	223	893	207	204	543	1310			999		

Direction, Lane #	EB 1	WB 1	NB 1	NB 2	NB 3	SB 1	SB 2	SB 3
Volume Total	77	168	10	538	36	112	153	102
Volume Left	52	50	10	0	0	112	0	0
Volume Right	12	115	0	0	36	0	0	102
cSH	190	358	1310	1700	1700	999	1700	1700
Volume to Capacity	0.41	0.47	0.01	0.32	0.02	0.11	0.09	0.06
Queue Length 95th (ft)	45	60	1	0	0	9	0	0
Control Delay (s)	36.9	23.6	7.8	0.0	0.0	9.1	0.0	0.0
Lane LOS	E	C	A			A		
Approach Delay (s)	36.9	23.6	0.1			2.8		
Approach LOS	E	C						

Intersection Summary

Average Delay	6.6
Intersection Capacity Utilization	57.7%
Analysis Period (min)	15
ICU Level of Service	B

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		↓	↑	↓	
Volume (veh/h)	30	0	101	30	0	68
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	33	0	110	33	0	74
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLTL			None		
Median storage (veh)	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			33		285	33
vC1, stage 1 conf vol					33	
vC2, stage 2 conf vol					252	
vCu, unblocked vol			33		285	33
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					5.4	
tF (s)			2.2		3.5	3.3
p0 queue free %			93		100	93
cM capacity (veh/h)			1579		714	1041
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	33	110	33	74		
Volume Left	0	110	0	0		
Volume Right	0	0	0	74		
cSH	1700	1579	1700	1041		
Volume to Capacity	0.02	0.07	0.02	0.07		
Queue Length 95th (ft)	0	6	0	6		
Control Delay (s)	0.0	7.4	0.0	8.7		
Lane LOS		A		A		
Approach Delay (s)	0.0	5.7		8.7		
Approach LOS				A		
Intersection Summary						
Average Delay			5.9			
Intersection Capacity Utilization			23.1%		ICU Level of Service	A
Analysis Period (min)			15			



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑		↓	↑	↓	
Volume (veh/h)	31	0	109	42	0	71
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	34	0	118	46	0	77
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	TWLTL			None		
Median storage veh	2					
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume			34		316	34
vC1, stage 1 conf vol					34	
vC2, stage 2 conf vol					283	
vCu, unblocked vol			34		316	34
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					5.4	
tF (s)			2.2		3.5	3.3
p0 queue free %			92		100	93
cM capacity (veh/h)			1578		688	1040

Direction, Lane #	EB 1	WB 1	WB 2	NB 1
Volume Total	34	118	46	77
Volume Left	0	118	0	0
Volume Right	0	0	0	77
cSH	1700	1578	1700	1040
Volume to Capacity	0.02	0.08	0.03	0.07
Queue Length 95th (ft)	0	6	0	6
Control Delay (s)	0.0	7.5	0.0	8.7
Lane LOS		A		A
Approach Delay (s)	0.0	5.4		8.7
Approach LOS				A

Intersection Summary			
Average Delay		5.7	
Intersection Capacity Utilization		23.8%	ICU Level of Service
Analysis Period (min)		15	A